

LED decorative ceiling fixture		days
be Scoute	d	Opportunities will be postedfor 30 days unless specified
describe tl	ne item application/ the end use of ite	em.* Provide the item number if applicable: (N95 Mask vs Protective Mask).
	ative ceiling fixture in the e	entry of each hotel guest room. Lighting Ceiling Fixture for project AHTV
Scouting		
1. Supplier Information 2. Summary of Technical and Performance Requirement	a. Type of supplier being : Manufacturer Other b. Reason for scouting su 2nd Supplier New Product Startu Other Other	□ Contract Manufacturer □ Distributor bmission* Price ■ Re-shore □ Past supplier no longer available
	Metal forming. Metal cle controlled application. Assembly of LED arrays 120V AC current. Secure frosted white acr b. Provide dimensions / si See attached drawing. 4 of 1" square metal rectar arrays. Arrays do not ha	raning and preparation for painting to prevent corrosion in indoor climate to metal housings. Wiring to driver and then to electrical leads for standard ylic diffusers to metal. Ize / tolerances / performance specifications for the item.* IO" OAW x 23" OAD x 3.5" OAH. 3 x 13W LED arrays illuminate the edges ngles painted bronze with frosted white acrylic diffusers in front of the live to be dimmable despite drawing reference to dimming.
	describe the descr	decorative ceiling fixture in the electric decoration for an analysis decoration for



			Steel, painted bronze. Finish chip to match will be provided. 3 x 13W LED arrays, 1000 lumens, 2700K color temperature, with driver. Frosted white acrylic strips. Ceiling Mounting bracket of galvanized steel punched for universal attachment to electrical junction box.
	Performance		d. Are there applicable certification requirements?* Yes No Please explain
		2. Summary of	Underwriters Laboratory (UL) or Eletrical Testing Lab (ETL) Listed.
		<u> </u>	e. Are there applicable regulations?* Yes No Please explain
	Requirements cont:	echnical S _I	
	ments	Technical Specifications and	f. Are there any other standards, requirements, etc.?* Yes No Please explain
	cont:		
			g. Additional Comments: Is there other information that would impact the item's performance or usefulness? Please explain.
			Company can provide a provide a sample of the fixture to supplier to understand construction.
ВІ	Pr	⊒ I	3a. Estimated potential business volume (i.e., # Units Per Day, Month, Year) *:
BUSINESS II	Pricing		Order quantity 170. This is a first order to qualify supplier. Remington supplies guest room and corridor lighting to upscale and midscale hotels across the US and the Caribbean. Some business is custom make to order and some standarized make to stock.
VFO			b. Estimated target price / unit cost information (flexible and negotiable not accepted) *:
NFORMATION			\$120.00 each including packaging
ΑΤΙ	Re	4.	a. When is it needed by? (Immediate, 30 Days, 6 months, etc.)*
ON:	Requirements:	Delivery	Pre-production sample within 30 days. Full production within 45 days.
			b. Describe packaging requirements (i.e., individually/group packaging)*
			Packed in cardboard carton with foam to secure the fixture from damage in transit and installation handling.
			c. Where will this item be shipped?*
			Ship to company, Mechanicsburg, PA 17055
	Α	5.	Is there other information you would like to include?



See	attached drawing	and photo		

Photos or diagrams of the item (helpful but not required).

DRAWING NOT TO SCALE | TOLERANCE: NON-CRITICAL: ± 6 [1/4"] CRITICAL: ± 3 [1/8" PART NAME PART DESCRIPTION / FINISHES / SPECIFICATIONS NOTES: **1.)** BREAK AND DEBURR ALL SHARP EDGES. CONCEALED (120V) LED DRIVER THREE (3) 13W LED, 1000 LM, 2700K, DIMMABLE 2.) ALL DIMENSIONS ARE IN MILLIMETERS [INCHES] LED ARRAY FROSTED WHITE ACRYLIC (A32MF477.02) DIFFUSER 3.) ALL VISIBLE SCREWS EXCEPT FOR THUMB SCREWS SHALL BE PAINTED FINISH ON METAL TO MATCH DARK BRONZE PT-034 (M10MP677) WITH GLOSSY LACQUER BODY, BACKPLATE, FINIALS CUSTOM MOUNTING BRACKET WITH UNIVERSAL CUT-OUT TO ATTACH TO ELECTRICAL JUNCTION BOX MOUNTING BRACKET COUNTERSUNK AND FLUSH WITH SURROUNDING SURFACES. 6 ELECTRICAL HARDWIRE / HOTWIRE (120V) 39W LED, 120V AC (IN BLACK TEXT WITH CLEAR BACKING) ©2021 REMILUX, LLC. ALL RIGHTS RESERVED. THE DRAWINGS HEREIN MAY NOT BE USED. WATTAGE LABEL UL LISTED WITH C UL US LABEL OR ETL LISTED WITH C ETL US LABEL UL / ETL LABEL REPRODUCED, STORED, OR TRANSMITTED IN WHOLE OR IN PART. IN ANY FORM OR BY ANY -10 [3/8"] MEANS, ELECTRONIC, MECHANICAL ID#4 PHOTOCOPYING, OR OTHERWISE, WITHOUT REMILUX'S PRIOR WRITTEN CONSENT. ANY UNAUTHORIZED USE MAY CONSTITUTE COMMON ID#2 AW AND STATUTORY COPYRIGHT INFRINGEMEN IN VIOLATION OF THE U.S. COPYRIGHT ACT. AMONG OTHERS CAUSES OF ACTION. 5/8″. 2 ID#3 144 ID#4 ISOMETRIC VIEW **DETAIL A-A** 246 [9 5/8"] SCALE: NTS SCALE: NTS MOUNTING **BRACKET - ID#5** SCALE: NTS 635 [25"] -38 [1 1/2"] 457 [18"] -254 [10"] 25 [1"] SQ. [23"] 584 0 76 [3"] 216 787 [31"] **TOP VIEW** SCALE: NTS 1016 [40"] DAW 254 [10"] ID#8 ID#6 14 [1/2"] **ID#7** 64 [2 1/2"] ID#2 25 [1"] SQ. ID#3 89 [3 1/2"] DAH ID#5 **FRONT VIEW** ID#4 ID#1 SCALE: NTS **REV** CHANGES: DATE **STATUS** ITEM: DL-5206 PROJECT: AHTV APPROVED FLUSH MOUNT CEILING FIXTURE ID#4 FINISH 08/20/21 FOR REFERENCE **AUTHOR** ID#4 FINISH 08/26/21 **PAGE** REM# DATE REV REMINGTON 1 OF 1 08/04/21 14685 EST? 1932 DRAWING NOT TO SCALE | TOLERANCE: NON-CRITICAL: ± 6 [1/4"] CRITICAL: ± 3 [1/8"]



