

# MEPNN Supplier Scouting Opportunity Synopsis

## Section 1: General Information

|                    |                                                                                                                                                                                                                                      |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Scouting Number    | 2025-150                                                                                                                                                                                                                             |
| Item to be Scouted | Variable Refrigerant Flow (VRF) HVAC System                                                                                                                                                                                          |
| Days to be scouted | 15                                                                                                                                                                                                                                   |
| Response Due By    | 05/22/2025                                                                                                                                                                                                                           |
| Description        | DEW Construction (GC) and our trade partner (Thomas Mechanical, Inc.) need assistance sourcing a variable refrigerant flow HVAC system, both the indoor and outdoor units for a project in South Burlington, VT. The specified Trane |

## Section 2: Technical Information

|                                                                                               |                                                                                                                                                                                                                                                                   |
|-----------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type of supplier being sought                                                                 | Manufacturer                                                                                                                                                                                                                                                      |
| Reason                                                                                        | Variable Refrigerant Flow (VRF) HVAC System                                                                                                                                                                                                                       |
|                                                                                               | BABA                                                                                                                                                                                                                                                              |
|                                                                                               | Vermont                                                                                                                                                                                                                                                           |
| Describe the manufacturing processes (elaborate to provide as much detail as possible)        | May include but is not limited to component fabrication (compressors, coils, circuit boards), precision assembly of indoor and outdoor units, electrical and refrigerant system integration, pressure and performance testing, and quality assurance inspections. |
| Provide dimensions / size / tolerances / performance specifications for the item              | See attached contract drawing "M002 Mechanical Schedules", contract specification section #238129, and engineer of record approved submittal "238129-001-0 VRF System PD & SD_NET."                                                                               |
| List required materials needed to make the product, including materials of product components | Unknown, this is not standard information listed in a product data submittal and has no bearing on the engineer of record's acceptance of this product.                                                                                                           |
| Are there applicable certification requirements?                                              | Yes                                                                                                                                                                                                                                                               |
| Certification(s) required                                                                     | UL                                                                                                                                                                                                                                                                |
| Are there applicable regulations?                                                             | No                                                                                                                                                                                                                                                                |
| Are there any other standards, requirements, etc.?                                            | Yes                                                                                                                                                                                                                                                               |
| Details                                                                                       | AHRI 210 / 240, AHRI 1230, ASCE 7, ASHRAE Std 15, ITS (DIR), NEMA 250, NFPA 70, UL 1995.                                                                                                                                                                          |
| Additional Technical Comments                                                                 |                                                                                                                                                                                                                                                                   |

## Section 4: Business Information

|                                                                         |                                                                                                            |
|-------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|
| Estimated potential business volume                                     | Qty 1, One-Time Order                                                                                      |
| Estimated target price / unit cost information (if unavailable explain) | \$4,375.00= total cost for 1 unit.                                                                         |
| When is it needed by?                                                   | Immediate.                                                                                                 |
| Describe packaging requirements                                         | Packaging up to the manufacturer. Best available. Delivered undamaged. Specifics discussed in negotiation. |
| Where will this item be shipped?                                        | South Burlington, VT 05495                                                                                 |

## Additional Comments

Is there other information you would like to include?

Funding Agency: Department of Commerce, National Institute of Standards and Technology. Attached for reference is the grant award letter provided to Burlington High School for this project. DEW Construction, BABA Contact: Michael Snyder, Cell: (802) 798-4976, Email: msnyder@dewconstruction.com.

**SECTION 23 8129**  
**VARIABLE REFRIGERANT FLOW HVAC SYSTEMS**

|                  |           |
|------------------|-----------|
| Job #            | 10424     |
| Cost #           |           |
| Construction Set |           |
| Received         | 11/7/2024 |
| DEW CONSTRUCTION |           |

**PART 1 GENERAL**

**1.01 SECTION INCLUDES**

- A. Air-source outdoor units.
- B. Refrigerant piping.
- C. Refrigerant branch units.
- D. Indoor units.

**1.02 REFERENCE STANDARDS**

- A. AHRI 210/240 - Performance Rating of Unitary Air-Conditioning and Air-Source Heat Pump Equipment.
- B. AHRI 1230 - Performance Rating of Variable Refrigerant Flow (VRF) Multi-Split Air-Conditioning and Heat Pump Equipment.
- C. ASCE 7 - Minimum Design Loads and Associated Criteria for Buildings and Other Structures.
- D. ASHRAE Std 15 - Safety Standard for Refrigeration Systems.
- E. ITS (DIR) - Directory of Listed Products.
- F. NEMA 250 - Enclosures for Electrical Equipment (1000 Volts Maximum).
- G. NFPA 70 - National Electrical Code.
- H. UL 1995 - Heating and Cooling Equipment.

**1.03 SUBMITTALS**

- A. See Section 01 3000 - Administrative Requirements for submittal procedures.
- B. Pre-Bid Submittals: For proposed substitute systems/products, as defined in PART 2, and alternate systems/products, as defined above, proposer shall submit all data described in this article, under the terms given for substitutions stated in PART 2.
- C. Product Data: Submit manufacturer's standard data sheets showing the following for each item of equipment, marked to correlate to equipment item markings indicated in Contract Documents:
  - 1. Outdoor Units:
    - a. Refrigerant Type and Size of Charge.
    - b. Output and Input Cooling Capacity: Btu/h.
    - c. Output and Input Heating Capacity: Btu/h.
    - d. Operating Temperature Range, Cooling and Heating.
    - e. Fan Capacity: Flow in cfm with respective fan curves.
    - f. External Static Pressure (ESP): In-wc.
    - g. Sound Pressure Level: dB(A).
    - h. Electrical Data: Complete including motor size.
    - i. Maximum number of indoor units that can be served.
    - j. Maximum refrigerant piping run from outdoor unit to indoor unit(s).
    - k. Maximum height difference between outdoor unit to Indoor unit(s), both above and below.
  - 2. Indoor Units:
    - a. Output and Input Cooling Capacity: Btu/h.
    - b. Output and Input Heating Capacity: Btu/h.
    - c. Fan Capacity: Flow in cfm with respective fan curves.
    - d. External Static Pressure (ESP): In-wc.
    - e. Electrical Data: Complete including motor size.

- f. Maximum Lift of Built-in Condensate Pump.
- 3. Control Panels: Complete data of controllers, input-output points, and zones.
- D. Shop Drawings: Installation drawings custom-made for this project; include as-designed HVAC layouts, locations of equipment items, refrigerant piping sizes and locations, condensate piping sizes and locations, remote sensing devices, control components, electrical connections, control wiring connections. Include:
  - 1. Detailed piping diagrams, with branch balancing devices.
  - 2. Condensate piping routing, size, and pump connections.
  - 3. Detailed power wiring diagrams.
  - 4. Detailed control wiring diagrams.
  - 5. Locations of required access through fixed construction.
  - 6. Drawings required by manufacturer.
- E. Operating and Maintenance Data:
  - 1. Manufacturer's complete standard instructions for each unit of equipment and control panel.
  - 2. Custom-prepared system operation, troubleshooting, and maintenance instructions and recommendations.
  - 3. Identification of replaceable parts and local source of supply.

#### **1.04 DELIVERY, STORAGE AND HANDLING**

- A. Deliver, store, and handle equipment and refrigerant piping according to manufacturer's recommendations.

#### **1.05 WARRANTY**

- A. See Section 01 7800 - Closeout Submittals for additional warranty requirements.

### **PART 2 PRODUCTS**

#### **2.01 MANUFACTURERS**

- A. Mitsubishi Electric Trane HVAC US, LLC; \_\_\_\_\_: [www.metahvac.com/#sle](http://www.metahvac.com/#sle).

#### **2.02 VARIABLE REFRIGERANT FLOW SYSTEM**

- A. Minimum System Requirements:
  - 1. System Testing, Capacity Rating, and Performance:
    - a. AHRI 1230 when cooling capacity is equal or greater than 65,000 Btu/h.
    - b. AHRI 210/240 when cooling capacity is below 65,000 Btu/h.
  - 2. Safety Certification: Bear UL 1995 tested and ITS (DIR) listed certification label.
  - 3. Outdoor Units: Furnish installation and surface support hardware products in accordance with ASCE 7 for wind restraint.
  - 4. Cooling Mode Interior Performance:
    - a. Daytime Setpoint: 68 degrees F, plus or minus 2 degrees F.
    - b. Setpoint Range: 57 degrees F to 77 degrees F.
    - c. Night Setback: 78 degrees F.
    - d. Interior Relative Humidity: 20 percent, maximum.
  - 5. Heating Mode Interior Performance:
    - a. Setpoint: 68 degrees F, plus or minus 2 degrees F.
    - b. Setpoint Range: 59 to 80 degrees F.
    - c. Night Setback: 60 degrees F.
    - d. Minimum Interior Relative Humidity: 10 percent RH.
- B. System Design and Installation Considerations:
  - 1. Conditioned spaces and zones are indicated on drawings.
  - 2. Required equipment unit capacities are indicated on drawings.
  - 3. Refrigerant piping sizes are not indicated on drawings.

4. Condensate piping to nearest drain is indicated on drawings.
5. Provide calculations showing ASHRAE Std 15 guideline compliance.

## **2.03 AIR-SOURCE OUTDOOR UNITS**

- A. Manufacturers:
  1. Air Conditioner, Cooling Outdoor Units:
  2. Heat Recovery, Cooling and Heating Outdoor Units:
    - a. Mitsubishi Electric Trane HVAC US, LLC: [www.metahvac.com/#sle](http://www.metahvac.com/#sle).
- B. Air Conditioning Type:
  1. DX refrigeration unit piped to one or more compatible indoor units either directly or indirectly through one or more intermediate refrigeration branch units.
- C. Unit Cabinet:
  1. Capable of being installed with wiring and piping to the left, right, rear or bottom.
  2. Designed to allow side-by-side installation with minimum spacing and vibration isolation.
  3. Weatherproof and corrosion resistant; rust-proofed mild steel panels coated with baked enamel finish.
  4. Sound Pressure Level: 55 dB measured at 3 feet from front of unit.
- D. Heat Sink Side:
  1. Condenser Fans:
    - a. Provide minimum of 2 fans for each condenser within the outdoor unit.
    - b. Minimum External Static Pressure: Factory set at 0.12 in-wc.
    - c. Fan Type: Vertical discharging, direct-driven propeller type with variable speed operation using DC-controlled ECM motors mechanically connected using permanently lubricated bearings having whole assembly protected with fan guards.
  2. Condenser Coils:
    - a. Hi-X seamless copper tubes expanded into aluminum fins to form mechanical bond; waffle louver fin and rifled bore tube design to ensure high efficiency performance.
- E. Refrigeration Side:
  1. Factory assembled and wired with instrumentation, switches, and controller(s) to handle unit specifics with direct coordination of remote controller(s) from indoor unit(s).
  2. Refrigeration Circuit: ECM driven dual scroll compressors, fans, condenser heat sink coil, expansion valves, solenoid valves, distribution headers, capillaries, filters, shutoff valves, oil separators, service ports, and refrigerant regulator.
  3. Refrigerant: R-410a factory charged. Controller to alarm when charge is below capacity.
  4. Variable Volume Control: Modulate compressed refrigerant capacity automatically to maintain constant suction and condensing pressures under varying refrigerant volume required to handle remote loads. Include defrost control.
  5. Provide refrigerant subcooling to ensure the liquid refrigerant does not flash when supplying to use indoor units.
  6. Capable of heating operation at low end of operating range as specified, without additional low ambient controls or auxiliary heat source; during heating operation, reverse cycle, oil return, or defrost is not permitted due to potential reduction in space temperature.
  7. Power Failure Mode: Automatically restarts operation after power failure without loss of programmed settings.
  8. Safety Devices: High pressure sensor with cut-out switch, low pressure sensor with cut-out switch, control circuit fuses, crankcase heaters, fusible plug, overload relay, inverter overload protector, thermal protectors for compressor and fan motors, overcurrent protection for the inverter and antirecycling timers.
  9. Oil Recovery Cycle: Automatic, occurring 2 hours after start of operation and then every 8 hours of operation; maintain continuous heating during oil return operation.

- F. Local Controls:
  - 1. Include factory-wired instruments, sensors, switches, and safeties for unit control.
  - 2. Configured to coordinate internal unit operation with remote indoor units and with built-in capacity to coordinate other manifolded outdoor units and remote refrigerant branch unit(s).
  - 3. Include screen and button interface to setup operating schedules, setpoints, alarms, and remote unit setpoint coordination. Also used for system troubleshooting.
- G. Power:
  - 1. Electrical Requirement: 208 to 230 VAC, 3-phase, 60 Hz.
  - 2. Outdoor Mounted: Provide fused NEMA 250 Type 4X disconnect switch.

## **2.04 REFRIGERANT PIPING**

- A. Two-Pipe Run: Provide low-pressure vapor and high-pressure vapor gas pipes for each indoor unit selected for seasonal heating or cooling service.
- B. Three-Pipe Run: Provide low-pressure vapor, high-pressure vapor gas, and liquid pipes for each indoor unit selected for off-season heating and cooling changeover service.
- C. Refrigerant Flow Balancing: Provide refrigerant piping joints and headers specifically designed to ensure proper refrigerant balance and flow for optimum system capacity and performance; T-style joints are prohibited.

## **2.05 REFRIGERANT BRANCH UNITS**

- A. Outdoor unit interface to handle two or more indoor units required to do automatic off-season heating and cooling changeover.
- B. Concealed box consisting internally-piped refrigeration loops, subcooling heat exchanger, and other devices coordinated by electronic valves to facilitate off-season load management between outdoor and indoor units.
- C. Minimum Requirements:
  - 1. Control direction of refrigerant flow using electronic expansion valves; use of solenoid valves for changeover and pressure equalization is not permitted due to refrigerant noise; use of multi-port branch selector boxes is not permitted unless spare ports are provided for redundancy.
  - 2. Provide one electronic expansion valve for each downstream indoor unit served except when multiple indoor units are connected, provide balancing joints in downstream piping to keep total capacity within branch unit capacity.
  - 3. Energize subcooling heat exchanger during simultaneous heating and cooling service.
  - 4. Casing: Galvanized steel sheet with flame and heat resistant foamed polyethylene sound and thermal insulation.
  - 5. Refrigerant Connections: Braze type.
  - 6. Condensate Drainage: Provide unit that does not require condensate drainage.

## **2.06 INDOOR UNITS**

- A. Manufacturers:
- B. Minimum Unit Requirements:
  - 1. DX Evaporator Coil:
    - a. Copper tubes expanded into aluminum fins to form a mechanical bond; waffle louver fin and high heat exchange, rifled bore tube design; factory tested.
    - b. 2-, 3-, or 4-row cross fin design with 14 to 17 fins per inch and flare end-connections.
    - c. Provide thermistor on liquid and gas lines wired into local controller.
    - d. Refrigerant circuits factory-charged with dehydrated air for field charging.
  - 2. Fan Section:

- a. Variable or three-speed ECM fan with automatic airflow adjustment; external static pressure selectable during commissioning.
  - b. Thermally protected, direct-drive motor with statically and dynamically balanced fan blades.
  - c. Minimum-adjustable external static pressure 0.32 in-wc; provide for mounting of field-installed ducts.
- 3. Local Unit Controls:
  - a. Temperature Control: Return air control using thermistor tied to computerized Proportional-Integral-Derivative (PID) control of superheat.
  - b. Temperature Zones:
    - 1) Single Indoor Unit: Set served space(s) as the local temperature zone.
    - 2) Multiple Indoor Units: For large zones, group and coordinate related indoor units with served spaces as the local temperature zone with each indoor unit as sub-zone.
- 4. Return Air Filter:
  - a. Washable long-life net filter with mildew proof resin, unless otherwise indicated.
- 5. Condensate:
  - a. Built-in condensate drain pan with PVC drain connection for drainage.
  - b. Units With Built-In Condensate Pumps: Provide condensate safety shutoff and alarm.
  - c. Units Without Built-In Condensate Pump: Provide built-in condensate float switch and wiring connections.
- 6. Cabinet Insulation: Sound absorbing foamed polystyrene and polyethylene insulation.
- C. Ceiling-Recessed Cassette, Indoor Units:
  - 1. Ceiling mount, 4-way, 2-way, or 1-way supply air flow units with central return air grill, DX coil, tubed drain pan, and built-in controls with thermostat remotely coordinated by outdoor air unit to maintain local air temperature setpoint.
  - 2. Cabinet Height: Maximum of 10 inches above face of ceiling.
  - 3. Exposed Housing: White, impact resistant, with washable decoration panel.
  - 4. Supply Airflow Adjustment:
    - a. Horizontally and vertically adjustable dampers with electronic actuators.
    - b. Four-way distribution field-modifiable to 3-way and 2-way airflow.
    - c. Three auto-swing positions, including standard, draft prevention and ceiling stain prevention.
  - 5. Return Air Filter: Manufacturer's standard.
  - 6. Sound Pressure Range: Between 28 to 33 dB(A) at low speed measured at 5 feet below the unit.
  - 7. Fan: Direct-drive turbo type, with motor output range of 1/16 to 1/8 hp.
  - 8. Condensate Pump: Built-in with minimum lift of 21 inches.
  - 9. Fresh Air Intake: Provide side-mounted outdoor air intake duct connection.
- D. Ceiling-Concealed Ducted Indoor Units:
  - 1. Type: Ducted unit with DX coil, tubed drain pan, and built-in controls with thermostat remotely coordinated by outdoor air unit to maintain local air temperature setpoint.
  - 2. Ducted horizontal discharge and side or back-end return; galvanized steel cabinet.
  - 3. Variable or three-speed ECM fan with automatic airflow adjustment; external static pressure selectable during commissioning.
  - 4. Return Air Filter: Manufacturer's standard.
  - 5. Sound Pressure: Measured at low speed at 5 feet below unit.
  - 6. Provide external static pressure switch adjustable for high efficiency filter operation
  - 7. Condensate Pump: Built-in, with lift of 9 inches, minimum.
  - 8. Switchbox accessible from side or bottom.

E. Wall Mounted, Indoor Units:

1. DX coil, tubed drain pan, and built-in controls with thermostat remotely coordinated by outdoor air unit to maintain local air temperature setpoint.
2. Variable or three-speed ECM cross-flow fan with automatic airflow adjustment; external static pressure selectable during commissioning.
3. Return Air Filter: Manufacturer's standard.
4. Provide exposed unit casing with removable front grille; foamed polystyrene and polyethylene sound insulation; wall mounting plate; polystyrene condensate drain pan.
5. Airflow Control: Auto-swing louver that closes automatically when unit stops; five (5) steps of discharge angle, set using remote controller; upon restart, discharge angle defaults to same angle as previous operation.
6. Sound Pressure Range: Measured at low speed at 3.3 feet below and away from unit.
7. Condensate Drain Connection: Back, with piping concealed in wall.

### **PART 3 EXECUTION**

#### **3.01 INSTALLATION**

- A. Install in accordance with manufacturer's instructions.
- B. Install refrigerant piping in accordance with equipment manufacturer's instructions.
- C. Perform wiring in accordance with NFPA 70, National Electric Code (NEC).
- D. Coordinate with installers of systems and equipment connecting to this system.

#### **3.02 SYSTEM STARTUP**

- A. Prepare and start equipment and system in accordance with manufacturer's instructions and recommendations.
- B. Adjust equipment for proper operation within manufacturer's published tolerances.

#### **3.03 PROTECTION**

- A. Protect installed components from subsequent construction operations.
- B. Replace exposed components broken or otherwise damaged beyond repair.

### **END OF SECTION**



**McFarland Johnson**

## *SUBMITTAL COVER SHEET*

Received By MJ on:

(Receipt Stamp)

**PROJECT NAME:** BSD Aviation Technology Center

**SUBMITTAL NO.:** 23 8129-1.0

**CONTRACTOR:** DEW Construction Corp.

**DATE:** \_\_\_\_\_

**FUNDING AGENCY NO.:** Burlington School District

**M-J PROJ. NO.:** 18715.02

**TECH SPECIFICATION NO.:** 23 8129

NOTE: ONLY ONE TECH SPEC.  
PER SUBMITTAL PLEASE.

| COMPONENT NO. | DESCRIPTION                            | M-J ACTION |
|---------------|----------------------------------------|------------|
| 23 8129       | VARIABLE REFRIGERANT FLOW HVAC SYSTEMS | MCN        |
|               |                                        |            |
|               |                                        |            |
|               |                                        |            |
|               |                                        |            |
|               |                                        |            |
|               |                                        |            |

**M-J ACTION:**    **NET** – NO EXCEPTION TAKEN  
                          **R&R** – REVISE AND RESUBMIT  
                          **MCN** – MAKE CORRECTIONS NOTED

**REJ** – REJECTED  
**SSI** – SUBMIT SPECIFIED ITEM

### **REVIEW COMMENTS:**

- **Conform the submittal has documentation to meet BABA requirements.**

**APPROVAL DEPENDANT UPON THE ACCEPTANCE OF THE DE MINIMIS WAIVER**

### **CONTRACTOR'S CERTIFICATION:**

THE CONTRACTOR CERTIFIES THAT THEY HAVE REVIEWED THE ENCLOSED DOCUMENTS AND THEY ARE IN GENERAL CONFORMANCE WITH THE PROJECT DOCUMENTS.

Date \_\_\_\_\_

By \_\_\_\_\_

Title \_\_\_\_\_

THIS REVIEW IS ONLY FOR GENERAL CONFORMANCE WITH THE DESIGN CONCEPT AND THE INFORMATION GIVEN IN THE CONSTRUCTION DOCUMENTS. CORRECTIONS OR COMMENTS MADE ON THE SHOP DRAWINGS DURING THIS REVIEW DO NOT RELIEVE THE CONTRACTOR FROM COMPLIANCE WITH THE REQUIREMENTS OF THE PLANS AND SPECIFICATIONS. APPROVAL OF A SPECIFIC ITEM SHALL NOT INCLUDE APPROVAL OF AN ASSEMBLY OF WHICH THE ITEM IS A COMPONENT. THE CONTRACTOR IS RESPONSIBLE FOR; DIMENSIONS TO BE CONFIRMED AND CORRELATED AT THE JOBSITE; INFORMATION THAT PERTAINS SOLELY TO THE FABRICATION PROCESS OR TO THE MEANS, METHODS, TECHNIQUES, SEQUENCES AND PROCEDURES OF CONSTRUCTION; COORDINATION OF THE WORK WITH THAT OF ALL OTHER TRADES AND PERFORMING ALL WORK IN A SAFE AND SATISFACTORY MANNER



**McFarland Johnson**

Date 01/13/25 By WH



DEW Construction  
277 Blair Park Road, Suite 130  
Williston, Vermont 05495  
P: (802) 872-0505

Project: 10424 Burlington Tech Center Aviation  
200 DaVinci Drive  
South Burlington, Vermont 05403

## Submittal #238129-1.0 - VRF System - PD & SD 238129 - Variable Refrigerant Flow HVAC Systems

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                   |                                                 |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|-------------------------------------------------|
| Revision               | 0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Submittal Manager | Becky St. George (DEW Construction)             |
| Status                 | Open                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Date Created      | Dec 11, 2024                                    |
| Issue Date             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Spec Section      | 238129 - Variable Refrigerant Flow HVAC Systems |
| Responsible Contractor | Thomas Mechanical, Inc.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Received From     | Leslie Davis (Thomas Mechanical, Inc.)          |
| Received Date          | Dec 18, 2024                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Submit By         |                                                 |
| Final Due Date         | Jan 2, 2025                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Lead Time         |                                                 |
|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Cost Code         |                                                 |
| Location               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Type              | Product Information                             |
| Approvers              | Michael Snyder (DEW Construction), William Howland (McFarland Johnson), Michael Martin (McFarland Johnson)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                   |                                                 |
| Ball in Court          | Michael Snyder (DEW Construction)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                   |                                                 |
| Distribution           | Adam Frosino (McFarland Johnson), Becky St. George (DEW Construction), Deanna Utter (Sheet Metal Specialists), Leslie Davis (Thomas Mechanical, Inc.), Liza MacAuley (Thomas Mechanical, Inc.), Marty Spaulding (PCI - Capital Project Consulting), Michael Martin (McFarland Johnson), Michael Snyder (DEW Construction), Neil Valley (Thomas Mechanical, Inc.), Ron Snyder (PCI - Capital Project Consulting), Sara Bosworth (DEW Construction), William Howland (McFarland Johnson)                                                                                                                                                                                                                                                                                                                                                                                          |                   |                                                 |
| Description            | <b>2024-12-19: R0</b><br><br>Included in this submittal are the following:<br><br><ol style="list-style-type: none"><li>1. Substitution Form for Carrier VRF #38MARB (AC-130 in schedule)</li><li>2. Carrier #38MARB Outdoor Unit, Single Zone Ductless VRF System - PD (<b>substitution, not B.O.D. manuf.</b>)</li><li>3. Shop Drawings</li><li>4. Wiring Diagrams</li><li>5. Carrier #40MAHB High Wall Ductless Units - PD</li><li>6. Carrier Connect WiFi Thermostat - Install Guide</li><li>7. Carrier 24V Interface Kit - Install Guide</li><li>8. Intesis BACnet MS/TP Server - User Manual</li><li>9. DiversiTech Mini Split Stand - SD</li></ol><br>Notes:<br><ol style="list-style-type: none"><li>1. This system is <b>not</b> BABAA compliant. There are currently zero VRF systems manufactured that meet BABAA regulations. System value is \$4,375.00.</li></ol> |                   |                                                 |

### Submittal Workflow

| Name                            | Sent Date | Due Date     | Returned Date | Response                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Attachments |
|---------------------------------|-----------|--------------|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| General Information Attachments |           |              |               | <p>Checking is only for conformity to the design concept of the project and compliance with the information given in the contract documents and specifications. The Trade Partner is responsible for dimensions, to be confirmed and correlated at the project site, for information that pertains solely to the fabrication, the techniques of construction and for the coordination of their work with all trades.</p> <p>Project #: 10424 – Burlington Tech Center Aviation @ BTV<br/>Reviewed By: Michael Snyder, LEED AP BD+C      Date: 2024-12-19</p> |             |
| Michael Snyder                  |           | Dec 19, 2024 |               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |             |
| William Howland                 |           | Jan 2, 2025  |               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |             |
| Michael Martin                  |           | Jan 2, 2025  |               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |             |
|                                 |           |              |               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |             |

**Thomas Mechanical Inc.**  
**90 Ethan Allen Drive**  
**South Burlington, VT 05403**  
Phone (802) 865-9119  
Fax (802) 865-9501

## **Submittal Cover Sheet:**

Project Name: **BSD Aviation Technical Center**

Date: **12/18/2024**

Architect: **Freeman French Freeman, Inc.**

Contractor: **DEW Construction**

Engineer: **MCFarland - Johnson**

Specification Section: **Mechanical 22/23**

Revision:

Submitted per Specification Section: **VRF System**

Drawing #/Detail Reference:

Supplier: **R.J. Murray**

Manufacturer: **Various**

Substitution:

Color Selection Required:

Lead Time Upon Approval:

IOM Included:

Items Submitted:

**VRF System**

SECTION 016200

SUBSTITUTION REQUEST FORM

No substitutions will be considered without this completed substitution request form and supporting documentation. Substitutions made without completion of this form will be considered defective work as stated in AIA A201.

Date: 12/18/2024 Number: 02

Re: Request for Substitution

The Contractor proposes the following substitution in accordance with the requirements of the Contract Documents:

Scope of Substitution Carrier Variable Refrigerant System

Specification Reference 23 8129

Drawing Reference M002

Reason for Proposed Substitution Performance

Benefit to Owner Cost

Impact on Project Cost

Impact on Project Schedule

Impact on Guarantees and Warranties

Coordination and Compatibility Required with Adjacent Materials and System

List Deviations  
From Specified  
Requirements

---

---

---

---

Building Energy Performance: For substitutions of materials and products used for backstop and de-rated calculations, provide an updated envelope backstop and de-rating calculations based on the product being proposed for substitution and demonstrate the equivalence or difference with the original product[s]. Substitutions which, in the opinion of the architect, modify the energy design, and which are submitted without the required evidence of compliance with the code and the original design will be returned without review and are by definition not permitted.

Attachments: Attach supporting documentation sufficient for Architect to evaluate substitution. Substitution Request Forms submitted without adequate documentation will be returned without review.

Attachments

---

---

---

Response Date: List date by which response by Architect is requested to maintain project schedule and allow sufficient time for inclusion of proposed substitution.

Response Date

---

Submitted By

---

Firm and Address

---

---

Signature below signifies acceptance of responsibility for accuracy and completeness of information included in this Substitution Request Form.

Authorized Signature

---

ARCHITECT'S RESPONSE

Notations listed below shall have same meaning as on Architect's approval stamp. Clarifications to or changes in project schedule or time shall be processed using standard project forms.

Architect's  
Response

- ☐ Approved
- ☐ Approved as Corrected
- ☐ Revise and Resubmit
- ☐ Rejected
- ☐ Returned Without Review

Remarks

---

---

---

---

---

---

---

Date

---

Signed

---

END OF FORM



7 Northway Lane  
Latham, NY 12110  
(518) 690-4455  
Fax (518) 690-4990



www.rjmurray.com  
mail@rjmurray.com



79 Holly Court  
Williston, VT 05495  
(802) 862-8608  
Fax (802) 862-8344

**Date: 12/04/2024**

**TRANSMITTAL OF DRAWINGS, BULLETINS, CATALOGS, ETC.**

**TO: Thomas Mechanical**

**ATTN: Liza McAuley**

**RE: Burlington Aviation Technical Center**

We are transmitting herewith the following:

| <u>COPIES</u> | <u>TYPE OF INFORMATION</u>                                | <u>REMARKS</u> |
|---------------|-----------------------------------------------------------|----------------|
| 1             | Submittal for VRF System<br>Specification Section 23 8129 |                |

The above items are being transmitted for:

- ✓ Your Approval
- Your Review
- Your Record
- With Your Approval
- Your Correction
- Corrected as Noted

Please Return 1 Copy (ies) With Your Comments

Very truly yours,

BY: \_\_\_\_\_

Mike Bronder

---

Distributor  
HVACR  
Equipment & Parts

**R. J. MURRAY Co., Inc.**



## Equipment Submittal

|                         |                                                                           |                         |
|-------------------------|---------------------------------------------------------------------------|-------------------------|
| <b>Project Location</b> | <b>Burlington Aviation Technical Center<br/>South Burlington, Vermont</b> |                         |
| <b>Architect</b>        | <b>Freeman French Freeman</b>                                             |                         |
| <b>Engineer</b>         | <b>McFarland Johnson</b>                                                  |                         |
| <b>Contractor P.O.</b>  | <b>Thomas Mechanical<br/>PO# 5484-24</b>                                  |                         |
| <b>Submitted by</b>     | <b>Mike Bronder<br/>R. J. Murray Co., Inc.<br/>Latham, NY 12110</b>       | <b>Date: 12/04/2024</b> |

**Distributor for  
Heating, Ventilating and  
Air Conditioning Equipment**

|                 |
|-----------------|
| <b>Contents</b> |
|-----------------|

**Submittal for VRF System-Specification Section 23 8129**

7 NORTHWAY LANE  
LATHAM, NY 12110

R. J. MURRAY CO., INC.

WEBSITE: [WWW.RJMURRAY.COM](http://WWW.RJMURRAY.COM)

79 HOLLY COURT  
WILLISTON, VT 05495


TEL: (518) 690-4455  
FAX: (518) 690-4990

TEL: (802) 862-8608  
FAX: (802) 862-8634

**38MARB**  
**Outdoor Unit Single Zone Ductless System**  
**Sizes 06 to 36**



## Product Data



**Fig. 1 —Sizes 06K - 36K**

A220408

**NOTE:** Images are for illustration purposes **only**. Actual models may differ slightly.

### TABLE OF CONTENTS

|                                                | PAGE |
|------------------------------------------------|------|
| INDUSTRY LEADING FEATURES / BENEFITS . . . . . | 1    |
| MODEL NUMBER NOMENCLATURE . . . . .            | 3    |
| STANDARD FEATURES AND ACCESSORIES . . . . .    | 4    |
| DIMENSIONS . . . . .                           | 5    |
| CLEARANCES . . . . .                           | 9    |
| SPECIFICATIONS . . . . .                       | 10   |
| PERFORMANCE . . . . .                          | 11   |
| COOLING PERFORMANCE - AHU . . . . .            | 49   |
| HEATING PERFORMANCE - AHU . . . . .            | 61   |
| APPLICATION DATA . . . . .                     | 65   |
| WIRING . . . . .                               | 66   |
| ELECTRICAL DATA . . . . .                      | 68   |
| CONNECTION DIAGRAMS . . . . .                  | 69   |
| WIRING DIAGRAMS . . . . .                      | 70   |
| GUIDE SPECIFICATIONS . . . . .                 | 74   |

### INDUSTRY LEADING FEATURES / BENEFITS

#### A PERFECT BALANCE BETWEEN BUDGET LIMITS, ENERGY SAVINGS AND COMFORT.

The **38MARB** series ductless systems are a matched combination of an outdoor condensing unit and an indoor fan coil unit connected only by refrigerant tubing and wires.

The ductless system permits creative solutions to design problems such as:

- Add-ons to current space (an office or family room addition)
- Special space requirements
- When changes in the load cannot be handled by the existing system
- When adding air conditioning to spaces that are heated by hydronic or electric heat and have no ductwork
- Historical renovations or any application where preserving the look of the original structure is essential.

The ideal compliment to your ducted system when it is impractical or prohibitively expensive to use ductwork.

The compact indoor fan coil units take up very little space in the room and do not obstruct windows. The fan coils are attractively styled to blend with most room decors. Advanced system components incorporate innovative technology to provide reliable cooling performance at low sound levels.

## **Inverter Technology**

The inverter driven compressor is designed to run at various input power frequencies (Hz) which controls the compressor's motor speed.

**Even Temperature** – The control package, including the inverter, monitors the outdoor and indoor temperatures as they relate to the selected indoor set point and adjusts the compressor speed to match the load and keep the system operating continuously rather than cycling and creating temperature swings. This translates to higher comfort levels for the occupants.

**Rapid Pull Down/Warm-Up** – Comfort is increased by the inverter system's ability to ramp up the compressor speed enabling the system to reach the user selected room temperature set point quicker.

**Humidity Control** – Running the system for longer periods and continuously varying the compressor speed enhances the humidity control.

## **Individual Room Comfort**

Maximum comfort is provided because each space can be controlled individually based on the usage pattern.

## **Low Sound Levels**

When noise is a concern, ductless systems are the answer. The indoor units are whisper quiet. There are no compressors indoors, either in the conditioned space or directly over it, and there is none of the noise usually generated by air being forced through the ductwork.

When sound ordinances and proximity to neighbors demand quiet operation, the **38MARB** unit is the right choice. With the inverter technology, these units run at lower speeds most of the time resulting in reduced sound levels.

## **Inverter Technology – Enhanced Economical Operation**

Ductless systems are inherently economical to operate. Individual rooms are heated or cooled only when required, and since the air is delivered directly to the space, there is no need to use additional energy to move the air in the ductwork. This economical operation is enhanced further when the inverter system output matches the load resulting in a more efficient system.

## **Easy-To-Use Controls**

The systems have microprocessor-based controls to provide the ultimate in comfort and efficiency. The user friendly wired and wireless remote controls provide the interface between the user and the unit.

## **Secure Operation**

If security is an issue, outdoor and indoor units are connected only by refrigerant piping and wiring to prevent intruders from crawling through ductwork or wall openings. In addition, since the **38MARB** can be installed close to an outside wall, coils are protected from vandals and severe weather.

## **Fast Installation**

This compact ductless system is simple to install. Only wires and piping need to run between the indoor and outdoor units. These units are fast and easy to install ensuring minimal disruption to customers in homes or the workplace. This makes the **38MARB** systems the equipment of choice for retrofit applications.

## **Simple Servicing and Maintenance**

Removing the top panel of the outdoor unit provides immediate access to the control compartment, providing the service technician access to the diagnostic LEDs to facilitate the troubleshooting process. In addition, the draw-thru design of the outdoor unit means that dirt accumulates on the outside surface of the coil. Coils can be cleaned quickly from the inside using a pressure hose and detergent.

On the indoor units, service and maintenance expense is reduced due to the permanent easy to clean filters. Also, error codes are displayed on the front panel to alert the user to certain system malfunctions.

## **Built-in Reliability**


Ductless system indoor and outdoor units are designed to provide years of trouble-free operation. Both the indoor and outdoor units are well protected. Whenever the microprocessor detects abnormal conditions, the unit stops and an error code appears.

Inverter systems provide additional reliability due to the soft start. This refers to the ability of the inverter to start the compressor motor using reduced voltage and reduced current. This feature is beneficial from an electrical standpoint (eliminates current spikes) as well as an overall reliability standpoint due to reduced stress on all associated system components.

## **Agency Listings**

All systems are listed with AHRI (Air conditioning, Heating, and Refrigeration Institute) and are UL certified per UL 60335-2-40 standard.

MODEL NUMBER NOMENCLATURE



A220411



Use of the AHRI Certified  
TM Mark indicates a  
manufacturer's  
participation in the  
program For verification  
of certification for individual  
products, go to  
[www.ahrirectory.org](http://www.ahrirectory.org).



A220412

## STANDARD FEATURES AND ACCESSORIES

|                                                |   |
|------------------------------------------------|---|
| <b>Ease Of Installation</b>                    |   |
| Low Voltage Controls                           | S |
| <b>Comfort Features</b>                        |   |
| Microprocessor Controls                        | S |
| Auto Restart Function                          | S |
| Auto Changeover                                | S |
| <b>Energy Saving Features</b>                  |   |
| Inverter Driven Compressor                     | S |
| 46° F Heating Mode (Heating Setback)           | S |
| <b>Safety And Reliability</b>                  |   |
| 3 Minute Time Delay For Compressor             | S |
| High Compressor Discharge Temperature          | S |
| Low Voltage Protection                         | S |
| Compressor Overload Protection                 | S |
| Compressor Over Current Protection             | S |
| IPM Module Protection                          | S |
| Condenser High Temp Protection in Cooling Mode | S |
| Aluminum Hydrophilic pre-coated fins           | S |
| <b>Ease Of Service And Maintenance</b>         |   |
| Diagnostics                                    | S |
| Liquid Line Pressure Taps                      | S |
| <b>Application Flexibility</b>                 |   |
| Crankcase Heater                               | S |
| Base pan Heater                                | S |

### Outdoor Units

#### Crankcase Unit

The crankcase heater is standard on all unit sizes. Heater clamps must be placed around the compressor oil stump.

#### Base pan Heater

The base pan heater is standard on all unit sizes.

### Legend


- S - Standard
- A - Accessory

### Accessories

| Outdoor Unit Model Number                                    | Base Pan Base Rubber Plugs RCD Part No. | Quantity per Unit |
|--------------------------------------------------------------|-----------------------------------------|-------------------|
| 38MARBQ12AA1<br>38MARBQ06AA3<br>38MARBQ09AA3<br>38MARBQ12AA3 | 12600801A00077                          | 13                |
| 38MARBQ18AA3                                                 | 12600801A00077                          | 25                |
| 38MARBQ24AA3<br>38MARBQ30AA3<br>38MARBQ36AA3<br>38MARBQ36AB3 | 12600801A00117                          | 5                 |

**NOTE: The base pan is built in with multiple holes for proper draining during the defrost process. For applications where it is required to seal these holes, and re-direct the condensate drain, rubber plugs are available through RCD.**

## DIMENSIONS



**Fig. 2 — Outdoor Unit**

A220414

| SYSTEM SIZE  |                    | 12K       | 6K           | 9K          | 12K          | 18K          | 24K           | 30K           | 36K          |
|--------------|--------------------|-----------|--------------|-------------|--------------|--------------|---------------|---------------|--------------|
|              |                    | (115V)    | (208/230V)   | (208/230V)  | (208/230V)   | (208/230V)   | (208/230V)    | (208/230V)    | (208/230V)   |
| OUTDOOR UNIT | <b>UNIT</b>        |           |              |             |              |              |               |               |              |
|              | Height (H)         | in (mm)   | 21.85 (555)  | 21.85 (555) | 21.81 (554)  | 21.81 (554)  | 26.50 (673)   | 31.89 (810)   | 31.89(810)   |
|              | Width (W)          | in (mm)   | 30.12 (765)  | 30.12 (765) | 31.69 (805)  | 31.69 (805)  | 35.04 (890)   | 37.24 (946)   | 37.24 (946)  |
|              | Depth (D)          | in (mm)   | 11.93 (303)  | 11.93 (303) | 12.99 (330)  | 12.99 (330)  | 13.46 (342)   | 16.14 (410)   | 16.14(410)   |
|              | Weight - Net       | lbs. (kg) | 66.80 (30.3) | 63.71(28.9) | 74.07 (33.6) | 73.63 (33.4) | 100.97 (45.8) | 134.48 (61)   | 141.76(64.3) |
|              | L1                 | in. (mm)  | 17.81 (452)  | 17.81 (452) | 20.10 (511)  | 20.10 (511)  | 26.10 (663)   | 26.50 (673)   | 26.50 (673)  |
|              | L2                 | in. (mm)  | 11.25 (286)  | 11.25 (286) | 12.50 (317)  | 12.50 (317)  | 13.70 (347)   | 15.85 (403)   | 15.85 (403)  |
|              | <b>PACKAGING</b>   |           |              |             |              |              |               |               |              |
|              | Height             | in (mm)   | 24.02 (610)  | 24.02 (610) | 24.21 (615)  | 24.21 (615)  | 29.13 (740)   | 34.84 (885)   | 34.84(885)   |
|              | Width              | in (mm)   | 34.92 (887)  | 34.92 (887) | 36.02 (915)  | 36.02 (915)  | 39.17 (995)   | 42.91 (1090)  | 42.91(1090)  |
|              | Depth              | in (mm)   | 13.27 (337)  | 13.27 (337) | 14.57 (370)  | 14.57 (370)  | 15.67 (398)   | 19.69 (500)   | 19.69(500)   |
|              | Weight - Gross     | lbs. (kg) | 72.31 (32.8) | 69(31.3)    | 80.25 (36.4) | 79.37 (36)   | 108.03 (49)   | 144.40 (65.5) | 151.90(68.9) |
|              | Carton Drawing No. | --        | 877*327*590  | 877*327*590 | 905*360*590  | 905*360*590  | 985*388*720   | 1075*485*86   | 1075*485*86  |
|              | Carton Material    | --        | Carton Box   |             |              |              |               |               |              |
|              | Material Thickness | in (mm)   | 0.197 (5)    | 0.197 (5)   | 0.197 (5)    | 0.197 (5)    | 0.197 (5)     | 0.295 (7.5)   | 0.295(7.5)   |

**NOTE: ‡ AHU only**

DIMENSIONS (CONT)




Fig. 5 —Dimension Size 18K

A220417





Fig. 6 —Dimension Sizes 24K, 30K, and 36K

A220418

## CLEARANCES




### Fig. 7 —Clearances

A220419

| UNIT | MINIMUM VALUE<br>in. (mm) |
|------|---------------------------|
| A    | 24 (610)                  |
| B    | 24 (610)                  |
| C    | 24 (610)                  |
| D    | 4 (101)                   |
| E    | 4 (101)                   |

**NOTE: The outdoor unit must be mounted at least 2in (50mm) above the maximum anticipated snow depth.**



**Fig. 8 —Clearances for multiple units**

A220421

## SPECIFICATIONS

| System          | Size                                                      |             | 12K - 115V           | 6K                   | 9K                   | 12K - 208/230V       | 18K                  | 24K                  | 30K                  | 36K                  | 36K - AHU Only       |
|-----------------|-----------------------------------------------------------|-------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|
|                 | Outdoor Model                                             |             | 38MARBQ12AA1         | 38MARBQ06AA3         | 38MARBQ09AA3         | 38MARBQ12AA3         | 38MARBQ18AA3         | 38MARBQ24AA3         | 38MARBQ30AA3         | 38MARBQ36AA3         | 38MARBQ36AB3         |
| Electrical      | Voltage, Phase, Cycle                                     | V/Ph/Hz     | 115-1-60             | 208/230-1-60         | 208/230-1-60         | 208/230-1-60         | 208/230-1-60         | 208/230-1-60         | 208/230-1-60         | 208/230-1-60         | 208/230-1-60         |
|                 | MCA                                                       | A.          | 19                   | 13                   | 15                   | 15                   | 16                   | 25                   | 23                   | 28                   | 30                   |
|                 | Recommended Fuse Size                                     | A.          | 20                   | 15                   | 15                   | 15                   | 20                   | 30                   | 25                   | 30                   | 35                   |
|                 | MOCP - Fuse Rating                                        | A.          | 25                   | 15                   | 15                   | 15                   | 25                   | 35                   | 30                   | 35                   | 45                   |
|                 | Short Circuit Current Rating (SCCR)                       | kA          | 2.4                  | 2.4                  | 2.4                  | 2.4                  | 2.4                  | 2.4                  | 2.4                  | 2.4                  | 2.4                  |
| Operating Range | Cooling Outdoor DB Min - Max                              | *F(*C)      | -22 ~ 122 (-30 ~ 50) | -22 ~ 122 (-30 ~ 50) | -22 ~ 122 (-30 ~ 50) | -22 ~ 122 (-30 ~ 50) | -22 ~ 122 (-30 ~ 50) | -22 ~ 122 (-30 ~ 50) | -22 ~ 122 (-30 ~ 50) | -22 ~ 122 (-30 ~ 50) | -22 ~ 122 (-30 ~ 50) |
|                 | Heating Outdoor DB Min - Max                              | *F(*C)      | -22 ~ 86 (-30 ~ 30)  | -22 ~ 86 (-30 ~ 30)  | -22 ~ 86 (-30 ~ 30)  | -22 ~ 86 (-30 ~ 30)  | -22 ~ 86 (-30 ~ 30)  | -22 ~ 86 (-30 ~ 30)  | -22 ~ 86 (-30 ~ 30)  | -22 ~ 86 (-30 ~ 30)  | -22 ~ 86 (-30 ~ 30)  |
| Piping          | Total Piping Length                                       | ft (m)      | 82 (25)              | 82 (25)              | 82 (25)              | 82 (25)              | 98 (30)              | 164 (50)             | 164 (50)             | 213 (65)             | 213 (65)             |
|                 | Piping Lift*                                              | ft (m)      | 32 (10)              | 32 (10)              | 32 (10)              | 32 (10)              | 65 (20)              | 82 (25)              | 82 (25)              | 98 (30)              | 98 (30)              |
|                 | Pipe Connection Size - Liquid                             | in (mm)     | 1/4 (6.35)           | 1/4 (6.35)           | 1/4 (6.35)           | 1/4 (6.35)           | 1/4 (6.35)           | 3/8 (9.52)           | 3/8 (9.52)           | 3/8 (9.52)           | 3/8 (9.52)           |
|                 | Pipe Connection Size - Suction                            | in (mm)     | 1/2 (12.7)           | 3/8 (9.52)           | 3/8 (9.52)           | 1/2 (12.7)           | 1/2 (12.7)           | 5/8 (16)             | 5/8 (16)             | 5/8 (16)             | 5/8 (16)             |
| Refrigerant     | Refrigerant Type                                          |             | R410A                | R410A                | R410A                | R410A                | R410A                | R410A                | R410A                | R410A                | R410A                |
|                 | Charge                                                    | lbs (kg)    | 2.47 (1.12)          | 2.38 (1.08)          | 2.6 (1.18)           | 2.6 (1.18)           | 4.08 (1.85)          | 5.73 (2.6)           | 6.06 (2.75)          | 7.50 (3.40)          | 7.05 (3.2)           |
|                 | Additional Refrigerant (between Std & Max Piping Lengths) | Oz/ft (g/m) | 0.161 (15)           | 0.161 (15)           | 0.161 (15)           | 0.161 (15)           | 0.161 (15)           | 0.322 (30)           | 0.322 (30)           | 0.322 (30)           | 0.322 (30)           |
|                 | Metering Device                                           |             | EEV                  | EEV                  | EEV                  | EEV                  | EEV                  | EEV                  | EEV                  | EEV                  | EEV                  |
| Outdoor Coil    | Face Area                                                 | Sq. Ft.     | 4.04                 | 4.04                 | 4.67                 | 4.67                 | 5.9                  | 8.16                 | 8.14                 | 8.14                 | 8.16                 |
|                 | No. Rows                                                  |             | 2                    | 2                    | 2                    | 2                    | 2                    | 2                    | 3                    | 3                    | 2                    |
|                 | Fins per inch                                             |             | 21                   | 21                   | 20                   | 20                   | 20                   | 20                   | 18                   | 18                   | 20                   |
|                 | Circuits                                                  |             | 4                    | 4                    | 4                    | 4                    | 6                    | 4                    | 6                    | 6                    | 4                    |
| Compressor      | Type                                                      |             | Rotary Inverter      | Rotary Inverter      | Rotary Inverter      | Rotary Inverter      | Rotary Inverter      | Rotary Inverter      | Rotary Inverter      | Rotary Inverter      | Rotary Inverter      |
|                 | Model                                                     |             | KSK103D33UEZ3        | KSK103D33UEZ3        | KTN110D42UFZ         | KTN110D42UFZ         | KTM240D43UKT         | KTM240D43UKT         | KTF250D22UMT         | KTF250D22UMT         | KTF310D43UMT         |
|                 | Oil Type                                                  |             | VG74                 | VG74                 | VG74                 | VG74                 | VG74                 | VG74                 | VG74                 | VG74                 | VG74                 |
|                 | Oil Charge                                                | Fl. Oz.     | 10.48                | 10.48                | 11.84                | 11.84                | 20.97                | 20.97                | 22.66                | 22.66                | 33.8                 |
|                 | Rated Current                                             | RLA         | 11.5                 | 6.4                  | 6                    | 8.5                  | 14.25                | 14.8                 | 15                   | 18                   | 20                   |
| Airflow & Sound | Airflow                                                   | CFM         | 794.12               | 1324                 | 1323.53              | 1323.53              | 1764.71              | 2235.29              | 2235.29              | 2235.29              | 3000                 |
|                 | Sound Pressure                                            | dB(A)       | 54                   | 54.5                 | 54.5                 | 56                   | 59                   | 62                   | 63                   | 61.5                 | 64                   |

\* Condensing unit above or below the indoor unit

**NOTE: See the current compatibility chart for list of indoor unit and outdoor unit match ups.**

# PERFORMANCE

## High Wall

| System Size                     |       | 12K(115V)    | 6K(208/230V) | 9K(208/230V) | 12K(208/230V) | 18K(208/230V) | 24K(208/230V) | 30K(208/230V) | 36K(208/230V) |
|---------------------------------|-------|--------------|--------------|--------------|---------------|---------------|---------------|---------------|---------------|
| Energy Star*                    |       | YES          | YES          | YES          | YES           | YES           | YES           | NO            | NO            |
| Cooling System Tons             | Ton   | 1.00         | 0.50         | 0.75         | 1.00          | 1.50          | 2.00          | 2.50          | 3.00          |
| Cooling Rated Capacity          | Btu/h | 12,000       | 6,000        | 9,000        | 12,000        | 18,000        | 24,000        | 30,000        | 36,000        |
| Cooling Cap. Range Min - Max    | Btu/h | 3,500~13,200 | 3,400~12,000 | 3,300~14,300 | 3,300~14,300  | 8,900~19,400  | 6,850~27,000  | 8,900~32,600  | 9,300~38,800  |
| SEER2                           |       | 23.0         | 26.5         | 28.1         | 25.5          | 21.5          | 21.5          | 20.1          | 17.5          |
| EER2                            |       | 13.0         | 15.8         | 16.2         | 14.0          | 12.5          | 13.0          | 11.5          | 8.5           |
| Heating Rated Capacity (47°F)   | Btu/h | 12,000       | 7,000        | 12,000       | 12,000        | 18,000        | 29,000        | 30,000        | 36,000        |
| Heating Rated Capacity (17°F)   | Btu/h | 8,400        | 8,500        | 9,500        | 10,000        | 15,000        | 19,800        | 19,000        | 22,400        |
| Heating Rated Capacity (5°F)    | Btu/h | 7,100        | 7,500        | 10,500       | 12,000        | 18,000        | 25,200        | 20,600        | 20,400        |
| Heating Maximum Capacity (17°F) | Btu/h | 8,500        | 9,000        | 12,000       | 12,000        | 20,270        | 27,200        | 21,200        | 22,500        |
| Heating Cap. Range Min - Max    | Btu/h | 5,000~12,200 | 3,500~11,500 | 5,000~15,200 | 5,000~15,300  | 15,100~19,500 | 11,600~33,000 | 12,300~34,100 | 11,550~37,000 |
| HSPF2                           |       | 9.9          | 13.0         | 11.5         | 10.4          | 10.7          | 11.4          | 9.0           | 8.0           |
| COP (47°F)                      | W/W   | 3.52         | 3.92         | 3.81         | 3.88          | 3.10          | 3.40          | 2.90          | 2.51          |
| COP (17°F)                      | W/W   | 2.80         | 2.90         | 2.53         | 2.41          | 2.35          | 2.87          | 2.30          | 2.18          |
| COP (5°F)                       | W/W   | 2.18         | 2.10         | 1.80         | 1.80          | 1.80          | 1.80          | 1.94          | 1.80          |
| Capacity Maintenance (5°F)      | %     | 59%          | 107%         | 88%          | 100%          | 100%          | 87%           | 69%           | 57%           |
| Capacity Maintenance (17°F)     | %     | 70%          | 121%         | 79%          | 83%           | 83%           | 68%           | 63%           | 62%           |

\* Includes Cold Climate Designation

## Cassette

| System Size                     |       | 9K(208/230V) | 12K(208/230V) | 18K(208/230V) | 24K(208/230V) |
|---------------------------------|-------|--------------|---------------|---------------|---------------|
| Energy Star*                    |       | YES          | YES           | YES           | YES           |
| Cooling System Tons             | Ton   | 0.75         | 1.00          | 1.33          | 2.00          |
| Cooling Rated Capacity          | Btu/h | 9,000        | 12,000        | 16,000        | 24,000        |
| Cooling Cap. Range Min - Max    | Btu/h | 2,850~11,100 | 3,000~13,700  | 5,600~17,000  | 8,000~25,000  |
| SEER2                           |       | 20.5         | 22.3          | 20.0          | 20.5          |
| EER2                            |       | 13.0         | 12.7          | 12.5          | 11.0          |
| Heating Rated Capacity (47°F)   | Btu/h | 9,800        | 12,000        | 17,000        | 25,000        |
| Heating Rated Capacity (17°F)   | Btu/h | 9,000        | 9,900         | 15,900        | 21,000        |
| Heating Rated Capacity (5°F)    | Btu/h | 10,000       | 11,300        | 16,000        | 25,800        |
| Heating Maximum Capacity (17°F) | Btu/h | 11,800       | 14,000        | 17,000        | 25,800        |
| Heating Cap. Range Min - Max    | Btu/h | 2,250~12,500 | 2,000~15,300  | 8,700~21,000  | 11,800~27,000 |
| HSPF2                           |       | 10.3         | 10.2          | 9.5           | 11.5          |
| COP (47°F)                      | W/W   | 3.09         | 3.26          | 2.95          | 3.5           |
| COP (17°F)                      | W/W   | 1.91         | 2.54          | 2.44          | 2.64          |
| COP (5°F)                       | W/W   | 1.8          | 1.9           | 1.75          | 2             |
| Capacity Maintenance (5°F)      | %     | 102%         | 94%           | 94%           | 103%          |
| Capacity Maintenance (17°F)     | %     | 92%          | 83%           | 94%           | 84%           |

\* Includes Cold Climate Designation

## HIGH WALL (Sheet 2 of 2)

| MODEL          | COOLING                    |                  |       | OUTDOOR CONDITIONS (DB) |                  |                 |                |                |                |               |                |                |                |                 |                 |                 |
|----------------|----------------------------|------------------|-------|-------------------------|------------------|-----------------|----------------|----------------|----------------|---------------|----------------|----------------|----------------|-----------------|-----------------|-----------------|
|                | Indoor<br>Conditions<br>DB | WB               |       | (-22°F)<br>(-25°C)      | -13°F<br>(-25°C) | -4°F<br>(-20°C) | 0°F<br>(-17°C) | 5°F<br>(-15°C) | 17°F<br>(-8°C) | 47°F<br>(8°C) | 77°F<br>(25°C) | 86°F<br>(30°C) | 95°F<br>(35°C) | 104°F<br>(40°C) | 113°F<br>(45°C) | 122°F<br>(50°C) |
| 24K (208-230V) | 69.8°F<br>(21°C)           | 59°F<br>(15°C)   | TC    | 25.33                   | 25.02            | 24.71           | 21.71          | 23.65          | 21.89          | 28.18         | 25.19          | 24.00          | 22.65          | 21.45           | 18.45           | 15.41           |
|                |                            |                  | SC    | 18.11                   | 17.89            | 17.67           | 15.85          | 16.72          | 15.78          | 19.00         | 17.47          | 16.85          | 16.20          | 15.56           | 14.06           | 12.58           |
|                |                            |                  | Input | 1.26                    | 1.33             | 1.40            | 1.41           | 1.46           | 1.79           | 1.53          | 1.86           | 2.04           | 2.23           | 2.43            | 2.31            | 2.27            |
|                | 75.2°F<br>(24°C)           | 62.6°F<br>(17°C) | TC    | 26.11                   | 25.80            | 25.49           | 22.49          | 24.43          | 22.67          | 28.96         | 25.97          | 24.78          | 23.43          | 22.24           | 19.23           | 16.19           |
|                |                            |                  | SC    | 18.93                   | 18.70            | 18.48           | 16.31          | 17.71          | 16.43          | 21.00         | 18.83          | 17.96          | 16.99          | 16.12           | 13.94           | 11.73           |
|                |                            |                  | Input | 1.28                    | 1.34             | 1.41            | 1.42           | 1.48           | 1.81           | 1.54          | 1.87           | 2.05           | 2.24           | 2.44            | 2.32            | 2.28            |
|                | 80.6°F<br>(27°C)           | 66.2°F<br>(19°C) | TC    | 26.97                   | 26.66            | 26.35           | 23.36          | 25.29          | 23.53          | 29.83         | 26.84          | 25.64          | 24.30          | 23.10           | 20.09           | 17.05           |
|                |                            |                  | SC    | 19.48                   | 19.25            | 19.03           | 16.87          | 18.26          | 16.99          | 21.54         | 19.38          | 18.51          | 17.54          | 16.68           | 14.51           | 12.31           |
|                |                            |                  | Input | 1.29                    | 1.36             | 1.43            | 1.44           | 1.49           | 1.82           | 1.55          | 1.89           | 2.07           | 2.26           | 2.46            | 2.34            | 2.30            |
|                | 89.6°F<br>(32°C)           | 73.4°F<br>(23°C) | TC    | 28.76                   | 28.45            | 28.13           | 25.14          | 27.08          | 25.32          | 31.61         | 28.62          | 27.42          | 26.08          | 24.88           | 21.87           | 18.83           |
|                |                            |                  | SC    | 20.86                   | 20.63            | 20.40           | 18.23          | 19.64          | 18.36          | 22.93         | 20.76          | 19.89          | 18.91          | 18.05           | 15.86           | 13.66           |
|                |                            |                  | Input | 1.32                    | 1.39             | 1.46            | 1.47           | 1.52           | 1.85           | 1.59          | 1.92           | 2.10           | 2.29           | 2.49            | 2.37            | 2.33            |
| 30K (208-230V) | 69.8°F<br>(21°C)           | 59°F<br>(15°C)   | TC    | 33.23                   | 32.10            | 30.97           | 29.76          | 28.98          | 27.43          | 25.33         | 20.49          | 18.99          | 24.71          | 23.41           | 15.64           | 6.52            |
|                |                            |                  | SC    | 24.05                   | 23.23            | 22.42           | 20.12          | 19.71          | 18.99          | 18.02         | 15.53          | 14.82          | 17.89          | 16.92           | 13.36           | 6.52            |
|                |                            |                  | Input | 0.99                    | 1.08             | 1.17            | 1.18           | 1.27           | 1.40           | 1.69          | 1.34           | 1.51           | 3.01           | 3.31            | 2.34            | 1.52            |
|                | 75.2°F<br>(24°C)           | 62.6°F<br>(17°C) | TC    | 36.69                   | 35.56            | 34.43           | 33.23          | 32.44          | 30.89          | 28.79         | 23.96          | 22.45          | 28.17          | 26.87           | 19.10           | 9.98            |
|                |                            |                  | SC    | 22.88                   | 22.17            | 21.47           | 20.72          | 20.23          | 19.26          | 17.95         | 14.94          | 14.00          | 17.57          | 16.75           | 11.91           | 6.22            |
|                |                            |                  | Input | 1.96                    | 2.05             | 2.13            | 2.15           | 2.24           | 2.37           | 2.66          | 2.31           | 2.47           | 3.98           | 4.28            | 3.31            | 2.49            |
|                | 80.6°F<br>(27°C)           | 66.2°F<br>(19°C) | TC    | 39.85                   | 38.72            | 37.59           | 36.38          | 35.60          | 34.05          | 31.95         | 27.11          | 25.61          | 31.33          | 30.03           | 22.26           | 13.14           |
|                |                            |                  | SC    | 23.50                   | 22.83            | 22.17           | 21.46          | 20.99          | 20.08          | 18.84         | 15.99          | 15.10          | 18.48          | 17.71           | 13.13           | 7.75            |
|                |                            |                  | Input | 2.62                    | 2.71             | 2.79            | 2.81           | 2.90           | 3.03           | 3.32          | 2.97           | 3.13           | 4.64           | 4.94            | 3.97            | 3.15            |
|                | 89.6°F<br>(32°C)           | 73.4°F<br>(23°C) | TC    | 45.88                   | 44.76            | 43.63           | 42.42          | 41.64          | 40.09          | 37.98         | 33.15          | 31.64          | 37.37          | 36.06           | 28.29           | 19.17           |
|                |                            |                  | SC    | 23.96                   | 23.38            | 22.79           | 22.16          | 21.75          | 20.94          | 19.84         | 17.31          | 16.53          | 19.52          | 18.84           | 14.78           | 10.01           |
|                |                            |                  | Input | 3.59                    | 3.68             | 3.77            | 3.79           | 3.87           | 4.00           | 4.30          | 3.94           | 4.11           | 5.62           | 5.92            | 4.94            | 4.12            |
| 36K (208-230V) | 69.8°F<br>(21°C)           | 59°F<br>(15°C)   | TC    | 34.73                   | 33.79            | 32.85           | 31.66          | 31.22          | 25.11          | 29.92         | 28.89          | 28.36          | 29.08          | 23.61           | 19.48           | 7.62            |
|                |                            |                  | SC    | 23.26                   | 22.63            | 22.01           | 21.00          | 20.74          | 17.58          | 20.03         | 19.48          | 19.16          | 19.48          | 16.68           | 14.65           | 7.35            |
|                |                            |                  | Input | 1.23                    | 1.34             | 1.45            | 1.31           | 1.38           | 1.69           | 1.97          | 2.48           | 2.95           | 4.20           | 3.15            | 2.83            | 1.49            |
|                | 75.2°F<br>(24°C)           | 62.6°F<br>(17°C) | TC    | 37.72                   | 36.79            | 35.85           | 34.66          | 34.22          | 28.11          | 32.91         | 31.89          | 31.36          | 32.07          | 26.61           | 22.48           | 10.62           |
|                |                            |                  | SC    | 24.67                   | 24.05            | 23.44           | 22.66          | 22.38          | 18.38          | 21.52         | 20.85          | 20.50          | 20.97          | 17.40           | 14.70           | 6.94            |
|                |                            |                  | Input | 1.38                    | 1.49             | 1.61            | 1.46           | 1.53           | 1.84           | 2.13          | 2.63           | 3.10           | 4.35           | 3.30            | 2.98            | 1.65            |
|                | 80.6°F<br>(27°C)           | 66.2°F<br>(19°C) | TC    | 40.77                   | 39.83            | 38.90           | 37.70          | 37.27          | 31.16          | 35.96         | 34.94          | 34.41          | 35.12          | 29.66           | 25.52           | 13.67           |
|                |                            |                  | SC    | 25.89                   | 25.29            | 24.70           | 23.94          | 23.66          | 19.78          | 22.83         | 22.18          | 21.85          | 22.30          | 18.83           | 16.21           | 8.68            |
|                |                            |                  | Input | 1.52                    | 1.64             | 1.75            | 1.60           | 1.68           | 1.99           | 2.27          | 2.78           | 3.25           | 4.49           | 3.44            | 3.13            | 1.79            |
|                | 89.6°F<br>(32°C)           | 73.4°F<br>(23°C) | TC    | 46.49                   | 45.55            | 44.62           | 43.42          | 42.99          | 36.88          | 41.68         | 40.66          | 40.13          | 40.84          | 35.38           | 31.24           | 19.39           |
|                |                            |                  | SC    | 26.58                   | 26.05            | 25.51           | 24.83          | 24.58          | 21.09          | 23.83         | 23.25          | 22.94          | 23.35          | 20.23           | 17.87           | 11.09           |
|                |                            |                  | Input | 1.80                    | 1.91             | 2.02            | 1.88           | 1.95           | 2.26           | 2.54          | 3.05           | 3.52           | 4.77           | 3.72            | 3.40            | 2.06            |

## LEGEND

DB - Dry Bulb

WB - Wet Bulb

TC - Total Net Capacity (1000 Btu/hour)

SC - Sensible Capacity (1000 Btu/hour)

Input - Total Power (kW)

**NOTE: Values in grey are extrapolated based on tested performance.**

## WIRING


All wires must be sized per NEC (National Electrical Code) or CEC (Canadian Electrical Code) and local codes. Use Electrical Data table MCA (minimum circuit amps) and MOCP (maximum over current protection) to correctly size the wires and the disconnect fuse or breakers respectively.

### Recommended Connection Method for Power and Communication Wiring:

The main power is supplied to the outdoor unit. The field supplied 14/3 power/communication wiring, from the outdoor unit to the indoor unit, consists of four (4) wires and provides the power for the indoor unit. Two wires are high voltage AC power, one is communication wiring and the other is a ground wire. Wiring between indoor and outdoor unit is polarity sensitive. The use of BX wire is **NOT** recommended.

If installed in a high Electromagnetic field (EMF) area and communication issues exists, a 14/2 stranded shielded wire can be used to replace L2 and (S) between outdoor unit and indoor unit landing the shield onto ground in the outdoor unit only.

|                                                                                                  |
|--------------------------------------------------------------------------------------------------|
|  <b>CAUTION</b> |
| <b>EQUIPMENT DAMAGE HAZARD</b>                                                                   |
| Failure to follow this caution may result in equipment damage or improper operation.             |


|                                                                                                                                                                                           |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  <b>CAUTION</b>                                                                                          |
| <b>EQUIPMENT DAMAGE HAZARD</b>                                                                                                                                                            |
| Failure to follow this caution may result in equipment damage or improper operation.                                                                                                      |
| Be sure to comply with local codes while running wire from the indoor unit to the outdoor unit.                                                                                           |
| Every wire must be connected firmly. Loose wiring may cause the terminal to overheat or result in unit malfunction. A fire hazard may also exist. Ensure all wiring is tightly connected. |
| No wire should touch the refrigerant tubing, compressor or any moving parts.                                                                                                              |
| Disconnecting means must be provided and shall be located within sight and readily accessible from the air conditioner.                                                                   |

**NOTE: Matches with Multi-Family and Residential Fan Coils require separate power for the indoor and outdoor unit. A 24V interface kit is required for compatibility. Refer to the 24V Interface Kit Installation Manual.**

## Sound Pressure in Octave Bands

|                     | Frequency (Hz) | 63   | 125  | 250  | 500  | 1000 | 2000 | 4000 | 8000 |
|---------------------|----------------|------|------|------|------|------|------|------|------|
| <b>12 K (115 V)</b> | Cooling dB(A)  | 58.5 | 55.9 | 58.1 | 51.1 | 46.0 | 41.4 | 34.8 | 28.6 |
|                     | Heating dB(A)  | 58.8 | 57.4 | 57.4 | 53.6 | 47.3 | 43.5 | 37.2 | 31.9 |
|                     | Indoor dB(A)   | 40.8 | 33.0 | 34.3 | 34.1 | 33.7 | 26.6 | 19.4 | 14.1 |
| <b>6K (208V)</b>    | Cooling dB(A)  | 57.5 | 53.2 | 56.9 | 49.6 | 45.2 | 41.4 | 36.5 | 31   |
|                     | Heating dB(A)  | 57.3 | 53.2 | 58.4 | 51.2 | 46.1 | 43.6 | 38.5 | 34.9 |
|                     | Indoor dB(A)   | 38.1 | 30.9 | 33.6 | 33.5 | 31.7 | 25.9 | 22.6 | 16.7 |
| <b>9K (208V)</b>    | Cooling dB(A)  | 53.1 | 51.2 | 52.6 | 49.5 | 40.1 | 36.5 | 29.1 | 26.3 |
|                     | Heating dB(A)  | 57.6 | 55.0 | 52.3 | 50.1 | 45.5 | 42.2 | 36.8 | 30.0 |
|                     | Indoor dB(A)   | 45.2 | 38.8 | 38.1 | 40.8 | 38.9 | 35.1 | 24.0 | 14.8 |
| <b>12K (208V)</b>   | Cooling dB(A)  | 54.4 | 55.4 | 51.6 | 52.6 | 42.1 | 37.9 | 31.5 | 30.1 |
|                     | Heating dB(A)  | 63.7 | 59.9 | 55.4 | 52.2 | 48.7 | 45.1 | 39.1 | 34.8 |
|                     | Indoor dB(A)   | 39.5 | 31.0 | 33.3 | 32.5 | 31.5 | 23.9 | 17.9 | 14.4 |
| <b>18K (208V)</b>   | Cooling dB(A)  | 56.5 | 60.8 | 56.2 | 53.3 | 51.8 | 46.0 | 38.1 | 33.2 |
|                     | Heating dB(A)  | 58.8 | 63.5 | 57.9 | 54.3 | 51.7 | 45.0 | 38.9 | 31.2 |
|                     | Indoor dB(A)   | 39.5 | 41.5 | 41.9 | 41.6 | 43.0 | 37.5 | 33.5 | 21.4 |
| <b>24K (208V)</b>   | Cooling dB(A)  | 68.3 | 69.2 | 62.9 | 56.3 | 54.6 | 50.4 | 46.5 | 41.3 |
|                     | Heating dB(A)  | 65.9 | 68.6 | 65.3 | 58.7 | 57.5 | 53.8 | 48.5 | 44.5 |
|                     | Indoor dB(A)   | 44.3 | 38.8 | 42.9 | 39.4 | 40.5 | 34.5 | 26.2 | 25.6 |
| <b>30K (208V)</b>   | Cooling dB(A)  | 62.4 | 58.3 | 56.8 | 55.4 | 51.4 | 45.5 | 42.5 | 35.1 |
|                     | Heating dB(A)  | 62.5 | 58.4 | 57.5 | 54.6 | 52.4 | 48.4 | 45.0 | 38.7 |
|                     | Indoor dB(A)   | 47.2 | 38.9 | 45.8 | 42.3 | 42.2 | 37.6 | 28.4 | 23.8 |
| <b>36K (208V)</b>   | Cooling dB(A)  | 56.8 | 61.8 | 61.4 | 54.4 | 50.7 | 45.3 | 43.2 | 37.1 |
|                     | Heating dB(A)  | 58.4 | 65.0 | 62.9 | 57.0 | 54.9 | 50.5 | 46.9 | 42.3 |
|                     | Indoor dB(A)   | 43.5 | 40.6 | 45.6 | 42.2 | 41.9 | 37.3 | 28.6 | 21.5 |

## Outdoor Unit Sound Pressure Test Conditions



A220462

Fig. 9 —Outdoor Unit Sound Pressure Test

NOTE:  $H=0.5 \times \text{Height of outdoor unit}$ 

|                | INDOOR CONDITION |               | OUTDOOR CONDITION |               |
|----------------|------------------|---------------|-------------------|---------------|
|                | DB               | WB            | DB                | WB            |
| <b>Cooling</b> | 80.6°F (27°C)    | 66.2°F (19°C) | 95°F (35°C)       | 75.2°F (24°C) |
| <b>Heating</b> | 68°F (20°C)      | 59°F (15°C)   | 44.6°F (7°C)      | 42.8°F (6°C)  |

ELECTRICAL DATA

| SYSTEM SIZE                    | 12 K                                                                     | 9K/6K        | 12K          | 18K          | 24K          | 30K          | 36K          |
|--------------------------------|--------------------------------------------------------------------------|--------------|--------------|--------------|--------------|--------------|--------------|
| V-Ph-Hz                        | 115-1-60                                                                 | 208/230-1-60 | 208/230-1-60 | 208/230-1-60 | 208/230-1-60 | 208/230-1-60 | 208/230-1-60 |
| Power supply                   | 3Wires: includes ground wire (Outdoor); 115V-1Ph-60Hz, 208/230V-1Ph-60Hz |              |              |              |              |              |              |
| Interconnection to Indoor Unit | Yes                                                                      |              |              |              |              |              |              |
| Shielded Wire (Yes/No)         | Yes                                                                      |              |              |              |              |              |              |

\*Permissible limits of the voltage range at which the unit will operate satisfactorily.

LEGEND  
FLA - Full Load Amps  
MCA - Minimum Circuit Amps  
RLA - Rated Load Amps

Fan and Motor Specifications

| SYSTEM SIZE      |         | 12K                          | 6K                           | 9K                           | 12K                          | 18K                          | 24K                          | 30K                          | 36K                          |
|------------------|---------|------------------------------|------------------------------|------------------------------|------------------------------|------------------------------|------------------------------|------------------------------|------------------------------|
|                  |         | (115 V)                      | (208/230 V)                  | (208/230 V)                  | (208/230 V)                  | (208/230 V)                  | (208/230 V)                  | (208/230 V)                  | (208/230 V)                  |
| Material         | -       | Acrylonitrile Styrene +20%GF | Acrylonitrile Styrene +20%GF | Acrylonitrile Styrene +20%GF | Acrylonitrile Styrene +20%GF | Acrylonitrile Styrene +20%GF | Acrylonitrile Styrene +20%GF | Acrylonitrile Styrene +20%GF | Acrylonitrile Styrene +20%GF |
| Type             | -       | ZL-421*133*8-3KN             | ZL-421*133*8-3KN             | ZL-434*144*8-3KN             | ZL-434*144*8-3KN             | ZL-535*133*12-3KFN           | ZL-560*139*12-3KN            | ZL-560*139*12-3KN            | ZL-560*139*12-3KN            |
| Diameter         | inch    | 16.58 (421)                  | 16.58 (421)                  | 17.09 (434)                  | 17.09 (434)                  | 21.06 (535)                  | 22.05 (560)                  | 22.05 (560)                  | 22.05 (560)                  |
| Height           | inch    | 5.24 (133)                   | 5.24 (133)                   | 5.67(144)                    | 5.67(144)                    | 5.24 (133)                   | 5.47 (139)                   | 5.47 (139)                   | 5.47 (139)                   |
| Model            | -       | ZKFN-34-10-1                 | ZKFN-34-10-1                 | ZKFN-34-10-1                 | ZKFN-34-10-1                 | ZKFN-80-8-3                  | ZKFN-120-8-2                 | ZKFN-120-8-2                 | ZKFN-120-8-2                 |
| FLA              | A       | 0.4                          | 0.4                          | 0.4                          | 0.4                          | 0.76                         | 0.5                          | 1.0                          | 1.35                         |
| Rated HP         | HP      | 0.045                        | 0.045                        | 0.045                        | 0.045                        | 0.11                         | 0.16                         | 0.16                         | 0.16                         |
| Output           | W       | 34                           | 34                           | 34                           | 34                           | 80                           | 120                          | 120                          | 120                          |
| Type             | -       | DC                           | DC                           | DC                           | DC                           | DC                           | DC                           | DC                           | DC                           |
| Insulation class | -       | B                            | B                            | B                            | B                            | E                            | E                            | E                            | E                            |
| Safe class       | -       | IP24                         | IP24                         | IP24                         | IP24                         | IPX4                         | IPX4                         | IPX4                         | IPX4                         |
| Input            | W       | 100.3                        | 100.3                        | 100.3                        | 100.3                        | 120                          | 173                          | 173                          | 173                          |
| Range of current | Amps    | 0.823±10%                    | 0.823±10%                    | 0.823±10%                    | 0.823±10%                    | 1±20%                        | 1.48±10%                     | 1.39±10%                     | 1.39±10%                     |
| Rated current    | Amps    | 0.89                         | 0.89                         | 0.89                         | 0.89                         | 0.82                         | 1.21                         | 1.21                         | 1.21                         |
| Capacitor        | µF      | NA                           | NA                           | NA                           | NA                           | NA                           | NA                           | NA                           | NA                           |
| Speed            | rev/min | 800/700/600                  | 800/700/600                  | 730/660/560                  | 730/660/560                  | 780/700/550                  | 950/800/500                  | 900/700/500                  | 950/700/500<br>950/700/500‡  |
| Rated RPM        | rev/min | 800                          | 800                          | 730                          | 730                          | 780                          | 950                          | 900                          | 950                          |
| Max. Input       | W       | 100.3                        | 100.3                        | 100.3                        | 100.3                        | 120.0                        | 170.0                        | 170.0                        | 170.0                        |

NOTE: ‡ Only Compatible with AHU

CONNECTION DIAGRAMS




Fig. 10 —Connection Diagram 12K (115V)

A220424





Fig. 11 —Connection Diagram Sizes 6K-36K (208/230-1-60V)

A220425

WIRING DIAGRAMS (CONTINUED)



Notes:  
COMPONENT IN DASH  
LINE IS OPTIONAL  
OR FIELD WIRING


A220429

Fig. 15 — Wiring Diagram Sizes 24-36K (208/230V)

| CODE     | PART NAME                    |
|----------|------------------------------|
| JX1      | TERMINAL BLOCK               |
| COMP_TOP | COMP. TOP OLP TEMP. SENSOR   |
| EEV      | ELECTRIC EXPANSIVE VALVE     |
| FM1      | DC FAN MOTOR                 |
| COMP     | COMPRESSOR                   |
| HEAT_Y   | CRACKCASE HEATER             |
| CT1      | AC CURRENT DETECTOR          |
| H-PRO    | HIGH PRESSURE SWITCH         |
| L-PRO    | LOW PRESSURE SWITCH          |
| SV       | REVERSE VALVE                |
| TP       | COMP. DISCHARGE TEMP. SENSOR |
| T3       | COIL TEMP. SENSOR            |
| T4       | OUTDOOR AMBIENT TEMP. SENSOR |
| HEAT_D   | CHASIS HEATER                |



## Product Data



**Fig. 1 — Sizes 06K - 36K**



**Fig. 2 — Remote Controller**

**NOTE:** Images are for illustration purposes only. Actual models may differ slightly.

### TABLE OF CONTENTS

|                                            | PAGE |
|--------------------------------------------|------|
| INDUSTRY LEADING FEATURES / BENEFITS ..... | 1    |
| MODEL NUMBER NOMENCLATURE .....            | 3    |
| STANDARD FEATURES AND ACCESSORIES .....    | 4    |
| DIMENSIONS - INDOOR .....                  | 5    |
| CLEARANCES.....                            | 5    |
| SPECIFICATIONS .....                       | 6    |
| COMPATIBILITY .....                        | 6    |
| APPLICATION DATA .....                     | 7    |
| WIRING.....                                | 8    |
| AIRFLOW DATA .....                         | 9    |
| AIR THROW DATA .....                       | 9    |
| AIR MOISTURE .....                         | 9    |
| SOUND PRESSURE .....                       | 9    |
| FAN AND MOTOR SPECIFICATIONS .....         | 10   |
| WIRING DIAGRAM.....                        | 11   |
| GUIDE SPECIFICATIONS.....                  | 12   |

### INDUSTRY LEADING FEATURES / BENEFITS

#### A PERFECT BALANCE BETWEEN BUDGET LIMITS, ENERGY SAVINGS AND COMFORT.

The **40MAHB** series ductless systems are a matched combination of an outdoor condensing unit and an indoor fan coil unit connected only by refrigerant tubing and wires.

The fan coil is mounted on the wall, near the ceiling. This selection of fan coils permits creative solutions to design problems such as:

- Add-ons to current space (an office or family room addition)
- Special space requirements
- When changes in the load cannot be handled by the existing system
- When adding air conditioning to spaces that are heated by hydronic or electric heat and have no ductwork
- Historical renovations or any application where preserving the look of the original structure is essential.

The ideal compliment to your ducted system when it is impractical or prohibitively expensive to use ductwork. These compact indoor fan coil units take up very little space in the room and do not obstruct windows. The fan coils are attractively styled to blend with most room decors.

Advanced system components incorporate innovative technology to provide reliable cooling performance at low sound levels.

## LOW SOUND LEVELS

When noise is a concern, the ductless systems are the answer. The indoor units are whisper quiet. There are no compressors indoors, either in the conditioned space or directly over it, and there is none of the noise usually generated by air being forced through ductwork.

## SECURE OPERATION

If security is an issue, outdoor and indoor units are connected only by refrigerant piping and wiring to prevent intruders from crawling through ductwork. In addition, since the outdoor units can be installed close to an outside wall, coils are protected from vandals and severe weather.

## FAST INSTALLATION

This compact ductless system is simple to install. A mounting bracket is standard with the indoor units and only wire and piping need to be run between the indoor and outdoor units. These units are fast and easy to install ensuring minimal disruption to customers in the home or workplace. This makes the 40MAHB ductless systems the equipment of choice, especially in retrofit situations.

## SIMPLE SERVICING AND MAINTENANCE

Removing the top panel on outdoor units provides immediate access to the control compartment, providing a service technician access to check unit operation. In addition, the draw-thru design of the outdoor section means that dirt accumulates on the outside surface of the coil. Coils can be cleaned quickly from the inside using a pressure hose and detergent.

On all indoor units, the New Removable Blower assembly and Hood Style cover make maintenance and service less complicated. Additionally, due to Newly Designed, easy-to-use and cleanable filters, service and maintenance expense is reduced. In addition, these high wall systems have extensive self-diagnostics to assist in troubleshooting.

## BUILT-IN RELIABILITY

Ductless system indoor and outdoor units are designed to provide years of trouble-free operation.

The high wall indoor units include protection against freeze-up and high evaporator temperatures on heat pumps.

The condensing units on heat pumps are protected by a three minute time delay before the compressor starts the over-current protection and the high temperature protection.

## INDIVIDUAL ROOM COMFORT

Maximum comfort is provided because each space can be controlled individually based on usage pattern. The air sweep feature provided permits optimal room air mixing to eliminate hot and cold spots for occupant comfort. Each unit is equipped with a New Humidity Sensor to keep your space comfortable. Year-round comfort can be provided with heat pumps.

## ECONOMICAL OPERATION

The ductless system design allows individual room heating or cooling when required. Equipped with a New Occupancy Sensor, the system can be set to only operate when the room is being utilized. There is no need to run large supply-air fans or chilled water pumps to handle a few spaces with unique load patterns. In addition, because air is moved only in the space required, no energy is wasted while air moves through the ducts.

## EASY-TO-USE CONTROLS

The high wall units have microprocessor-based controls to provide the ultimate in comfort and efficiency. The user friendly wireless remote control provides the interface between the user and the unit.

## ACCESSORIES

Customizing these ductless systems to your application is easily accomplished. Adding a condensate pump accessory to the high wall fan coil provides installation flexibility.

## OPTIONAL WIRED CONTROLLER


Optional 24V Interface for 3rd Party Control

Optional Wi-Fi Kit for Smart Phone Control

## AGENCY LISTING

All systems are listed with AHRI (Air Conditioning, Heating & Refrigeration Institute), and ETL.

MODEL NUMBER NOMENCLATURE



Use of the AHRI Certified  
TM Mark indicates a  
manufacturer's  
participation in the  
program For verification  
of certification for individual  
products, go to  
[www.ahridirectory.org](http://www.ahridirectory.org).



## STANDARD FEATURES AND ACCESSORIES

|                                                  |   |
|--------------------------------------------------|---|
| <b>Ease Of Installation</b>                      |   |
| Mounting Brackets                                | S |
| Low Voltage Controls                             | S |
| <b>Comfort Features</b>                          |   |
| Microprocessor Controls                          | S |
| Wired Remote Controller                          | A |
| Wireless Remote Controller                       | S |
| Automatic Up-Down Airflow Louver Swing           | S |
| Air Direction Control                            | S |
| Auto Restart Function                            | S |
| Cold Blow Protection On Heat Pumps               | S |
| Freeze Protection Mode on Heat Pumps             | S |
| Turbo Mode                                       | S |
| Silence Mode                                     | S |
| Auto Changeover on Heat Pumps                    | S |
| Follow Me                                        | S |
| <b>Energy Saving Features</b>                    |   |
| Sleep Mode                                       | S |
| Stop/Start Timer                                 | S |
| 46° F Heating Mode (Heating Setback)             | S |
| <b>Safety And Reliability</b>                    |   |
| Indoor Coil Freeze Protection                    | S |
| Indoor Coil High Temp Protection in Heating Mode | S |
| Aluminum Hydrophilic pre-coated fins             | S |
| <b>Ease Of Service And Maintenance</b>           |   |
| Cleanable Filters                                | S |
| Diagnostics                                      | S |
| Carbon Filter                                    | S |
| <b>Application Flexibility</b>                   |   |
| Condensate Pumps                                 | A |

### Legend

S - Standard

A - Accessory

## Accessories

| Accessory No. | Description                              | For Models      |
|---------------|------------------------------------------|-----------------|
| KSACN0801AAA  | WIRED REMOTE CONTROL 7 DAY PROGRAMMABLE  | All Sizes       |
| KSACN0101AAA  | WIRED REMOTE CONTROL WITH TIMER FUNCTION | All Sizes       |
| KSAIC0301230  | 24V INTERFACE KIT 230V                   | 208/230V MODELS |
| KSAIF0601AAA  | Wi-Fi Kit High Wall Mid-Tier             | All Sizes       |

DIMENSIONS - INDOOR

| UNIT SIZES |           | 12K          | 6K           | 9K           | 12K          | 18K          | 24K          | 30K          | 36K          |
|------------|-----------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|
| Voltages   |           | 115V         | 208/230V     | 208/230V     | 208/230V     | 208/230V     | 208/230V     | 208/230V     | 208/230V     |
| Height (H) | in (mm)   | 11.61 (295)  | 11.61 (295)  | 11.61 (295)  | 11.61 (295)  | 12.56 (319)  | 14.57 (370)  | 14.57 (370)  | 14.57 (370)  |
| Width (W)  | in (mm)   | 31.3 (795)   | 31.3 (795)   | 31.3 (795)   | 31.3 (795)   | 37.99 (965)  | 44.88 (1140) | 44.88 (1140) | 44.88 (1140) |
| Depth (D)  | in (mm)   | 8.86 (225)   | 8.86 (225)   | 8.86 (225)   | 8.86 (225)   | 9.41 (239)   | 10.83 (275)  | 10.83 (275)  | 10.83 (275)  |
| Net Weight | lbs (kgs) | 22.93 (10.4) | 22.71 (10.3) | 22.71 (10.3) | 22.93 (10.4) | 27.12 (12.3) | 43.65 (19.8) | 43.65 (19.8) | 43.65 (19.8) |

CLEARANCES




Fig. 3 — Indoor Unit Clearances

**NOTE:** The top clearance recommended for proper return airflow is 5.9in (15cm). Reduction of this clearance may decrease unit performance. This may be reduced to 2.0in (80mm) as long as the right and left clearances are achieved.

## SPECIFICATIONS

| System          | Size                                          |              | 12                                    | 6               | 9               | 12              | 18              | 24              | 30              | 36              |
|-----------------|-----------------------------------------------|--------------|---------------------------------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|
|                 | Indoor Model                                  |              | 40MAHBQ12XA1                          | 40MAHBQ06XA3    | 40MAHBQ09XA3    | 40MAHBQ12XA3    | 40MAHBQ18XA3    | 40MAHBQ24XA3    | 40MAHBQ30XA3    | 40MAHBQ36XA3    |
| Electrical      | Voltage, Phase, Cycle                         | V/Ph/Hz      | 115-1-60                              | 208/230-1-60    | 208/230-1-60    | 208/230-1-60    | 208/230-1-60    | 208/230-1-60    | 208/230-1-60    | 208/230-1-60    |
|                 | Power Supply                                  |              | Indoor unit powered from outdoor unit |                 |                 |                 |                 |                 |                 |                 |
|                 | MCA                                           | A.           | 0.2500                                | 0.3125          | 0.3125          | 0.3125          | 0.1625          | 0.6250          | 0.6250          | 0.6250          |
| Controls        | Wireless Remote Controller (*F/C Convertible) |              | Standard                              | Standard        | Standard        | Standard        | Standard        | Standard        | Standard        | Standard        |
|                 | Wired Remote Controller (*F/C Convertible)    |              | Optional                              | Optional        | Optional        | Optional        | Optional        | Optional        | Optional        | Optional        |
|                 | 24V Interface for 3rd Part Thermostat Control |              | Optional                              | Optional        | Optional        | Optional        | Optional        | Optional        | Optional        | Optional        |
|                 | Wi-Fi Control for Phone App Control           |              | Optional                              | Optional        | Optional        | Optional        | Optional        | Optional        | Optional        | Optional        |
| Operating Range | Cooling Indoor DB Min - Max                   | *F(*C)       | 63~90 (17~32)                         | 63~90 (17~32)   | 63~90 (17~32)   | 63~90 (17~32)   | 63~90 (17~32)   | 63~90 (17~32)   | 63~90 (17~32)   | 63~90 (17~32)   |
|                 | Heating Indoor DB Min -Max                    | *F(*C)       | 32~86 (0~30)                          | 32~86 (0~30)    | 32~86 (0~30)    | 32~86 (0~30)    | 32~86 (0~30)    | 32~86 (0~30)    | 32~86 (0~30)    | 32~86 (0~30)    |
| Piping          | Pipe Connection Size - Liquid                 | in (mm)      | 1/4 (6.35)                            | 1/4 (6.35)      | 1/4 (6.35)      | 1/4 (6.35)      | 1/4 (6.35)      | 3/8 (9.52)      | 3/8 (9.52)      | 3/8 (9.52)      |
|                 | Pipe Connection Size - Suction                | in (mm)      | 1/2 (12.7)                            | 3/8 (9.52)      | 3/8 (9.52)      | 1/2 (12.7)      | 1/2 (12.7)      | 5/8 (16)        | 5/8 (16)        | 5/8 (16)        |
| Indoor Coil     | Face Area                                     | Sq. Ft.      | 2.15                                  | 2.15            | 2.15            | 2.15            | 2.75            | 3.60            | 3.60            | 3.60            |
|                 | No. Rows                                      |              | 2                                     | 2               | 2               | 2               | 2               | 3               | 3               | 3               |
|                 | Fins per inch                                 |              | 20                                    | 20              | 20              | 20              | 20              | 20              | 20              | 20              |
|                 | Circuits                                      |              | 3                                     | 3               | 3               | 3               | 4               | 7               | 7               | 7               |
| Indoor          | Unit Width                                    | in (mm)      | 31.3 (795)                            | 31.3 (795)      | 31.3 (795)      | 31.3 (795)      | 37.99 (965)     | 44.88 (1140)    | 44.88 (1140)    | 44.88 (1140)    |
|                 | Unit Height                                   | in (mm)      | 11.61 (295)                           | 11.61 (295)     | 11.61 (295)     | 11.61 (295)     | 12.56 (319)     | 14.57 (370)     | 14.57 (370)     | 14.57 (370)     |
|                 | Unit Depth                                    | in (mm)      | 8.86 (225)                            | 8.86 (225)      | 8.86 (225)      | 8.86 (225)      | 9.41 (239)      | 10.83 (275)     | 10.83 (275)     | 10.83 (275)     |
|                 | Net Weight                                    | lbs (kg)     | 22.93 (10.4)                          | 22.71 (10.3)    | 22.71 (10.3)    | 22.93 (10.4)    | 27.12 (12.3)    | 43.65 (19.8)    | 43.65 (19.8)    | 43.65 (19.8)    |
|                 | Fan Speeds Numbers                            |              | 4                                     | 4               | 4               | 4               | 4               | 4               | 4               | 4               |
|                 | Airflow (lowest to highest)                   | CFM          | 235/294/353/412                       | 176/229/335/382 | 176/229/335/382 | 176/229/335/382 | 306/376/524/635 | 319/414/611/719 | 382/505/646/843 | 382/506/639/843 |
|                 | Sound Pressure (lowest to highest)            | dB(A)        | 24/30/41/47                           | 32/34/38/47     | 32/34/38/47     | 30/32/37/47     | 37/40/46/48     | 37/39/44/52     | 38/41/46/52     | 39/41/46/52     |
|                 | Air throw Data                                | ft (m)       | 27.9 (8.5)                            | 21.3 (7.1)      | 24.9 (7.6)      | 26.2 (8.0)      | 27.9 (8.5)      | 31.5 (9.6)      | 33.8 (10.3)     | 33.8 (10.3)     |
|                 | Moisture removal                              | Pint/h (L/h) | 58(1.16)                              | 16 (0.32)       | 18(0.35)        | 56(1.11)        | 110(2.18)       | 132(2.6)        | 188(3.7)        | 291(5.75)       |
|                 | Field Drain Pipe Size O.D.                    | in (mm)      | 0.625 (16)                            | 0.625 (16)      | 0.625 (16)      | 0.625 (16)      | 0.625 (16)      | 0.625 (16)      | 0.625 (16)      | 0.625 (16)      |

\* Performance may vary based on the Outdoor unit matched to. See compatible Outdoor Units pages for Performance Data

## COMPATIBILITY

|                          |              |              |              |              |              |              |              |              |
|--------------------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|
| Indoor Unit              | 40MAHBQ12XA1 | 40MAHBQ06XA3 | 40MAHBQ09XA3 | 40MAHBQ12XA3 | 40MAHBQ18XA3 | 40MAHBQ24XA3 | 40MAHBQ30XA3 | 40MAHBQ36XA3 |
| Outdoor Unit Single Zone | 38MARBQ12AA1 |              | 38MARBQ09AA3 | 38MARBQ12AA3 | 38MARBQ18AA3 | 38MARBQ24AA3 | 38MARBQ30AA3 | 38MARBQ36AA3 |
| Outdoor Unit Multi-zone  |              | 38MGRQ18B-3  |              |              |              |              |              |              |
|                          |              | 38MGRQ24C-3  |              |              |              |              |              |              |
|                          |              | 38MGRQ30D-3  |              |              |              |              |              |              |
|                          |              | 38MGRQ36D-3  |              |              |              |              |              |              |
|                          |              | 38MGRQ48E-3  |              |              |              |              |              |              |

Backward compatible with 38MAR Single Zone Systems.

## WIRING

All wires must be sized per NEC (National Electrical Code) or CEC (Canadian Electrical Code) and local codes. Use Electrical Data table MCA (minimum circuit amps) and MOCP (maximum over current protection) to correctly size the wires and the disconnect fuse or breakers respectively.

Per the caution note, only stranded copper conductors with a 600 volt insulation rating wire must be used.

### Recommended Connection Method for Power and Communication Wiring:

The main power is supplied to the outdoor unit. The field supplied 14/3 stranded wire with ground with a 600 volt insulation rating, power/communication wiring from the outdoor unit to indoor unit consists of four (4) wires and provides the power for the indoor unit. Two wires are line voltage AC power, one is communication wiring (S) and the other is a ground wire. Wiring between indoor and outdoor unit is polarity sensitive. The use of BX wire is NOT recommended.

If installed in a high Electromagnetic field (EMF) area and communication issues exists, a 14/2 stranded shielded wire can be used to replace L2/N and (S) between outdoor unit and indoor unit landing the shield onto ground in the outdoor unit only.



## CAUTION

### EQUIPMENT DAMAGE HAZARD

Failure to follow this caution may result in equipment damage or improper operation.

Wires should be sized based on NEC and local codes.



## CAUTION

### EQUIPMENT DAMAGE HAZARD

Failure to follow this caution may result in equipment damage or improper operation.

Be sure to comply with local codes while running wire from the indoor unit to the outdoor unit.

Every wire must be connected firmly. Loose wiring may cause the terminal to overheat or result in unit malfunction. A fire hazard may also exist. Ensure all wiring is tightly connected.

No wire should touch the refrigerant tubing, compressor or any moving parts.

Disconnecting means must be provided and shall be located within sight and readily accessible from the air conditioner.

## Control System

The indoor unit is equipped with a microprocessor control to perform two functions:

1. Provide safety for the system
2. Control the system and provide optimum levels of comfort and efficiency.

The main microprocessor is located on the control board of the fan coil unit (outdoor units also have a microprocessor) with thermistors located in the fan coil air inlet and on the indoor coil. Heat pump units have a thermistor on the outdoor coil. These thermistors monitor the system operation to maintain the unit within acceptable parameters and controls the operating mode.

## Wireless Remote Controller



Fig. 5 — Wireless Remote Controller

## 24 Interface (Optional)

P/N KSAIC0301230 for 208-230V models

Allows the Ductless System to be controlled using a Third Party Thermostat.

## Wi-Fi Kit for Smart Phone Control (Optional)

P/N KSAIF0601AAA

Allows the Ductless System to be controlled using a connected smart phone application.

## AIRFLOW DATA

| SYSTEM SIZE     |        | 12K<br>(115 V) | 6K<br>(208/230 V) | 9K<br>(208/230 V) | 12K<br>(208/230 V) | 18K<br>(208/230 V) | 24K<br>(208/230 V) | 30K<br>(208/230 V) | 36K<br>(208/230 V) |
|-----------------|--------|----------------|-------------------|-------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| Indoor<br>(CFM) | Turbo  | 411.76         | 382.35            | 382.35            | 382.35             | 635.29             | 718.82             | 842.94             | 842.94             |
|                 | High   | 352.94         | 335.29            | 335.29            | 335.29             | 523.53             | 611.18             | 646.47             | 639.41             |
|                 | Medium | 294.12         | 229.41            | 229.41            | 229.41             | 376.47             | 414.12             | 505.29             | 505.88             |
|                 | Low    | 235.29         | 176.47            | 176.47            | 176.47             | 305.88             | 318.82             | 382.35             | 382.35             |

## AIR THROW DATA

| HIGH WALL UNIT CAPACITY | MAX. APPROXIMATE AIR THROW FT. (M) |
|-------------------------|------------------------------------|
| 12K (115)               | 27.9(8.5)                          |
| 6K (230)                | 21.3 (7.1)                         |
| 9K (230)                | 24.9(7.6)                          |
| 12K (230)               | 26.2(8.0)                          |
| 18K (230)               | 27.9(8.5)                          |
| 24K (230)               | 31.5(9.6)                          |
| 30K (230)               | 33.8(10.3)                         |
| 36K (230)               | 33.8(10.3)                         |

## AIR MOISTURE

| Size                  |           | 12       | 6            | 9    | 12   | 18   | 24  | 30  | 36   |
|-----------------------|-----------|----------|--------------|------|------|------|-----|-----|------|
| Voltage, Phase, Cycle | V/Ph/Hz   | 115-1-60 | 208/230-1-60 |      |      |      |     |     |      |
| Dehumidifying Volume  | Liter/hr. | 1.16     | 0.32         | 0.35 | 1.11 | 2.18 | 2.6 | 3.7 | 5.75 |
| Dehumidifying Volume  | PINT/D    | 58       | 16           | 18   | 56   | 110  | 132 | 188 | 291  |

\* The dehumidifying volumes for the 6K unit will be available in a future release.

## SOUND PRESSURE

| SIZE                                          |                                                           | 12K<br>(115 V)          | 6K<br>(208/230 V)       | 9K<br>(208/230 V)       | 12K<br>(208/230 V)      | 18K<br>(208/230 V)      | 24K<br>(208/230 V)      | 30K<br>(208/230 V)    | 36K<br>(208/230 V)      |
|-----------------------------------------------|-----------------------------------------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-----------------------|-------------------------|
| Cooling<br>Operation Indoor                   | dB(A) at (Turbo/High(100%)<br>/ Med(60%)/Low(40%)<br>CFM) | 46.8/41.3/<br>30.2/24.4 | 47.2/37.9/<br>33.7/31.5 | 47.2/37.9/<br>33.7/31.5 | 46.7/37/<br>32.3/29.8   | 48.4/46/39.8/<br>36.5   | 52.1/43.5/<br>39.2/36.7 | 52.3/46/40.9/<br>38.3 | 52.1/45.7/<br>41.1/38.6 |
| Heating<br>Operation Indoor<br>Sound Pressure | dB(A) at (Turbo/High(100%)<br>/ Med(60%)/Low(40%)<br>CFM) | 46.1/38.1/<br>32.5/30.2 | 46.1/39/<br>34.5/32.4   | 46.1/39/<br>34.5/32.4   | 46.2/37.4/<br>32.9/30.5 | 46.9/44.7/<br>38.7/35.5 | 52/44.1/38.2/<br>36.5   | 50.4/43.5/<br>39/36.5 | 50.6/48.9/<br>43.0/36.6 |

## FAN AND MOTOR SPECIFICATIONS

| HIGH WALL UNIT SIZE |                  |         | 12K                                                      | 6K             | 9K             | 12K            | 18K            | 24K                                            | 30K                                            | 36K                                            |
|---------------------|------------------|---------|----------------------------------------------------------|----------------|----------------|----------------|----------------|------------------------------------------------|------------------------------------------------|------------------------------------------------|
|                     |                  |         | (115 V)                                                  | (208/230 V)    | (208/230 V)    | (208/230 V)    | (208/230 V)    | (208/230 V)                                    | (208/230 V)                                    | (208/230 V)                                    |
| High Wall fan       | Material         |         | Acrylonitrile Styrene +30%GF                             |                |                |                |                |                                                |                                                |                                                |
|                     | Type             |         | GL-98*638-IN                                             | GL-98*638-IN   | GL-98*638-IN   | GL-98*638-IN   | GL-98*758-IN   | GL-121*883-IN                                  | GL-121*883-IN                                  | GL-121*883-IN                                  |
|                     | Diameter         | In (mm) | 3.86(98)                                                 | 3.86(98)       | 3.86(98)       | 3.86(98)       | 3.86(98)       | 4.76(121)                                      | 4.76(121)                                      | 4.76(121)                                      |
|                     | Height           | In (mm) | 25.12(638)                                               | 25.12(638)     | 25.12(638)     | 25.12(638)     | 29.84(758)     | 34.76(883)                                     | 34.76(883)                                     | 34.76(883)                                     |
| High Wall fan motor | Model            |         | ZKFP-20-8-113                                            | ZKFP-20-8-6-21 | ZKFP-20-8-6-21 | ZKFP-20-8-6-21 | ZKFP-30-8-3-10 | ZKFP-58-8-1-6                                  | ZKFP-58-8-1-6                                  | ZKFP-58-8-1-6                                  |
|                     | Volts            | V       | 115                                                      | 208/230        | 208/230        | 208/230        | 208/230        | 208/230                                        | 208/230                                        | 208/230                                        |
|                     | Phase            |         | 1                                                        | 1              | 1              | 1              | 1              | 1                                              | 1                                              | 1                                              |
|                     | FLA              |         | 0.2                                                      | 0.25           | 0.25           | 0.25           | 0.13           | 0.5                                            | 0.5                                            | 0.5                                            |
|                     | MCA              |         | 0.25                                                     | 0.31           | 0.31           | 0.31           | 0.16           | 0.63                                           | 0.63                                           | 0.63                                           |
|                     | Type             |         | DC                                                       | DC             | DC             | DC             | DC             | DC                                             | DC                                             | DC                                             |
|                     | Insulation class |         | E                                                        | E              | E              | E              | E              | E                                              | E                                              | E                                              |
|                     | Safe class       |         | IP20<br>(Welling, Dayang)/<br>IPX0(Tongda)               | IPX0           | IPX0           | IPX0           | IPX4           | IP20(Welling)/<br>IP40(Dayang)                 | IP20(Welling)/<br>IP40(Dayang)                 | IP20(Welling)/<br>IP40(Dayang)                 |
|                     | Input            | W       | 65.8<br>(Welling, Tongda)/<br>68(Dayang)                 | 24.6           | 24.6           | 36             | 36             | 113.5(Welling)/<br>125(Dayang)                 | 113.5(Welling)/<br>125(Dayang)                 | 113.5(Welling)/<br>125(Dayang)                 |
|                     | Output           | W       | 20                                                       | 20             | 20             | 20             | 30             | 58                                             | 58                                             | 58                                             |
|                     | Range of current | Amps    | 0.467±10%<br>(Welling, Tongda)/<br>0.486±10%<br>(Dayang) | 0.182±10%      | 0.182±10%      | 0.182±10%      | 0.11±10%       | 0.364±10%<br>(Welling)/<br>0.4±10%<br>(Dayang) | 0.364±10%<br>(Welling)/<br>0.4±10%<br>(Dayang) | 0.364±10%<br>(Welling)/<br>0.4±10%<br>(Dayang) |
|                     | Rated current    | Amps    | 0.467<br>(Welling, Tongda)/<br>0.486(Dayang)             | 0.182          | 0.182          | 0.182          | 0.11           | 0.364(Welling)/<br>0.4(Dayang)                 | 0.364(Welling)/<br>0.4(Dayang)                 | 0.364(Welling)/<br>0.4(Dayang)                 |
|                     | Capacitor        | μF      | NA                                                       | NA             | NA             | NA             | NA             | NA                                             | NA                                             | NA                                             |
|                     | Rated HP         | HP      | 0.027                                                    | 0.027          | 0.027          | 0.027          | 0.04           | 0.077                                          | 0.077                                          | 0.077                                          |
|                     | Speed            | rev/min | 1200/910/720                                             | 1100/850/700   | 1100/850/700   | 1050/930/870   | 1240/1024/916  | 1000/850/700                                   | 1050/880/630                                   | 1050/880/630                                   |
|                     | Rated RPM        | rev/min | 1200                                                     | 1100           | 1100           | 1050           | 1240           | 1000                                           | 1050                                           | 1050                                           |
|                     | Max. input       | W       | 65.8                                                     | 24.6           | 24.6           | 24.6           | 36             | 113.5                                          | 113.5                                          | 113.5                                          |

**NOTE: Refer to the outdoor unit installation instructions (indoor unit powered by the outdoor unit).**



# Carrier Connect™ Wi-Fi Thermostat 33CONNECTSTAT43FX Installation Guide





Verify that you have the most current version of this document from [www.hvacpartners.com](http://www.hvacpartners.com), the **Carrier Partner Community** website, or your local Carrier office.

Important changes are listed in **Document revision history** at the end of this document.

©2024 Carrier. All rights reserved.



# Contents

|                                                                       |           |
|-----------------------------------------------------------------------|-----------|
| <b>What Is the Carrier Connect™ 33CONNECTSTAT43FX Thermostat?</b>     | <b>1</b>  |
| Specifications                                                        | 2         |
| Programmable and non-programmable installations                       | 3         |
| Inputs                                                                | 5         |
| Outputs                                                               | 6         |
| <b>Wiring the Carrier® Connect™ WI-FI Thermostat</b>                  | <b>8</b>  |
| To wire dual fuel systems and furnace / AC systems                    | 8         |
| To wire an air handler with heat pump or with AC                      | 10        |
| To wire hotel systems                                                 | 12        |
| To connect a remote input (sensor or contacts)                        | 12        |
| To wire for BACnet communication                                      | 14        |
| <b>Registering and setting up a mobile device for enhanced access</b> | <b>16</b> |
| Using the Connect website or app                                      | 17        |
| <b>Getting to know the user Interface</b>                             | <b>20</b> |
| Dormant screen                                                        | 20        |
| Home screen                                                           | 20        |
| Occupancy/Enter PIN screen                                            | 21        |
| Changing the setpoints                                                | 22        |
| Changing the fan                                                      | 23        |
| Changing the mode                                                     | 23        |
| <b>Using the menu for advanced features</b>                           | <b>24</b> |
| To adjust date and time                                               | 25        |
| To adjust occupancy settings                                          | 26        |
| To adjust the display settings                                        | 28        |
| To adjust the banner text                                             | 30        |
| <b>Using installer settings</b>                                       | <b>32</b> |
| To set up BACnet                                                      | 44        |
| To test the HVAC system                                               | 50        |
| To restore factory default settings                                   | 51        |
| <b>Setting up WI-FI</b>                                               | <b>54</b> |
| <b>Timers, memory, and deadband</b>                                   | <b>56</b> |
| <b>Faults and system events</b>                                       | <b>57</b> |
| <b>Appendix A: BACnet Points List</b>                                 | <b>59</b> |
| <b>Appendix B: BACnet Functionality</b>                               | <b>65</b> |
| <b>Appendix C: BACnet Constraints</b>                                 | <b>66</b> |
| <b>Appendix D: BACnet Object Instance Ranges</b>                      | <b>67</b> |
| <b>Appendix E: BACnet Object Notes</b>                                | <b>68</b> |
| <b>Document revision history</b>                                      | <b>70</b> |



## What is the Carrier Connect™ 33CONNECTSTAT43FX Thermostat?

### The Carrier Connect 33CONNECTSTAT43FX thermostat has:

- Space and remote temperature sensing
- Space and remote humidity sensing
- BACnet MS/TP communications
- Wi-Fi connectivity

### The Carrier® Connect™ Wi-Fi Thermostat package includes:

- Thermostat
- Mounting Hardware - two screws with drywall anchors and one security screw
- Quick Start Guide - Catalog No. 11-808-873-01


### Some of the features:

- Control of heating, cooling, and fan solid state 24 Vac outputs
- Space temperature sensing (> 0.5 °F accuracy from 60 °F to 90 °F)
- Outdoor temperature sensing using a 10K @ 25 °C J Curve (type II) thermistor connected to **T** and **C** terminals or Wi-Fi outdoor temperature, available by GPS location services, determined when the thermostat is installed
- Humidity sensing and control
- Remote humidity sensing from a 33ZCSENRH-02 Humidity Duct Sensor or 33ZCSENSRH-02 wall sensor
- Remote CO2 sensing from a 0-10 vdc or 4-20 mA sensor
- Wi-Fi connectivity (supports 802.11 a/b/g/n standards and utilizes a Broadcom chipset)
- Cloud Connectivity using the Carrier Connect mobile app (iOS and Android).
- Optimized installation ("finger friendly" spring-loaded connectors that accept 16 to 24 AWG wire and NO screwdriver required for wire insertion and removal)
- Optimized boot time (5 seconds total boot time until temperature displays and thermostat is fully operational)
- 4.3" segment display
- Thirteen touch points for display buttons
- OTA functionality (reprogrammable via Wi-Fi)

What is the Carrier Connect™ 33CONNECTSTAT43FX Thermostat?

## Specifications

|                                 |                                                                                                                                                                                     |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power requirements              | 24 Vac +/- 10% @ 3VA                                                                                                                                                                |
| Network Requirements            | Wi-Fi connectivity supports Wi-Fi: 802.11 a/b/g/n standards on 2.4 GHz networks                                                                                                     |
| Environmental temperature range | Operating: 32° to 104° F (0° to 40° C)<br>Storage: -40° to 135° F (-40° to 57° C)                                                                                                   |
| Humidity range                  | Operating: 10% to 95%, non-condensing, 32° to 104° F (0° to +40° C)<br>Storage: 10% to 95%, non-condensing                                                                          |
| Connections                     | Connectors P104 and P105. 2 banks of "finger friendly" spring type terminal blocks intended to be wired by the end-user or installer                                                |
| Inputs                          | <ul style="list-style-type: none"><li>• <b>C</b> - connection</li><li>• <b>R</b> - connection</li><li>• <b>H</b> - 0-10 Volt input</li><li>• <b>T</b> - remote thermistor</li></ul> |
| Outputs                         | Connections: <b>Y3, O/B, Y2, Y1, G, W1, and W2</b>                                                                                                                                  |
| Communications                  | 485 signal: <b>A+</b> and <b>B</b>                                                                                                                                                  |
| Mounting                        | Standard 4 x 2 in. electrical box using the 6-32 x 1/2 in. mounting screws and plastic wall anchors provided                                                                        |
| Overall dimensions              | Width: 5.15 in. (13.1 cm)<br>Height: 3.25 in. (8.2 cm)<br>Depth: 0.95 in. (2.4 cm)                                                                                                  |
| BACnet Support                  | Conforms to the BACnet Application Specific Controller (B-ASC) Device Profile as defined in ANSI/ ASHRAE Standard 135-2012 (BACnet) Annex L, Protocol Revision 14                   |
| Listed by                       | FCC Part 15, Subpart J compliant                                                                                                                                                    |



## Programmable and non-programmable installations

---

The thermostat combines all 24 Vac output demand control functions needed for the following types of thermostat programmable and non-programmable installations:

### **Cool only** (up to 3 stages of cooling)

- Cooling
  - **Y1** - first stage cooling
  - **Y2** - second stage cooling
  - **Y3** - third stage cooling

### **Heat only with gas heat** (up to 2 stages of heating)

- Heating
  - **W1** - first stage heat
  - **W1 + W2** - second stage heat

### **Heat only with electric heat** (up to 3 stages of heating)

- Heating
  - **W1** - first stage heat
  - **W2** - second stage heat
  - **W1 + W2** - third stage heat

### **AC with gas heat** (up to 3 stages of cooling and 2 stages heating)

What is the Carrier Connect™ 33CONNECTSTAT43FX Thermostat?

- Cooling
  - **Y1** - first stage cooling
  - **Y2** - second stage cooling
  - **Y3** - third stage cooling
- Heating
  - **W1** - first stage heat
  - **W1 + W2** - second stage heat

**AC with electric heat** (up to 3 stages of cooling and 3 stages heating)

- Cooling
  - **Y1** - first stage cooling
  - **Y2** - second stage cooling
  - **Y3** - third stage cooling
- Heating
  - **W1** - first stage heat
  - **W2** - second stage heat
  - **W1 + W2** - third stage heat

**HP with electric heat** (up to 2 stages of cooling and 5 stages of heating with 3 stages auxiliary)

- Cooling
  - **Y1 + O/B** - first stage cooling
  - **Y1 + Y2 + O/B** - second stage cooling
- Heating
  - **Y1** - first stage HP heating
  - **Y1 + Y2** - second stage HP heating
  - **Y1 + Y2 + W1** - HP heating + first stage aux heat
  - **Y1 + Y2 + W2** - HP heating + second stage aux heat
  - **Y1 + Y2 + W1 + W2** - HP heating + third stage aux heat

**HP with gas heat** (up to 2 stages of cooling and 4 stages of heating with 2 stages auxiliary)

- This system is known as a dual fuel system.
- When gas heat turns on, the HP heat turns off unless defrost is active.
- Once the gas is turned on, the heating demand is satisfied with gas heat. The thermostat does not stage down from gas to heat pump heat.
- Cooling
  - **Y1 + O/B** - first stage cooling
  - **Y1 + Y2 + O/B** - second stage cooling
- Heating

- **Y1** - first stage HP heating
- **Y1 + Y2** - second stage HP heating
- **W1** - first stage aux heat
- **W1 + W2** - second stage aux heat

#### Definitions

|                              |                                                                                                                                                                                                                                                   |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Heat demand</b>           | The space temperature is less than the heat setpoint (HEAT TO setting).                                                                                                                                                                           |
| <b>Cool demand</b>           | The space temperature is greater than the cool setpoint (COOL TO setting).                                                                                                                                                                        |
| <b>Heat demand satisfied</b> | The space temperature is greater than the heat setpoint (HEAT TO setting).                                                                                                                                                                        |
| <b>Cool demand satisfied</b> | The space temperature is less than the cool setpoint (COOL TO setting).                                                                                                                                                                           |
| <b>Heating equipment</b>     | If the Y1, W1, or W2 (W2 in electric heat systems only) outputs are energized when the mode is set to HEAT, EHEAT, or AUTO, operating in Heat, then the heating equipment is on. When all of these outputs are off, the heating equipment is off. |
| <b>Cooling equipment</b>     | If the Y1 output is energized when the mode is set to <b>COOL</b> or <b>AUTO</b> operating in Cool, then the cooling equipment is on. When Y1 is off, the cooling equipment is off.                                                               |

## Inputs

### Power supply

Class II transformer secondary voltage supplied to the thermostat is 18.0 to 30.0 Vac, 50/60 Hz. Voltage is applied between **R** and **C** connector.

### Space air temperature

The space air temperature measurement is supplied by an NTC "J" curve (type II) thermistor. The resistance of the thermistor is 10K ohm nominal at +25 °C with an accuracy of ±0.20 °C from +15.6 °C to +32.2 °C (approximately 0.5 °F accuracy from 60 °F to 90 °F).

If the thermistor reading is invalid, the space temperature is measured by the Sensirion SHT21 humidity and temperature sensor.

### Remote temperature sensor

The remote temperature measurement is supplied by a NTC "J" curve (type II) thermistor connected between **T** and **C**. This thermistor is supplied by the installer to use for Space, Outdoor, Supply Air, or an average with the space air temperature. When used for the space temperature sensor, up to 9 remote space sensors can be averaged (1, or multiples of 4, or 9). The **T** input allows for remote occupancy override with T55 style sensor.

- If the **Occupancy Input** installer setting is set to **OCCUPIED**, when a short in the circuit from 2 up to 5 seconds in duration is sensed, a change is made from the unoccupied heating and cooling setpoints to the occupied

heating and cooling setpoints for the current time period, for the configured allowable time.

- If the **Occupancy Input** installer setting is set to **UNOCCUPIED**, when a short in the circuits sensed for more than 2 seconds, the occupied heating and cooling setpoints change to the unoccupied heating and cooling setpoints for the current time period.
- Alternatively, you can use the remote temperature sensor input as a remote occupied/unoccupied selection as well as an indicator of economizer fault or Filter Reminder.
- Alternatively, Wi-Fi outdoor temperature is available by GPS location services – determined when the thermostat is installed and registered through a Wi-Fi connection.

#### Remote humidity or CO2 sensor (0-10 volt or 4-20 mA)

The remote measurement is calculated from the 0-10 volt or the 4-20 mA signal applied between **H** and **C**. When the output of the sensor is the 4-20 mA signal, a 500 ohm load resistor must be connected between **H** and **C**.

#### Space humidity sensor

The humidity is read via synchronous communications from a Sensirion SHT21 Humidity and Temperature Sensor. The Sensirion humidity is accurate to +/- 2 % relative humidity between 20 and 80 % relative humidity.

## Outputs


Connections are made via a compact and robust single pole, “finger friendly” spring-type terminal block. All outputs have a max rating of 1.25 Amp @ 24 Vac.


| Terminal  | Output for...                             | Is energized when the thermostat has a... |
|-----------|-------------------------------------------|-------------------------------------------|
| <b>G</b>  | Fan                                       | fan demand                                |
| <b>W1</b> | First Stage Heat or AUX Heat              | first stage heat or aux heat demand       |
| <b>W2</b> | Second stage heat or AUX heat             | second stage heat or aux heat demand      |
| <b>Y1</b> | First stage cooling or HP heating output  | first stage cooling or HP heating output  |
| <b>Y2</b> | Second Stage Cooling or HP Heating Output | second stage cooling or HP heating demand |
| <b>O</b>  | Reversing Valve Output                    | reversing valve demand                    |
| <b>Y3</b> | Third Stage AC Cooling                    | third stage AC cooling demand             |

What is the Carrier Connect™ 33CONNECTSTAT43FX Thermostat?


| Terminal                             | Output for...           | Is energized when the thermostat has a...                                                                                                                                                                                                                    |
|--------------------------------------|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>O</b> or <b>Y3</b> or <b>W2</b>   | Humidifier Output       | humidification demand<br><b>NOTE</b> You can connect to any of these 3 outputs that are unused and select it in the system settings menu.                                                                                                                    |
| <b>O</b> , <b>Y3</b> , and <b>W2</b> | HumidiMiZer™            | HumidiMiZer™ demand<br><b>NOTE</b> You can connect to any of these 3 terminals that are unused and select it in the system settings menu.                                                                                                                    |
| <b>O</b> , <b>Y3</b> , and <b>W2</b> | Economizer or Occupancy | the thermostat is running in occupied mode, as determined by the program, the occupancy input, BMS occupancy, or an override condition<br><b>NOTE</b> You can connect to any of these 3 terminals that are unused and select it in the system settings menu. |

## To wire an air handler with heat pump or with AC





## To wire hotel systems



## To connect a remote input (sensor or contacts)

**NOTE** Use the specified type of wire and cable for maximum signal integrity.

|                |                                                                                            |
|----------------|--------------------------------------------------------------------------------------------|
| Power          | N/A                                                                                        |
| Description    | Stranded, twisted pair                                                                     |
| Conductor      | If < 100 ft (30.5 meters) 22 AWG, unshielded<br>If > 100 ft (30.5 meters) 22 AWG, shielded |
| Maximum length | 500 feet (152 meters)                                                                      |
| Insulation     | Plenum rated                                                                               |
| Thermistor     | 10K Type II (CP/MCI)                                                                       |




Use Remote Sensor input terminals S1 and S2 for the following inputs:


- OAT
- T55
- SAT
- Occupancy contacts
- Econ Fault

#### Wiring for space temperature sensor averaging

##### 4 sensors

Connect  
Thermostat





## To wire for BACnet communication

**NOTE** Use the specified type of wire and cable for maximum signal integrity.

|                |                                                                        |
|----------------|------------------------------------------------------------------------|
| Cable          | 22 or 24 AWG, low-capacitance, twisted, stranded, shielded copper wire |
| Maximum length | 2000 feet (610 meters) per segment                                     |
| Baud rate      | 9600 bps, 19.2 kbps, 38.4 kbps, or 76.8 kbps, 115.2 kbps               |



Connect communication wiring to terminals **A+** and **B-**. Do not terminate shield at the thermostat.



**CAUTION** Maintain the same polarity.

**NOTE** For more networking details, see the *Open Controller Network Wiring Installation Guide*.


## Registering and setting up a mobile device for enhanced access

Downloading the Connect™ App provides enhanced access to your device. The Connect™ App is available for Apple iOS® at App Store® or at Google Play® for Android devices. Search for **Carrier Connect™ Thermostat**.

**NOTE** Device compatibility: Apple iOS® 7.0 or later or Android 4.2 or later

- 1 After downloading Connect™ App, select **USER SETUP** and **Register New Account**.

**NOTE** You can also register new accounts using the website [connectstat.carrier.com](http://connectstat.carrier.com).



- 2 Enter an email address that you can access on your mobile device and receive the confirmation email to complete the registration process.
- 3 Select **SETUP NEW THERMOSTAT** and follow the Connect™ App instructions.
- 4 After registering the thermostat, enter servicing contractor's name and phone number on the **SERVICE INFO** screen.
- 5 On the **THERMOSTATS** screen, select the thermostat from list and the mobile app's **HOME** screen appears.




## Using the Connect website or app

After you register for an account, you can access the thermostat by using the app directly or through the Web at [connectstat.carrier.com](https://connectstat.carrier.com).

You can:

- Monitor the thermostat operation
- Set up occupied and unoccupied (holiday) schedules
- Adjust setpoints
- Share thermostat access with other users
- Create groups of thermostats that you have registered
- Create groups of thermostats that other owners have shared with you
- Get online product information
- Find local dealer support

### To navigate

- On a touchscreen device, use any of the following:
    - swipe the screen
    - tap the arrow on the side
    - tap a dot on the bottom of the screen on either side of the HOME button
  - On a non-touchscreen device, click on the gray arrow  on either the side of the screen.
  - You can press or click  to access the following drop-down list:
    - **My Systems**
    - **My Account**
    - **Shared Systems**
    - **Product Information**
    - **Find and Expert**
    - **Logout**
- 1 After logging in, a list appears of thermostats that you have registered and that have been shared with you.
  - 2 Click .
  - 3 Swipe or click to navigate to the **SETTINGS** screen.



NOTES

- Navigate by clicking or pressing the buttons such as **SETPOINTS**, **FAN**, **PROGRAM**, etc...
- Grayed out function buttons indicate that feature is not being used on the thermostat.

| Screens                                                                                                                      | Use to...                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SETPOINTS                                                                                                                    | Adjust the occupied and unoccupied setpoints by selecting each temperature.                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| FAN                                                                                                                          | <div>View and modify fan settings.</div> <ul style="list-style-type: none"><li>• The default setting for fan operation is <b>AUTO</b> for both Occupied and Unoccupied periods. When operating in <b>AUTO MODE</b>, the fan only runs when there is an active heating or cooling demand.</li><li>• When you select <b>ON</b>, the fan runs continuously, except during the <b>Blower On Delay</b> when a heat cycle is starting. There is a 30-second minimum on/off timer when changing the <b>FAN MODE</b>.</li></ul> |
| <b>NOTE</b> The following selections are not available if the thermostat has been configured for non-programmable operation. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| HUMIDITY                                                                                                                     | Adjust the thermostat's humidify and dehumidify setpoints.                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| PROGRAM                                                                                                                      | <div>You can:</div> <ul style="list-style-type: none"><li>• Set Occupied and Unoccupied start times, depending on the configured number of periods and the user's security level.</li><li>• Select the time at the bottom of the screen to adjust the start or stop time of each period in 15 minute increments.</li><li>• Select <b>Copy</b> to apply that schedule to other days of the week.</li><li>• Adjust the setpoints for each period.</li></ul>                                                               |

| Screens         | Use to...                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>HOLIDAY</b>  | <p>Set <b>HOLIDAY</b> (same as unoccupied) periods with the following options:</p> <ul style="list-style-type: none"> <li>Length of time from 1 to 365 days</li> <li>Same day of each week of the month</li> <li>Specific day of specific week(s) of the month</li> </ul> <p><b>NOTE</b> Requires advanced security level to edit these settings</p> <ul style="list-style-type: none"> <li>Select <b>+ADD HOLIDAY</b> to add start month, day, and number of days.</li> <li>Select <b>ADVANCED</b> to configure same day of each week(s) of that month.</li> <li>To delete a holiday on the: <ul style="list-style-type: none"> <li>Mobile app - swipe the selected holiday to the left and select <b>Delete</b></li> <li>Web app - select <b>x</b> on right side of the holiday</li> </ul> </li> </ul> |
| <b>SETTINGS</b> | <p>Enter the name and location of the thermostat for the user's reference. The user can enter an email address for alerts and a mobile phone number to receive text alert messages.</p> <p><b>NOTE</b> Requires advanced security level to edit these settings.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>ALERTS</b>   | <p>Displays a list of alerts that have been flagged in the thermostat.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>SERVICE</b>  | <p>Displays the name and phone number of the service company or individual who is responsible for servicing the system.</p> <p><b>NOTE</b> Requires advanced security level to edit these settings.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>C02</b>      | <p>Displays the graph for up to 30 days of C02 history. Presents the high and average for today as well as the last 30 days.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |

## Getting to know the user interface

### Dormant screen

The dormant screen is displayed when not interacting with the thermostat.



The banner scrolls through date and time, humidity, outdoor air temperature, if configured, and any active faults or system events. The room temperature is prominently displayed.

There are no buttons on this screen, but the 13 touch locations are active, so when the display is touched, the thermostat transitions to the **LOCK** screen, if lockout is enabled, or the home screen, if lockout is disabled.



### Home screen

You interact with the thermostat primarily from the Home screen.



The center portion of the screen displays the current space temperature in whole degrees. The default temperature scale is °F, but can be changed to °C in the *Installer settings* (page 32).

The top of the screen displays a banner that cycles system information every 3 seconds. To see the scrolling messages faster than 3 seconds, press the banner area of the screen to advance to the next message.

The  icon indicates the current Wi-Fi signal strength by the number of bars. A strong signal has 3 arched bars.  indicates the thermostat is not connected to a router.

Above the space temperature, the current state of occupied or unoccupied displays, unless you have temporarily overridden the program schedule settings. When overridden, the banner displays **PAUSED** and shows the time remaining in the override.

From the home screen, you can:

- *change the mode* (page 23)
- *force an occupied or unoccupied override* (page 22)
- *change the setpoints* (page 22)
- *set the filter reminder* (page 40)
- *enter the menu for more advanced functionality* (page 24)


You access the program schedule by holding the bottom middle button (labeled **OCC**, **UNOCC**, or **RESUME SCHEDULE**) for 3 seconds.

Access the installer configurations by setting the **MODE** to **OFF** and holding the **MENU** button for 5 seconds.

## Occupancy/Enter PIN screen

The Occupancy/ENTER PIN screen is displayed when you touch the dormant screen with lockout enabled.

To enter the PIN that unlocks the thermostat, press 1 of the 3 digits in the center of the display and then use the up or down arrows to adjust to the correct value. Repeat with the remaining 2 digits. When the 3-digit PIN is correct, press **SAVE**.



This screen has an **OCC/UNOCC** button to temporarily override the program schedule settings without knowing the PIN. The PIN must be entered for all other thermostat changes. Pressing the **OCC/UNOCC** button temporarily overrides the program schedule settings with the occupied or unoccupied settings. This override remains active until the next time range in the program schedule or until the **MAX HOLD** time expires.

If the correct PIN is entered, the thermostat displays the home screen. The thermostat remains unlocked until no interaction results in the dormant screen. When the dormant screen displays, the thermostat is locked.

If the correct PIN is not entered, an **INVALID PIN** message displays for 3 seconds and the thermostat transitions to the dormant screen.

If an invalid PIN is entered 5 consecutive times, the thermostat is completely locked out for 15 minutes. The top banner displays **LOCKOUT** and shows the time remaining until another unlock can be attempted.

## Changing the setpoints

You can change the setpoints from the home screen using the up and down arrows.

If the mode is:

- **OFF**—the setpoints, occupancy button, and the up and down arrows do not display
- **HEAT** or **EHEAT**—only the heat setpoint displays
- **COOL**—only the cool setpoint displays
- **AUTO**—both setpoints display



When changing the setpoints in **AUTO** mode, the setpoint modified by the up and down arrows is the last setpoint that was changed. To adjust the opposite mode setpoint, touch the setpoint value on the display. **HEAT TO** or **COOL TO** flashes above the setpoint and can be changed by using the up and down arrows. The setpoints enforce a 2-degree deadband. Setpoints in °F are displayed in whole degrees. Setpoints in °C are displayed with half degree resolution.

Pressing once on the center button at the bottom of the display changes the setpoints to either the program schedule's occupied or unoccupied settings. The label on this button shows the opposite of the word above the space temperature.

**Example** If the thermostat is in an occupied program period, the middle button displays **UNOCC** so you can change the thermostat settings to the unoccupied values. Overriding the program schedule using the **OCC/UNOCC** button modifies both the setpoint values and the fan setting.

A program schedule override is treated the same whether you manually change the setpoints or use the **OCC/UNOCC** button. When an override is active, the center button label changes to **RESUME SCHEDULE**, the period icon above the space temperature is not displayed, and the amount of time remaining in the override is displayed in the banner. The thermostat returns to the program schedule value at the next programmed period, when the max hold timer expires or if you press the **RESUME SCHEDULE** button.

**NOTE** If the thermostat is setup as a non-programmable thermostat or them **MAX HOLD** time is set to **OFF**, then the bottom middle button is not displayed.

The installer designates and clamps setpoints within a range.

## Changing the fan

The fan's current state is displayed on the home screen above the **MENU** button.



You can change the fan setting by pressing **MENU** and then the current fan setting is displayed.

To change the fan setting, press **SELECT** and then use the up and down arrows to toggle the fan setting between **AUTO** and **ON** and then press **SAVE**.

- **ON** specifies continuous fan that is always running.
- **AUTO** specifies that the fan only runs while actively heating or cooling.



When the fan setting differs from the program schedule setting for the current period, the banner displays **FAN OVERRIDE**. The override remains active for the rest of the current program schedule.

## Changing the mode

You can change the mode from the home screen by pressing the **MODE** button.

Changing from one mode to another does not affect the thermostat's operation until the mode selection has remained constant for at least 5 seconds. Changing from one mode to another (e.g. **HEAT** mode to **COOL** mode) requires the thermostat to first satisfy any **MINIMUM ON** timer requirements and then restarts the **MINIMUM OFF** timer that must expire before equipment is turned on in the new mode.

Going from any heating or cooling mode to **OFF** mode immediately shuts off any equipment that is active (after the 5-second mode button). See *Timers* (page 56) for additional descriptions of the **MINIMUM OFF** timer and the **MINIMUM ON** timer.

**NOTE** Some modes may not be available, based on the **INDOOR EQUIPMENT TYPE** or the **COMPRESSOR TYPE** selections made in Installer Settings.


## Using the menu for advanced features

The menu allows the user to access more advanced features of the thermostat.


- 1 When you press the **MENU** button, the first menu option is **CURRENT FAN**.



- 2 Press **SELECT** to activate the up and down arrows.



- 3 Press the up or down arrows to advance through the menu options to view or change the value for each setting.



- You must **SAVE** to store the current value and return to the **SELECT** screen.
- Press **CANCEL** to revert the value to the last saved value and return to the **SELECT** screen.

**NOTES**

- Press **DEFAULT** to set the value to the factory default and press **SAVE** to store the value.





## To adjust date and time

---

| Screen settings                                                                                                                                                                                                                                                                                                                                                                                                                            | Default/Range              |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|
| <b>SET YEAR</b> —The current year                                                                                                                                                                                                                                                                                                                                                                                                          | D: 2020<br>R: 2020 to 2099 |
| <b>SET MONTH</b> —The current month                                                                                                                                                                                                                                                                                                                                                                                                        | D: Jan<br>R: Jan to Dec    |
| <b>SET DAY OF MONTH</b> —The current day of the month                                                                                                                                                                                                                                                                                                                                                                                      | D: 1<br>R: 1 to 31         |
| <b>SET HOUR</b> —The hour of the day using 12 hour a.m. (A) / p.m. (P) format                                                                                                                                                                                                                                                                                                                                                              | D: 12 A<br>R: 12 A - 11 P  |
| <b>SET MINUTE</b> —The current minute                                                                                                                                                                                                                                                                                                                                                                                                      | D: 0<br>R: 0 to 59         |
| <b>SYNC TIME TO SERVER</b> —When the thermostat is first registered and connected to a Wi-Fi router, both the date and time are synced with the server, based on the geographic location of the phone or tablet connecting the thermostat to a router or based on the ISP location if a PC is used.<br>The time and date are updated/synced automatically at the top of each hour, unless <b>SYNC TIME TO SERVER</b> is set to <b>NO</b> . | D: YES<br>R: YES<br>NO     |
| <b>DST ENABLE</b> —Enable or disable automatic Daylight Saving Time change in the thermostat                                                                                                                                                                                                                                                                                                                                               | D: YES<br>R: YES<br>NO     |

## To adjust occupancy settings

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Default/Range                        |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|
| <p><b>SET OCC FAN</b>—Operates the fan in <b>AUTO</b> or <b>ON</b> during occupied periods</p> <p><b>NOTE</b> If the installer configured the thermostat for non-programmable operation and remote occupancy is disabled, this setting is not available.</p> <p><b>REMINDER!</b> The <b>AUTO</b> setting is a violation of ASHRAE 90.1 and Title 24 but is a feature of the thermostat for building owners that mandate auto fan operation during occupied periods for energy conservation purposes.</p> | <p>D: AUTO</p> <p>R: AUTO<br/>ON</p> |
| <p><b>SET UNOC FAN</b>—Operates the fan in <b>AUTO</b> or <b>ON</b> during unoccupied periods</p> <p><b>NOTE</b> If the installer has configured the thermostat for non-programmable operation and remote occupancy is disabled, this setting is not available.</p>                                                                                                                                                                                                                                      | <p>D: AUTO</p> <p>R: AUTO<br/>ON</p> |
| <p><b>UNOCC COOL</b>—The cool setpoint during unoccupied periods</p> <p><b>NOTES</b></p> <ul style="list-style-type: none"> <li>The minimum value you can set is limited by the unoccupied heat setpoint (cool setpoint cannot be less than the heat setpoint) and the installer setting for <b>MIN COOL SETPOINT</b>.</li> <li>If the installer has configured the thermostat for non-programmable operation and remote occupancy is disabled, this setting is not available.</li> </ul>                | <p>D: 85°F</p> <p>R: 52 to 90°F</p>  |
| <p><b>UNOCC HEAT</b>—The heat setpoint during unoccupied periods</p> <p><b>NOTES</b></p> <ul style="list-style-type: none"> <li>The maximum value is limited by the unoccupied cool setpoint (heat setpoint cannot be greater than the cool setpoint) and the installer setting for <b>MAX HEAT SETPOINT</b>.</li> <li>If the installer has configured the thermostat for non-programmable operation and remote occupancy is disabled, this setting is not available.</li> </ul>                         | <p>D: 62°F</p> <p>R: 50 to 88°F</p>  |
| <p><b>OCC COOL</b>—The cool setpoint during occupied periods</p> <p><b>NOTES</b></p> <ul style="list-style-type: none"> <li>The minimum value is limited by the occupied heat setpoint (cool setpoint cannot be less than the heat setpoint) and the installer setting for <b>MIN COOL SETPOINT</b>.</li> <li>If the installer has configured the thermostat for non-programmable operation and remote occupancy is disabled, this setting is not available.</li> </ul>                                  | <p>D: 75°F</p> <p>R: 52 to 90°F</p>  |
| <p><b>OCC HEAT</b>—The heat setpoint during occupied periods</p> <p><b>NOTES</b></p> <ul style="list-style-type: none"> <li>The maximum value is limited by the occupied cool setpoint (heat setpoint cannot be greater than the cool setpoint) and the installer setting for <b>MAX HEAT SETPOINT</b>.</li> <li>If the installer has configured the thermostat for non-programmable operation and remote occupancy is disabled, this setting is not available.</li> </ul>                               | <p>D: 70°F</p> <p>R: 50 to 88°F</p>  |
| <p><b>DAY PARTS</b>—The number of programmable periods in a single day. The setting is adjustable as either 2 (default) or 4 periods in a day. Typically, commercial or light commercial products use 2.</p> <p><b>NOTE</b> If the installer has configured the thermostat for non-programmable operation and remote occupancy is disabled, this setting is not available.</p>                                                                                                                           | <p>D: 2</p> <p>R: 2 or 4</p>         |

| Setting                                                                                                                                                                                                                                                                                       | Default/Range |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| <p><b>PROGRAM SCHEDULE</b>—The program schedule specifies the programmed start times for the thermostat to control the space to the occupied or unoccupied fan and setpoint values.</p>                                                                                                       |               |
| <p>1 From the <b>SET PROGRAM</b> screen, press <b>SELECT</b> to view the program schedule for <b>SUNDAY P1</b>.</p>                                                                                                                                                                           |               |
|                                                                                                                                                                                                              |               |
| <p>2 From the <b>SUNDAY P1</b> screen, use the up and down arrows to advance through the program schedule to the next period (<b>SUNDAY P2</b>), or press <b>SELECT</b> again to change the start time or occupancy setting.</p>                                                              |               |
| <p><b>NOTE</b></p>                                                                                                                                                                                                                                                                            |               |
|                                                                                                                                                                                                             |               |
| <p><b>NOTES</b></p>                                                                                                                                                                                                                                                                           |               |
| <ul style="list-style-type: none"> <li>○ <b>BACK</b> returns to the menu</li> <li>○ Use up and down arrows to change start time</li> <li>○ Use <b>OCC/UNOCC</b> to change occupancy</li> <li>○ The bottom middle button is labeled the opposite of the current occupancy selection</li> </ul> |               |

## To adjust the display settings

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                          | Default/Range                                     |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------|
| <b>SOUND EFFECT</b> —Select the sound feedback when you press a button.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                          | D: CLCK (Click)<br>R: OFF<br>CLCK (Click)<br>BEEP |
| <b>BACKLIGHT</b> —There are two backlight settings, one for interacting with the thermostat and another for the dormant screen.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                          |                                                   |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | <b>BACKLIGHT ACTIVE</b> —Set the active backlight to 10% to 100% of the full backlight capability.                       | D: 75%<br>R: 10 to 100%<br>(5% increments)        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | <b>BACKLIGHT SLEEP</b> —Set the inactive backlight for the dormant screen to 0% to 25% of the full backlight capability. | D: 25%<br>R: to 25%<br>(5% increments)            |
| <b>LOCKOUT ENABLE</b> —Enable or disable adjustments to prevent unauthorized changes from the touchscreen interface. When <b>LOCKOUT</b> is changed from <b>NO</b> to <b>YES</b> , the user must enter a 3-digit PIN. After setting the <b>LOCKOUT</b> to <b>YES</b> and entering a PIN, the thermostat locks when the user returns to the home or the dormant screen.<br><br>When <b>LOCKOUT</b> is enabled: <ul style="list-style-type: none"> <li>The user must enter the 3-digit PIN after pressing any button on the home screen.</li> <li>If the PIN is entered successfully, the thermostat is unlocked until the dormant screen displays.</li> <li>After 5 failed attempts to unlock the thermostat, a notification (fault) is sent through the Wi-Fi to the registered owner of the thermostat. Additional unlock attempts are not allowed for 15 minutes.</li> </ul> <b>NOTE</b> If the user enables <b>LOCKOUT</b> but does not save a PIN, <b>LOCKOUT</b> automatically disables (sets back to <b>NO</b> ). |                                                                                                                          | D: NO<br>R: YES<br>NO                             |
| <b>SET LOCK PIN</b> —The end user can choose or modify their own 3-digit lock PIN for the thermostat.<br><br>One digit of the 3-digit PIN flashes to indicate which digit is changeable using the up and down arrows. To change which digit is adjustable, touch the digit on the display.<br><br><b>NOTE</b> If <b>LOCKOUT ENABLE</b> is set to <b>NO</b> , the <b>SET LOCK PIN</b> screen does not appear.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                          | D: N/A - no default<br>R: 000 - 999               |
| <b>CLEAN SCREEN</b> —Completely disables touch functionality for 10 seconds so the screen can be cleaned with a dry nonabrasive cloth. During this time, a 10-second countdown value shows and then normal touchscreen function resumes.<br><br>Two screens display the thermostat software versions. They are for informational purposes only. <ul style="list-style-type: none"> <li><b>APP VERSION</b> displays the application.</li> <li><b>BOOT VERSION</b> displays the bootloader.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                          |                                                   |

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Default/Range                         |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|
| <p><b>HUMIDIFY SETPOINT</b>—Sets the humidify setpoint. When the heating equipment is energized and the humidity level is more than 2% below the humidify setpoint, the humidifier turns on.</p> <p>When the heating equipment turns off or the humidity level is more than 2% above the humidify setpoint, the humidifier turns off.</p> <p><b>NOTES</b></p> <ul style="list-style-type: none"> <li>If the installer set <b>HUMIDIFIER</b> to <b>NO</b>, this setting is not available.</li> <li>If the installer did not set the <b>HUM OUTPUT</b> to 1 of the 3 configurable outputs, this setting is not available.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | <p>D: 15%rh</p> <p>R: 15 – 5%rh</p>   |
| <p><b>DEHUMIDIFY SETPOINT</b>—Sets the dehumidify setpoint. When the humidity level is greater than the dehumidify setpoint, dehumidification operates according to the installer configuration for the dehumidifier.</p> <p><b>NOTE</b> If cooling equipment is not available (based on the <b>OUTDOOR EQUIPMENT TYPE</b> selection, then dehumidification is not available in the thermostat.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | <p>D: 65%rh</p> <p>R: 35 to 65%rh</p> |
| <p><b>HOLIDAYS</b>—View or edit all holidays for the current year. When the current date in the thermostat is the same as a day in the holiday list, the setpoints for the first <b>UNOCCUPIED</b> time range are used for the entire day unless you later change them.</p> <p>When the <b>HOLIDAYS</b> screen displays, press <b>SELECT</b> to view the holidays. The up and down arrows scroll through the holidays, displaying one per screen.</p> <p>Maximum number of holidays in the holiday list is 24.</p> <p>There are two different holiday formats.</p> <ul style="list-style-type: none"> <li>Standard holidays are the same every year, such as Jan 1st and Dec 25th.</li> <li>Special holidays are occurrences of a day of the week such as Memorial Day, Labor Day, and Thanksgiving. The day of the week is shown in the heat setpoint location.</li> <li>For both types of holidays, the duration of the holiday is shown in the cool setpoint location.</li> <li>The top banner scrolls the holiday details.</li> </ul> <p>To program holidays:</p> <ul style="list-style-type: none"> <li>Press <b>SELECT</b> to display the <b>SAVE</b> and <b>CANCEL</b> buttons</li> <li>When the month flashes, use the up and down arrows to change it.</li> <li>To change the day of the month, touch the screen location that shows the day of the month and it flashes.</li> <li>To change the duration, touch the duration value and it flashes.</li> <li>To delete a holiday, set the duration field to zero and press <b>SAVE</b>. The banner scrolls <b>DELETE HOLIDAY</b>.</li> <li>To add a holiday, scroll through the list of holidays to the end. The last entry is the <b>ADD HOLIDAY</b> screen. Press <b>SELECT</b> to add a new holiday. The new holiday is initialized to 1/01 with a duration of one day.</li> <li>The day of the month advances from 1 to the last day of the month and then Su, Mo, Tu, We, Th, Fr and Sa, and then back to 1. When the days of the week are displayed, an occurrence value is shown in the heat setpoint. This allows the user to enter a special holiday.</li> </ul> <p><b>NOTE</b> If the thermostat has been configured for non-programmable operation, the <b>HOLIDAY</b> screen is not available in the Menu settings.</p> |                                       |

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Default/Range                                                |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------|
| <b>SCREEN TIMEOUT</b> —Set the number of seconds you want the home screen to stay active without any user interactions before transitioning to the dormant screen.<br>Banner displays <b>SCREEN TIMEOUT</b> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | D: 15 seconds<br>R: 5 to 30 seconds<br>(5 second increments) |
| <b>WI-FI ENABLE</b> —Enable (yes) or disable (no) the Wi-Fi functionality for the thermostat. If disabled, the Wi-Fi radio in this product is turned off and Wi-Fi functionality is unavailable, including <b>SYNC TIME TO SERVER</b> , <b>OUTDOOR TEMPERATURE</b> via Wi-Fi geolocation, <b>SERVER &amp; WI-FI ERRORS</b> and <b>REMOTE ACCESS SERVICES</b> via APP or WEB.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | D: YES<br>R: YES<br>NO                                       |
| <b>FLTR HRS LEFT xxxx</b> —The number of hours left before the filter reminder displays<br><b>RESET FILTER</b> —Reset the filter hours to the installer-specified number if the filter is changed prior to the timer counting down to zero. Press <b>SELECT</b> , use up and down arrows to display <b>YES</b> , and press <b>SAVE</b> .<br><b>NOTE</b> Decrements to the timer happen each hour of total equipment runtime. The accumulated run time hours are stored to non-volatile memory, but the minutes are not, so a power cycle does not retain partial hour runtime.<br><b>FILTER REMINDER</b> displays on the home screen and dormant screen banners when the filter timer counts down to zero.<br>If you touch the home screen banner when the <b>FILTER REMINDER</b> message displays, the thermostat transitions directly to <b>FLT HRS LEFT</b> screen. The banner message button is a shortcut to the <b>FLT HRS LEFT</b> screen when the filter timer has expired. You can access the <b>FLT HRS LEFT</b> screen at any time through the menu. | D: NO<br>R: YES<br>NO                                        |

## To adjust the banner text

These settings allow you to customize the information shown on the top banners of the home and dormant screens.

The **FAN STATUS**, **HEAT SETPOINT**, and **COOL SETPOINT** selections only apply to the dormant screen banner because this information is already displayed in other areas of the home screen.

| Setting                                                                                                                                                                                                                                                                                                                                                                                           | Default/Range |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| <b>DATE AND TIME</b> <ul style="list-style-type: none"> <li>When the date and time setting is <b>NO</b>, the date and time information are not displayed on the home or dormant screen banners.</li> <li>When the date and time setting is <b>YES</b>, the date, in month/day/year format, and the time, in 12 hour AM/PM format, display in both the home and dormant screen banners.</li> </ul> | R: YES<br>NO  |
| <b>FAN STATUS</b> <ul style="list-style-type: none"> <li>When set to <b>NO</b>, the state of the fan output (the G relay) is not displayed on the dormant screen banner.</li> <li>When set to <b>YES</b>, the dormant screen banner displays either <b>FAN OFF</b> or <b>FAN ON</b>, based on the state of the fan output.</li> </ul>                                                             | R: YES<br>NO  |

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Default/Range |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| <b>OUTDOOR TEMP</b> <ul style="list-style-type: none"> <li>When set to <b>NO</b>, the outdoor temperature is not displayed on the home and dormant screen banners.</li> <li>When set to <b>YES</b>, the home and dormant screen banners display the outdoor air temperature. If there is not a source for the outdoor air temperature, <b>OUTDOOR N/A</b> shows.</li> </ul>                                                                                                                                            | R: YES<br>NO  |
| <b>COOL SETPT</b><br>When set to: <ul style="list-style-type: none"> <li><b>NO</b> - The cool setpoint is not displayed on the dormant screen banner.</li> <li><b>YES</b> - The cool setpoint is displayed on the dormant screen banner.</li> </ul> <b>NOTES</b> <ul style="list-style-type: none"> <li>The cool setpoint is not displayed on the home screen banner.</li> <li>The cool setpoint is displayed on the dormant screen when the mode is set to <b>COOL</b> or <b>AUTO</b>.</li> </ul>                     | R: YES<br>NO  |
| <b>HEAT SETPT</b> <ul style="list-style-type: none"> <li>When set to <b>NO</b>, the heat setpoint is not displayed on the dormant screen banner.</li> <li>When set to <b>YES</b>, the heat setpoint is displayed on the dormant screen banner.</li> </ul> <b>NOTES</b> <ul style="list-style-type: none"> <li>The heat setpoint is not displayed on the home screen banner.</li> <li>The heat setpoint is displayed on the dormant screen when the mode is set to <b>HEAT</b>, <b>EHEAT</b> or <b>AUTO</b>.</li> </ul> | R: YES<br>NO  |
| <b>HUMIDITY</b> <ul style="list-style-type: none"> <li>When set to <b>NO</b>, the humidity level is not displayed on the home and dormant screen banners.</li> <li>When set to <b>YES</b>, the home and dormant screen banners display the relative humidity percent.</li> </ul>                                                                                                                                                                                                                                       | R: YES<br>NO  |
| <b>SAT TEMP</b> (Supply Air Temperature) <ul style="list-style-type: none"> <li>When set to <b>NO</b>, the supply air temperature is not displayed on the home and dormant screen banners.</li> <li>When set to <b>YES</b>, the home and dormant screen banners display the supply air temperature.</li> <li><b>SAT TEMP</b> setting is only displayed if the <b>REMOTE SENSOR</b> (Installer Settings) is set to <b>SAT</b></li> </ul>                                                                                | R: YES<br>NO  |
| <b>CO2</b> <ul style="list-style-type: none"> <li>When set to <b>NO</b>, the CO2 value is not displayed on the home and dormant banners.</li> <li>When set to <b>YES</b>, the home and dormant screen banners will display the CO2 value.</li> <li>This option is only available if the CO2 sensor input is enabled.</li> </ul>                                                                                                                                                                                        |               |

## Using installer settings

To reach the Installer Settings screens, set the mode to **OFF** and press and hold the **MENU** button for 5 seconds.

Scrolling through the installer settings:

- The **HOME** button returns the installer to the home screen.
- The **UP** and **DOWN** arrows scroll through the settings.
- The **SELECT** button allows the installer to change the value of the setting.
- Press **DEFAULT** to set the value to the factory default. Press **SAVE** to store the value.
- Press **SAVE** to store the current value and return to the **SELECT** screen.
- Press **CANCEL** to return the setting value to the last saved value and then return to the **SELECT** screen.

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Default/Range                            |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|
| <b>HEAT EQUIP</b> —Set the type of heating equipment being used.<br>If you set the <b>COMPRESSOR</b> to <b>HP</b> , the heading of this screen is <b>EHEAT EQUIP</b> instead <b>HEAT EQUIP</b> .                                                                                                                                                                                                                                                                                                                | D: GAS<br>R: GAS<br>ELEC (Electric Heat) |
| <b>HEAT STAGES</b> <ul style="list-style-type: none"> <li>• If the <b>COMPRESSOR EQUIPMENT TYPE</b> is set to <b>HP</b>, the heading of this screen is <b>EHEAT STAGES</b>.</li> <li>• The option of <b>0</b> heat stages is only available if the <b>HEATING EQUIPMENT</b> is set to electric heat (<b>ELEC</b>).</li> <li>• If set to <b>2</b>, the <b>W2 RELAY OUTPUT</b> is not available for optional functions such as <b>HUMIDIFIER</b>, <b>DEHUMIDIFICATION</b>, and <b>OCCUPANCY OUTPUT</b></li> </ul> | D: 1<br>R: 0 to 2                        |
| <b>COMPRESSOR</b><br>When set to <b>NONE</b> : <ul style="list-style-type: none"> <li>• <b>COOL</b> mode is disabled</li> <li>• <b>DEHUMIDIFY</b> setting is not available</li> <li>• <b>COOL STAGES</b> setting is not available</li> <li>• <b>AUTO ALLOWED</b> setting is not available</li> </ul> When set to <b>HP</b> , the <b>0</b> output is not available for optional functions such as <b>HUMIDIFIER</b> , <b>DEHUMIDIFICATION</b> , and <b>OCCUPANCY OUTPUT</b> .                                    | D: AC<br>R: NONE<br>AC<br>HP             |

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Default/Range                                                                            |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
| <p><b>COOL STAGES</b>—The numbers of stages define the number of <b>HP</b> or <b>AC</b> cooling stages that are present in the compressor equipment. The numbers of stages chosen also define the number of HP heating stages that are present in the compressor equipment if the <b>COMPRESSOR</b> selection is <b>HP</b>.</p> <p><b>NOTES</b></p> <ul style="list-style-type: none"> <li>This setting is not available to the installer if the <b>COMPRESSOR</b> is set to <b>NONE</b>.</li> <li>The maximum number of stages is 2 if <b>HP</b> is selected.</li> <li>The maximum number of stages is 3 if <b>AC</b> is selected.</li> </ul> <p>If <b>COOL STAGES</b> is set to <b>3</b>, the Y3 relay output is used for the third-stage compressor cooling and is not available for optional functions such as <b>HUMIDIFIER</b>, <b>DEHUMIDIFICATION</b>, and <b>OCCUPANCY OUTPUT</b>.</p> | <p>D: 1</p> <p>R: 1 to 3</p>                                                             |
| <p><b>AUTO ALLOWED</b>—Enable or disable the selection of <b>AUTO</b> mode when the mode button is pressed. <b>AUTO</b> mode allows the thermostat to automatically switch from heating to cooling to maintain the conditioned temperature between the heating and cooling setpoints.</p> <p>NOTE <b>AUTO ALLOWED</b> is only available if both a heating source and a cooling source are available (<b>HEAT STAGES</b> greater than <b>0</b> and <b>COMPRESSOR</b> equal to <b>AC</b> or <b>HP</b>).</p>                                                                                                                                                                                                                                                                                                                                                                                       | <p>D: YES</p> <p>R: YES (Auto mode is available)<br/>NO (Auto mode is not available)</p> |
| <p><b>AUTO CHANGEOVER</b>—Defines an auto changeover of the minimum number of minutes of equipment off-time before switching from heat-to-cool or from cool-to-heat, when operating in <b>AUTO</b> Mode.</p> <p>This setting is only available if <b>AUTO ALLOWED</b> is set to <b>YES</b>. The top line in this screen scrolls to display <b>AUTO CHANGEOVER</b>.</p> <p>If the setpoint or the mode is changed, the auto changeover time is bypassed to provide a timely response to the user's request. The auto changeover time becomes active the next time the system is operating in heat and there is a cool demand, or the system is operating in cooling and there is a heating demand.</p>                                                                                                                                                                                           | <p>D: 30 minutes</p> <p>R: 5 to 30 minutes</p>                                           |

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Default/Range                                         |               |               |               |            |      |       |       |            |       |       |       |            |       |       |       |            |       |       |       |                                                                                                                                                |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------|---------------|---------------|---------------|------------|------|-------|-------|------------|-------|-------|-------|------------|-------|-------|-------|------------|-------|-------|-------|------------------------------------------------------------------------------------------------------------------------------------------------|
| <p><b>PROGRAMMABLE OR NON-PROGRAMMABLE</b>—Set the thermostat to operate as a non-programmable (simplified) thermostat or a programmable thermostat.</p> <p>Operating the thermostat in a programmable mode allows the end user to setup heating and cooling setpoints for 2 or 4 periods of each day of the seven days of the week.</p> <p>The thermostat has default heating and cooling setpoints outlined in the <b>Default Setpoint Times and Temperature Settings</b> table shown below.</p> <p>The program heating and cooling setpoints and transition times for the 2 or 4 periods can be viewed or modified in <i>PROGRAM SCHEDULE</i> (page 26) on the thermostat.</p> <p>Choosing the non-programmable mode for the thermostat allows it to run in a simplified mode that will satisfy heating or cooling setpoints based on the setpoint value and mode.</p> <p>When the thermostat is set to <b>NP</b> (non-programmable):</p> <ul style="list-style-type: none"><li>• <b>OCC/UNOCC/RESUME SCHEDULE</b> button is not displayed on the home screen.</li><li>• <b>OCCUPIED</b>, <b>UNOCCUPIED</b>, and <b>SCHEDULE PAUSED</b> icons are not displayed on the home screen.</li><li>• The program schedule cannot be viewed.</li></ul> <p>When the <b>REMOTE SENSOR</b> setting is set to <b>OCC</b> (Occupancy), this setting is forced to <b>NP</b> and is not displayed to the installer.</p> <p><b>Default setpoint times and temperature settings</b></p> <table><tr><th>Setting</th><th>Start time</th><th>Heat setpoint</th><th>Cool setpoint</th></tr><tr><td>1st Period</td><td>7 AM</td><td>70 °F</td><td>75 °F</td></tr><tr><td>2nd Period</td><td>5 PM.</td><td>62 °F</td><td>85 °F</td></tr><tr><td>3rd Period</td><td>10 PM</td><td>70 °F</td><td>75 °F</td></tr><tr><td>4th Period</td><td>11 PM</td><td>62 °F</td><td>85 °F</td></tr></table> | Setting                                               | Start time    | Heat setpoint | Cool setpoint | 1st Period | 7 AM | 70 °F | 75 °F | 2nd Period | 5 PM. | 62 °F | 85 °F | 3rd Period | 10 PM | 70 °F | 75 °F | 4th Period | 11 PM | 62 °F | 85 °F | <p>D:    PROG</p> <p>R:    PROG            (programmable thermostat)</p> <p>      NP            [non-programmable (simplified) thermostat]</p> |
| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Start time                                            | Heat setpoint | Cool setpoint |               |            |      |       |       |            |       |       |       |            |       |       |       |            |       |       |       |                                                                                                                                                |
| 1st Period                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 7 AM                                                  | 70 °F         | 75 °F         |               |            |      |       |       |            |       |       |       |            |       |       |       |            |       |       |       |                                                                                                                                                |
| 2nd Period                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 5 PM.                                                 | 62 °F         | 85 °F         |               |            |      |       |       |            |       |       |       |            |       |       |       |            |       |       |       |                                                                                                                                                |
| 3rd Period                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 10 PM                                                 | 70 °F         | 75 °F         |               |            |      |       |       |            |       |       |       |            |       |       |       |            |       |       |       |                                                                                                                                                |
| 4th Period                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 11 PM                                                 | 62 °F         | 85 °F         |               |            |      |       |       |            |       |       |       |            |       |       |       |            |       |       |       |                                                                                                                                                |
| <p><b>MAXIMUM HOLD HOURS</b>—Set the amount of time, in hours, that a setpoint change overrides the program schedule.</p> <p>Range</p> <ul style="list-style-type: none"><li>• <b>OFF</b> - When set to <b>OFF</b>, the setpoints cannot be changed from their program schedule values.</li><li>• <b>1 to 6</b> - User setpoint change remains active for this number of hours and then the setpoint returns to the <b>PROGRAM SCHEDULE</b> setpoints.</li></ul> <p><b>NOTE</b> This selection is not available if the thermostat has been configured as non-programmable.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | <p>D:    2 Hours</p> <p>R:    OFF<br/>      1 - 6</p> |               |               |               |            |      |       |       |            |       |       |       |            |       |       |       |            |       |       |       |                                                                                                                                                |
| <p><b>F OR C UNITS</b>—Sets the temperature units to either F (Fahrenheit) or C (Celsius).</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | <p>D:    F</p> <p>R:    F/C</p>                       |               |               |               |            |      |       |       |            |       |       |       |            |       |       |       |            |       |       |       |                                                                                                                                                |

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Default/Range                                                                                   |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|
| <p><b>SMART RECOVERY</b> — Transitions the conditioned space from one programmable temperature period to the next with 1°F increments of the heating setpoint or 1°F decrements of the cooling setpoint, so that by the time the next period starts, the setpoints are at the desired temperature. The purpose of the gradual transition is to use less energy by preventing staging up (because of a higher demand) to higher stages. The transitions occur in a linear fashion over the smart recovery time period.</p> <ul style="list-style-type: none"> <li>If you start a temporary hold in the middle of a smart recovery, the setpoints of the temporary hold are used.</li> <li>If a temporary hold is already active during the time that smart recovery would have been started, a smart recovery does not start.</li> </ul> <p>If the temporary hold ends in the middle of what would have been a smart recovery, the smart recovery starts where it would have been in the linear progression at the same time as when the temporary hold was not active.</p> <p><b>NOTE</b> The smart recovery setting is only available if the thermostat is configured as a programmable thermostat.</p> | <p>D: 30</p> <p>R: NO<br/>30 minutes<br/>60 minutes<br/>90 minutes</p>                          |
| <p><b>FAN ON WITH W</b>—Sets the fan to turn on with any <b>W</b> output when the fan is set to <b>AUTO</b>.</p> <p>Range</p> <ul style="list-style-type: none"> <li><b>YES</b> - The <b>G</b> output is turned on by the thermostat when the <b>W1</b> or <b>W2</b> outputs are energized.</li> <li><b>NO</b> - The <b>G</b> output is not turned on by the thermostat when the <b>W1</b> or <b>W2</b> outputs are energized.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | <p>D: YES</p> <p>R: YES<br/>NO</p>                                                              |
| <p><b>REVERSING VALVE</b> — Defines whether the <b>ON</b> state of the reversing valve (<b>O/B</b>) is used for heat pump heating or heat pump cooling if <b>OUTDOOR EQUIPMENT TYPE</b> is set to <b>HP</b>.</p> <ul style="list-style-type: none"> <li>When the <b>ON</b> state of the reversing valve is used for cooling, the signal is typically referred to as a <b>O</b>.</li> <li>When the <b>ON</b> state of the reversing valve is used for heating, the signal is typically referred to as a <b>B</b> demand.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | <p>R: HEAT<br/>COOL</p>                                                                         |
| <p><b>SPACE TEMP OFFSET</b>—Sets an offset to the displayed space temperature, which gives the end user the convenience of matching the actual sensed temperature to a different perceived temperature or a different temperature measuring device.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | <p>D: OFF</p> <p>R: -5 to -1<br/>OFF<br/>1 to 5°F<br/>-2.7 to -0.5<br/>OFF<br/>0.5 to 2.7°C</p> |

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Default/Range                                                                          |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|
| <p><b>REMOTE SENSOR</b>—Set the functionality of the remote sensor input that is connected to the <b>T</b> and <b>C</b> terminals.</p> <p>Range</p> <ul style="list-style-type: none"> <li>• <b>NONE</b> - Any input on the remote sensor is ignored by the thermostat.</li> <li>• <b>ID</b> - The remote sensor input is used for the space temperature.</li> <li>• <b>ODT</b> - The remote sensor input is used for the outdoor air temperature.</li> <li>• <b>AVG</b> - The space temperature is calculated as the average of the local thermistor and the remote thermistor.</li> <li>• <b>OCC</b> - The remote sensor input determines if the occupied or unoccupied setpoints are used. When a short is detected, the occupied settings are used.</li> <li>• <b>SAT</b> - The remote sensor input determines the supply air temperature as displayed in the BACnet SAT Analog Value object.</li> <li>• <b>ECFL</b> - The remote sensor input is used to detect an Economizer fault. When the input is shorted, the home screen banner indicates an alarm is detected by displaying the words <b>ECONOMIZER FAULT</b>. This fault is logged into the fault history as well.</li> <li>• <b>FLTR</b> - The remote input can be configured to detect a dirty filter. When the input is shorted, the message <b>FILTER REMINDER</b> is displayed on the home screen banner. The message is cleared when the remote input is not shorted. This selection disables the timed air filter reminder.</li> </ul> <p><b>NOTES</b></p> <ul style="list-style-type: none"> <li>• If the remote sensor is set to <b>NONE</b> or <b>ID</b>, the outdoor temperature is acquired via Wi-Fi through the server (based on the geolocation of the phone/tablet used to connect the thermostat to a router).</li> <li>• The outdoor temperature is available if the thermostat is not connected to Wi-Fi and the <b>ODT</b> option is not selected for the <b>REMOTE SENSOR</b>.</li> <li>• If you select <b>OCC</b>, the non-programmable (<b>NP</b>) setting is set automatically and not displayed in the installer settings until this setting is changed.</li> </ul> | <p>D: NONE</p> <p>R: NONE<br/>ID<br/>ODT<br/>AVG<br/>OCC<br/>SAT<br/>ECFL<br/>FLTR</p> |
| <p><b>SAT OFFSET</b>—Sets an offset to the supply air temperature, which allows the value read from the SAT_TEMP BACnet object to be calibrated to match other presentations of this measurement.</p> <p>This setting is only available if the <b>REMOTE SENSOR</b> is set to <b>SAT</b>.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | <p>D: OFF</p> <p>R: -5 to 1, OFF, 1° - 5°F<br/>-2.7 to -0.5, OFF,<br/>0.5° - 2.7°C</p> |
| <p><b>COOL LOCKOUT</b>—Sets an outdoor air temperature below which the cooling equipment is held off.</p> <p><b>NOTE</b> If the <b>REMOTE SENSOR</b> is set to something other than <b>ODT</b>, there is no outdoor air temperature being provided by the server and the <b>COOL LOCKOUT</b> is set to a temperature, the message <b>OUTDOOR N/A</b> is displayed on the home and dormant screen banners to indicate an outdoor sensor is required but there is no outdoor temperature information available.</p> <p>If there is no valid outdoor temperature in the system, the cooling is not inhibited.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | <p>D: OFF</p> <p>R: OFF<br/>0°F - 80°F (in 5°F increments)</p>                         |

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Default/Range                                                             |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|
| <p><b>LOW COOL LOCKOUT TEMPERATURE</b></p> <p>Range</p> <ul style="list-style-type: none"> <li><b>OFF</b> - Functionality disabled. Cooling always starts with first stage compressor (<b>Y1</b>) and stages up to second stage (<b>Y1</b> and <b>Y/Y2</b>) when the demand is sufficient and staging and cycle timer constraints have been satisfied.</li> <li><b>80° - 110° F</b> - (5° F increments) Outdoor temperature above which both the first and second stages of the compressor are energized to satisfy all cooling demands. This check is performed when the first stage of the compressor is energized. If at the time the compressor is energized the outdoor air temperature is greater than or equal to the low cool lockout temperature, then the second stage of the compressor is energized also. When a cycle starts under a low cool lockout condition, it finishes the cooling cycle on high speed. If the cooling equipment is energized to satisfy a dehumidify demand only (no cooling demand), the low cool lockout is not applied.</li> <li><b>ON</b> - The <b>Y1</b> and <b>Y/Y2</b> outputs are simultaneously energized to satisfy all cooling demands.</li> </ul> <p><b>NOTES</b></p> <ul style="list-style-type: none"> <li>If there is no valid outdoor temperature and the <b>LOW COOL LOCKOUT</b> is set to a temperature (not <b>OFF</b> or <b>ON</b>), the message <b>OUTDOOR N/A</b> is displayed in the banner and the low cool lockout setting is ignored (acts as if the setting is <b>OFF</b>).</li> <li>If the system does not have a 2-stage heat pump, this selection is not available.</li> </ul>                                                                                                                   | <p>D: OFF</p> <p>R: OFF<br/>80° - 110° F<br/>(5° F increments)<br/>ON</p> |
| <p><b>LOW HEAT LOCKOUT TEMPERATURE</b>—Sets an outdoor air temperature below which low speed compressor heating is locked out. Below the specified air temperature, all heating demands that use the compressor use high speed compressor heating.</p> <p>Range</p> <ul style="list-style-type: none"> <li><b>OFF</b> - Functionality disabled. Compressor heating always starts with first stage compressor <b>Y1</b> and stages up to second stage <b>Y1</b> and <b>Y/Y2</b> when the demand is sufficient and staging and cycle timer constraints have been satisfied.</li> <li><b>20° - 50° F</b> - Outdoor temperature below which both the first and second stages of the compressor are energized to satisfy all heating demands. This check is performed when the first stage of the compressor is energized. If at the time the compressor is energized, the outdoor air temperature is less than or equal to the <b>LOW HEAT LOCKOUT TEMPERATURE</b>, then the second stage of the compressor is energized also. When a cycle starts under a low heat lockout condition, it will finish the heating cycle on high speed.</li> <li><b>ON</b> - The <b>Y1</b> and <b>Y/Y2</b> outputs are simultaneously energized to satisfy all compressor heating demands, regardless of outdoor air temperature.</li> </ul> <p><b>NOTES</b></p> <ul style="list-style-type: none"> <li>If there is no valid outdoor temperature and the <b>LOW HEAT LOCKOUT</b> is set to a temperature (not <b>OFF</b> or <b>ON</b>), the message <b>OUTDOOR N/A</b> displays in the banner and the low heat lockout setting is ignored (acts as if the setting is <b>OFF</b>).</li> <li>If the system does not have a 2-stage heat pump, this selection is not available.</li> </ul> | <p>D: OFF</p> <p>R: OFF<br/>20° - 50° F<br/>ON</p>                        |

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Default/Range                                                |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------|
| <p><b>TIME BETWEEN FUEL TYPES (ELECTRIC TO GAS)</b>—Sets a minimum amount of time that the system runs on compressor heat before transitioning to the furnace.</p> <p>Range - The minimum number of minutes the compressor is energized to satisfy a heating demand before transitioning to gas heat.</p> <p><b>NOTES</b></p> <ul style="list-style-type: none"> <li>This selection is only available if the <b>HEATING EQUIPMENT</b> is set to <b>GAS</b> and the <b>COMPRESSOR</b> is set to <b>HP</b>.</li> <li>The minimum number of minutes the compressor runs in heating before staging up to gas heat is the larger of this setting and the <b>STAGE DELAY</b> setting.</li> </ul>                             | <p>D: 15 minutes</p> <p>R: 10, 15, 20, 25 minutes</p>        |
| <p><b>CYCLES PER HOUR</b>—Sets a maximum number of equipment cycles per hour. Based on selecting 2, 4, 6 or 8 cycles per hour, this timer is set to 30, 15, 10 or 8 minutes. This time must elapse from the start of one cycle before another cycle can start.</p> <p>The Range - The maximum number of times the equipment can turn on per hour.</p> <p><b>NOTE</b> When the equipment is off and the user changes the setpoint to create a heating or cooling demand, the cycles per hour requirement is ignored to provide a timely response to the user's request. The cycles per hour limitation become active again when the <b>Y1, Y2, W1</b> or <b>W2</b> outputs transition from <b>ON</b> to <b>OFF</b>.</p> | <p>D: 4</p> <p>R: 2, 4, 6, or 8</p>                          |
| <p><b>MAX HEAT SETPOINT</b>—Sets a maximum heating setpoint. This is the maximum heat setpoint value that can be used in the program schedule or when the user adjusts the setpoint to temporarily override the program schedule.</p> <p><b>NOTE</b> This setting is not available if <b>HEATING EQUIPMENT</b> is set to <b>NONE</b>. (<b>HEAT EQUIP</b> = <b>ELEC</b> and <b>HEAT STAGES</b> = <b>0</b>)</p>                                                                                                                                                                                                                                                                                                          | <p>D: 88 °F</p> <p>R: 50 ° – 88 °F<br/>(1 °F increments)</p> |
| <p><b>MIN COOL SETPOINT</b>—Sets a minimum cooling setpoint that can be used in the program schedule or when the user adjusts the setpoint to temporarily override the program schedule.</p> <p><b>NOTE</b> This setting is not available if the <b>COMPRESSOR</b> is set to <b>NONE</b>.</p>                                                                                                                                                                                                                                                                                                                                                                                                                          | <p>D: 52 °F</p> <p>R: 52 – 90 °F<br/>(1 °F increments)</p>   |

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Default/Range                                                    |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------|
| <p><b>AUX HEAT LOCKOUT</b>—Sets an outdoor temperature above which the <b>AUX HEAT (W1 and W2)</b> outputs are not energized in <b>HEAT</b> mode.</p> <p>If the selected mode is <b>EMERGENCY HEAT</b>, the auxiliary heat is allowed to turn on.</p> <p>The auxiliary heat lockout is checked when there is sufficient demand to energize <b>W1</b>, but the output has not been turned on. Once the output has been energized, it remains energized until the demand algorithm no longer requires the capacity of the auxiliary heat, regardless of the value of the outdoor air temperature.</p> <p><b>NOTES</b></p> <ul style="list-style-type: none"> <li>• The <b>AUX HEAT LOCKOUT</b> functionality is not available (and is set to the <b>OFF</b> setting) with the <b>OUTDOOR EQUIPMENT TYPE</b> of <b>NONE</b> or <b>AC</b> selected, because the <b>AUX HEAT LOCKOUT</b> functionality needs HP heating to operate.</li> <li>• If the <b>REMOTE SENSOR</b> is set to something other than <b>ODT</b>, there is no outdoor air temperature being provided by the server and <b>AUX HEAT LOCKOUT</b> is set to a temperature, the message <b>OUTDOOR N/A</b> is displayed in the home and dormant screen banners to indicate an outdoor sensor is required but there is no outdoor temperature information available.</li> <li>• In a dual fuel unit, the auxiliary heat lockout temperature is set to a value less than the heat pump lockout temperature. This is to prevent the condition where the range of outdoor air temperatures between the auxiliary heat lockout and the heat pump lockout temperature result in no equipment operation. Below the heat pump lockout temperature, the air source attempts to turn on but the auxiliary heat lockout temperature prevents it from doing so. If the auxiliary heat lockout temperature is changed so that it is less than the heat pump lockout temperature, the heat pump lockout temperature is set equal to auxiliary heat lockout temperature value. This change to the heat pump lockout temperature is not visible to the user while the auxiliary heat lockout temperature is being changed.</li> </ul> | <p>D: OFF</p> <p>R: OFF<br/>5° – 55 °F<br/>(5 °F increments)</p> |

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Default/Range                                                            |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|
| <p><b>HP LOCKOUT</b>—Sets an outdoor temperature below which the heat pump does not operate. If set to <b>OFF</b>, the heating equipment cycle always starts with the heat pump, regardless of the outdoor air temperature. If a lockout temperature is selected and the outdoor air temperature is less than the selected temperature, the heating cycle is started with the <b>AUX HEAT SOURCE</b>. If the outdoor air temperature is equal to or greater than the selected temperature, the heating cycle is started with the heat pump. If the outdoor temperature is not available, all heating cycles with compressor heat.</p> <p>When the heat pump is not energized but there is demand sufficient to request heat pump heating, the heat pump lockout temperature is checked against the outdoor air temperature and if the outdoor air temperature is greater than the heat pump lockout temperature the heat pump is energized. Once the heat pump is energized, it remains energized until the heating demand no longer requires heat pump heating, regardless of the outdoor air temperature.</p> <p>NOTES</p> <ul style="list-style-type: none"> <li>The <b>HP LOCKOUT</b> functionality is not available if the <b>OUTDOOR EQUIPMENT TYPE</b> is set to <b>NONE</b> or <b>AC</b>, because the <b>AUX HEAT LOCKOUT</b> functionality is only applicable to heat pump systems.</li> <li>If the <b>REMOTE SENSOR</b> is set to something other than <b>ODT</b>, there is no outdoor air temperature is provided by the server and the <b>HP LOCKOUT</b> is set to a temperature, the message <b>OUTDOOR N/A</b> is displayed in the home screen and dormant screen banners to indicate an outdoor sensor is required but there is no outdoor temperature information available.</li> <li>Do not set the heat pump lockout temperature to a value greater than the auxiliary heat lockout temperature unless the auxiliary heat lockout temperature setting is <b>OFF</b>. This prevents the condition where the range of outdoor air temperatures between the auxiliary heat lockout and the heat pump lockout temperature result in no equipment operation. Below the heat pump lockout temperature, the AUX heat source attempts to turn on, but the auxiliary heat lockout temperature prevents it from doing so. If the heat pump lockout temperature is changed so that it is greater than the auxiliary heat lockout temperature, the auxiliary heat lockout temperature value is set equal to the heat pump lockout temperature.</li> </ul> | <p>D: OFF</p> <p>R: OFF<br/>5° – 55° F<br/>(5° F increments)</p>         |
| <p><b>STAGE DELAY</b>—Sets the minimum amount of time the current stage must be energized before staging up to the next stage of capacity.</p> <p><b>NOTE</b> Multiple heating stages or multiple cooling stages must exist to use this feature.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | <p>D: 10 minutes</p> <p>R: 2 to 15 minutes<br/>(1 minute decrements)</p> |

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Default/Range                                                                        |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| <p><b>FORCED STAGE UP</b>—Sets the maximum number of minutes that the equipment runs at the current stage before forcing the equipment to stage up. The forced stage up occurs even if the differential demand is not met.</p> <p><b>NOTE</b> Multiple heating stages or multiple cooling stages must exist to use this feature.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | <p>D: 30 minutes</p> <p>R: OFF<br/>10 to 120 minutes<br/>(10 minute decrements)</p>  |
| <p><b>DIFFERENTIAL</b>—Sets a value that specifies the required difference between the current space temperature and the setpoint that results in the equipment being energized to satisfy the demand. This value is additive for each additional stage of equipment being demanded.</p> <p>(e.g. A chosen differential value of 0.5 °F requires 0.5° difference between setpoint and space temperature before first stage is turned on. Then a value of 1.0 degree of difference between setpoint and space temperature before second stage is turned on.)</p>                                                                                                                                                                                                                                                                                                                                                                                                               | <p>D: 1 °F</p> <p>R: 0.3 ° to 2.0 °F<br/>(0.1 °F increments)</p>                     |
| <p><b>AIR FILTER REMINDER</b>—Sets a value that specifies the number of equipment run hours before a <b>FILTER REMINDER</b> message is displayed on the home and dormant screen banners to remind the user to change the indoor air filter.</p> <p>No message is displayed to the user if the setting is <b>OFF</b>. Decrements to the timer occur each hour total equipment runtime is accumulated. Minute counts within each hour are not stored in non-volatile memory, so a power reset clears out the minutes within each hour of run time. The filter reset reminder hour timer value is stored in non-volatile memory.</p> <p>The top line in this screen scrolls to display AIR FILTER REMINDER HRS x 100</p> <p><b>NOTE</b> If the <b>REMOTE SENSOR</b> is set to <b>FLTR</b> to detect a dirty filter, this setting is disabled and not available to the installer.</p>                                                                                             | <p>D: 3000 hours</p> <p>R: OFF<br/>500 to 15,000 hours<br/>(100 hour increments)</p> |
| <p><b>OCCUPANCY OUTPUT</b>—Select which output relay to use for the Occupancy Output. The choices only include outputs that are not already assigned to another function.</p> <p>The output that you select (<b>Y3</b>, <b>O/B</b>, or <b>W2</b>) is energized when in the occupied state and de-energized when in the unoccupied state.</p> <p><b>NOTE</b> The occupancy output option is not available if the <b>Y3</b>, <b>O/B</b>, and <b>W2</b> relays are already being used for other functions. The <b>Y3</b> output is used for 3 stages of cooling, the humidifier, and the dehumidifier setting of HumidiMiZer™. The <b>O/B</b> output is used for heat pump equipment, the humidifier, and the dehumidifier setting of HumidiMiZer™. The <b>W2</b> output is used for 2 stages of heating, the humidifier, and the dehumidifier setting of HumidiMiZer™.</p> <p>Any output that is already being used is not shown in the <b>OCCUPANCY OUTPUT</b> selections.</p> | <p>D: OFF</p> <p>R: OFF<br/>Y3<br/>O/B<br/>W2</p>                                    |
| <p><b>OCCUPANCY INPUT</b>—Select what to do when a short on the remote temperature sensor is detected.</p> <p>The <b>OCC</b> (occupied) setting changes the current heat and cool setpoints to the occupied setpoints for the current time range for the maximum hold time when a short is detected on the remote temperature sensor for the duration of 2 to 5 seconds.</p> <p>The <b>UNOCC</b> (unoccupied) setting changes the current heat and cool setpoints to the unoccupied setpoints for the current time range for the maximum hold time when a short is detected on the remote temperature sensor for the duration of 2 to 5 seconds.</p>                                                                                                                                                                                                                                                                                                                          | <p>D: OCC</p> <p>R: OCC<br/>UNOCC</p>                                                |

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Default/Range                                     |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------|
| <p><b>ANALOG INPUT</b>—This setting allows the installer to specify the sensor that is connected to the Analog Input terminals (H and C)</p> <p>Range</p> <ul style="list-style-type: none"> <li><b>NONE</b> - no sensor is connected</li> <li><b>RH</b> - a remote humidity sensor is connected</li> <li><b>CO2</b> - A remote CO2 sensor is connected</li> </ul> <p>Default</p> <ul style="list-style-type: none"> <li><b>NONE</b></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | <p>D: STAT</p> <p>R: STAT<br/>RMT</p>             |
| <p><b>ANALOG INPUT SCALING</b>—Specify the type of electrical signal that is output by the remote sensor configured for use in the <b>ANALOG INPUT</b> setting. This setting is not available if the <b>ANALOG INPUT</b> is set to <b>NONE</b>.</p> <p>Range</p> <ul style="list-style-type: none"> <li><b>0 to 10</b> - When using a 0-10 V signal from sensor</li> <li><b>2 to 10</b> - When using a 4-20ma signal with 500 ohm resistor</li> </ul> <p>Default</p> <ul style="list-style-type: none"> <li><b>2 to 10</b></li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                     | <p>D: 2 to 10</p> <p>R: 0 to 10<br/>2 to 10</p>   |
| <p><b>HUMIDITY OFFSET</b>—Set an offset to the displayed humidity. This functionality offers the end user the convenience of matching the actual sensed humidity to a different perceived humidity or a different humidity measuring device.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | <p>D: OFF</p> <p>R: OFF<br/>-9 to 9%rh</p>        |
| <p><b>HUMIDIFIER</b>—Enables humidifier control functionality. When humidifier control is enabled, the humidifier is energized if there is humidity demand and any heating equipment is energized.</p> <p>The output (<b>Y3</b>, <b>O/B</b> or <b>W2</b>) is a 24 Vac output only (sourced from <b>R</b>) and must be isolated with a relay at the indoor equipment if 120 Vac is needed to interface to a humidifier unit.</p> <p>NOTE Humidifier functionality is not available if <b>HEATING STAGES</b> is set to <b>NONE</b>.</p>                                                                                                                                                                                                                                                                                                                                                                                                                     | <p>D: NO</p> <p>R: NO<br/>YES</p>                 |
| <p><b>HUM OUTPUT</b>—Select which output relay to use for the humidifier. The choices only include outputs that are not already assigned to another function.</p> <p>The output that is selected (<b>Y3</b>, <b>O/B</b> or <b>W2</b>) is used to control the humidifier equipment.</p> <p>NOTE <b>HUM OUTPUT</b> is only available if the <b>HUMIDIFIER</b> setting is <b>YES</b>.</p> <p>The <b>HUM OUTPUT</b> option is not available if the Y3, O/B and W2 relays are already being used for other functions.</p> <ul style="list-style-type: none"> <li>The <b>Y3</b> output is used for 3 stages of cooling, the humidifier, and the dehumidifier setting of HumidiMiZer™.</li> <li>The <b>O/B</b> output is used for heat pump equipment, the humidifier, and the dehumidifier setting of the HumidiMiZer™.</li> <li>The <b>W2</b> output is used for 2 stages of heating, the humidifier, and the dehumidifier setting of HumidiMiZer™.</li> </ul> | <p>D: OFF</p> <p>R: OFF<br/>Y3<br/>O/B<br/>W2</p> |

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Default/Range                                                                                                                                                       |           |                           |                               |                                               |                                                                                                                                                                     |                           |                                                                                                  |                                                     |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|---------------------------|-------------------------------|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|--------------------------------------------------------------------------------------------------|-----------------------------------------------------|
| <p><b>DEHUMIDIFIER</b>—Enable the dehumidification functionality.</p> <p>Range:</p> <ul style="list-style-type: none"> <li><b>NO</b> – Dehumidification is disabled</li> <li><b>YES</b> – When the humidity is above the dehumidify target, the cooling setpoint is adjusted downward, increasing the cooling demand according to the following equations. The system uses the first stage of cooling to satisfy the dehumidify demand.</li> </ul> <table border="1"> <thead> <tr> <th>Cooling setpoint</th><th>Algorithm</th></tr> </thead> <tbody> <tr> <td><math>\leq 70^{\circ}\text{F}</math></td><td>Use the cooling setpoint only</td></tr> <tr> <td><math>70.1^{\circ}\text{F} - 74.9^{\circ}\text{F}</math></td><td>Cooling setpoint = Cooling Setpoint – (Cooling Setpoint - <math>70^{\circ}\text{F}</math>) x (Dehumidify Error / 10) with maximum dehumidify Error of 6% (i.e. use 6% if &gt;6%)</td></tr> <tr> <td><math>\geq 75^{\circ}\text{F}</math></td><td>Cooling setpoint = Cooling Setpoint – (Dehumidify Error / 2) with maximum dehumidify Error of 6%</td></tr> </tbody> </table> <ul style="list-style-type: none"> <li><b>OVCL</b> - Commands the system to operate the compressor, within limits, when there is a dehumidification demand, even if there is no cooling demand. The system uses first stage of cooling to overcool up to <math>2^{\circ}\text{F}</math> and no more, when satisfying a dehumidification demand.</li> <li><b>HMZR</b> - When configured as a HumidiMiZer™ output, and the humidity level is above the dehumidify target, 24V is output at the selected terminal. When the humidity level is below the dehumidify target, 0 Vac is output on the selected terminal. There is a +1/-4% hysteresis around the dehumidify target to prevent rapid on/off cycling of the selected output.</li> </ul> <p>This output may be connected to compressor outputs on commercial equipment. If the selected output is energized without any compressors being energized, the 5-minute time guard must be enforced.</p> <p>NOTE If the <b>COMPRESSOR TYPE</b> is set to <b>NONE</b>, dehumidification is not available.</p> | Cooling setpoint                                                                                                                                                    | Algorithm | $\leq 70^{\circ}\text{F}$ | Use the cooling setpoint only | $70.1^{\circ}\text{F} - 74.9^{\circ}\text{F}$ | Cooling setpoint = Cooling Setpoint – (Cooling Setpoint - $70^{\circ}\text{F}$ ) x (Dehumidify Error / 10) with maximum dehumidify Error of 6% (i.e. use 6% if >6%) | $\geq 75^{\circ}\text{F}$ | Cooling setpoint = Cooling Setpoint – (Dehumidify Error / 2) with maximum dehumidify Error of 6% | <p>D: NO</p> <p>R: NO<br/>YES<br/>OVCL<br/>HMZR</p> |
| Cooling setpoint                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Algorithm                                                                                                                                                           |           |                           |                               |                                               |                                                                                                                                                                     |                           |                                                                                                  |                                                     |
| $\leq 70^{\circ}\text{F}$                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Use the cooling setpoint only                                                                                                                                       |           |                           |                               |                                               |                                                                                                                                                                     |                           |                                                                                                  |                                                     |
| $70.1^{\circ}\text{F} - 74.9^{\circ}\text{F}$                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Cooling setpoint = Cooling Setpoint – (Cooling Setpoint - $70^{\circ}\text{F}$ ) x (Dehumidify Error / 10) with maximum dehumidify Error of 6% (i.e. use 6% if >6%) |           |                           |                               |                                               |                                                                                                                                                                     |                           |                                                                                                  |                                                     |
| $\geq 75^{\circ}\text{F}$                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Cooling setpoint = Cooling Setpoint – (Dehumidify Error / 2) with maximum dehumidify Error of 6%                                                                    |           |                           |                               |                                               |                                                                                                                                                                     |                           |                                                                                                  |                                                     |
| <p><b>DEHUM OUTPUT</b>— Select which output relay to use for the HumidiMiZer™ function of the dehumidifier. The choices only include outputs that aren't already assigned to another function and is only available if the dehumidifier selection is set to HumidiMiZer™.</p> <p>When dehumidifier setting is HumidiMiZer™, the selected relay controls the HumidiMiZer™ equipment.</p> <p>This setting is not available if the configurable outputs (<b>Y3</b>, <b>O/B</b>, and <b>W2</b>) are already assigned to other functions.</p> <p>Any configurable output that is already assigned to another function is not shown in the <b>DEHUM OUTPUT</b> selections.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | <p>D: OFF</p> <p>R: OFF<br/>Y3<br/>O/B<br/>W2</p>                                                                                                                   |           |                           |                               |                                               |                                                                                                                                                                     |                           |                                                                                                  |                                                     |

Using installer settings

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Default/Range |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| <p><b>CO2 FAULT THRESHOLD</b> - Allows the installer to specify the threshold for the High CO2 fault. The <b>ANALOG INPUT</b> parameters must be set to CO2 for this setting to be available.</p> <p>Range</p> <ul style="list-style-type: none"> <li>• <b>900 to 1600 PPM</b></li> </ul> <p>Default</p> <ul style="list-style-type: none"> <li>• <b>1100 PPM</b></li> </ul>                                                                                                                                                                                                                                                                                                     |               |
| <p><b>CO2 CALIBRATION</b> - The <b>CO2 CALIBRATION</b> screen can be used to compensate for the variability of the components in the analog input circuitry. If the CO2 level is known from a reference or by measuring the DC voltage out of the sensor (<math>PPM = 200 \times VDC</math>), the calibration screen can be used to increase or decrease the value until it matches the reference. The Analog Input parameter must be set to CO2 for this setting to be available.</p> <p>Range</p> <ul style="list-style-type: none"> <li>• +/- 30% of uncalibrated value</li> </ul> <p>Default</p> <ul style="list-style-type: none"> <li>• Raw, uncalibrated value</li> </ul> |               |

## To set up BACnet

There are two points that act as gateways, allowing or prohibiting BACnet writes to configuration items (**BACNET CONFIG WRITE**) and occupancy control (**BACNET BMS OCC**). These variables are only accessible via the local screen.

A write to the Active Heat or Cool Setpoint (AV:409 or AV:410) places the thermostat into temporary override. This override will remain in effect until the MAX Temperature Hold Time (AV:502) expires. Default is 2 hours.

Long-term setpoint adjustment is accomplished by writing to the baseline setpoints (AV:400- AV:403).

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Default/Range                                                     |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|
| <p><b>BACNET ENABLE</b>—Enable or disable the BACnet communications. After restoring factory defaults, the user is prompted to decide whether or not to enable BACnet. Until this choice is made, the installer menu loads after every restart and the installer menu goes directly to the <b>BACNET ENABLE</b> setting where ? is displayed.</p> <p>NOTE Changing the <b>BACNET ENABLE</b> requires the thermostat to be restarted. When the installer exits the configuration settings after making changes to the BACnet settings, there is a prompt to either cancel those settings or save the new settings which force a thermostat reset.</p> | <p>D: NO (disabled)</p> <p>R: YES (enabled)<br/>NO (disabled)</p> |

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Default/Range                                                                                           |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|
| <p><b>MSTP MAX MASTER</b>—Set the maximum MAC address for BACnet MS/TP master devices. BACnet MS/TP MAC addresses for master devices exist in the range from 0 to 127. Each BACnet MS/TP device periodically looks for other devices (sends Poll for Master message) with addresses from its own address, plus one, to the next known address (wrapping to 0 after 127).</p> <p>Performance gains can be made on a BACnet MS/TP network by not leaving any gaps in MAC address and setting the MS/TP Max Master parameter of the device with the highest MAC address to a value equal to its MAC address. The downside to setting the MS/TP Max Master to a value less than 127 is, if new devices are added to the network with addresses above the Max Master value, they won't be discovered or added to the network.</p> <p>NOTES</p> <ul style="list-style-type: none"> <li>Changing the MS/TP Max Master requires restarting the thermostat. When the installer exits the configuration settings after making changes to the BACnet settings, there is a prompt to either cancel those settings or save the new settings, which forces a thermostat reset.</li> <li>The Max Master parameter should be set to a value equal to or greater than the MS/TP MAC Address.</li> </ul> <p>This setting is not displayed if BACnet is disabled</p> | <p>D: 127</p> <p>R: 1 to 127</p>                                                                        |
| <p><b>MSTP BAUD RATE</b>—Set the baud rate for the BACnet MS/TP communications to one of the following values: 9600, 19.2K (19200), 38.4K (38400), 76.8K (76800) or 115k (115200). The BACnet MS/TP baud rate must be set to match the other devices on the BACnet MS/TP network.</p> <p>NOTE Changing the MS/TP baud rate requires restarting the thermostat. When the installer exits the configuration settings after making changes to the BACnet settings, there is a prompt to either cancel those settings or save the new setting, which forces a thermostat reset.</p> <p>This setting is not be displayed if BACnet is disabled.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | <p>D: 76.8K</p> <p>R: 9600<br/>19.2K (19200)<br/>38.4K (38400)<br/>76.8K (76800)<br/>115k (115200).</p> |
| <p><b>MSTP MAC</b>—Set the BACnet MS/TP MAC addresses for master devices. Each BACnet MS/TP device on a MS/TP segment, must have a unique MAC address. Performance gains can be made on a BACnet MS/TP network by not leaving any gaps in MAC addresses, eliminating the need for each device to continuously check the addresses above its address and up to the next known device for new devices. Although the BACnet standard does not limit the use of MAC address zero, it is often reserved for an MS/TP router.</p> <p>NOTES</p> <ul style="list-style-type: none"> <li>Changing the MS/TP baud rate requires the thermostat to be restarted. When the installer exits the configuration settings after making changes to the BACnet settings, there is a prompt to either cancel those settings or save the new settings, which forces a thermostat reset.</li> <li>The MSTP MAC is set to a value less than or equal to the MSTP Max Master setting.</li> </ul> <p>This setting is not displayed if BACnet is disabled.</p>                                                                                                                                                                                                                                                                                                             | <p>D: 1</p> <p>R: 0-127<br/>(increments of 1)</p>                                                       |

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Default/Range                                                                                                                       |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| <p><b>BACNET UTC OFFSET</b>—Specify a UTC offset to be set from -13 to +13 hours in increments of 15 minutes.</p> <p>When a BACnet UTC Time synchronization message is received by the device, the value in UTC Offset is subtracted from the UTC Time to determine the local standard time. The Daylight Saving time logic is then applied to the standard time to get the local time with Daylight Saving.</p> <p>NOTE For reception of the UTC Time synchronization service to be enabled (and UTC offset used) on the device, the <b>SYNCH TIME TO SERVER</b> option has to be set to <b>NO</b> and <b>DST</b> must be set to <b>ENABLED</b>.</p> <p>This setting is not displayed if BACnet is disabled.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | <p>D: 5:00 (5 hours 0 minutes)</p> <p>R: -13:00 to 13:00<br/>(15 minute increments)</p>                                             |
| <p><b>DEVICE ID</b>—Specify a Device ID from 0 to 4194302. The Device ID can also be updated over BACnet when the <b>BACNET CONFIG WRITE</b> configuration is set to <b>YES</b>.</p> <p>Device IDs on BACnet devices must not only be unique on MS/TP segment like the MAC address, but must also be unique internetwork-wide. Each device broadcasts its Device ID using the I-Am service upon power up and in response to the Who-Is service. Changing the Device ID triggers a new I-Am message to be sent including the new Device ID.</p> <p>The top line in this screen scrolls to display the <b>DEVICE ID</b> and the ID value.</p> <p>The <b>SELECT</b> button changes the screen to the Device ID editor. Initially the first non-zero is flashing, indicating that it can be changed by the up and down arrows. There are left and right arrows in the middle row of the screen that can be pressed to move the cursor left and right to change each digit individually. Changing the Device ID triggers an I-Am message to be sent over BACnet and will increment the Database Revision property in the Device object.</p> <p>This setting is not displayed if BACnet is disabled.</p> | <p>D: 16xxxx where xxxx is the last four digits of the thermostat serial number.</p> <p>R: 0 to 4,194,302<br/>(increments of 1)</p> |
| <p><b>DEVICE NAME</b></p> <p>This setting can be viewed but not modified from the display. The <b>DEVICE NAME</b> can be updated over BACnet when the <b>BACNET CONFIG WRITE</b> is set to <b>YES</b>.</p> <p>Device Object Names on BACnet devices must not only be unique on MS/TP segment like the MAC address, but must also be unique internetwork-wide.</p> <p>The top line in this screen scrolls to display <b>DEVICE NAME</b> and the name.</p> <p>NOTE Changing the Device Object Name causes the Database Revision property of the Device to be incremented.</p> <p>This setting is not displayed if BACnet is disabled.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | <p>D: DEVICE 16xxxx (last 4 digits of the serial number)</p> <p>R: Any printable string with a maximum length of 16 characters</p>  |
| <p><b>DEVICE LOCATION</b>—To view, but not modify from the display, the Device Location, which is an optional property used to describe the physical location of the BACnet device.</p> <p>The <b>DEVICE LOCATION</b> can be updated over BACnet when the <b>BACNET CONFIG WRITE</b> configuration is set to <b>YES</b>.</p> <p>The top line in this screen scrolls to display the <b>DEVICE LOC</b> and the location.</p> <p>This setting is not displayed if BACnet is disabled.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | <p>D: LOCATION</p> <p>R: The display is limited to showing only the first 28 characters of the maximum 32 characters allowed.</p>   |

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Default/Range                                                                                                                        |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| <p><b>DEVICE DESCRIPTION</b>—To view, but not modify from the display, the Device Description. Description is an optional property used to add descriptive information about the BACnet device.</p> <p>The Device Description can be updated over BACnet when the <b>BACNET CONFIG WRITE</b> configuration is set to <b>YES</b>.</p> <p>The top line in this screen scrolls to display the <b>DEVICE DES</b> and the description.</p> <p><b>NOTE</b> This setting is not displayed if BACnet is disabled.</p>                                                                                                                                                                                                  | <p>D: DESCRIPTION</p> <p>R: The display is limited to showing only the first 28 characters of the maximum 32 characters allowed.</p> |
| <p><b>BACnet BMS OCC</b>—Enable or disable occupancy scheduling through the BACnet BMS by enabling or disabling the connection between the Present Value of the BACnet Binary Object Value named <b>BMS_OCC</b> and the occupancy state of the controller.</p> <p><b>NOTE</b> Occupancy is determined using 1 of 3 methods. <b>BACnet BMS OCC</b> is mutually exclusive with both <b>PROGRAMMABLE MODE</b> and <b>REMOTE SENSOR</b> set to <b>OCCUPANCY</b>. Setting <b>BACnet BMS OCC</b> to <b>Yes</b> forces <b>PROG</b> or <b>NON-PROG</b> to <b>NON-PROG</b> and switches <b>REMOTE SENSOR</b> to <b>None</b> if set to <b>OCCUPANCY</b>.</p> <p>This setting is not displayed if BACnet is disabled.</p> | <p>D: YES (enabled)</p> <p>R: YES (enabled)<br/>NO (disabled)</p>                                                                    |
| <p><b>BACNET CONFIG WRITE</b>—Allow (<b>YES</b>) or disallow (<b>NO</b>) BACnet writes to modify system settings. Many of the configuration items are exposed as BACnet objects. These BACnet objects can be read to verify the thermostat's configuration. If <b>BACnet Config Write</b> is set to <b>YES</b>, these objects can also be written to change the thermostat's configuration. If set to <b>NO</b>, these objects are read-only. <b>NOTE</b> This setting is not displayed if BACnet is disabled.</p>                                                                                                                                                                                             | <p>D: YES</p> <p>R: YES<br/>NO</p>                                                                                                   |
| <p><b>NET GP OUT TIMEOUT</b>—Set the timeout associated within network general purpose outputs. If this value is set to 2 minutes, 20 minutes, or 60 minutes, this number represents the maximum time that can lapse between writes to the Present Value property of the output object before the value returns to the inactive state.</p> <p><b>NOTE</b> This setting is not displayed if BACnet is disabled.</p>                                                                                                                                                                                                                                                                                             | <p>D: 2 minutes</p> <p>R: 2 – 2 minutes<br/>20 – 20 minutes<br/>60 – 60 minutes<br/>UNLM - Unlimited</p>                             |

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Default/Range                                                                                               |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|
| <p><b>NET GP Y3 MODE</b>—Select Network General Purpose Output <b>Y3</b> for control over the BACnet network.</p> <p>Setting the mode to:</p> <ul style="list-style-type: none"> <li>• <b>OFF</b> (disabled) sets the Present Value of the BACnet object to inactive and read-only and the corresponding output relay will be in a de-energized state.</li> <li>• <b>ACTV</b> (energized active) allows BACnet writes to the Present Value and energizes the output relay when the Present Value is active</li> <li>• <b>INAC</b> (energized inactive) allows BACnet writes to the Present Value and energizes the output relay when the Present Value is inactive. If a Network General Purpose Output timeout occurs, the Present Value goes to the inactive state and the relay is either energized <b>ACTV</b> or de-energized <b>INAC</b> depending on the mode.</li> </ul> <p>The outputs have primary assignments:</p> <ul style="list-style-type: none"> <li>• <b>Y3</b> - 3rd stage cooling</li> <li>• <b>W2</b> - 2nd stage heating</li> <li>• <b>OB</b> - Heat pump reversing valve</li> </ul> <p>If any of these outputs are required by the system configuration for their primary function, they are available for optional equipment (humidifier, dehumidifier, and occupancy output). Any output that is still available after configuring primary and optional equipment can be made available as a BACnet network-controlled output.</p> <p>This setting is not displayed if BACnet is disabled.</p>                                                                                                                                                                                 | <p>D: OFF (disabled)</p> <p>R: OFF (disabled)<br/>ACTV (energized active)<br/>INAC (energized inactive)</p> |
| <p><b>NET GP W2 MODE</b>—Select the Network General Purpose Output <b>W2</b> mode for control over the BACnet network. Setting the mode to OFF (disabled) sets the Present Value of the BACnet object to Inactive and read-only and the corresponding output relay will be in a de-energized state.</p> <p>Setting the mode to:</p> <ul style="list-style-type: none"> <li>• <b>OFF</b> (disabled) sets the Present Value of the BACnet object to inactive and read-only and the corresponding output relay will be in a de-energized state.</li> <li>• <b>ACTV</b> (energized active) allows BACnet writes to the Present Value and will energize the output relay when the Present Value is active.</li> <li>• <b>INAC</b> (energized inactive) allows BACnet writes to the Present Value and will energize the output relay when the Present Value is inactive. If a Network General Purpose Output timeout occurs, the Present Value goes to the inactive state and the relay is either energized ACTV or de-energized INAC depending on the mode.</li> </ul> <p>The outputs have primary assignments:</p> <ul style="list-style-type: none"> <li>• <b>Y3</b> - 3rd Stage cooling</li> <li>• <b>W2</b> - 2nd Stage heating</li> <li>• <b>OB</b> - Heat Pump reversing valve</li> </ul> <p>If any of these outputs are required by the system configuration for their primary function, they are available for optional equipment (humidifier, dehumidifier and occupancy output). Any output that is still available after configuring primary and optional equipment can be made available as a BACnet network-controlled output.</p> <p>This setting is not displayed if BACnet is disabled.</p> | <p>D: OFF (disabled)</p> <p>R: OFF (disabled)<br/>ACTV (energized active)<br/>INAC (energized inactive)</p> |

| Setting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Default/Range                                                                                               |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|
| <p><b>NET GP OB MODE</b>—Select the Network General Purpose Output <b>OB</b> mode for control over the BACnet network. Setting the mode to <b>OFF</b> (disabled) sets the Present Value of the BACnet object.</p> <p>Setting the mode to:</p> <ul style="list-style-type: none"> <li>• <b>OFF</b> (disabled) sets the Present Value of the BACnet object to inactive and read-only and the corresponding output relay will be in a de-energized state.</li> <li>• <b>ACTV</b> (energized active) allows BACnet writes to the Present Value and energizes the output relay when the Present Value is active.</li> <li>• <b>INAC</b> (energized inactive) allows BACnet writes to the Present Value and energizes the output relay when the Present Value is inactive. If a Network General Purpose Output timeout occurs, the Present Value goes to the inactive state and the relay is either energized ACTV or de-energized INAC depending on the mode.</li> </ul> <p>The outputs have primary assignments:</p> <ul style="list-style-type: none"> <li>• <b>Y3</b> - 3rd stage cooling</li> <li>• <b>W2</b> - 2nd stage heating</li> <li>• <b>OB</b> - Heat pump reversing valve</li> </ul> <p>If any of these outputs are required by the system configuration for their primary function, they are available for optional equipment (humidifier, dehumidifier, and occupancy output). Any output that is still available after configuring primary and optional equipment can be made available as a BACnet network-controlled output.</p> <p>This setting is not displayed if BACnet is disabled.</p> | <p>D: OFF (disabled)</p> <p>R: OFF (disabled)<br/>ACTV (energized active)<br/>INAC (energized inactive)</p> |
| <p><b>DISCONNECT WI-FI</b>—Allows the installer to disconnect from the Wi-Fi network.</p> <p><b>NOTE</b> This setting is not displayed if the thermostat is already disconnected from the Wi-Fi network.</p> <p>If the user chooses to disconnect the Wi-Fi, the control advances to the next setting since this one should not be displayed anymore.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | <p>D: NO</p> <p>R: YES<br/>NO</p>                                                                           |
| <p><b>MAXIMUM SETPOINT ERROR</b>—Select the number of degrees that cause an ID TEMP RANGE HIGH or ID TEMP RANGE LOW fault between the space temperature and the heat setpoint, if heating, or the cool setpoint, if cooling.</p> <p><b>NOTE</b> This value is added to the cooling setpoint or subtracted from the heating setpoint.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | <p>D: 10 °F</p> <p>R: 2 to 30 °F</p>                                                                        |
| <p><b>INDOOR TEMP FAULT INHIBIT</b>—Select the time delay applied to the ID TEMP RANGE HIGH and ID TEMP RANGE LOW faults. The fault condition must be present for the selected number of minutes for the fault to become active. This allows for recovery time when transitioning from unoccupied to occupied periods</p> <p>The top line in this screen scrolls to display ID TEMP FLT INHIBIT.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | <p>D: 60 minutes</p> <p>R: 10 to 240 minutes<br/>(10 minute increments)</p>                                 |

## To test the HVAC system

---

The installer uses this setting to test the HVAC system.

- 1 Press **SELECT** to open **INSTALLER TEST**.

**NOTE** The **HOME** and **SELECT** buttons are replaced with **MODE** and **CANCEL** buttons.



- 2 Press **MODE** to cycle through **OFF**, **COOL**, **HEAT**, and **EHEAT**.

### NOTES

- The availability of the modes are based on the installer configuration settings.
- The selected **MODE** operates each equipment stage for 3 minutes.
- The center of the display counts down the number of seconds remaining for the current stage of equipment operation.
- When the countdown reaches zero, if another stage exists, the banner text changes to **2ND STAGE** and a new 180-second countdown timer starts. If no other stage exists, the test cycle ends and the **MODE** is set to **OFF**.
- When **HEAT** or **EHEAT** modes are running and there is a configured humidifier, the output that controls the humidifier is energized.
- When **COOL** mode is running and a dehumidifier has been configured for operating a HumidiMiZer™, the output configured for the dehumidifier output is energized.

- 3 Press **CANCEL** to turn off the currently running equipment and transition the screen to the installer menu selections.

After 20 minutes of inactivity (no button presses by the installer), **INSTALLER TEST** terminates, and the home screen displays.

### NOTES

- **EHEAT** is only a choice when a heat pump is selected in the configuration.
- **HEAT** is not available in a cooling-only configuration.
- **COOL** is not available in a heating-only configuration.

## To restore factory default settings

This setting allows the installer to reset all system settings back to factory default values.

From the **RESTORE DEFAULTS** screen, press and hold the **DEFAULT** button to start a 5-second countdown.

### NOTES

- At the end of 5 seconds, the factory settings are restored.
- Release the **DEFAULT** button to cancel the countdown at any time before the 5 seconds elapse.
- After the factory settings are restored, the control returns to **BACNET ENABLE** to allow the installer to properly configure the thermostat.

| Screen                  | Factory defaults |
|-------------------------|------------------|
| HEATING EQUIP TYPE      | GAS              |
| HEATING EQUIP STAGES    | 1                |
| COMPRESSOR EQUIP TYPE   | A/C              |
| COMPRESSOR EQUIP STAGES | 1                |
| AUTO ALLOWED?           | YES              |
| AUTO CHANGEOVER         | 30 MIN           |
| PROG OR NON-PROG        | PROG             |
| MAX TEMP HOLD TIME      | 2                |
| FAHRENHEIT OR CELSIUS   | °F               |
| SMART RECOVERY          | 30               |
| FAN ON WITH W           | YES              |
| REVERSING VALVE         | COOL             |
| SPACE TEMP OFFSET       | OFF              |
| SPACE HUM OFFSET        | 0%               |
| HUM SOURCE              | STAT             |
| REMOTE HUM SCALING      | 2-10             |
| REMOTE SENSOR           | NONE             |
| COOL LOCKOUT            | OFF              |
| LOW COOL LOCKOUT TEMP   | OFF              |



Using installer settings

| Screen                     | Factory defaults         |
|----------------------------|--------------------------|
| LOW HEAT LOCKOUT TEMP      | OFF                      |
| TIME B/W FUEL TYPES        | 15 MIN                   |
| CYCLES PER HOUR            | 4                        |
| HUMIDIFIER                 | NO                       |
| DEHUMIDIFIER               | NO                       |
| MAX HEAT SETPOINT -        | 88°F                     |
| MIN COOL SETPOINT          | 52°F                     |
| AUX HEAT LOCKOUT           | OFF                      |
| HP LOCKOUT                 | OFF                      |
| STAGE DELAY                | 10 MIN                   |
| FORCED STAGE UP            | 30 MIN                   |
| DIFFERENTIAL               | 1.0°F                    |
| AIR FILTER REMINDER        | 3000 HRS                 |
| OCCUPANCY OUTPUT           | OFF                      |
| OCCUPANCY INPUT            | OCCUPIED                 |
| BACNET ENABLE              | NO                       |
| MSTP BAUD RATE             | 76.8k                    |
| MSTP MAC                   | 1                        |
| BACNET UTC OFFSET          | 5h, 0min (EST)           |
| MSTP MAX MASTER            | 127                      |
| DEVICE ID                  | 160000 + last 4 of S/N   |
| DEVICE NAME                | DEVICE16 + last 4 of S/N |
| DEVICE LOCATION -          | LOCATION                 |
| DEVICE DESCRIPTION         | DESCRIPTION              |
| BACNET BMS OCCUPANCY       | NO                       |
| BACNET CONFIG WRITE ENABLE | NO                       |

| Screen                 | Factory defaults |
|------------------------|------------------|
| NETWORK GP OUT TIMEOUT | 2 MIN            |
| NETWORK GP Y3 MODE     | OFF              |
| NETWORK GP W2 MODE     | OFF              |
| NETWORK GP OB MODE     | OFF              |

## Setting up Wi-Fi

To display the **SETUP WI-FI** screen, press:

-  if the thermostat is connected to a Wi-Fi network
-  if the thermostat is not connected to a Wi-Fi network

Except for the **SETUP WI-FI** screen, which can be changed from **NO** to **YES**, the information in the Wi-Fi settings screens is read-only and cannot be changed.

The Wi-Fi screens have a fixed timeout of 60 seconds.

### Connect to a network

If the thermostat is not connected to a Wi-Fi network and **NO** is displayed on the **SETUP WIFI** screen, follow these steps to connect the thermostat to a network:

- 1 Press the **SELECT** button.
- 2 Change **NO** to **YES**.
- 3 Press **SAVE**.

**NOTE** This puts the thermostat into the setup mode and ready to receive Wi-Fi join commands.

The thermostat is already in the setup mode if **SETUP WI-FI** was changed from **NO** to **YES** in the past 2 minutes or if the installer disconnected from a Wi-Fi network in the past 2 minutes.

The following screen indicates that the thermostat is ready to join a Wi-Fi network. If the thermostat is connected to a Wi-Fi network, the **SETUP WI-FI** screen is not displayed.



**NOTE** The **SELECT** button is not displayed because the thermostat is already in the setup mode.

### SSID

When the thermostat is not connected to a Wi-Fi network, the SSID is a factory-configured value that starts with **CMML** followed by 12 numbers. The SSID scrolls across the top of the display for 5 seconds and then displays only the 12 digits for the remainder of the screen timeout time. The user needs these 12 digits to connect to the Carrier Connect Mobile App.

**SSID** - Scrolls for the first 5 seconds

**CMML** - Scrolls after 5 seconds

When the thermostat is connected to a Wi-Fi network, the network SSID is displayed.

## MAC address

The MAC address is a unique 12-digit identifier associated with the Wi-Fi radio chip that contains the letters A through F and the numbers 0 through 9.

## DSN

The DSN is the name used to identify the thermostat in the Carrier Connect Mobile App. The name starts with the letters **AC** followed by 13 letters and numbers. The DSN scrolls across the top of the display.

## Registration

When the thermostat has been successfully registered to a user account with the Carrier Connect mobile app, the registered status displays **YES**.

When the thermostat is not registered to a Carrier Connect user account, the status is **NO**.

## Timers, memory, and deadband

### MINIMUM OFF timer

Once a heating or cooling demand is satisfied on the thermostat, the **MINIMUM OFF** timer is set to a 300-second value (5 minutes) and then begins to count down each second. Heating and cooling outputs are de-energized the entire time that this timer has a value greater than 0.

### MINIMUM ON timer

Once a heating or cooling output becomes active, the 5-minute **MINIMUM ON** timer begins to count down. The output will not de-energize until the timer reaches zero and the demand is satisfied. If the user changes the setpoint to satisfy the demand, the 5 minute minimum on time is ignored and the heating or cooling equipment turns off.

### Non-volatile memory

The thermostat can store settings in non-volatile memory to ensure that settings remain the same after a power outage (either intentional or unintentional). Items stored in non-volatile memory include:

- Installer settings
- Menu settings
- Program schedule
- Date and time
- Software information
- Dealer information
- Fault and system event information

### Deadband

The thermostat controls the number of degrees (°F or °C) between the heating and cooling setpoints. If the user changes a setpoint that violates the deadband requirement, the opposite mode setpoint is “pushed” to enforce the deadband. The deadband setting is fixed at 2°F.

## Faults and system events


The faults and system events are displayed in the home and dormant screen banners. Faults and system events include:

- Startup
- Software Update Events
- Power Cycle Events
- Parameter Out-of-Range Events
- Server Connectivity Events
- Non-Volatile Memory Faults
- Temperature Faults

The Faults and System events display in the banner while fault condition exists. You can see a history of the faults and system events in Carrier Connect mobile app under **Alerts**. The history is comprised of the 5 most recent logged items, with the most recent event being listed at the top.

| Faults              |                                                                                                                                                                                                                                                                                           |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ID TEMP SENSOR HIGH | <p>Fault becomes active when main thermistor (P102 or RT1) reads &gt; 100° F. Fault is cleared when temperature ≤ 99° F.</p> <p>When this fault occurs, the thermostat uses the temperature reading from the temperature/humidity sensor as the space temperature.</p>                    |
| ID TEMP SENSOR LOW  | <p>Fault becomes active when main thermistor (P102 or RT1) reads &lt; 39° F. Fault is cleared when temperature ≥ 40° F.</p> <p>When this fault occurs, the thermostat uses the temperature reading from the temperature/humidity sensor as the space temperature.</p>                     |
| REMOTE SENSOR HIGH  | Remote temperature > 122° F; only flagged if remote sensor set to use as indoor temperature (REMOTE SENSOR setting set to INDOOR or AVERAGE)                                                                                                                                              |
| REMOTE SENSOR LOW   | Remote temperature = 0° F; only flagged if remote sensor set to use as indoor temperature (REMOTE SENSOR setting set to INDOOR or AVERAGE)                                                                                                                                                |
| ID TEMP RANGE HIGH  | If the mode is cooling (Cool or Auto operating in Cool), the space temperature is greater than the cool setpoint plus the Maximum Setpoint Error and this condition exists for the number of minutes specified by the INDOOR TEMP FAULT INHIBIT time.                                     |
| ID TEMP RANGE LOW   | If the mode is heating ( <b>HEAT</b> , <b>EHEAT</b> or <b>AUTO</b> operating in <b>HEAT</b> ), the space temperature is less than the heat setpoint minus the Maximum Setpoint Error and this condition exists for the number of minutes specified by the INDOOR TEMP FAULT INHIBIT time. |
| HUM SENSOR FAILURE  | <p>Humidity sensor timed out</p> <ul style="list-style-type: none"> <li>• humidity reading is &gt; 99%</li> <li>• humidity reading is 0%.</li> </ul>                                                                                                                                      |
| HUMIDITY RANGE HIGH | Humidity reading is > 90%                                                                                                                                                                                                                                                                 |

## Faults and system events

| <b>Faults</b>        |                                                                                                                             |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------|
| HUMIDITY RANGE LOW   | Humidity reading is < 10%                                                                                                   |
| OUTDOOR TEMP FAILURE | OD temp > 127 °F or < -60 °F                                                                                                |
| NO WI-FI SERVER      | Not connected to Ayla server                                                                                                |
| NO WI-FI ROUTER      | Router signal strength is  (not connected) |
| WI-FI HARDWARE FAULT | Communications error occurred with Wi-Fi module (resets after valid message received)                                       |
| LOCKOUT 5 WRONG PINS | An incorrect PIN was entered consecutive times.                                                                             |
| ECONOMIZER FAULT     | Remote sensor is set to ECFL and there is a short between terminals T and C.                                                |
| HIGH CO2             | CO2 is above the programmed threshold (default 1100 PPM).                                                                   |
| <b>System Events</b> |                                                                                                                             |
| FILTER REMINDER      | Filter change reminder is active (run hours have expired or remote input shorted).                                          |

## Appendix A: BACnet Points List

| Point Name                    | Point Access   | Units                     | BACnet Point Name | BACnet Object ID |
|-------------------------------|----------------|---------------------------|-------------------|------------------|
| Indoor Space Temperature      | WRITE_WHEN_OOS | DEGREES_FAHRENHEIT        | ID_SPACE_TEMP     | AI:100           |
| Indoor Space Humidity         | WRITE_WHEN_OOS | PERCENT_RELATIVE_HUMIDITY | ID_SPACE_HUM      | AI:101           |
| Indoor Space CO2              | WRITE_WHEN_OOS | PARTS_PER_MILLION         | ID_SPACE_CO2      | AI: 102          |
| Remote Space Temperature      | READ_ONLY      | DEGREES_FAHRENHEIT        | REM_SPACE_TEMP    | AV:100           |
| Outdoor Temperature           | READ_ONLY      | DEGREES_FAHRENHEIT        | OD_TEMP           | AV:101           |
| Supply Air Temperature        | READ_ONLY      | DEGREES_FAHRENHEIT        | SAT               | AV:102           |
| Network Space Temperature     | READ_WRITE     | DEGREES_FAHRENHEIT        | NET_SP_TEMP       | AV:103           |
| Space Temperature for Control | READ_ONLY      | DEGREES_FAHRENHEIT        | SP_TEMP_CTRL      | AV:104           |
| Network Space Humidity        | READ_WRITE     | PERCENT_RELATIVE_HUMIDITY | NET_SP_HUM        | AV:105           |
| Space Humidity for Control    | READ_ONLY      | PERCENT_RELATIVE_HUMIDITY | SP_HUM_CTRL       | AV:106           |
| Air Filter Hours Left         | READ_ONLY      | HOURS                     | AIR_FLTR_HRS_LFT  | AV:300           |
| Override Time Remaining       | READ_ONLY      | HOURS                     | OVRD_TIME         | AV:301           |
| Occupied Heat Setpoint        | READ_WRITE     | DEGREES_FAHRENHEIT        | OCC_HT_SP         | AV:400           |
| Occupied Cool Setpoint        | READ_WRITE     | DEGREES_FAHRENHEIT        | OCC_CL_SP         | AV:401           |
| Unoccupied Heat Setpoint      | READ_WRITE     | DEGREES_FAHRENHEIT        | UNOCC_HT_SP       | AV:402           |
| Unoccupied Cool Setpoint      | READ_WRITE     | DEGREES_FAHRENHEIT        | UNOCC_CL_SP       | AV:403           |
| Dehumidification Setpoint     | READ_WRITE     | PERCENT_RELATIVE_HUMIDITY | DEHUM_SP          | AV:406           |
| Humidification Setpoint       | READ_WRITE     | PERCENT_RELATIVE_HUMIDITY | HUM_SP            | AV:407           |
| Screen Timeout                | READ_WRITE     | SECONDS                   | SCRN_TMT          | AV:408           |
| Heat Setpoint                 | READ_WRITE     | DEGREES_FAHRENHEIT        | HEAT_SP           | AV:409           |
| Cool Setpoint                 | READ_WRITE     | DEGREES_FAHRENHEIT        | COOL_SP           | AV:410           |
| Active Backlight              | READ_WRITE     | PERCENT                   | ACTV_BCKLT        | AV:411           |
| Dormant Backlight             | READ_WRITE     | PERCENT                   | DRMNT_BCKLT       | AV:412           |
| Indoor Equip Stages           | GATED_WRITE    |                           | ID_STAGES         | AV:500           |
| Outdoor Equip Stages          | GATED_WRITE    |                           | OD_STAGES         | AV:501           |
| Max Temperature Hold Time     | GATED_WRITE    | HOURS                     | MAX_HOLD_TIME     | AV:502           |
| Auto Changeover Delay         | GATED_WRITE    | MINUTES                   | AUTO_XOVR         | AV:503           |
| Cool Lockout Temperature      | GATED_WRITE    | DEGREES_FAHRENHEIT        | COOL_LOCKOUT      | AV:504           |
| Low Cool Lockout (HP only)    | GATED_WRITE    | DEGREES_FAHRENHEIT        | LO_CL_LCKOUT      | AV:505           |
| Low Heat Lockout (HP only)    | GATED_WRITE    | DEGREES_FAHRENHEIT        | LO_HT_LCKOUT      | AV:506           |
| Delay Between Fuel (HP only)  | GATED_WRITE    | MINUTES                   | DLY_BW_FUEL       | AV:507           |
| Cycles Per Hour               | GATED_WRITE    | CYCLES_PER_HOUR           | CYCLES_HR         | AV:508           |
| Max Heat Setpoint             | GATED_WRITE    | DEGREES_FAHRENHEIT        | MAX_HT_SP         | AV:509           |
| Min Cool Setpoint             | GATED_WRITE    | DEGREES_FAHRENHEIT        | MIN_CL_SP         | AV:510           |

Appendix A: BACnet Points List

| Point Name                     | Point Access | Units                     | BACnet Point Name | BACnet Object ID |
|--------------------------------|--------------|---------------------------|-------------------|------------------|
| Aux Heat Lockout (HP only)     | GATED_WRITE  | DEGREES_FAHRENHEIT        | AUX_HT_LCKOUT     | AV:511           |
| Heat Pump Lockout              | GATED_WRITE  | DEGREES_FAHRENHEIT        | HP_LCKOUT         | AV:512           |
| Stage Delay                    | GATED_WRITE  | MINUTES                   | STG_DELAY         | AV:513           |
| Forced Stage Up Delay          | GATED_WRITE  | MINUTES                   | FRCD_STG_UP       | AV:514           |
| Stage Change Temp Differential | GATED_WRITE  | DELTA_DEGREES_FAHRENHEIT  | DIFFERENTIAL      | AV:515           |
| Indoor Temperature Offset      | GATED_WRITE  | DELTA_DEGREES_FAHRENHEIT  | ID_TEMP_OFF       | AV:517           |
| Indoor Humidity Offset         | GATED_WRITE  | PERCENT_RELATIVE_HUMIDITY | ID_HUM_OFF        | AV:518           |
| SAT Temp Offset                | GATED_WRITE  | DELTA_DEGREES_FAHRENHEIT  | SAT_OFFSET        | AV:519           |
| Air Filter Hours               | READ_ONLY    | HOURS                     | AIR_FLT_HRS       | AV:520           |
| Max Setpoint Error             | GATED_WRITE  | DELTA_DEGREES_FAHRENHEIT  | MAX_SP_ERR        | AV:521           |
| Indoor Temp Fault Inhibit      | GATED_WRITE  | MINUTES                   | ID_TMP_FLT_INHBT  | AV:522           |
| CO2 Fault Threshold            | GATED_WRITE  | BACNET_UNITS_PPM          | CO2_FLT_THRESHOLD | AV:523           |
| 1st Stage Cooling Out Status   | READ_ONLY    | 0=OFF<br>1=ON             | Y1_OUT            | BV:200           |
| 2nd Stage Cooling Out Status   | READ_ONLY    | 0=OFF<br>1=ON             | Y2_OUT            | BV:201           |
| 3rd Stage Cooling Out Status   | READ_ONLY    | 0=OFF<br>1=ON             | Y3_OUT            | BV:202           |
| 1st Stage Heating Out Status   | READ_ONLY    | 0=OFF<br>1=ON             | W1_OUT            | BV:203           |
| 2nd Stage Heating Out Status   | READ_ONLY    | 0=OFF<br>1=ON             | W2_OUT            | BV:204           |
| Fan Out Status                 | READ_ONLY    | 0=OFF<br>1=ON             | G_OUT             | BV:205           |
| Reversing Valve Out Status     | READ_ONLY    | 0=OFF<br>1=ON             | OB_OUT            | BV:206           |
| Occupancy Out Status           | READ_ONLY    | 0=OFF<br>1=ON             | OCC_OUT           | BV:208           |
| Humidifier Out Status          | READ_ONLY    | 0=OFF<br>1=ON             | HUM_OUT           | BV:209           |
| Dehumidifier Out Status        | READ_ONLY    | 0=OFF<br>1=ON             | DEHUM_OUT         | BV:210           |
| Network General Purpose Out Y3 | READ_WRITE   | 0=OFF<br>1=ON             | NET_GP_Y3_OUT     | BV:211           |
| Network General Purpose Out W2 | READ_WRITE   | 0=OFF<br>1=ON             | NET_GP_W2_OUT     | BV:212           |
| Network General Purpose Out OB | READ_WRITE   | 0=OFF<br>1=ON             | NET_GP_OB_OUT     | BV:213           |
| Wi-Fi Time Synchronization     | READ_WRITE   | 0=DISABLED<br>1=ENABLED   | WIFI_TIME_SYNC    | BV:400           |
| Auto DST Time Shift            | READ_WRITE   | 0=DISABLED<br>1=ENABLED   | AUTO_DST          | BV:402           |

| Point Name                    | Point Access | Units                                        | BACnet Point Name | BACnet Object ID |
|-------------------------------|--------------|----------------------------------------------|-------------------|------------------|
| Wi-Fi Enable                  | READ_WRITE   | 0=DISABLED<br>1=ENABLED                      | WIFI_ENABLE       | BV:403           |
| Setpoint Override             | READ_WRITE   | 0=DISABLED<br>1=ENABLED                      | SETPT_OVERRIDE    | BV:404           |
| BACnet BMS Occupancy          | GATED_WRITE  | 0=UNOCCUPIED<br>1=OCCUPIED                   | BMS_OCC           | BV:405           |
| Filter Timer Reset            | READ_WRITE   | 0=INACTIVE<br>1=ACTIVE                       | FLTR_TMR_RST      | BV:406           |
| Network Space Temp Enable     | READ_WRITE   | 0=DISABLED<br>1=ENABLED                      | NET_SP_TEMP_EN    | BV:407           |
| Network Space Humidity Enable | READ_WRITE   | 0=DISABLED<br>1=ENABLED                      | NET_SP_HUM_EN     | BV:408           |
| Occupancy Input Polarity      | GATED_WRITE  | 0=OCCUPIED<br>1=UNOCCUPIED                   | OCC_IN_POL        | BV:500           |
| Auto Mode Allowed             | GATED_WRITE  | 0=NO<br>1=YES                                | ALLOW_AUTO        | BV:501           |
| Prog Mode Allowed             | GATED_WRITE  | 0=NO<br>1=YES                                | ALLOW_PROG        | BV:502           |
| Celsius Display               | GATED_WRITE  | 0=F°<br>1=C°                                 | CELSIUS_DISP      | BV:503           |
| Fan On with W                 | GATED_WRITE  | 0=NO<br>1=YES                                | FAN_WITH_W        | BV:504           |
| Rvs Vlv Energized Ht          | GATED_WRITE  | 0=ENERGIZED FOR COOL<br>1=ENERGIZED FOR HEAT | RVS_VLV_DIR       | BV:505           |
| Humidifier Installed          | GATED_WRITE  | 0=NO<br>1=YES                                | HUM_INST          | BV:506           |
| BMS Occupancy Enable          | GATED_WRITE  | 0=DISABLED<br>1=ENABLED                      | BMS_OCC_EN        | BV:507           |
| BACnet Config Write Enable    | GATED_WRITE  | 0=DISABLED<br>1=ENABLED                      | CFG_WR_EN         | BV:511           |
| CO2 Sensor Connected          | GATED_WRITE  | 0=DISABLED<br>1=ENABLED                      | CO2_CONNECTED     | BV:512           |
| ID TEMP SENSOR HIGH           | READ_ONLY    | 0=DISABLED<br>1=ENABLED                      | ID_TEMP_SENS_HI   | BV:900           |
| ID TEMP SENSOR LOW            | READ_ONLY    | 0=INACTIVE<br>1=ACTIVE                       | ID_TEMP_SENS_LO   | BV:901           |
| REMOTE SENSOR HIGH            | READ_ONLY    | 0=INACTIVE<br>1=ACTIVE                       | REM_TEMP_HI       | BV:902           |
| REMOTE SENSOR LOW             | READ_ONLY    | 0=INACTIVE<br>1=ACTIVE                       | REM_TEMP_LO       | BV:903           |
| HUM TEMP SENSOR HIGH          | READ_ONLY    | 0=INACTIVE<br>1=ACTIVE                       | HUM_TEMP_HI       | BV:904           |
| HUM TEMP SENSOR LOW           | READ_ONLY    | 0=INACTIVE<br>1=ACTIVE                       | HUM_TEMP_LO       | BV:905           |
| ID TEMP RANGE HIGH            | READ_ONLY    | 0=INACTIVE<br>1=ACTIVE                       | ID_TEMP_RNG_HI    | BV:906           |

Appendix A: BACnet Points List

| Point Name                      | Point Access | Units                                           | BACnet Point Name | BACnet Object ID |
|---------------------------------|--------------|-------------------------------------------------|-------------------|------------------|
| ID TEMP RANGE LOW               | READ_ONLY    | 0=INACTIVE<br>1=ACTIVE                          | ID_TEMP_RNG_LO    | BV:907           |
| HUM SENSOR FAILURE              | READ_ONLY    | 0=INACTIVE<br>1=ACTIVE                          | HUM_SENS_FAIL     | BV:908           |
| HUMIDITY RANGE HIGH             | READ_ONLY    | 0=INACTIVE<br>1=ACTIVE                          | HUM_TOO_HI        | BV:909           |
| HUMIDITY RANGE LOW              | READ_ONLY    | 0=INACTIVE<br>1=ACTIVE                          | HUM_TOO_LO        | BV:910           |
| OUTDOOR SENSOR FAILURE          | READ_ONLY    | 0=INACTIVE<br>1=ACTIVE                          | OD_TEMP_FAIL      | BV:911           |
| NOT CONNECTED TO SERVER         | READ_ONLY    | 0=INACTIVE<br>1=ACTIVE                          | SRVR_CONN_FAIL    | BV:912           |
| NOT CONNECTED TO ROUTER         | READ_ONLY    | 0=INACTIVE<br>1=ACTIVE                          | RTR_CONN_FAIL     | BV:913           |
| WIFI HARDWARE FAULT             | READ_ONLY    | 0=INACTIVE<br>1=ACTIVE                          | WIFI_CONF_FAIL    | BV:914           |
| ECONOMIZER FAULT                | READ_ONLY    | 0=INACTIVE<br>1=ACTIVE                          | ECON_FAULT        | BV:915           |
| LOCKOUT-5 BAD PIN ENTRIES       | READ_ONLY    | 0=INACTIVE<br>1=ACTIVE                          | LOCKOUT_FAIL      | BV:916           |
| HIGH CO2                        | READ_ONLY    | 0=INACTIVE<br>1=ACTIVE                          | HIGH_CO2          | BV:917           |
| Current Mode Status             | READ_ONLY    | 1=OFF<br>2=HEAT<br>3=COOL                       | CURRENT_MODE      | MSV:300          |
| User Mode                       | READ_WRITE   | 1=OFF<br>2=HEAT<br>3=COOL<br>4=AUTO<br>5=E-HEAT | USER_MODE         | MSV:400          |
| IR Proximity Sensitivity        | READ_WRITE   | 1=HIGH<br>2=MEDIUM<br>3=LOW                     | PROX_SENS         | MSV:401          |
| Sound Effect                    | READ_WRITE   | 1=OFF<br>2=CLICK<br>3=BEEP                      | SOUND             | MSV:402          |
| Number of Parts in Schedule Day | READ_WRITE   | 1=2 PARTS<br>2=4 PARTS                          | SCHED_DAY_PARTS   | MSV:403          |
| Occupied Fan Mode               | READ_WRITE   | 1=AUTO<br>2=ON                                  | OCC_FAN           | MSV:404          |
| Unoccupied Fan Mode             | READ_WRITE   | 1=AUTO<br>2=ON                                  | UNOCC_FAN         | MSV:405          |

| Point Name                       | Point Access | Units                                                                                | BACnet Point Name | BACnet Object ID |
|----------------------------------|--------------|--------------------------------------------------------------------------------------|-------------------|------------------|
| Current Fan Mode                 | READ_WRITE   | 1=AUTO<br>2=ON<br>3=OVERRIDE AUTO<br>4=OVERRIDE ON                                   | FAN MODE          | MSV:406          |
| Indoor Equipment Type            | READ_ONLY    | 1=NO INDOOR<br>2=FURNACE<br>3=AIR HANDLER                                            | ID_EQUIP_TYPE     | MSV:500          |
| Outdoor Equipment Type           | GATED_WRITE  | 1=NO OUTDOOR<br>2=A/C<br>3=HEAT PUMP                                                 | OD_EQUIP_TYPE     | MSV:501          |
| Remote Sensor Type               | GATED_WRITE  | 1=NONE<br>2=OUTDOOR<br>3=SPACE<br>4=AVERAGE<br>5=OCCUPANCY<br>6=FAULT_INPUT<br>7=SAT | REMOTE_SENSOR     | MSV:502          |
| Dehumidification Type            | GATED_WRITE  | 1=NO<br>2=YES<br>3=OVRCL(2F)<br>4=HUMIDIMIZER                                        | DEHUM_TYPE        | MSV:503          |
| Occupancy Output Terminal        | GATED_WRITE  | 1=OFF<br>2=Y3<br>3=O/B<br>4=W2                                                       | OCC_OUTPUT        | MSV:504          |
| Humidification Output Terminal   | GATED_WRITE  | 1=OFF<br>2=Y3<br>3=O/B<br>4=W2                                                       | HUM_OUTPUT        | MSV:505          |
| Dehumidification Output Terminal | GATED_WRITE  | 1=OFF<br>2=Y3<br>3=O/B<br>4=W2                                                       | DEHUM_OUTPUT      | MSV:506          |
| Smart Recovery                   | GATED_WRITE  | 1=NO<br>2=30 MIN<br>3=60 MIN<br>4=90 MIN                                             | SMART_RECVRY      | MSV:507          |
| Network GP W2 Mode               | GATED_WRITE  | 1=DISABLED<br>2=ENERGIZED_ACTIVE<br>3=ENERGIZED_INACTIVE                             | NET_GP_W2_MODE    | MSV:510          |
| Network GP OB Mode               | GATED_WRITE  | 1=DISABLED<br>2=ENERGIZED_ACTIVE<br>3=ENERGIZED_INACTIVE                             | NET_GP_OB_MODE    | MSV:511          |
| Analog Input                     | GATED_WRITE  | NONE<br>1=HUMIDITY<br>2=CO2                                                          | ANALOG_INPUT      | MSV:512          |

Appendix A: BACnet Points List

| Point Name           | Point Access | Units                             | BACnet Point Name | BACnet Object ID |
|----------------------|--------------|-----------------------------------|-------------------|------------------|
| Analog Input Scaling | GATED_WRITE  | 1=2-10V<br>(4-20mA w/ext 500 Ohm) | ANALOG_IN_SCALE   | MSV:513          |

## Appendix B: BACnet Functionality

### **BACnet Communication**

BACnet MS/TP

Baud Rates: 9600, 19200, 38400, 76800, 115200

### **BACnet Objects**

Device Object

Analog Input Objects

Analog Value Objects

Binary Value Objects

Multistate Value Objects

### **BACnet Interoperability Building Blocks (BIBBs)**

#### **Data Sharing BIBBs**

Execute Read Property (DS-RP-B)

Execute Read Property Multiple (DS-RPM-B)

Execute Write Property (DS-WP-B)

Execute Write Property Multiple (DS-WPM-B)

#### **Device Management BIBBs**

Execute Who-Is and Initiate I-Am (DM-DDB-B)

Execute Who-Has and Initiate I-Have (DM-DOB-B)

Execute TimeSynchronization (DM-TS-B)

Execute UTCTimeSynchronization (DM-UTC-B)

Execute ReinitializeDevice (DM-RD-B)

Execute DeviceCommunicationControl (DM-DCC-B)

## Appendix C: BACnet Constraints

### UTC Time Synchronization

If the device is to support UTCTimeSynchronization, time syncs with Local Time is disabled to avoid ambiguity, Daylight Saving calculations are enabled and the UTC\_Offset is set according to the local time zone.

The following settings are in the Advanced menu:

**SYNCH TIME TO SERVER**—NO

**DST**—ENABLED

The following setting is in the installer settings menu:

**BACNET UTC OFFSET**—Xh Xm (5h 0m – U.S. Eastern Time Zone)

### BACnet Reliability Property

In addition to indicating sensor issues, the BACnet Reliability property of the BACnet Objects conveys when the configuration does not support a given point.

| Reliability Value | Meaning                                                             |
|-------------------|---------------------------------------------------------------------|
| No-fault-detected | Configuration matches the object description and value is in range. |
| Shorted-loop      | The Present_Value of this object indicates a shorted sensor.        |
| Open-loop         | The Present_Value of this object indicates an open sensor.          |
| Under-range       | The Present_Value of this object is below normal.                   |
| Over-range        | The Present_Value of this object is above normal.                   |
| No-output         | The output is not used in the current configuration.                |
| Unreliable-other  | This object is not relevant with the current configuration.         |
| No-sensor         | The sensor is not used in the current configuration.                |

**Appendix D: BACnet Object Instance Ranges**

| Instance Range | Object Type             |
|----------------|-------------------------|
| 1XX            | Device Inputs           |
| 2XX            | Device Outputs          |
| 3XX            | Status                  |
| 4XX            | User Configuration      |
| 5XX            | Installer Configuration |
| 9XX            | Faults                  |

## Appendix E: BACnet Object Notes


### Gated Installer Configuration

After the installer enables BACnet in the installer menu, they will have the opportunity to also select BACNET CONFIG WRITE. Enabling BACNET CONFIG WRITE allows the installer to write to all the installer configuration BACnet Objects (AV5XX, BV5XX and MSVXX) remotely over the BACnet network. When the installer has completed configuring the device, they may write Inactive to CFG\_WR\_EN (BV511) to disable writes to installer configuration objects.

**NOTE** Re-enabling BACNET CONFIG WRITE must be done from the installer menu at the thermostat.

### Multiplexed Inputs

Each analog input has a corresponding multiplexer that is used to select between the measured input value (AI1 in the figure below) and a network object value (AV1 in the figure below). The output of the multiplexer (AV2 in the figure below) is used in the equipment control algorithms. When the gate object (BV1 in the figure below) is active the network object's value is passed on to the output of the multiplexer, when the gate object is inactive the measured input value is passed on to the output of the multiplexer. The gate object value is a configuration object and is backed up to non-volatile memory. If the network object's value has not been written to within 5 minutes, the output of the multiplexer defaults to the measured input value.



| Input          | Meas. Input Object    | Network Object      | Object Used for Equip. Control |
|----------------|-----------------------|---------------------|--------------------------------|
| Space Temp     | ID_SPACE_TEMP (AI100) | NET_SP_TEMP (AV103) | SP_TEMP_CTRL (AV104)           |
| Space Humidity | ID_SPACE_HUM (AI101)  | NET_SP_HUM (AV105)  | SP_HUM_CTRL (AV106)            |

### Network Controlled Outputs

The thermostat has 3 outputs (**Y3**, **W2**, and **OB**) that can be assigned to optional equipment when the default assignment is not required for the equipment configuration. When any of these 3 outputs are left unassigned, they can be configured to be network controlled outputs by changing their mode from **DISABLED/OFF** to **ENERGIZED\_ACTIVE** or **ENERGIZED\_INACTIVE** in the installer menu or through the network configuration objects. There are 3 BV objects that control whether an output is active or inactive. These objects must be repeatedly written to over the network within the time configured in the GP\_OUT\_TIMEOUT (MSV508) configuration object or the output goes to the configured inactive state. The following truth table describes the action of the physical outputs as they relate to the controlling object, Mode Object, and the timeout status.

| Controlling Object Value | Mode Object Value | Timed out? | Physical Output State |
|--------------------------|-------------------|------------|-----------------------|
| *                        | DISABLED          | *          | De-energized          |
| *                        | ENERGIZED_ACTIVE  | Yes        | De-energized          |

| Controlling Object Value | Mode Object Value  | Timed out? | Physical Output State |
|--------------------------|--------------------|------------|-----------------------|
| *                        | ENERGIZED_INACTIVE | Yes        | Energized             |
| Inactive                 | ENERGIZED_ACTIVE   | No         | De-energized          |
| Inactive                 | ENERGIZED_INACTIVE | No         | Energized             |
| Active                   | ENERGIZED_ACTIVE   | No         | Energized             |
| Active                   | ENERGIZED_INACTIVE | No         | De-energized          |

The following table shows the three outputs and the objects that configure and control them.

| Controlling Object    | Mode Object             | Physical Output |
|-----------------------|-------------------------|-----------------|
| NET_GP_Y3_OUT (BV211) | NET_GP_Y3_MODE (MSV509) | Y3              |
| NET_GP_W2_OUT (BV212) | NET_GP_W2_MODE (MSV510) | W2              |
| NET_GP_OB_OUT (BV213) | NET_GP_OB_MODE (MSV511) | OB              |

## Document revision history

Important changes to this document are listed below. Minor changes such as typographical or formatting errors are not listed.

| Date    | Topic            | Change description        | Code* |
|---------|------------------|---------------------------|-------|
| 4/16/24 | To set up BACnet | Added section above table | SE    |

\* For internal use only



# Installation Instructions



**Fig. 1 — 24V Interface**

**NOTES:** Images are for illustration purposes only. Actual models may differ slightly.


Read and become familiar with these instructions before beginning the installation.

## TABLE OF CONTENTS

|                                                                                                                                             | PAGE |
|---------------------------------------------------------------------------------------------------------------------------------------------|------|
| SAFETY CONSIDERATIONS.....                                                                                                                  | 1    |
| INTRODUCTION .....                                                                                                                          | 2    |
| ACCESSORIES .....                                                                                                                           | 2    |
| DIMENSIONS .....                                                                                                                            | 3    |
| CLEARANCES .....                                                                                                                            | 3    |
| INSTALLATION .....                                                                                                                          | 4    |
| SYSTEM CONFIGURATION SCENARIOS.....                                                                                                         | 4    |
| SCENARIO 1: SINGLE ZONE OUTDOOR UNITS (38MPRA, 38MARB, 38MHR) WITH APPROVED DUCTLESS INDOOR UNITS.....                                      | 5    |
| SCENARIO 2: SINGLE ZONE OUTDOOR UNITS (38MBRC) WITH APPROVED DUCTLESS INDOOR UNITS.....                                                     | 6    |
| SCENARIO 3: MULTI-ZONE OUTDOOR UNITS (38MGR*) WITH APPROVED DUCTLESS INDOOR UNITS.....                                                      | 7    |
| SCENARIO 4: SINGLE ZONE OUTDOOR UNIT 38MARB and 38MBRC (4 & 5 TON ONLY) WITH APPROVED MULTI-FAMILY 24V FAN COILS FMA/FX4D/FB4C/FMC/FMU..... | 8    |
| SCENARIO 5: SINGLE ZONE OUTDOOR UNIT 38MARB and 38MBRC (4 AND 5 TON ONLY) WITH APPROVED 24V FAN COILS FV4.....                              | 9    |
| TXV REPLACEMENT PROCESS FOR PIPING ADAPTER FOR CAP**/ CNPV* SERIES EVAPORATOR COILS .....                                                   | 10   |
| SCENARIO 6: SINGLE ZONE OUTDOOR UNIT 38MARB and 38MBRC (4 and 5 TON ONLY) WITH APPROVED FURNACES.....                                       | 11   |
| WIRING.....                                                                                                                                 | 12   |
| DIP SWITCHES CONFIGURATION .....                                                                                                            | 13   |
| ERROR CODES .....                                                                                                                           | 14   |
| WIRING DIAGRAM .....                                                                                                                        | 15   |
| APPENDIX 1 - PIPING ADAPTER BUSHINGS/REDUCERS.....                                                                                          | 16   |
| APPENDIX 2 - FV4C TRANSFORMER .....                                                                                                         | 16   |
| APPENDIX 3 - ADDITIONAL REFRIGERANT CHARGE FOR CONVENTIONAL FAN COILS .....                                                                 | 17   |
| APPENDIX 4 - FV4C AIRFLOW DELIVERY .....                                                                                                    | 17   |
| APPENDIX 5 - FURNACE RELAY FOR FURNACE OPERATION .....                                                                                      | 18   |

## SAFETY CONSIDERATIONS

Read these instructions thoroughly and follow all warnings or cautions included in the literature and attached to the unit. Consult the local building codes and National Electrical Code (NEC) for special requirements. Recognize safety information.

This is the safety-alert symbol . When you see this symbol on the unit and in instructions or manuals, be alert to the potential for personal injury. Understand these signal words: **DANGER**, **WARNING**, and **CAUTION**. These words are used with the safety-alert symbol.

**DANGER** identifies the most serious hazards which may result in severe personal injury or death. **WARNING** signifies hazards which could also result in personal injury or death. **CAUTION** is used to identify unsafe practices which may result in minor personal injury or product and property damage. **NOTE** is used to highlight suggestions which result in enhanced installation, reliability, or operation.



## WARNING

### ELECTRICAL SHOCK HAZARD

Failure to follow this warning could result in personal injury or death.

Before beginning any modification or installation of this kit, ensure the main electrical disconnect is in the **OFF** position. Ensure the power is not connected to the fan coil unit. On some systems, both the fan coil and the outdoor unit may be on the same disconnect. Tag the disconnect switch with a suitable warning label. There may be more than one disconnect.



## CAUTION

### EQUIPMENT DAMAGE HAZARD

Failure to follow this warning may result in equipment damage. **DO NOT** install the wired controller in an area subjected to excessive steam, oil or sulfide gas. Doing so may cause the controller to deform and/or fail.



## CAUTION

### INSTALLATION

Entrust a licensed contractor to install the unit. Installation by unskilled persons may lead to improper installation, electric shock, or fire. Reinstallation must be performed by authorized professionals. Non-compliance may lead to electric shock or fire.

## INTRODUCTION

The 24V Interface provides further flexibility, functionality and control which allows for a single zone or a multi-zone ductless system to be controlled by any 3rd party single-stage conventional thermostat\* keeping the Inverter compressor operating as a variable-speed system, making adjustments to maintain more consistent operation.

Additionally the 24V interface provides compatibility between a ductless single zone outdoor unit, an approved residential conventional fan coil and a 3rd party single-stage conventional thermostat\*.

### Features:

- Keeps the Inverter compressor operating as a variable-speed system
- One 24V Interface Kit per indoor head is required
- Rated for outdoor and indoor mounting
- 24V transformer built-in (for ductless applications)
- Dry mode contact for active dehumidification control (for ductless applications)
- Remote on/off contact
- Auxiliary heat control through the third party conventional thermostat\*\*
- Diagnostic code display LEDs

### NOTES:

- \*A conventional 5-wire thermostat is required.
- \*\*A secondary output is necessary for auxiliary heat control

**WARNING**

**EXPLOSION HAZARD**

Failure to follow this warning could result in death, serious personal injury, and/or property damage.

Never use air or gases containing oxygen for leak testing or operating refrigerant compressors. Pressurized mixtures of air or gases containing oxygen can lead to an explosion.

**WARNING**

**INSTALLATION**

Entrust a licensed contractor to install the unit. Installation by unskilled persons may lead to improper installation, electric shock, or fire.

Re-installation must be performed by authorized professionals.

Non-compliance may lead to electric shock or fire.

## ACCESSORIES

The system is shipped with the following accessories (see Table 1). Use all of the installation parts and accessories to install the system. Improper installation may result in, electrical shock and fire, or cause the equipment to fail. Keep the installation manual in a safe place and do not discard any accessories until the installation has been completed.

**Table 1 — Accessories**

| No. | Description                                                                                | Qty | Remarks                                                                   |
|-----|--------------------------------------------------------------------------------------------|-----|---------------------------------------------------------------------------|
| 1   | 24V Interface Control box                                                                  | 1   | N/A                                                                       |
| 2   | Installation Manual                                                                        | 1   | N/A                                                                       |
| 3   | Screws                                                                                     | 3   | M4X20 (for wall mounting)                                                 |
| 4   | Wall Anchors                                                                               | 3   | For wall mounting                                                         |
| 7   | Return Air Thermistor Assembly (Hybrid Solutions) (RCD part number 11201007003448)         | 1   | Required and installed near or on the unit and on the air inlet side      |
| 8   | 16ft. (5m) Return Air Thermistor Assembly Extension Wires (RCD part number 17401204010126) | 1   | For a Return Air Temperature Sensor T1 on Conventional Fan Coil Solutions |

**Table 2 — Accessories**

| No. | Description                                          | Qty | Type | Remarks |
|-----|------------------------------------------------------|-----|------|---------|
| 1   | Switch Box                                           | 1   | N/A  | N/A     |
| 2   | Wiring Tube (insulating sleeve and tightening screw) | 1   | N/A  | N/A     |

**WARNING**

Wires must be properly sized according to the NEC/NFPA 70, CEC and all prevailing codes, ordinances and standards.

All conductors must be installed with a strain relief eliminating stress on the wire following installation which may result in wire damage and/or overheating with a potential for fire.

Installation must be performed in accordance with the requirement of NEC and CEC by authorized personnel only.

All wiring to be rated for the control box amperage rating.

All wiring installed to meet general industry standards and practices.

Do not install near flammable liquids or gases.

Do not operate the unit with wet hands, as this could lead to electrical shock.

**CAUTION**

When connecting with RS 485 communication to the outdoor unit, shielded wire must be used and grounded at one end only.

When using shielded wire the cable should be grounded at one end to reduce EMI.

Return Air Temperature Sensor T1 cable shall not exceed 23ft (7m).

DIMENSIONS





Fig. 2 — 24V Interface Structure Size

CLEARANCES

Table 3 — 24V Interface Clearance Dimensions

| Clearances     |                       |
|----------------|-----------------------|
| Unit           | Minimum Value In (mm) |
| Sides          | 5.9 (150)             |
| Front          | 24 (610)*             |
| Top and Bottom | 3 (76.2)              |

NOTE: \*24 in (610mm) minimum for service access or use local code.



NOTE: ALL DIMENSIONS ARE IN INCH (MM)  
Fig. 3 — Clearances

## INSTALLATION

### Installation Location

The 24V INTERFACE KIT is rated for outdoor and indoor mounting (depending on the application). It is recommended that the kit installation be as close as possible to the indoor unit and the thermostat.

**IMPORTANT:** Follow the recommended clearances (see "CLEARANCES" on page 3) and install in an area above the ground away from locations where water could enter.




Fig. 4 — Installation Floor Mount View (right way)




Fig. 5 — Installation Floor Mount View (wrong way)



### CAUTION

**DO NOT** install the 24V INTERFACE KIT near flammable liquids or gases such as gasoline or hydrogen sulfide. Doing so creates a fire hazard.

1. Remove the cover of the 24V INTERFACE KIT. Remove the six screws of the 24V INTERFACE KIT with a screwdriver or similar tool. Rotate the lid along the hem to disassemble.




Fig. 6 — Remove the cover

**NOTE:** Minimum free space required around the kit is 7" (180 mm) for service purposes.

2. Mount the 24V INTERFACE KIT horizontally (see Fig. 7), by fastening the back plate to the wall with 3 screws (M4x20) and anchors.



### CAUTION

The 24V Interface kit cover has a directional arrow on the cover. In case of an outdoor installation be sure to verify, during the mounting process, that this arrow points **UP** upon installation. Failure to mount the kit correctly can cause water ingress into the box which may compromise the electrical component integrity.




Fig. 7 — 24V Interface Kit

**NOTE:** Place the unit on a flat surface. Be careful not to distort the back plate of the 24V INTERFACE KIT by over-tightening the screws.

3. **WIRING** - Based on the system used, wire the unit as described in "SYSTEM CONFIGURATION SCENARIOS" on page 4).
4. Cover the 24V INTERFACE KIT lid, and lock back in place using the six screws previously removed.




Fig. 8 — Cover the screw

## SYSTEM CONFIGURATION

### NOTES:

- The thermostat should be configured for use with as a single stage **COOLING** and **HEATING** (**DO NOT** configure the thermostat as a Heat Pump).
- The wireless remote controller, wired controller KSACN and Wi-Fi kits KSAIF cannot be used with this 24V interface Kit at the same time. The **SWING** and **LED** function may be accessed with the wireless remote controller.

Table 4 — Connection Wiring Specification

| Connection Wiring | Outdoor<br>L1, L2, S & G,<br>S1, S2        | Indoor<br>L1, L2, S & G,<br>S1, S2        | R,C             | Y/W/G/G1/<br>G2/G3/Dry |
|-------------------|--------------------------------------------|-------------------------------------------|-----------------|------------------------|
| Size              | Refer to the outdoor connecting wires size | Refer to the indoor connecting wires size | 18AWG (minimum) | 18AWG (minimum)        |

## SYSTEM CONFIGURATION SCENARIOS

Based on the system, utilize the appropriate configuration scenario:

**Scenario 1:** Single Zone Ductless System with 38MPRA, 38MARB, 38MHR

**Scenario 2:** Single Zone Ductless System with 38MBR/38MBRB

**Scenario 3:** Multi-zone Ductless System with 38MGR

**Scenario 4:** Single Zone Fan Coils FMA/FX4D/FB4C with 38MARB

**Scenario 5:** Single Zone Fan Coils FV4C with 38MARB

**Scenario 6:** Compatible Single Zone Furnace with 38MARB

## SCENARIO 1: SINGLE ZONE OUTDOOR UNITS (38MPRA, 38MARB, 38MHR) WITH APPROVED DUCTLESS INDOOR UNITS

- High Wall (sizes 6K-36K)[208-230V]\*\*
- Cassette (sizes 9K-24K)
- Ducted (sizes 9K-24K) (\*refer to NOTES in the adjacent column)
- Console (sizes 18K-24K)



### CAUTION

Refer to the Compatibility Charts on [hvacpartners.com](http://hvacpartners.com) for the proper matches and serial number compatibility. Units built prior to the generation of this serial number require a Control Board Replacement on the indoor unit.

#### Installation Steps:

1. Run the interconnecting piping from the indoor to the outdoor unit using the correct indoor piping size.
2. Run the interconnecting wiring from the outdoor unit to the 24V interface using terminal connections L1(1), L2(2), S(3) and G.
3. Run the interconnecting wiring from the 24V interface to the indoor unit using terminal connections L1(1), L2(2), S(3) and G.
4. Run the thermostat wiring from the thermostat to the 24V interface using connections R and C on CN15 and Y, W, G on CN19.
5. Configure the dip switches on the 24V interface accordingly.
6. Configure the thermostat to operate in single stage cooling and heating scenarios (**DO NOT configure the thermostat as a Heat Pump**).

#### NOTES:

Follow the indoor and outdoor unit's general installation instructions.

\*For the Ducted units, in order to initially setup the static pressure, the 24V interface must be bridged. Temporarily connect the communication wires L1, L2, S and G from the indoor to the outdoor unit until the static pressure settings are complete (refer to the Ducted unit installation manual).

On selected indoor units, the Up-Down Swing Louver functions as a control to turn off the indoor unit display (LED) and is available on the unit's wireless remote controller. The Wi-Fi KSAIF and wired remote controllers KSACN are not functional when using the 24V interface.

\*\*For 115V Ductless applications, the 24V transformer must be replaced in the field. This part is available through RCD (part number 11203103000393).



### CAUTION

The conventional thermostat must be configured for use with a single stage air conditioner (Y output **ONLY**) and a single stage heating (W) system.




Fig. 9 — Wiring Diagram

**IMPORTANT:** All ground wiring must be installed according to the equipment's installation manual.

## SCENARIO 2: SINGLE ZONE OUTDOOR UNITS (38MBRC) WITH APPROVED DUCTLESS INDOOR UNITS

- Cassette (sizes 36K-48K)
- Ducted (sizes 36K-58K) (\*refer to **NOTES** in the adjacent column)
- Console (sizes 36K-58K)



### CAUTION

Refer to the Compatibility Charts on [hvacpartners.com](http://hvacpartners.com) for the proper matches and serial number compatibility. Units built prior to the generation of this serial number would require a Control Board Replacement on the Indoor unit.

#### Installation Steps:

1. Run the interconnecting piping from the indoor unit to the outdoor unit using the correct indoor piping size.
2. Run the interconnecting wiring from the outdoor unit to the 24V interface using terminal connections L1(1), L2(2), and G. Connect the wiring for the S1 and S2 outdoor interface to CN8.
3. Run the interconnecting wiring from the 24V interface to the indoor unit using terminal connections L1(1), L2(2) and G. Connect the wiring for the S1 and S2 outdoor interface to CN9.
4. Run the thermostat wiring from the thermostat to the 24V interface using connections R and C on CN15 and Y, W, G on CN19.
5. Configure the dip switches on the 24V interface accordingly.
6. Configure the thermostat to operate in single stage cooling and heating scenarios (**DO NOT** configure the thermostat as a Heat Pump).

#### NOTES:

Follow the indoor and outdoor unit's general installation instructions.

\*For Ducted units, in order to initially setup the static pressure, the 24V interface must be bridged. Temporarily connect the communication wires, S1 and S2, from the indoor unit to the outdoor unit until the static pressure settings are complete (see the Ducted unit installation manual). When the static pressure is adjusted, connect S1 and S2 to CN8 and CN9 (see Fig. 21).

On selected indoor units, the Up-Down Swing Louver functions as a control to turn off the indoor unit display (LED) and is available on the unit's wireless remote controller. The Wi-Fi accessories KSAIF and wired remote controllers KSACN are not functional when using the 24V interface.



### CAUTION

The conventional thermostat must be configured for use with a single stage air conditioner (Y output **ONLY**) and a single stage heating (W) system.




Fig. 10 — Wiring Diagram



# BACnet MS/TP Server

For Ductless Indoor units

## USER MANUAL

Issue date: 06/2020 r1.0 ENGLISH



## Important User Information

### Disclaimer

The information in this document is for informational purposes only. Please inform HMS Industrial Networks of any inaccuracies or omissions found in this document. HMS Industrial Networks disclaims any responsibility or liability for any errors that may appear in this document.

HMS Industrial Networks reserves the right to modify its products in line with its policy of continuous product development. The information in this document shall therefore not be construed as a commitment on the part of HMS Industrial Networks and is subject to change without notice. HMS Industrial Networks makes no commitment to update or keep current the information in this document.

The data, examples and illustrations found in this document are included for illustrative purposes and are only intended to help improve understanding of the functionality and handling of the product. In view of the wide range of possible applications of the product, and because of the many variables and requirements associated with any particular implementation, HMS Industrial Networks cannot assume responsibility or liability for actual use based on the data, examples or illustrations included in this document nor for any damages incurred during installation of the product. Those responsible for the use of the product must acquire sufficient knowledge in order to ensure that the product is used correctly in their specific application and that the application meets all performance and safety requirements including any applicable laws, regulations, codes and standards. Further, HMS Industrial Networks will under no circumstances assume liability or responsibility for any problems that may arise as a result from the use of undocumented features or functional side effects found outside the documented scope of the product. The effects caused by any direct or indirect use of such aspects of the product are undefined and may include e.g. compatibility issues and stability issues.

## Gateway for the integration of a Ductless air conditioning unit in BACnet MSTP enabled monitoring and control systems.

### Compatibility:

Only specific Carrier DLS indoor product families are tested for compatibility with the Intesis BACnet MS/TP 1:1 gateway INBACMID001I100. Ductless indoor unit backward compatibility as well as future versions' compatibility is not guaranteed.

|                |
|----------------|
| Phased Out     |
| Not Compatible |
| Current Model  |



Net dimensions (DxWxH): (3.7 x 2.1 x 2.3 in) ( 93 x 53 x 58 mm)

Compatibility between the Intesis BACnet gateway and the factory wired wall controller.



| Carrier Model Number | Indoor Unit Type     | Size | Midea protocol | Compatible        | Phased Out   | KSACN0101AAA | KSACN0601AAA | KSACN0701AAA | KSACN0801AAA |
|----------------------|----------------------|------|----------------|-------------------|--------------|--------------|--------------|--------------|--------------|
| 40 MPHA              | HighWall             | All  | V4             | YES               |              | No           | No           | No           | No           |
| 40 MAQ               | HighWall             | All  | V4             | YES** See Note 1  | Yes Q1, 2021 | No           | No           | No           | No           |
| 40 MAHB              | HighWall             | All  | V4             | YES** See Note 2  |              | Yes          | No           | No           | No           |
| 40 MHHQ              | HighWall             | All  | V4             | Yes               |              | Yes          | No           | No           | No           |
| 40 MHHC              | HighWall             | All  | Forced / V4    | YES*** See Note 3 |              | Yes          | No           | No           | No           |
| 40 MBCQ              | Cassette             | All  | V4             | Yes               |              | Yes          | No           | Yes          | No           |
| 40 MBAA              | Ducted               | N/A  | N/A            | Not Compatible    |              | N/A          | N/A          | N/A          | N/A          |
| 40 MBDQ              | Ducted               | All  | V4             | Yes               |              | Yes          | No           | Yes          | No           |
| 40 MBFQ              | Underceiling / Floor | N/A  | N/A            | Not Compatible    |              | N/A          | N/A          | N/A          | N/A          |

### Notes:

\* 1: 40MAQ The mid-tier Ductless High Wall 40MAQB\*\*B---3 indoor unit type, will need to have the display and adaptor board replaced to function with the Intesis MS/TP BACnet gateway.  
The 40MAQ Adapter Board, P/N 17222000A50275, and Display Board Assembly, P/N 17222000A17852, can be ordered from RC.

\*\* 2: The 40MAHB Indoor unit requires that a multi function board and 7 pin wiring harness are added to the indoor unit at the time of installation.  
The multifunction board P/N 17122000A38610 and wiring harness P/N 17401204A02537 can be ordered as an accessory.

\*\*\* 3: The 40MHHC is a cooling only system. Please consider this when completing the integration. The only Modes that should be mapped to the BACnet controls system should be Cooling & Fan.

The wireless infrared controller that comes with the indoor unit can be used at the same time as the Intesis BACnet gateway or disabled by configuration.

### ORDER CODE:

**INBACMID001I100: Ductless to BACnet MSTP Interface - 1 Indoor Unit**

| ORDER CODE      | LEGACY ORDER CODE |
|-----------------|-------------------|
| INBACMID001I100 | -                 |

**INDEX**

|        |                                                                 |    |
|--------|-----------------------------------------------------------------|----|
| 1      | Description .....                                               | 6  |
| 1.1    | Introduction .....                                              | 6  |
| 1.2    | Functionality .....                                             | 7  |
| 1.3    | Capacity of Intesis .....                                       | 7  |
| 1.4    | Quick Setup .....                                               | 7  |
| 2      | Protocol Implementation Conformance Statement .....             | 8  |
| 2.1    | BACnet Standardized Device Profile (Annex L): .....             | 8  |
| 2.2    | Segmentation Capability: .....                                  | 8  |
| 2.3    | Data Link Layer Options: .....                                  | 8  |
| 2.4    | Device Address Binding: .....                                   | 9  |
| 2.5    | Networking Options: .....                                       | 9  |
| 2.6    | Character Sets Supported .....                                  | 9  |
| 2.7    | Gateway .....                                                   | 9  |
| 3      | BACnet Interoperability Building Blocks Supported (BIBBs) ..... | 10 |
| 3.1    | Data Sharing BIBBs .....                                        | 10 |
| 3.2    | Alarm and Event Management BIBBs .....                          | 10 |
| 3.3    | Scheduling BIBBs .....                                          | 11 |
| 3.4    | Trending BIBBs .....                                            | 11 |
| 3.5    | Network Management BIBBs .....                                  | 11 |
| 3.6    | Device Management BIBBs .....                                   | 12 |
| 4      | Service Types .....                                             | 13 |
| 5      | Objects .....                                                   | 14 |
| 5.1    | Supported Object Types .....                                    | 14 |
| 5.2    | Member objects .....                                            | 15 |
| 5.2.1  | Type: Gateway .....                                             | 15 |
| 5.2.2  | Type: Indoor Unit .....                                         | 15 |
| 5.3    | Objects and properties .....                                    | 16 |
| 5.3.1  | AC Gateway (Device Object Type) .....                           | 16 |
| 5.3.2  | OnOff_status (Binary Input Object Type) .....                   | 18 |
| 5.3.3  | OnOff_command (Binary Output Object Type) .....                 | 19 |
| 5.3.4  | Mode_status (Multistate Input Object Type) .....                | 20 |
| 5.3.5  | Mode_command (Multistate Output Object Type) .....              | 21 |
| 5.3.6  | Setpoint_status (Analog Input Object Type) .....                | 22 |
| 5.3.7  | Setpoint_command (Analog Output Object Type) .....              | 23 |
| 5.3.8  | FanSpeed_status (Multistate Input Object Type) .....            | 24 |
| 5.3.9  | FanSpeed_command (Multistate Output Object Type) .....          | 25 |
| 5.3.10 | AirDirectionUD_status (Multistate Input Object Type) .....      | 26 |
| 5.3.11 | AirDirectionUD_command (Multistate Output Object Type) .....    | 27 |
| 5.3.12 | RoomTemperature_status (Analog Input Object Type) .....         | 28 |

# Intesis™ BACnet MSTP – Ductless Indoor Units

User

Manual r1.0 EN

|        |                                                                        |    |
|--------|------------------------------------------------------------------------|----|
| 5.3.13 | RoomTemperature_command (Analog Output Object Type).....               | 29 |
| 5.3.14 | ErrorCode (Analog Input Object Type) .....                             | 30 |
| 5.3.15 | ErrorCodeM (Multistate Input Object Type) .....                        | 31 |
| 5.3.16 | ErrorActive (Binary Input Object Type) .....                           | 33 |
| 5.3.17 | OnTimeCounter (Analog Value Object Type) .....                         | 34 |
| 5.3.18 | Occupancy (Multistate Value Object Type) .....                         | 35 |
| 5.3.19 | OccupiedCoolSetPoint (Analog Value Object Type) .....                  | 36 |
| 5.3.20 | OccupiedHeatSetPoint (Analog Value Object Type) .....                  | 37 |
| 5.3.21 | UnoccupiedCoolSetPoint (Analog Value Object Type) .....                | 38 |
| 5.3.22 | UnoccupiedHeatSetPoint (Analog Value Object Type) .....                | 39 |
| 5.3.23 | OccupancyContinuousCheck (Binary Value Object Type) .....              | 40 |
| 5.3.24 | UnoccupiedDeadbandAction (Binary Value Object Type) .....              | 41 |
| 5.3.25 | RemoteControllerProhibit_status (Multistate Input Object Type) .....   | 42 |
| 5.3.26 | RemoteControllerProhibit_command (Multistate Output Object Type) ..... | 43 |
| 5.3.27 | DIP_SW_S1_status (Analog Input Object Type) .....                      | 44 |
| 5.3.28 | DIP_SW_S2_status (Analog Input Object Type) .....                      | 45 |
| 5.3.29 | SerialNumber (Analog Input Object Type) .....                          | 46 |
| 5.3.30 | AC IU address (Multistate Value Object Type) .....                     | 47 |
| 5.3.31 | Midea_DIP_SW_setting (Multistate Input Object Type) .....              | 48 |
| 5.4    | Considerations on Temperature Objects .....                            | 49 |
| 6      | Connections and switches .....                                         | 51 |
| 6.1    | Connect to the XYE terminals .....                                     | 51 |
| 6.2    | Connect to BACnet MS/TP .....                                          | 52 |
| 6.2.1  | MS/TP MAC address switch configuration .....                           | 52 |
| 6.2.2  | BACnet MS/TP baudrate .....                                            | 52 |
| 6.3    | Connect to an external power supply .....                              | 52 |
| 7      | Set-up process and troubleshooting .....                               | 54 |
| 7.1    | Pre-requisites .....                                                   | 54 |
| 7.2    | Physical checking .....                                                | 54 |
| 7.3    | LED status .....                                                       | 54 |
| 7.4    | Occupancy .....                                                        | 55 |
| 8      | Restore factory Settings .....                                         | 56 |
| 8.1    | Restore factory Settings .....                                         | 56 |
| 9      | AC Unit Types compatibility .....                                      | 57 |
| 10     | Mechanical & electrical characteristics .....                          | 57 |
| 11     | Error codes .....                                                      | 59 |

## 1 Description

### 1.1 Introduction


This document describes the integration of Ductless air conditioning systems into BACnet MS/TP compatible devices and systems using gateway *INBACMID001I100*.

The aim of this integration is to monitor and control your Ductless air conditioning system, remotely, from your Control Center using any commercial SCADA or monitoring software that includes a BACnet driver or connect it to other BACnet devices to do any automation. To do it so, Intesis allows BACnet communication allowing polling or subscription requests (COV).

Intesis makes available the Ductless air conditioning system indoor units through independent BACnet objects.

Abstraction of Ductless air conditioning system properties and functionalities as fixed BACnet Objects. Intesis allows fixed BACnet object IDs mapping. Simple configuration is needed: just select the appropriate communication parameters (MAC address, baud rate...).

This document assumes that the user is familiar with BACnet and Ductless technologies and their technical terms.



**BACnet MS/TP installation sketch**

## 1.2 Functionality

Intesis continuously read the Ductless AC unit and keeps the updated status of all objects in its memory, ready to be served when requested from the BACnet side.

The role of Intesis consists in associate the elements of the Ductless AC unit with BACnet objects.

The control of the indoor units through the INBACMID001I100 is permitted, so commands toward the Ductless AC unit are permitted too.

The indoor unit is offered in a set of BACnet objects and extra functionality.

## 1.3 Capacity of Intesis

Intesis is capable of integrate one single Ductless AC unit and its associated elements.

| Element                | Max. | Notes                                                            |
|------------------------|------|------------------------------------------------------------------|
| Number of indoor units | 1    | Number of indoor units that can be controlled through Intesis    |
| Number of Objects      | 30   | Number of Ductless AC signals available as objects into Intesis. |

## 1.4 Quick Setup

1. Install Intesis in the desired installation site (DIN rail mounting inside a metallic industrial cabinet connected to ground is recommended).
2. Connect the communication cables. Details in section [6 CONNECTIONS AND SWITCHES](#).
3. Check the BACnet objects list for its integration to your BACnet project. Details in section [5.3 OBJECTS AND PROPERTIES](#).
4. Check if there is communication between BACnet and AC system through device LED. Details in section [7.3 LED STATUS](#).
5. The Intesis is ready to be used in your system.

## 2 Protocol Implementation Conformance Statement

### BACnet Protocol Implementation Conformance Statement (PICS)

**Date:** 2015-04-01

**Vendor Name:** HMS Industrial Networks S.L.U

**Product Name:** INBACMID001I100

**Product Model Number:** INBACMID001I100

**Application Software Version:** 1.0

**Firmware Revision:** 1.0.0.0

**BACnet Protocol Revision:** 12

#### Product Description:

*Ductless air conditioning systems – BACnet MS/TP*

Abstraction of Ductless air conditioning system properties and functionalities as BACnet Objects.

#### 2.1 BACnet Standardized Device Profile (Annex L):

- ☐ BACnet Operator Workstation (B-OWS)
- ☐ BACnet Building Controller (B-BC)
- ☐ BACnet Advanced Application Controller (B-AAC)
- ☒ BACnet Application Specific Controller (B-ASC)
- ☐ BACnet Smart Sensor (B-SS)
- ☐ BACnet Smart Actuator (B-SA)

Additional BACnet Interoperability Building Blocks Supported (Annex K):  
*Reference of BIBBs List*

#### 2.2 Segmentation Capability:

|                               |                             |                                         |                           |
|-------------------------------|-----------------------------|-----------------------------------------|---------------------------|
| Segmented request supported   | <input type="checkbox"/> No | <input checked="" type="checkbox"/> Yes | Window Size : <u>16</u> . |
| Segmented responses supported | <input type="checkbox"/> No | <input checked="" type="checkbox"/> Yes | Window Size : <u>16</u> . |

#### 2.3 Data Link Layer Options:

- ☐ BACnet IP, (Annex J)
- ☐ BACnet IP, (Annex J), Foreign Device
- ☐ ISO 8802-3, Ethernet (Clause 7)
- ☐ ANSI/ATA 878.1, 2.5 Mb. ARCNET (Clause 8)
- ☐ ANSI/ATA 878.1, RS-485 ARCNET (Clause 8), baud rate(s) \_\_\_\_\_
- ☒ MS/TP master (Clause 9), baud rate(s): 9600, 19200, 38400, 76800
- ☐ MS/TP slave (Clause 9), baud rate(s): \_\_\_\_\_
- ☐ Point-To-Point, EIA 232 (Clause 10), baud rate(s): \_\_\_\_\_
- ☐ Point-To-Point, modem, (Clause 10), baud rate(s): \_\_\_\_\_
- ☐ LonTalk, (Clause 11), medium: \_\_\_\_\_
- ☐ Other: \_\_\_\_\_

**2.4 Device Address Binding:**

Is static device binding supported? (This is currently necessary for two-way communication with MS/TP slaves and certain other devices.) ☐ Yes ☒ No

**2.5 Networking Options:**

- ☐ Router, Clause 6 - List all routing configurations, e.g., ARCNET-Ethernet, Ethernet-MS/TP, etc.
- ☐ Annex H, BACnet Tunneling Router over IP
- ☐ BACnet/IP Broadcast Management Device (BBMD)  
Does the BBMD support registrations by Foreign Devices? ☐ Yes ☐ No

**2.6 Character Sets Supported**

Indicating support for multiple character sets does not imply that they can all be supported simultaneously.

- ☒ ANSI X3.4
- ☐ IBM™/Microsoft™ DBCS
- ☐ JIS C 6226
- ☐ ISO 10646 (UCS-4)
- ☐ ISO 10646 (UCS-2)
- ☐ ISO 8859-1

**2.7 Gateway**

If this product is a communication gateway, describe the types of non-BACnet equipment/network(s) that the gateway supports:

**Ductless Air Conditioning Units .**

### 3 BACnet Interoperability Building Blocks Supported (BIBBs)

#### 3.1 Data Sharing BIBBs

| BIBB Type | Active                              | BACnet Service             | Initiate                            | Execute                             |
|-----------|-------------------------------------|----------------------------|-------------------------------------|-------------------------------------|
| DS-RP-A   | <input type="checkbox"/>            | ReadProperty               | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| DS-RP-B   | <input checked="" type="checkbox"/> | ReadProperty               | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| DS-RPM-A  | <input type="checkbox"/>            | ReadPropertyMultiple       | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| DS-RPM-B  | <input checked="" type="checkbox"/> | ReadPropertyMultiple       | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| DS-RPC-A  | <input type="checkbox"/>            | ReadPropertyConditional    | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| DS-RPC-B  | <input type="checkbox"/>            | ReadPropertyConditional    | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| DS-WP-A   | <input type="checkbox"/>            | WriteProperty              | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| DS-WP-B   | <input checked="" type="checkbox"/> | WriteProperty              | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| DS-WPM-A  | <input type="checkbox"/>            | WritePropertyMultiple      | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| DS-WPM-B  | <input checked="" type="checkbox"/> | WritePropertyMultiple      | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| DS-COV-A  | <input type="checkbox"/>            | SubscribeCOV               | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
|           | <input type="checkbox"/>            | ConfirmedCOVNotification   | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
|           | <input type="checkbox"/>            | UnconfirmedCOVNotification | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| DS-COV-B  | <input checked="" type="checkbox"/> | SubscribeCOV               | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
|           | <input checked="" type="checkbox"/> | ConfirmedCOVNotification   | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
|           | <input checked="" type="checkbox"/> | UnconfirmedCOVNotification | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| DS-COVP-A | <input type="checkbox"/>            | SubscribeCOV               | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
|           | <input type="checkbox"/>            | ConfirmedCOVNotification   | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
|           | <input type="checkbox"/>            | UnconfirmedCOVNotification | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| DS-COVP-B | <input type="checkbox"/>            | SubscribeCOV               | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
|           | <input type="checkbox"/>            | ConfirmedCOVNotification   | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
|           | <input type="checkbox"/>            | UnconfirmedCOVNotification | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| DS-COVU-A | <input type="checkbox"/>            | UnconfirmedCOVNotification | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| DS-COVU-B | <input type="checkbox"/>            | UnconfirmedCOVNotification | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |

#### 3.2 Alarm and Event Management BIBBs

| BIBB Type | Active                   | BACnet Service               | Initiate                            | Execute                             |
|-----------|--------------------------|------------------------------|-------------------------------------|-------------------------------------|
| AE-N-A    | <input type="checkbox"/> | ConfirmedEventNotification   | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
|           | <input type="checkbox"/> | UnconfirmedEventNotification | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| AE-N-I-B  | <input type="checkbox"/> | ConfirmedEventNotification   | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
|           | <input type="checkbox"/> | UnconfirmedEventNotification | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| AE-N-E-B  | <input type="checkbox"/> | ConfirmedEventNotification   | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
|           | <input type="checkbox"/> | UnconfirmedEventNotification | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| AE-ACK-A  | <input type="checkbox"/> | AcknowledgeAlarm             | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| AE-ACK-B  | <input type="checkbox"/> | AcknowledgeAlarm             | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| AE-ASUM-A | <input type="checkbox"/> | GetAlarmSummary              | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| AE-ASUM-B | <input type="checkbox"/> | GetAlarmSummary              | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| AE-ESUM-A | <input type="checkbox"/> | GetEnrollmentSummary         | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| AE-ESUM-B | <input type="checkbox"/> | GetEnrollmentSummary         | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| AE-INFO-A | <input type="checkbox"/> | GetEventInformation          | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| AE-INFO-B | <input type="checkbox"/> | GetEventInformation          | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| AE-LS-A   | <input type="checkbox"/> | LifeSafetyOperation          | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| AE-LS-B   | <input type="checkbox"/> | LifeSafetyOperation          | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |

## 3.3 Scheduling BIBBs

| BIBB Type |                                                                                                                 | Active                   | BACnet Service             | Initiate                            | Execute                             |
|-----------|-----------------------------------------------------------------------------------------------------------------|--------------------------|----------------------------|-------------------------------------|-------------------------------------|
| SCHED-A   | Scheduling-A<br>(must support DS-RP-A and DS-WP-A)                                                              | <input type="checkbox"/> |                            |                                     |                                     |
|           |                                                                                                                 | <input type="checkbox"/> |                            |                                     |                                     |
| SCHED-I-B | Scheduling-Internal-B<br>(shall support DS-RP-B and DS-WP-B)<br>(shall also support either DM-TS-B or DS-UTC-B) | <input type="checkbox"/> |                            |                                     |                                     |
|           |                                                                                                                 | <input type="checkbox"/> |                            |                                     |                                     |
| SCHED-E-B | Scheduling-External-B<br>(shall support SCHED-I-B and DS-WP-A)                                                  | <input type="checkbox"/> |                            |                                     |                                     |
|           |                                                                                                                 | <input type="checkbox"/> |                            |                                     |                                     |
| T-VMT-A   | Trending - Viewing and Modifying Trends-A                                                                       | <input type="checkbox"/> | ReadRange                  | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| T-VMT-I-B | Trending - Viewing and Modifying Trends Internal-B                                                              | <input type="checkbox"/> | ReadRange                  | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| T-VMT-E-B | Trending - Viewing and Modifying Trends External-B                                                              | <input type="checkbox"/> | ReadRange                  | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| T-ATR-A   | Trending - Automated Trend Retrieval-A                                                                          | <input type="checkbox"/> | ConfirmedEventNotification | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
|           |                                                                                                                 | <input type="checkbox"/> | ReadRange                  | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| T-ATR-B   | Trending - Automated Trend Retrieval-B                                                                          | <input type="checkbox"/> | ConfirmedEventNotification | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
|           |                                                                                                                 | <input type="checkbox"/> | ReadRange                  | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |

## 3.4 Trending BIBBs

| BIBB Type |                                                    | Active                   | BACnet Service             | Initiate                            | Execute                             |
|-----------|----------------------------------------------------|--------------------------|----------------------------|-------------------------------------|-------------------------------------|
| T-VMT-A   | Trending - Viewing and Modifying Trends-A          | <input type="checkbox"/> | ReadRange                  | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| T-VMT-I-B | Trending - Viewing and Modifying Trends Internal-B | <input type="checkbox"/> | ReadRange                  | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| T-VMT-E-B | Trending - Viewing and Modifying Trends External-B | <input type="checkbox"/> | ReadRange                  | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| T-ATR-A   | Trending - Automated Trend Retrieval-A             | <input type="checkbox"/> | ConfirmedEventNotification | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
|           |                                                    | <input type="checkbox"/> | ReadRange                  | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| T-ATR-B   | Trending - Automated Trend Retrieval-B             | <input type="checkbox"/> | ConfirmedEventNotification | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
|           |                                                    | <input type="checkbox"/> | ReadRange                  | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |

## 3.5 Network Management BIBBs

| BIBB Type |                                                 | Active                   | BACnet Service                   | Initiate                            | Execute                             |
|-----------|-------------------------------------------------|--------------------------|----------------------------------|-------------------------------------|-------------------------------------|
| NM-CE-A   | Network Management - Connection Establishment-A | <input type="checkbox"/> | Establish-Connection-To-Network  | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
|           |                                                 | <input type="checkbox"/> | Disconnect-Connection-To-Network | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| NM-CE-B   | Network Management - Connection Establishment-B | <input type="checkbox"/> | Establish-Connection-To-Network  | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
|           |                                                 | <input type="checkbox"/> | Disconnect-Connection-To-Network | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| NM-RC-A   | Network Management - Router Configuration-A     | <input type="checkbox"/> | Who-Is-Router-To-Network         | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
|           |                                                 | <input type="checkbox"/> | I-Am-Router-To-Network           | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
|           |                                                 | <input type="checkbox"/> | I-Could-Be-Router-To-Network     | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
|           |                                                 | <input type="checkbox"/> | Initialize-Routing-Table         | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| NM-RC-B   | Network Management - Router Configuration-B     | <input type="checkbox"/> | Initialize-Routing-Table-Ack     | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
|           |                                                 | <input type="checkbox"/> | Who-Is-Router-To-Network         | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
|           |                                                 | <input type="checkbox"/> | I-Am-Router-To-Network           | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
|           |                                                 | <input type="checkbox"/> | Initialize-Routing-Table         | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
|           |                                                 | <input type="checkbox"/> | Initialize-Routing-Table-Ack     | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |

### 3.6 Device Management BIBBs

| BIBB Type |                                                    | Active                              | BACnet Service             | Initiate                            | Execute                             |
|-----------|----------------------------------------------------|-------------------------------------|----------------------------|-------------------------------------|-------------------------------------|
| DM-DDB-A  | Device Management - Dynamic Device Binding–A       | <input type="checkbox"/>            | Who-Is                     | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
|           |                                                    | <input type="checkbox"/>            | I-Am                       | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| DM-DDB-B  | Device Management - Dynamic Device Binding–B       | <input checked="" type="checkbox"/> | Who-Is                     | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
|           |                                                    | <input checked="" type="checkbox"/> | I-Am                       | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| DM-DOB-A  | Device Management - Dynamic Object Binding–A       | <input type="checkbox"/>            | Who-Has                    | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
|           |                                                    | <input type="checkbox"/>            | I-Have                     | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| DM-DOB-B  | Device Management - Dynamic Object Binding–B       | <input checked="" type="checkbox"/> | Who-Has                    | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
|           |                                                    | <input checked="" type="checkbox"/> | I-Have                     | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| DM-DCC-A  | Device Management - DeviceCommunicationControl–A   | <input type="checkbox"/>            | DeviceCommunicationControl | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| DM-DCC-B  | Device Management - DeviceCommunicationControl–B   | <input checked="" type="checkbox"/> | DeviceCommunicationControl | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| DM-PT-A   | Device Management - PrivateTransfer–A              | <input type="checkbox"/>            | ConfirmedPrivateTransfer   | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
|           |                                                    | <input type="checkbox"/>            | UnconfirmedPrivateTransfer | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| DM-PT-B   | Device Management - PrivateTransfer–B              | <input type="checkbox"/>            | ConfirmedPrivateTransfer   | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
|           |                                                    | <input type="checkbox"/>            | UnconfirmedPrivateTransfer | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| DM-TM-A   | Device Management - Text Message–A                 | <input type="checkbox"/>            | ConfirmedTextMessage       | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
|           |                                                    | <input type="checkbox"/>            | UnconfirmedTextMessage     | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| DM-TM-B   | Device Management - Text Message–B                 | <input type="checkbox"/>            | ConfirmedTextMessage       | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
|           |                                                    | <input type="checkbox"/>            | UnconfirmedTextMessage     | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| DM-TS-A   | Device Management - TimeSynchronization–A          | <input type="checkbox"/>            | TimeSynchronization        | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| DM-TS-B   | Device Management - TimeSynchronization–B          | <input type="checkbox"/>            | TimeSynchronization        | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| DM-UTC-A  | Device Management - UTCTimeSynchronization–A       | <input type="checkbox"/>            | UTCTimeSynchronization     | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| DM-UTC-B  | Device Management - UTCTimeSynchronization–B       | <input type="checkbox"/>            | UTCTimeSynchronization     | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| DM-RD-A   | Device Management - ReinitializeDevice–A           | <input type="checkbox"/>            | ReinitializeDevice         | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| DM-RD-B   | Device Management - ReinitializeDevice–B           | <input checked="" type="checkbox"/> | ReinitializeDevice         | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| DM-BR-A   | Device Management - Backup and Restore–A           | <input type="checkbox"/>            | AtomicReadFile             | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
|           |                                                    | <input type="checkbox"/>            | AtomicWriteFile            | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
|           |                                                    | <input type="checkbox"/>            | CreateObject               | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
|           |                                                    | <input type="checkbox"/>            | ReinitializeDevice         | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| DM-BR-B   | Device Management - Backup and Restore–B           | <input type="checkbox"/>            | AtomicReadFile             | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
|           |                                                    | <input type="checkbox"/>            | AtomicWriteFile            | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
|           |                                                    | <input type="checkbox"/>            | ReinitializeDevice         | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| DM-R-A    | Device Management - Restart–A                      | <input type="checkbox"/>            | UnconfirmedCOVNotification | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| DM-R-B    | Device Management - Restart–B                      | <input type="checkbox"/>            | UnconfirmedCOVNotification | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| DM-LM-A   | Device Management - List Manipulation–A            | <input type="checkbox"/>            | AddListElement             | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
|           |                                                    | <input type="checkbox"/>            | RemoveListElement          | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| DM-LM-B   | Device Management - List Manipulation–B            | <input type="checkbox"/>            | AddListElement             | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
|           |                                                    | <input type="checkbox"/>            | RemoveListElement          | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| DM-OCD-A  | Device Management - Object Creation and Deletion–A | <input type="checkbox"/>            | CreateObject               | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
|           |                                                    | <input type="checkbox"/>            | DeleteObject               | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
| DM-OCD-B  | Device Management - Object Creation and Deletion–B | <input type="checkbox"/>            | CreateObject               | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
|           |                                                    | <input type="checkbox"/>            | DeleteObject               | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
| DM-VT-A   | Device Management - Virtual Terminal–A             | <input type="checkbox"/>            | VT-Open                    | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |
|           |                                                    | <input type="checkbox"/>            | VT-Close                   | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
|           |                                                    | <input type="checkbox"/>            | VT-Data                    | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| DM-VT-B   | Device Management - Virtual Terminal–B             | <input type="checkbox"/>            | VT-Open                    | <input type="checkbox"/>            | <input checked="" type="checkbox"/> |
|           |                                                    | <input type="checkbox"/>            | VT-Close                   | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
|           |                                                    | <input type="checkbox"/>            | VT-Data                    | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |

## 4 Service Types

| Service type                      | Service name                 | Supported                           | Remarks |
|-----------------------------------|------------------------------|-------------------------------------|---------|
| Alarm and Event Services          | AcknowledgeAlarm             | <input type="checkbox"/>            |         |
|                                   | ConfirmedCOVNotification     | <input type="checkbox"/>            |         |
|                                   | ConfirmedEventNotification   | <input type="checkbox"/>            |         |
|                                   | GetAlarmSummary              | <input type="checkbox"/>            |         |
|                                   | GetEnrollmentSummary         | <input type="checkbox"/>            |         |
|                                   | SubscribeCOV                 | <input checked="" type="checkbox"/> |         |
| File Access Services              | AtomicReadFile               | <input type="checkbox"/>            |         |
|                                   | AtomicWriteFile              | <input type="checkbox"/>            |         |
| Object Access Services            | AddListElement               | <input type="checkbox"/>            |         |
|                                   | RemoveListElement            | <input type="checkbox"/>            |         |
|                                   | CreateObject                 | <input type="checkbox"/>            |         |
|                                   | DeleteObject                 | <input type="checkbox"/>            |         |
|                                   | ReadProperty                 | <input checked="" type="checkbox"/> |         |
|                                   | ReadPropertyConditional      | <input type="checkbox"/>            |         |
|                                   | ReadPropertyMultiple         | <input checked="" type="checkbox"/> |         |
|                                   | ReadRange                    | <input type="checkbox"/>            |         |
| Remote Device Management Services | WriteProperty                | <input checked="" type="checkbox"/> |         |
|                                   | WritePropertyMultiple        | <input checked="" type="checkbox"/> |         |
|                                   | DeviceCommunicationControl   | <input type="checkbox"/>            |         |
|                                   | ConfirmedPrivateTransfer     | <input type="checkbox"/>            |         |
|                                   | ConfirmedTextMessage         | <input type="checkbox"/>            |         |
| Virtual Terminal Services         | ReinitializeDevice           | <input checked="" type="checkbox"/> |         |
|                                   | VtOpen                       | <input type="checkbox"/>            |         |
|                                   | VtClose                      | <input type="checkbox"/>            |         |
| Security Services                 | VtData                       | <input type="checkbox"/>            |         |
|                                   | Authenticate                 | <input type="checkbox"/>            |         |
| Unconfirmed Services              | RequestKey                   | <input type="checkbox"/>            |         |
|                                   | I-Am                         | <input checked="" type="checkbox"/> |         |
|                                   | I-Have                       | <input checked="" type="checkbox"/> |         |
|                                   | UnconfirmedCOVNotification   | <input type="checkbox"/>            |         |
|                                   | UnconfirmedEventNotification | <input type="checkbox"/>            |         |
|                                   | UnconfirmedPrivateTransfer   | <input type="checkbox"/>            |         |
|                                   | UnconfirmedTextMessage       | <input type="checkbox"/>            |         |
|                                   | TimeSynchronization          | <input type="checkbox"/>            |         |
|                                   | UtcTimeSynchronization       | <input type="checkbox"/>            |         |
|                                   | Who-Has                      | <input checked="" type="checkbox"/> |         |
|                                   | Who-Is                       | <input checked="" type="checkbox"/> |         |
|                                   | LifeSafetyOperation          | <input type="checkbox"/>            |         |
|                                   | SubscribeCOVProperty         | <input checked="" type="checkbox"/> |         |
|                                   | GetEventInformation          | <input type="checkbox"/>            |         |

## 5 Objects

### 5.1 Supported Object Types

The objects supported are shown in the table below.

| Object Type        | ID | Supported                           | Management Point                                                                                                          |
|--------------------|----|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Analog-Input       | 0  | <input checked="" type="checkbox"/> | SetPoint_status<br>Room Temperature_status<br>ErrorCode<br>DIP_SW_S1_status<br>DIP_SW_S2_status<br>SerialNumber           |
| Analog-Output      | 1  | <input checked="" type="checkbox"/> | SetPoint_command<br>RoomTemperature_command                                                                               |
| Analog-Value       | 2  | <input checked="" type="checkbox"/> | OnTimeCounter<br>OccupiedCoolSetPoint<br>OccupiedHeatSetPoint<br>UnoccupiedCoolSetPoint<br>UnoccupiedHeatSetPoint         |
| Averaging          | 18 | <input type="checkbox"/>            |                                                                                                                           |
| Binary-Input       | 3  | <input checked="" type="checkbox"/> | OnOff_status<br>ErrorActive                                                                                               |
| Binary-Output      | 4  | <input checked="" type="checkbox"/> | OnOff_command                                                                                                             |
| Binary-Value       | 5  | <input checked="" type="checkbox"/> | OccupancyContinousCheck<br>UnoccupiedDeadBandAction                                                                       |
| Calendar           | 6  | <input type="checkbox"/>            |                                                                                                                           |
| Command            | 7  | <input type="checkbox"/>            |                                                                                                                           |
| Device             | 8  | <input checked="" type="checkbox"/> | INBACMID0011100                                                                                                           |
| Event-Enrollment   | 9  | <input type="checkbox"/>            |                                                                                                                           |
| File               | 10 | <input type="checkbox"/>            |                                                                                                                           |
| Group              | 11 | <input type="checkbox"/>            |                                                                                                                           |
| Life-Safety-Point  | 21 | <input type="checkbox"/>            |                                                                                                                           |
| Life-Safety-Zone   | 22 | <input type="checkbox"/>            |                                                                                                                           |
| Loop               | 12 | <input type="checkbox"/>            |                                                                                                                           |
| Multistate-Input   | 13 | <input checked="" type="checkbox"/> | Mode_status<br>FanSpeed_status<br>AirDirectionUD_status<br>ErrorCodeM<br>RemoteControllerProhibit_status<br>Midea_setting |
| Multistate-Output  | 14 | <input checked="" type="checkbox"/> | Mode_command<br>FanSpeed_command<br>AirDirectionUD_command<br>RemoteControllerProhibit_command                            |
| Multistate-Value   | 19 | <input checked="" type="checkbox"/> | Occupancy<br>AC_IU_address                                                                                                |
| Notification-Class | 15 | <input type="checkbox"/>            |                                                                                                                           |
| Program            | 16 | <input type="checkbox"/>            |                                                                                                                           |
| Schedule           | 17 | <input type="checkbox"/>            |                                                                                                                           |
| Trend-Log          | 20 | <input type="checkbox"/>            |                                                                                                                           |

## 5.2 Member objects

### 5.2.1 Type: Gateway

| Object-name     | Description           | Object-type | Object-instance |
|-----------------|-----------------------|-------------|-----------------|
| INBACMID0011100 | Ductless AC Interface | Device      | 246000*         |

\* This is the default value.

### 5.2.2 Type: Indoor Unit

| Object-name                      | Description | Object-type | Object-instance |
|----------------------------------|-------------|-------------|-----------------|
| OnOff_status                     |             | BI          | 0               |
| OnOff_command                    |             | BO          | 0               |
| Mode_status                      |             | MI          | 0               |
| Mode_command                     |             | MO          | 0               |
| SetPoint_status                  |             | AI          | 0               |
| SetPoint_command                 |             | AO          | 0               |
| FanSpeed_status                  |             | MI          | 1               |
| FanSpeed_command                 |             | MO          | 1               |
| AirDirectionUD_status            |             | MI          | 2               |
| AirDirectionUD_command           |             | MO          | 2               |
| RoomTemperature_status           |             | AI          | 1               |
| RoomTemperature_command          |             | AO          | 1               |
| ErrorCode                        |             | AI          | 2               |
| ErrorCodeM                       |             | MI          | 4               |
| ErrorActive                      |             | BI          | 1               |
| OnTimeCounter                    |             | AV          | 0               |
| Occupancy                        |             | MV          | 0               |
| OccupiedCoolSetPoint             |             | AV          | 1               |
| OccupiedHeatSetPoint             |             | AV          | 2               |
| UnoccupiedCoolSetPoint           |             | AV          | 3               |
| UnoccupiedHeatSetPoint           |             | AV          | 4               |
| OccupancyContinuousCheck         |             | BV          | 0               |
| UnoccupiedDeadbandAction         |             | BV          | 1               |
| RemoteControllerProhibit_status  |             | MI          | 6               |
| RemoteControllerProhibit_command |             | MO          | 5               |
| DIP_SW_S1_status                 |             | AI          | 9               |
| DIP_SW_S2_status                 |             | AI          | 10              |
| SerialNumber                     |             | AI          | 11              |
| AC_IU_address                    |             | MV          | 1               |
| Midea_setting                    |             | MI          | 11              |

## 5.3 Objects and properties

### 5.3.1 Ductless AC Gateway (Device Object Type)

Below you can find relevant information about the properties of the object type.

**Object\_Identifier:** identifying the device in the BACnet MSTP network can be done automatically or manually:

- Automatic addressing. This is the device factory mode. Automatic addressing is based on using a base address of 246000 and adding to this number the address selected in SW2 P1...P7.
- Manual addressing. Device will switch into manual addressing mode once a value is received from BACnet side in this property. During manual addressing mode, SW2 P1...P7 address is not considered.

⚠ **Important:** If **Object\_Identifier** is overwritten from BACnet, SW2 configuration will not be considered for device instance calculation until a **Restore factory Settings** reset is performed.

**Object\_Name:** In the **Device Object**, is configurable writing directly on this property.

**Description:** In the **Device Object**, is configurable writing directly on the property, length maximum 63 chars.

| Property Identifier             | Property Datatype                        | Value                               | ASHRAE | IBOX |
|---------------------------------|------------------------------------------|-------------------------------------|--------|------|
| Object_Identifier               | BACnetObjectIdentifier                   | (Device, 246000*)                   | R      | W    |
| Object_Name                     | CharacterString                          | "INBACMID0011100"                   | R      | W    |
| Object_Type                     | BACnetObjectType                         | DEVICE (8) (Device Object Type)     | R      | R    |
| System_Status                   | BACnetDeviceStatus                       | OPERATIONAL (0)                     | R      | R    |
| Vendor_Name                     | CharacterString                          | "HMS Industrial Networks S.L.U"     | R      | R    |
| Vendor_Identifier               | Unsigned16                               | 246                                 | R      | R    |
| Model_Name                      | CharacterString                          | "INBACMID0011100"                   | R      | R    |
| Firmware_Revision               | CharacterString                          | "1.0.0.0"                           | R      | R    |
| Application_Software_Version    | CharacterString                          | "1.0.0.0"                           | R      | R    |
| Location                        | CharacterString                          | ""                                  | O      | -    |
| Description                     | CharacterString                          | "Ductless AC interface"             | O      | W    |
| Protocol_Version                | Unsigned                                 | 1                                   | R      | R    |
| Protocol_Revision               | Unsigned                                 | 12                                  | R      | R    |
| Protocol_Services_Supported     | BACnetServiceSupported                   | Refer to section 4 [Service Types]  | R      | R    |
| Protocol_Object_Types_Supported | BACnetObjectTypes Supported              | Refer to section 5.1 [Object Types] | R      | R    |
| Object_List                     | BACnetArray[N] of BACnetObjectIdentifier | BACnetARRAY[N]                      | R      | R    |
| Structured_Object_List          | BACnetArray[N] of BACnetObjectIdentifier | -                                   | O      | -    |
| Max_APDU_Length_Accepted        | Unsigned                                 | 480                                 | R      | R    |
| Segmentation_Supported          | BACnetSegmentation                       | SEGMENTED-BOTH (0)                  | R      | R    |
| Max_Segments_accepted           | Unsigned                                 | 16                                  | O      | R    |
| VT_Classes_Supported            | List of BACnetVTClass                    | -                                   | O      | -    |
| Active_VT_Sessions              | List of BACnetVTSession                  | -                                   | O      | -    |

| Property Identifier                 | Property Datatype                        | Value                         | ASHRAE | IBOX |
|-------------------------------------|------------------------------------------|-------------------------------|--------|------|
| Local_Date                          | Date                                     | -                             | O      | -    |
| Local_Time                          | Time                                     | -                             | O      | -    |
| UTC_Offset                          | INTEGER                                  | -                             | O      | -    |
| Daylight_Savings_Status             | BOOLEAN                                  | -                             | O      | -    |
| APDU_Segment_Timeout                | Unsigned                                 | 3000                          | R      | R    |
| APDU_Timeout                        | Unsigned                                 | 3000                          | R      | R    |
| Number_of_APDU_Retries              | Unsigned                                 | 3                             | R      | R    |
| List_Of_Session_Keys                | List of BACnetSessionKey                 | -                             | O      | -    |
| Time_Synchronization_Recipients     | List of BACnetRecipient                  | -                             | O      | -    |
| Max_Master                          | Unsigned                                 | 32                            | R      | W    |
| Max_Info_Frames                     | Unsigned                                 | 1                             | O      | R    |
| Device_Address_Binding              | List of BACnetAddressBinding             | NULL (empty)                  | R      | R    |
| Database_Revision                   | Unsigned                                 | 0                             | R      | R    |
| Configuration_Files                 | BACnetArray[N] of BACnetObjectIdentifier | -                             | O      | -    |
| Last_Restore_Time                   | BACnetTimeStamp                          | -                             | O      | -    |
| Backup_Failure_Timeout              | Unsigned16                               | -                             | O      | -    |
| Active_COV_Subscriptions            | List of BACnetCOVSubscription            | List of BACnetCOVSubscription | O      | R    |
| Slave_Proxy_Enable                  | BACnetArray[N] of BOOLEAN                | -                             | O      | -    |
| Manual_Slave_Address_Binding        | List of BACnetAddressBinding             | -                             | O      | -    |
| Auto_Slave_Discovery                | BACnetArray[N] of BOOLEAN                | -                             | O      | -    |
| Slave_Address_Binding               | BACnetAddressBinding                     | -                             | O      | -    |
| Last_Restart_Reason                 | BACnetRestartReason                      | -                             | O      | -    |
| Time_Of_Device_Restart              | BACnetTimeStamp                          | -                             | O      | -    |
| Restart_Notification_Recipients     | List of BACnetRecipient                  | -                             | O      | -    |
| UTC_Time_Synchronization_Recipients | List of BACnetRecipient                  | -                             | O      | -    |
| Time_Synchronization_Interval       | Unsigned                                 | -                             | O      | -    |
| Align_Intervals                     | BOOLEAN                                  | -                             | O      | -    |
| Interval_Offset                     | Unsigned                                 | -                             | O      | -    |
| Profile_Name                        | CharacterString                          | -                             | O      | -    |

\* This is the default value.

### 5.3.2 OnOff\_status (Binary Input Object Type)

It indicates if the indoor unit is in On or Off status.

| Property Identifier       | Property Datatype                    | Value                                          | ASHRAE | IBOX |
|---------------------------|--------------------------------------|------------------------------------------------|--------|------|
| Object_Identifier         | BACnetObjectIdentifier               | (Binary Input, 0)                              | R      | R    |
| Object_Name               | CharacterString                      | "OnOff_status"                                 | R      | R    |
| Object_Type               | BACnetObjectType                     | BINARY_INPUT (3)                               | R      | R    |
| Present_Value             | BACnetBinaryPV                       | INACTIVE (0) / ACTIVE (1)                      | R      | R    |
| Description               | CharacterString                      | -                                              | O      | -    |
| Device_Type               | CharacterString                      | -                                              | O      | -    |
| Status_Flags              | BACnetStatusFlags                    | {FALSE, FALSE/TRUE, FALSE, FALSE}              | R      | R    |
| Event_State               | BACnetEventState                     | STATE_NORMAL (0)                               | R      | R    |
| Reliability               | BACnetReliability                    | NO_FAULT_DETECTED (0),<br>UNRELIABLE_OTHER (7) | O      | R    |
| Out_Of_Service            | BOOLEAN                              | FALSE                                          | R      | R    |
| Polarity                  | BACnetPolarity                       | NORMAL (0)                                     | R      | R    |
| Inactive_Text             | CharacterString                      | "Off"                                          | O      | R    |
| Active_Text               | CharacterString                      | "On"                                           | O      | R    |
| Change_Of_State_Time      | BACnetDatetime                       | -                                              | O      | -    |
| Change_Of_State_Count     | Unsigned                             | -                                              | O      | -    |
| Time_Of_State_Count_Reset | BACnetDatetime                       | -                                              | O      | -    |
| Elapsed_Active_Time       | Unsigned                             | -                                              | O      | -    |
| Time_Of_Active_Time_Reset | BACnetDatetime                       | -                                              | O      | -    |
| Time_Delay                | Unsigned                             | -                                              | O      | -    |
| Notification_Class        | Unsigned                             | -                                              | O      | -    |
| Alarm_Value               | BACnetBinaryPV                       | -                                              | O      | -    |
| Event_Enable              | BACnetEventTransitionBits            | -                                              | O      | -    |
| Acked_Transitions         | BACnetEventTransitionBits            | -                                              | O      | -    |
| Notify_Type               | BACnetNotifyType                     | -                                              | O      | -    |
| Event_Time_Stamps         | BACnetArray[N] of<br>BACnetTimeStamp | -                                              | O      | -    |
| Profile_Name              | CharacterString                      | -                                              | O      | -    |

## 5.3.3 OnOff\_command (Binary Output Object Type)

It sets the indoor unit to On or Off.

| Property Identifier       | Property Datatype                 | Value                        | ASHRAE | IBOX |
|---------------------------|-----------------------------------|------------------------------|--------|------|
| Object_Identifier         | BACnetObjectIdentifier            | (Binary Output, 0)           | R      | R    |
| Object_Name               | CharacterString                   | "OnOff_command"              | R      | R    |
| Object_Type               | BACnetObjectType                  | BINARY_OUTPUT (4)            | R      | R    |
| Present_Value             | BACnetBinaryPV                    | INACTIVE (0) / ACTIVE (1)    | W      | W    |
| Description               | CharacterString                   | -                            | O      | -    |
| Device_Type               | CharacterString                   | -                            | O      | -    |
| Status_Flags              | BACnetStatusFlags                 | {FALSE, FALSE, FALSE, FALSE} | R      | R    |
| Event_State               | BACnetEventState                  | STATE_NORMAL (0)             | R      | R    |
| Reliability               | BACnetReliability                 | NO_FAULT_DETECTED (0)        | O      | R    |
| Out_Of_Service            | BOOLEAN                           | FALSE                        | R      | R    |
| Polarity                  | BACnetPolarity                    | NORMAL (0)                   | R      | R    |
| Inactive_Text             | CharacterString                   | "Off"                        | O      | R    |
| Active_Text               | CharacterString                   | "On"                         | O      | R    |
| Change_Of_State_Time      | BACnetDatetime                    | -                            | O      | -    |
| Change_Of_State_Count     | Unsigned                          | -                            | O      | -    |
| Time_Of_State_Count_Reset | BACnetDatetime                    | -                            | O      | -    |
| Elapsed_Active_Time       | Unsigned                          | -                            | O      | -    |
| Time_Of_Active_Time_Reset | BACnetDatetime                    | -                            | O      | -    |
| Minimum_Off_Time          | Unsigned32                        | -                            | O      | -    |
| Minimum_On_Time           | Unsigned32                        | -                            | O      | -    |
| Priority_Array            | BACnetPriorityArray               | BACnetPriorityArray          | R      | R    |
| Relinquish_Default        | BACnetBinaryPV                    | INACTIVE (0)                 | R      | R    |
| Time_Delay                | Unsigned                          | -                            | O      | -    |
| Notification_Class        | Unsigned                          | -                            | O      | -    |
| Feedback_Value            | BACnetBinaryPV                    | -                            | O      | -    |
| Event_Enable              | BACnetEventTransitionBits         | -                            | O      | -    |
| Acked_Transitions         | BACnetEventTransitionBits         | -                            | O      | -    |
| Notify_Type               | BACnetNotifyType                  | -                            | O      | -    |
| Event_Time_Stamps         | BACnetArray[N] of BACnetTimeStamp | -                            | O      | -    |
| Profile_Name              | CharacterString                   | -                            | O      | -    |

## 5.3.4 Mode\_status (Multistate Input Object Type)

It indicates the active mode for the indoor unit.

| Property Identifier | Property Datatype                    | Value                                          | ASHRAE | IBOX |
|---------------------|--------------------------------------|------------------------------------------------|--------|------|
| Object_Identifier   | BACnetObjectIdentifier               | (Multi-state Input, 0)                         | R      | R    |
| Object_Name         | CharacterString                      | "Mode_status"                                  | R      | R    |
| Object_Type         | BACnetObjectType                     | MULTISTATE_INPUT (13)                          | R      | R    |
| Present_Value       | Unsigned                             | 1 ~ 5                                          | R      | R    |
| Description         | CharacterString                      | -                                              | O      | -    |
| Device_Type         | CharacterString                      | -                                              | O      | -    |
| Status_Flags        | BACnetStatusFlags                    | {FALSE, FALSE/TRUE, FALSE, FALSE}              | R      | R    |
| Event_State         | BACnetEventState                     | STATE_NORMAL (0)                               | R      | R    |
| Reliability         | BACnetReliability                    | NO_FAULT_DETECTED (0),<br>UNRELIABLE_OTHER (7) | O      | R    |
| Out_Of_Service      | BOOLEAN                              | FALSE                                          | R      | R    |
| Number_Of_States    | Unsigned                             | 5                                              | R      | R    |
| State_Text          | BACnetArray[N] of<br>CharacterString | <i>Check Mode Status setting table below.</i>  | O      | R    |
| Time_Delay          | Unsigned                             | -                                              | O      | -    |
| Notification_Class  | Unsigned                             | -                                              | O      | -    |
| Alarm_Values        | List of Unsigned                     | -                                              | O      | -    |
| Fault_Values        | List of Unsigned                     | -                                              | O      | -    |
| Event_Enable        | BACnetEventTransitionBits            | -                                              | O      | -    |
| Acked_Transitions   | BACnetEventTransitionBits            | -                                              | O      | -    |
| Notify_Type         | BACnetNotifyType                     | -                                              | O      | -    |
| Event_Time_Stamps   | BACnetArray[N] of<br>BACnetTimeStamp | -                                              | O      | -    |
| Profile_Name        | CharacterString                      | -                                              | O      | -    |

### Mode status setting table

Mode status interpretation is possible using the value in the following correspondence table.

| Present_Value | Contents displayed in State_Text |
|---------------|----------------------------------|
| 1             | Heat                             |
| 2             | Cool                             |
| 3             | Fan                              |
| 4             | Dry                              |
| 5             | Auto                             |

## 5.3.5 Mode\_command (Multistate Output Object Type)

It allows control over the indoor unit's mode.

| Property Identifier | Property Datatype                 | Value                                         | ASHRAE | IBOX |
|---------------------|-----------------------------------|-----------------------------------------------|--------|------|
| Object_Identifier   | BACnetObjectIdentifier            | (Multi-state Output, 0)                       | R      | R    |
| Object_Name         | CharacterString                   | "Mode_command"                                | R      | R    |
| Object_Type         | BACnetObjectType                  | MULTISTATE_OUTPUT (14)                        | R      | R    |
| Present_Value       | Unsigned                          | 1 ~ 5                                         | W      | W    |
| Description         | CharacterString                   | -                                             | O      | -    |
| Device_Type         | CharacterString                   | -                                             | O      | -    |
| Status_Flags        | BACnetStatusFlags                 | {FALSE, FALSE, FALSE, FALSE}                  | R      | R    |
| Event_State         | BACnetEventState                  | STATE_NORMAL (0)                              | R      | R    |
| Reliability         | BACnetReliability                 | NO_FAULT_DETECTED (0)                         | O      | R    |
| Out_Of_Service      | BOOLEAN                           | FALSE                                         | R      | R    |
| Number_Of_States    | Unsigned                          | 5                                             | R      | R    |
| State_Text          | BACnetArray[N] of CharacterString | Check <b>Mode Command setting table</b> below | O      | R    |
| Priority_Array      | BACnetPriorityArray               | BACnetPriorityArray                           | R      | R    |
| Relinquish_Default  | Unsigned                          | 1                                             | R      | R    |
| Time_Delay          | Unsigned                          | -                                             | O      | -    |
| Notification_Class  | Unsigned                          | -                                             | O      | -    |
| Feedback_Value      | Unsigned                          | -                                             | O      | -    |
| Event_Enable        | BACnetEventTransitionBits         | -                                             | O      | -    |
| Acked_Transitions   | BACnetEventTransitionBits         | -                                             | O      | -    |
| Notify_Type         | BACnetNotifyType                  | -                                             | O      | -    |
| Event_Time_Stamps   | BACnetArray[N] of BACnetTimeStamp | -                                             | O      | -    |
| Profile_Name        | CharacterString                   | -                                             | O      | -    |

### Mode Command setting table

Mode commands can be set using the values in the following correspondence table.

| Present_Value | Contents displayed in State_Text |
|---------------|----------------------------------|
| 1             | Heat                             |
| 2             | Cool                             |
| 3             | Fan                              |
| 4             | Dry                              |
| 5             | Auto                             |

## 5.3.6 Setpoint\_status (Analog Input Object Type)

It indicates the current setpoint temperature in the indoor unit.

| Property Identifier | Property Datatype                    | Value                                            | ASHRAE | IBOX |
|---------------------|--------------------------------------|--------------------------------------------------|--------|------|
| Object_Identifier   | BACnetObjectIdentifier               | (Analog Input, 0)                                | R      | R    |
| Object_Name         | CharacterString                      | "SetPoint_status"                                | R      | R    |
| Object_Type         | BACnetObjectType                     | ANALOG_INPUT (0)                                 | R      | R    |
| Present_Value*      | REAL                                 | 16...32 °C // 61...90 °F                         | R      | R    |
| Description         | CharacterString                      | -                                                | O      | -    |
| Device_Type         | CharacterString                      | -                                                | O      | -    |
| Status_Flags        | BACnetStatusFlags                    | {FALSE, FALSE/TRUE, FALSE, FALSE}                | R      | R    |
| Event_State         | BACnetEventState                     | STATE_NORMAL (0)                                 | R      | R    |
| Reliability         | BACnetReliability                    | NO_FAULT_DETECTED (0),<br>UNRELIABLE_OTHER (7)   | O      | R    |
| Out_Of_Service      | BOOLEAN                              | FALSE                                            | R      | R    |
| Update_Interval     | Unsigned                             | -                                                | O      | -    |
| Units *             | BACnetEngineeringUnits               | Degrees Celsius (62),<br>Degrees Fahrenheit (64) | R      | R    |
| Min_Pres_Value *    | REAL                                 | 16°C / 61 °F                                     | O      | R    |
| Max_Pres_Value *    | REAL                                 | 32°C / 90°F                                      | O      | R    |
| Resolution          | REAL                                 | -                                                | O      | -    |
| COV_Increment       | REAL                                 | 0                                                | O      | W    |
| Time_Delay          | Unsigned                             | -                                                | O      | -    |
| Notification_Class  | Unsigned                             | -                                                | O      | -    |
| High_Limit          | REAL                                 | -                                                | O      | -    |
| Low_Limit           | REAL                                 | -                                                | O      | -    |
| Deadband            | REAL                                 | -                                                | O      | -    |
| Limit_Enable        | BACnetLimitEnable                    | -                                                | O      | -    |
| Event_Enable        | BACnetEventTransitionBits            | -                                                | O      | -    |
| Acked_Transitions   | BACnetEventTransitionBits            | -                                                | O      | -    |
| Notify_Type         | BACnetNotifyType                     | -                                                | O      | -    |
| Event_Time_Stamps   | BACnetArray[N] of<br>BACnetTimeStamp | -                                                | O      | -    |
| Profile_Name        | CharacterString                      | -                                                | O      | -    |

\* Use of Celsius or Fahrenheit units can be selected through the switch configuration. Check section 6.1 for more information.

### 5.3.7 Setpoint\_command (Analog Output Object Type)

It sets the desired temperature in the indoor unit.

| Property Identifier | Property Datatype                    | Value                                            | ASHRAE | IBOX |
|---------------------|--------------------------------------|--------------------------------------------------|--------|------|
| Object_Identifier   | BACnetObjectIdentifier               | (Analog Output, 0)                               | R      | R    |
| Object_Name         | CharacterString                      | "SetPoint_command"                               | R      | R    |
| Object_Type         | BACnetObjectType                     | ANALOG_OUTPUT (1)                                | R      | R    |
| Present_Value *     | REAL                                 | 16...32 °C // 61...90 °F                         | R      | R    |
| Description         | CharacterString                      | -                                                | O      | -    |
| Device_Type         | CharacterString                      | -                                                | O      | -    |
| Status_Flags        | BACnetStatusFlags                    | {FALSE, FALSE, FALSE, FALSE}                     | R      | R    |
| Event_State         | BACnetEventState                     | STATE_NORMAL (0)                                 | R      | R    |
| Reliability         | BACnetReliability                    | NO_FAULT_DETECTED (0)                            | O      | R    |
| Out_Of_Service      | BOOLEAN                              | FALSE                                            | R      | R    |
| Update_Interval     | Unsigned                             | -                                                | O      | -    |
| Units *             | BACnetEngineeringUnits               | Degrees Celsius (62),<br>Degrees Fahrenheit (64) | R      | R    |
| Min_Pres_Value      | REAL                                 | 16°C / 61 °F                                     | O      | R    |
| Max_Pres_Value      | REAL                                 | 32°C / 90°F                                      | O      | R    |
| Resolution          | REAL                                 | -                                                | O      | -    |
| COV_Increment       | REAL                                 | 0                                                | O      | W    |
| Priority_Array      | BACnetPriorityArray                  | BACnetPriorityArray                              | R      | R    |
| Relinquish_Default  | Unsigned                             | 22                                               | R      | R    |
| Time_Delay          | Unsigned                             | -                                                | O      | -    |
| Notification_Class  | Unsigned                             | -                                                | O      | -    |
| High_Limit          | REAL                                 | -                                                | O      | -    |
| Low_Limit           | REAL                                 | -                                                | O      | -    |
| Deadband            | REAL                                 | -                                                | O      | -    |
| Limit_Enable        | BACnetLimitEnable                    | -                                                | O      | -    |
| Event_Enable        | BACnetEventTransitionBits            | -                                                | O      | -    |
| Acked_Transitions   | BACnetEventTransitionBits            | -                                                | O      | -    |
| Notify_Type         | BACnetNotifyType                     | -                                                | O      | -    |
| Event_Time_Stamps   | BACnetArray[N] of<br>BACnetTimeStamp | -                                                | O      | -    |
| Profile_Name        | CharacterString                      | -                                                | O      | -    |

\* Use of Celsius or Fahrenheit units can be selected through the switch configuration. Check section 6.1 for more information.

### 5.3.8 FanSpeed\_status (Multistate Input Object Type)

It indicates the fan speed status of the indoor unit.

| Property Identifier | Property Datatype                    | Value                                                  | ASHRAE | IBOX |
|---------------------|--------------------------------------|--------------------------------------------------------|--------|------|
| Object_Identifier   | BACnetObjectIdentifier               | (Multi-state Input, 1)                                 | R      | R    |
| Object_Name         | CharacterString                      | "FanSpeed_status"                                      | R      | R    |
| Object_Type         | BACnetObjectType                     | MULTISTATE_INPUT (13)                                  | R      | R    |
| Present_Value       | Unsigned                             | 1 ~ 4                                                  | R      | R    |
| Description         | CharacterString                      | -                                                      | O      | -    |
| Device_Type         | CharacterString                      | -                                                      | O      | -    |
| Status_Flags        | BACnetStatusFlags                    | {FALSE, FALSE/TRUE, FALSE, FALSE}                      | R      | R    |
| Event_State         | BACnetEventState                     | STATE_NORMAL (0)                                       | R      | R    |
| Reliability         | BACnetReliability                    | NO_FAULT_DETECTED (0),<br>UNRELIABLE_OTHER (7)         | O      | R    |
| Out_Of_Service      | BOOLEAN                              | FALSE/TRUE                                             | R      | R    |
| Number_Of_States    | Unsigned                             | 4                                                      | R      | R    |
| State_Text          | BACnetArray[N] of<br>CharacterString | <i>Check Fan Speed status setting table<br/>below.</i> | O      | R    |
| Time_Delay          | Unsigned                             | -                                                      | O      | -    |
| Notification_Class  | Unsigned                             | -                                                      | O      | -    |
| Alarm_Values        | List of Unsigned                     | -                                                      | O      | -    |
| Fault_Values        | List of Unsigned                     | -                                                      | O      | -    |
| Event_Enable        | BACnetEventTransitionBits            | -                                                      | O      | -    |
| Acked_Transitions   | BACnetEventTransitionBits            | -                                                      | O      | -    |
| Notify_Type         | BACnetNotifyType                     | -                                                      | O      | -    |
| Event_Time_Stamps   | BACnetArray[N] of<br>BACnetTimeStamp | -                                                      | O      | -    |
| Profile_Name        | CharacterString                      | -                                                      | O      | -    |

#### Fan Speed status setting table

Fan speed interpretation is possible using the value in the following correspondence table.

| Present_Value | Contents displayed in State_Text |
|---------------|----------------------------------|
| 1             | Auto                             |
| 2             | Fan Speed 1                      |
| 3             | Fan Speed 2                      |
| 4             | Fan Speed 3                      |

## 5.3.9 FanSpeed\_command (Multistate Output Object Type)

It allows control over the fan speed for the indoor unit.

| Property Identifier | Property Datatype                 | Value                                              | ASHRAE | IBOX |
|---------------------|-----------------------------------|----------------------------------------------------|--------|------|
| Object_Identifier   | BACnetObjectIdentifier            | (Multi-state Output, 1)                            | R      | R    |
| Object_Name         | CharacterString                   | "FanSpeed_command"                                 | R      | R    |
| Object_Type         | BACnetObjectType                  | MULTISTATE_OUTPUT (14)                             | R      | R    |
| Present_Value       | Unsigned                          | 1 ~ 4                                              | W      | W    |
| Description         | CharacterString                   | -                                                  | O      | -    |
| Device_Type         | CharacterString                   | -                                                  | O      | -    |
| Status_Flags        | BACnetStatusFlags                 | {FALSE, FALSE, FALSE, FALSE}                       | R      | R    |
| Event_State         | BACnetEventState                  | STATE_NORMAL (0)                                   | R      | R    |
| Reliability         | BACnetReliability                 | NO_FAULT_DETECTED (0)                              | O      | R    |
| Out_Of_Service      | BOOLEAN                           | FALSE                                              | R      | R    |
| Number_Of_States    | Unsigned                          | 4                                                  | R      | R    |
| State_Text          | BACnetArray[N] of CharacterString | <i>Check Fan Speed command setting table below</i> | O      | R    |
| Priority_Array      | BACnetPriorityArray               | BACnetPriorityArray                                | R      | R    |
| Relinquish_Default  | Unsigned                          | 1                                                  | R      | R    |
| Time_Delay          | Unsigned                          | -                                                  | O      | -    |
| Notification_Class  | Unsigned                          | -                                                  | O      | -    |
| Feedback_Value      | Unsigned                          | -                                                  | O      | -    |
| Event_Enable        | BACnetEventTransitionBits         | -                                                  | O      | -    |
| Acked_Transitions   | BACnetEventTransitionBits         | -                                                  | O      | -    |
| Notify_Type         | BACnetNotifyType                  | -                                                  | O      | -    |
| Event_Time_Stamps   | BACnetArray[N] of BACnetTimeStamp | -                                                  | O      | -    |
| Profile_Name        | CharacterString                   | -                                                  | O      | -    |

### Fan Speed command setting table

Fan speed interpretation is possible using the value in the following correspondence table.

| Present_Value | Contents displayed in State_Text |
|---------------|----------------------------------|
| 1             | Auto                             |
| 2             | Fan Speed 1                      |
| 3             | Fan Speed 2                      |
| 4             | Fan Speed 3                      |

**5.3.10 AirDirectionUD\_status (Multistate Input Object Type)**

It indicates the status of the vertical vane (Up/Down) for the indoor unit.

| Property Identifier | Property Datatype                    | Value                                                      | ASHRAE | IBOX |
|---------------------|--------------------------------------|------------------------------------------------------------|--------|------|
| Object_Identifier   | BACnetObjectIdentifier               | (Multi-state Input, 2)                                     | R      | R    |
| Object_Name         | CharacterString                      | "AirDirectionUD_status"                                    | R      | R    |
| Object_Type         | BACnetObjectType                     | MULTISTATE_INPUT(13)                                       | R      | R    |
| Present_Value       | Unsigned                             | 1 ~ 2                                                      | R      | R    |
| Description         | CharacterString                      | -                                                          | O      | -    |
| Device_Type         | CharacterString                      | -                                                          | O      | -    |
| Status_Flags        | BACnetStatusFlags                    | {FALSE, FALSE/TRUE, FALSE, FALSE}                          | R      | R    |
| Event_State         | BACnetEventState                     | STATE_NORMAL (0)                                           | R      | R    |
| Reliability         | BACnetReliability                    | NO_FAULT_DETECTED (0),<br>UNRELIABLE_OTHER (7)             | O      | R    |
| Out_Of_Service      | BOOLEAN                              | FALSE/TRUE                                                 | R      | R    |
| Number_Of_States    | Unsigned                             | 2                                                          | R      | R    |
| State_Text          | BACnetArray[N] of<br>CharacterString | <i>Check Air Direction Status setting table<br/>below.</i> | O      | R    |
| Time_Delay          | Unsigned                             | -                                                          | O      | -    |
| Notification_Class  | Unsigned                             | -                                                          | O      | -    |
| Alarm_Values        | List of Unsigned                     | -                                                          | O      | -    |
| Fault_Values        | List of Unsigned                     | -                                                          | O      | -    |
| Event_Enable        | BACnetEventTransitionBits            | -                                                          | O      | -    |
| Acked_Transitions   | BACnetEventTransitionBits            | -                                                          | O      | -    |
| Notify_Type         | BACnetNotifyType                     | -                                                          | O      | -    |
| Event_Time_Stamps   | BACnetArray[N] of<br>BACnetTimeStamp | -                                                          | O      | -    |
| Profile_Name        | CharacterString                      | -                                                          | O      | -    |

**Air direction Up/Down status setting table**

Air direction interpretation is possible using the value in the following correspondence table.

| Present_Value | Contents displayed in State_Text |
|---------------|----------------------------------|
| 1             | Stop                             |
| 2             | Swing                            |

**5.3.11 AirDirectionUD\_command (Multistate Output Object Type)**

It allows control over the vertical air direction (Up/Down) for the indoor unit.

| Property Identifier | Property Datatype                 | Value                                                  | ASHRAE | IBOX |
|---------------------|-----------------------------------|--------------------------------------------------------|--------|------|
| Object_Identifier   | BACnetObjectIdentifier            | (Multi-state Output, 2)                                | R      | R    |
| Object_Name         | CharacterString                   | "AirDirectionUD_command"                               | R      | R    |
| Object_Type         | BACnetObjectType                  | MULTISTATE_OUTPUT (14)                                 | R      | R    |
| Present_Value       | Unsigned                          | 1 ~ 2                                                  | W      | W    |
| Description         | CharacterString                   | -                                                      | O      | -    |
| Device_Type         | CharacterString                   | -                                                      | O      | -    |
| Status_Flags        | BACnetStatusFlags                 | {FALSE, FALSE, FALSE, FALSE}                           | R      | R    |
| Event_State         | BACnetEventState                  | STATE_NORMAL (0)                                       | R      | R    |
| Reliability         | BACnetReliability                 | NO_FAULT_DETECTED (0)                                  | O      | R    |
| Out_Of_Service      | BOOLEAN                           | FALSE                                                  | R      | R    |
| Number_Of_States    | Unsigned                          | 2                                                      | R      | R    |
| State_Text          | BACnetArray[N] of CharacterString | <i>Check Air Direction Command setting table below</i> | O      | R    |
| Priority_Array      | BACnetPriorityArray               | -                                                      | R      | R    |
| Relinquish_Default  | Unsigned                          | -                                                      | R      | R    |
| Time_Delay          | Unsigned                          | -                                                      | O      | -    |
| Notification_Class  | Unsigned                          | -                                                      | O      | -    |
| Feedback_Value      | Unsigned                          | -                                                      | O      | -    |
| Event_Enable        | BACnetEventTransitionBits         | -                                                      | O      | -    |
| Acked_Transitions   | BACnetEventTransitionBits         | -                                                      | O      | -    |
| Notify_Type         | BACnetNotifyType                  | -                                                      | O      | -    |
| Event_Time_Stamps   | BACnetArray[N] of BACnetTimeStamp | -                                                      | O      | -    |
| Profile_Name        | CharacterString                   | -                                                      | O      | -    |

**Air direction Up/Down Command setting table**

Air direction commands can be set using the values in the following correspondence table.

| Present_Value | Contents displayed in State_Text |
|---------------|----------------------------------|
| 1             | Stop                             |
| 2             | Swing                            |

## 5.3.12 RoomTemperature\_status (Analog Input Object Type)

It indicates the room temperature from the sensor in the indoor unit.

| Property Identifier | Property Datatype                    | Value                                           | ASHRAE | IBOX |
|---------------------|--------------------------------------|-------------------------------------------------|--------|------|
| Object_Identifier   | BACnetObjectIdentifier               | (Analog Input, 1)                               | R      | R    |
| Object_Name         | CharacterString                      | "RoomTemperature_status"                        | R      | R    |
| Object_Type         | BACnetObjectType                     | ANALOG_INPUT (0)                                | R      | R    |
| Present_Value       | REAL                                 | -20...100°C // -4...212 °F                      | R      | R    |
| Description         | CharacterString                      | -                                               | O      | -    |
| Device_Type         | CharacterString                      | -                                               | O      | -    |
| Status_Flags        | BACnetStatusFlags                    | {FALSE, FALSE/TRUE, FALSE, FALSE}               | R      | R    |
| Event_State         | BACnetEventState                     | STATE_NORMAL (0)                                | R      | R    |
| Reliability         | BACnetReliability                    | NO_FAULT_DETECTED (0),<br>UNRELIABLE_OTHER (7)  | O      | R    |
| Out_Of_Service      | BOOLEAN                              | FALSE/TRUE                                      | R      | R    |
| Update_Interval     | Unsigned                             | -                                               | O      | -    |
| Units               | BACnetEngineeringUnits               | Degrees Celsius (62)<br>Degrees Fahrenheit (64) | R      | R    |
| Min_Pres_Value      | REAL                                 | -20°C / -4°F                                    | O      | -    |
| Max_Pres_Value      | REAL                                 | 100°C / 212°F                                   | O      | -    |
| Resolution          | REAL                                 | -                                               | O      | -    |
| COV_Increment       | REAL                                 | 0                                               | O      | W    |
| Time_Delay          | Unsigned                             | -                                               | O      | -    |
| Notification_Class  | Unsigned                             | -                                               | O      | -    |
| High_Limit          | REAL                                 | -                                               | O      | -    |
| Low_Limit           | REAL                                 | -                                               | O      | -    |
| Deadband            | REAL                                 | -                                               | O      | -    |
| Limit_Enable        | BACnetLimitEnable                    | -                                               | O      | -    |
| Event_Enable        | BACnetEventTransitionBits            | -                                               | O      | -    |
| Acked_Transitions   | BACnetEventTransitionBits            | -                                               | O      | -    |
| Notify_Type         | BACnetNotifyType                     | -                                               | O      | -    |
| Event_Time_Stamps   | BACnetArray[N] of<br>BACnetTimeStamp | -                                               | O      | -    |
| Profile_Name        | CharacterString                      | -                                               | O      | -    |

### 5.3.13 RoomTemperature\_command (Analog Output Object Type)

It sets the desired temperature in the indoor unit.

| Property Identifier | Property Datatype                    | Value                                            | ASHRAE | IBOX |
|---------------------|--------------------------------------|--------------------------------------------------|--------|------|
| Object_Identifier   | BACnetObjectIdentifier               | (Analog Output, 1)                               | R      | R    |
| Object_Name         | CharacterString                      | "RoomTemperature_command"                        | R      | R    |
| Object_Type         | BACnetObjectType                     | ANALOG_OUTPUT (1)                                | R      | R    |
| Present_Value *     | REAL                                 | -20...100°C // -4...212 °F                       | R      | R    |
| Description         | CharacterString                      | -                                                | O      | -    |
| Device_Type         | CharacterString                      | -                                                | O      | -    |
| Status_Flags        | BACnetStatusFlags                    | {FALSE, FALSE, FALSE, FALSE}                     | R      | R    |
| Event_State         | BACnetEventState                     | STATE_NORMAL (0)                                 | R      | R    |
| Reliability         | BACnetReliability                    | NO_FAULT_DETECTED (0)                            | O      | R    |
| Out_Of_Service      | BOOLEAN                              | FALSE                                            | R      | R    |
| Update_Interval     | Unsigned                             | -                                                | O      | -    |
| Units *             | BACnetEngineeringUnits               | Degrees Celsius (62),<br>Degrees Fahrenheit (64) | R      | R    |
| Min_Pres_Value      | REAL                                 | -20°C / -4°F                                     | O      | R    |
| Max_Pres_Value      | REAL                                 | 100°C / 212°F                                    | O      | R    |
| Resolution          | REAL                                 | -                                                | O      | -    |
| COV_Increment       | REAL                                 | 0                                                | O      | W    |
| Priority_Array      | BACnetPriorityArray                  | BACnetPriorityArray                              | R      | R    |
| Relinquish_Default  | Unsigned                             | 22                                               | R      | R    |
| Time_Delay          | Unsigned                             | -                                                | O      | -    |
| Notification_Class  | Unsigned                             | -                                                | O      | -    |
| High_Limit          | REAL                                 | -                                                | O      | -    |
| Low_Limit           | REAL                                 | -                                                | O      | -    |
| Deadband            | REAL                                 | -                                                | O      | -    |
| Limit_Enable        | BACnetLimitEnable                    | -                                                | O      | -    |
| Event_Enable        | BACnetEventTransitionBits            | -                                                | O      | -    |
| Acked_Transitions   | BACnetEventTransitionBits            | -                                                | O      | -    |
| Notify_Type         | BACnetNotifyType                     | -                                                | O      | -    |
| Event_Time_Stamps   | BACnetArray[N] of<br>BACnetTimeStamp | -                                                | O      | -    |
| Profile_Name        | CharacterString                      | -                                                | O      | -    |

\* Use of Celsius or Fahrenheits units can be selected throught the switch configuration. Check section 6.1 for more information.

### 5.3.14 ErrorCode (Analog Input Object Type)

It indicates the current error present in the AC system.

| Property Identifier | Property Datatype                 | Value                        | ASHRAE | IBOX |
|---------------------|-----------------------------------|------------------------------|--------|------|
| Object_Identifier   | BACnetObjectIdentifier            | (Analog Input, 2)            | R      | R    |
| Object_Name         | CharacterString                   | "ErrorCode"                  | R      | R    |
| Object_Type         | BACnetObjectType                  | ANALOG_INPUT (0)             | R      | R    |
| Present_Value       | REAL                              | -1... 6846                   | R      | R    |
| Description         | CharacterString                   | -                            | O      | -    |
| Device_Type         | CharacterString                   | -                            | O      | -    |
| Status_Flags        | BACnetStatusFlags                 | {FALSE, FALSE, FALSE, FALSE} | R      | R    |
| Event_State         | BACnetEventState                  | STATE_NORMAL (0)             | R      | R    |
| Reliability         | BACnetReliability                 | NO_FAULT_DETECTED (0)        | O      | R    |
| Out_Of_Service      | BOOLEAN                           | FALSE                        | R      | R    |
| Update_Interval     | Unsigned                          | 300                          | O      | -    |
| Units               | BACnetEngineeringUnits            | NO_UNITS (95)                | R      | R    |
| Min_Pres_Value      | REAL                              | -                            | O      | -    |
| Max_Pres_Value      | REAL                              | -                            | O      | -    |
| Resolution          | REAL                              | -                            | O      | -    |
| COV_Increment       | REAL                              | 0                            | O      | W    |
| Time_Delay          | Unsigned                          | -                            | O      | -    |
| Notification_Class  | Unsigned                          | -                            | O      | -    |
| High_Limit          | REAL                              | -                            | O      | -    |
| Low_Limit           | REAL                              | -                            | O      | -    |
| Deadband            | REAL                              | -                            | O      | -    |
| Limit_Enable        | BACnetLimitEnable                 | -                            | O      | -    |
| Event_Enable        | BACnetEventTransitionBits         | -                            | O      | -    |
| Acked_Transitions   | BACnetEventTransitionBits         | -                            | O      | -    |
| Notify_Type         | BACnetNotifyType                  | -                            | O      | -    |
| Event_Time_Stamps   | BACnetArray[N] of BACnetTimeStamp | -                            | O      | -    |
| Profile_Name        | CharacterString                   | -                            | O      | -    |

## 5.3.15 ErrorCodeM (Multistate Input Object Type)

It indicates the current error present in the AC system.

| Property Identifier | Property Datatype                 | Value                                | ASHRAE | IBOX |
|---------------------|-----------------------------------|--------------------------------------|--------|------|
| Object_Identifier   | BACnetObjectIdentifier            | (Multi-state Input, 4)               | R      | R    |
| Object_Name         | CharacterString                   | "ErrorCodeM"                         | R      | R    |
| Object_Type         | BACnetObjectType                  | MULTISTATE_INPUT(13)                 | R      | R    |
| Present_Value       | Unsigned                          | 1 ~ 34                               | R      | R    |
| Description         | CharacterString                   | -                                    | O      | -    |
| Device_Type         | CharacterString                   | -                                    | O      | -    |
| Status_Flags        | BACnetStatusFlags                 | {FALSE, FALSE, FALSE, FALSE}         | R      | R    |
| Event_State         | BACnetEventState                  | STATE_NORMAL (0)                     | R      | R    |
| Reliability         | BACnetReliability                 | NO_FAULT_DETECTED (0)                | O      | R    |
| Out_Of_Service      | BOOLEAN                           | FALSE                                | R      | R    |
| Number_Of_States    | Unsigned                          | 34                                   | R      | R    |
| State_Text          | BACnetArray[N] of CharacterString | <i>Check Error Code table below.</i> | O      | R    |
| Time_Delay          | Unsigned                          | -                                    | O      | -    |
| Notification_Class  | Unsigned                          | -                                    | O      | -    |
| Alarm_Values        | List of Unsigned                  | -                                    | O      | -    |
| Fault_Values        | List of Unsigned                  | -                                    | O      | -    |
| Event_Enable        | BACnetEventTransitionBits         | -                                    | O      | -    |
| Acked_Transitions   | BACnetEventTransitionBits         | -                                    | O      | -    |
| Notify_Type         | BACnetNotifyType                  | -                                    | O      | -    |
| Event_Time_Stamps   | BACnetArray[N] of BACnetTimeStamp | -                                    | O      | -    |
| Profile_Name        | CharacterString                   | -                                    | O      | -    |

## Error Code table

In the table below you will find the error correspondence value.

| Pesent_Value | State_Text | Pesent_Value | State_Text |
|--------------|------------|--------------|------------|
| 1            | -          | 19           | P1         |
| 2            | CommError  | 20           | P2         |
| 3            | E0         | 21           | P3         |
| 4            | E1         | 22           | P4         |
| 5            | E2         | 23           | P5         |
| 6            | E3         | 24           | P6         |
| 7            | E4         | 25           | P7         |
| 8            | E5         | 26           | P8         |
| 9            | E6         | 27           | P9         |
| 10           | E7         | 28           | PA         |
| 11           | E8         | 29           | PB         |
| 12           | E9         | 30           | PC         |
| 13           | EA         | 31           | PD         |
| 14           | EB         | 32           | PE         |
| 15           | EC         | 33           | PF         |
| 16           | ED         |              |            |
| 17           | EE         |              |            |
| 18           | EF         |              |            |

## 5.3.16 ErrorActive (Binary Input Object Type)

It indicates if there is an error active in the indoor unit.

| Property Identifier       | Property Datatype                 | Value                        | ASHRAE | IBOX |
|---------------------------|-----------------------------------|------------------------------|--------|------|
| Object_Identifier         | BACnetObjectIdentifier            | (Binary Input, 1)            | R      | R    |
| Object_Name               | CharacterString                   | "ErrorActive"                | R      | R    |
| Object_Type               | BACnetObjectType                  | BINARY_INPUT (3)             | R      | R    |
| Present_Value             | BACnetBinaryPV                    | INACTIVE (0) / ACTIVE (1)    | R      | R    |
| Description               | CharacterString                   | -                            | O      | -    |
| Device_Type               | CharacterString                   | -                            | O      | -    |
| Status_Flags              | BACnetStatusFlags                 | {FALSE, FALSE, FALSE, FALSE} | R      | R    |
| Event_State               | BACnetEventState                  | STATE_NORMAL (0)             | R      | R    |
| Reliability               | BACnetReliability                 | NO_FAULT_DETECTED (0)        | O      | R    |
| Out_Of_Service            | BOOLEAN                           | FALSE                        | R      | R    |
| Polarity                  | BACnetPolarity                    | NORMAL (0)                   | R      | R    |
| Inactive_Text             | CharacterString                   | "No"                         | O      | R    |
| Active_Text               | CharacterString                   | "Error"                      | O      | R    |
| Change_Of_State_Time      | BACnetDatetime                    | -                            | O      | -    |
| Change_Of_State_Count     | Unsigned                          | -                            | O      | -    |
| Time_Of_State_Count_Reset | BACnetDatetime                    | -                            | O      | -    |
| Elapsed_Active_Time       | Unsigned                          | -                            | O      | -    |
| Time_Of_Active_Time_Reset | BACnetDatetime                    | -                            | O      | -    |
| Time_Delay                | Unsigned                          | -                            | O      | -    |
| Notification_Class        | Unsigned                          | -                            | O      | -    |
| Alarm_Value               | BACnetBinaryPV                    | -                            | O      | -    |
| Event_Enable              | BACnetEventTransitionBits         | -                            | O      | -    |
| Acked_Transitions         | BACnetEventTransitionBits         | -                            | O      | -    |
| Notify_Type               | BACnetNotifyType                  | -                            | O      | -    |
| Event_Time_Stamps         | BACnetArray[N] of BACnetTimeStamp | -                            | O      | -    |
| Profile_Name              | CharacterString                   | -                            | O      | -    |

### 5.3.17 OnTimeCounter (Analog Value Object Type)

It indicates the current Setpoint when Cool mode is selected and Occupancy is enabled.

| Property Identifier | Property Datatype                 | Value                        | ASHRAE | IBOX |
|---------------------|-----------------------------------|------------------------------|--------|------|
| Object_Identifier   | BACnetObjectIdentifier            | (Analog Value, 0)            | R      | R    |
| Object_Name         | CharacterString                   | "OnTimeCounter"              | R      | R    |
| Object_Type         | BACnetObjectType                  | ANALOG_VALUE (2)             | R      | R    |
| Present_Value       | REAL                              | 0 .. 65535                   | R      | R    |
| Description         | CharacterString                   | -                            | O      | -    |
| Status_Flags        | BACnetStatusFlags                 | {FALSE, FALSE, FALSE, FALSE} | R      | R    |
| Event_State         | BACnetEventState                  | STATE_NORMAL (0)             | R      | R    |
| Reliability         | BACnetReliability                 | NO_FAULT_DETECTED (0)        | O      | R    |
| Out_Of_Service      | BOOLEAN                           | FALSE                        | R      | R    |
| Update_Interval     | Unsigned                          | -                            | O      | -    |
| Units               | BACnetEngineeringUnits            | Hours (71)                   | R      | R    |
| Min_Pres_Value      | REAL                              | -                            | O      | -    |
| Max_Pres_Value      | REAL                              | -                            | O      | -    |
| Resolution          | REAL                              | -                            | O      | -    |
| COV_Increment       | REAL                              | 0                            | O      | W    |
| Time_Delay          | Unsigned                          | -                            | O      | -    |
| Notification_Class  | Unsigned                          | -                            | O      | -    |
| High_Limit          | REAL                              | -                            | O      | -    |
| Low_Limit           | REAL                              | -                            | O      | -    |
| Deadband            | REAL                              | -                            | O      | -    |
| Limit_Enable        | BACnetLimitEnable                 | -                            | O      | -    |
| Event_Enable        | BACnetEventTransitionBits         | -                            | O      | -    |
| Acked_Transitions   | BACnetEventTransitionBits         | -                            | O      | -    |
| Notify_Type         | BACnetNotifyType                  | -                            | O      | -    |
| Event_Time_Stamps   | BACnetArray[N] of BACnetTimeStamp | -                            | O      | -    |
| Profile_Name        | CharacterString                   | -                            | O      | -    |

## 5.3.18 Occupancy (Multistate Value Object Type)

It indicates the use or not of the occupancy function.

| Property Identifier | Property Datatype                 | Value                                      | ASHRAE | IBOX |
|---------------------|-----------------------------------|--------------------------------------------|--------|------|
| Object_Identifier   | BACnetObjectIdentifier            | (Multi-state Output, 0)                    | R      | R    |
| Object_Name         | CharacterString                   | "Occupancy"                                | R      | R    |
| Object_Type         | BACnetObjectType                  | MULTISTATE_VALUE (19)                      | R      | R    |
| Present_Value       | Unsigned                          | 1 ~ 3                                      | W      | W    |
| Description         | CharacterString                   | -                                          | O      | -    |
| Status_Flags        | BACnetStatusFlags                 | {FALSE, FALSE, FALSE, FALSE}               | R      | R    |
| Event_State         | BACnetEventState                  | STATE_NORMAL (0)                           | R      | R    |
| Reliability         | BACnetReliability                 | NO_FAULT_DETECTED (0)                      | O      | R    |
| Out_Of_Service      | BOOLEAN                           | FALSE                                      | R      | R    |
| Number_Of_States    | Unsigned                          | 3                                          | R      | R    |
| State_Text          | BACnetArray[N] of CharacterString | <i>Check Occupancy setting table below</i> | O      | R    |
| Priority_Array      | BACnetPriorityArray               | -                                          | R      | -    |
| Relinquish_Default  | Unsigned                          | -                                          | R      | -    |
| Time_Delay          | Unsigned                          | -                                          | O      | -    |
| Notification_Class  | Unsigned                          | -                                          | O      | -    |
| Alarm_Value         | Unsigned                          | -                                          | O      | -    |
| Fault_Value         | Unsigned                          | -                                          | O      | -    |
| Event_Enable        | BACnetEventTransitionBits         | -                                          | O      | -    |
| Acked_Transitions   | BACnetEventTransitionBits         | -                                          | O      | -    |
| Notify_Type         | BACnetNotifyType                  | -                                          | O      | -    |
| Event_Time_Stamps   | BACnetArray[N] of BACnetTimeStamp | -                                          | O      | -    |
| Profile_Name        | CharacterString                   | -                                          | O      | -    |

## Occupancy values table

Check possible Occupancy values in the following correspondence table.

| Present_Value | Contents displayed in State_Text |
|---------------|----------------------------------|
| 1             | Occupied                         |
| 2             | Unoccupied                       |
| 3             | Disabled                         |

### 5.3.19 OccupiedCoolSetPoint (Analog Value Object Type)

It indicates the current Setpoint when Cool mode is selected and Occupancy is enabled and the room is occupied.

| Property Identifier | Property Datatype                 | Value                        | ASHRAE | IBOX |
|---------------------|-----------------------------------|------------------------------|--------|------|
| Object_Identifier   | BACnetObjectIdentifier            | (Analog Value, 1)            | R      | R    |
| Object_Name         | CharacterString                   | "OccupiedCoolSetPoint"       | R      | R    |
| Object_Type         | BACnetObjectType                  | ANALOG_VALUE (2)             | R      | R    |
| Present_Value       | REAL                              | 0 .. 65535                   | R      | R    |
| Description         | CharacterString                   | -                            | O      | -    |
| Status_Flags        | BACnetStatusFlags                 | {FALSE, FALSE, FALSE, FALSE} | R      | R    |
| Event_State         | BACnetEventState                  | STATE_NORMAL (0)             | R      | R    |
| Reliability         | BACnetReliability                 | NO_FAULT_DETECTED (0)        | O      | R    |
| Out_Of_Service      | BOOLEAN                           | FALSE                        | R      | R    |
| Update_Interval     | Unsigned                          | -                            | O      | -    |
| Units               | BACnetEngineeringUnits            | Degrees Celsius (62)         | R      | R    |
| Min_Pres_Value      | REAL                              | -                            | O      | -    |
| Max_Pres_Value      | REAL                              | -                            | O      | -    |
| Resolution          | REAL                              | -                            | O      | -    |
| COV_Increment       | REAL                              | 0                            | O      | W    |
| Time_Delay          | Unsigned                          | -                            | O      | -    |
| Notification_Class  | Unsigned                          | -                            | O      | -    |
| High_Limit          | REAL                              | -                            | O      | -    |
| Low_Limit           | REAL                              | -                            | O      | -    |
| Deadband            | REAL                              | -                            | O      | -    |
| Limit_Enable        | BACnetLimitEnable                 | -                            | O      | -    |
| Event_Enable        | BACnetEventTransitionBits         | -                            | O      | -    |
| Acked_Transitions   | BACnetEventTransitionBits         | -                            | O      | -    |
| Notify_Type         | BACnetNotifyType                  | -                            | O      | -    |
| Event_Time_Stamps   | BACnetArray[N] of BACnetTimeStamp | -                            | O      | -    |
| Profile_Name        | CharacterString                   | -                            | O      | -    |

## 5.3.20 OccupiedHeatSetPoint (Analog Value Object Type)

It indicates the current Setpoint when Heat mode is selected, and Occupancy is enabled and the room is occupied.

| Property Identifier | Property Datatype                 | Value                        | ASHRAE | IBOX |
|---------------------|-----------------------------------|------------------------------|--------|------|
| Object_Identifier   | BACnetObjectIdentifier            | (Analog Value, 2)            | R      | R    |
| Object_Name         | CharacterString                   | "OccupiedHeatSetPoint"       | R      | R    |
| Object_Type         | BACnetObjectType                  | ANALOG_VALUE (2)             | R      | R    |
| Present_Value       | REAL                              | 0 .. 65535                   | R      | R    |
| Description         | CharacterString                   | -                            | O      | -    |
| Status_Flags        | BACnetStatusFlags                 | {FALSE, FALSE, FALSE, FALSE} | R      | R    |
| Event_State         | BACnetEventState                  | STATE_NORMAL (0)             | R      | R    |
| Reliability         | BACnetReliability                 | NO_FAULT_DETECTED (0)        | O      | R    |
| Out_Of_Service      | BOOLEAN                           | FALSE                        | R      | R    |
| Update_Interval     | Unsigned                          | -                            | O      | -    |
| Units               | BACnetEngineeringUnits            | Degrees Celsius (62)         | R      | R    |
| Min_Pres_Value      | REAL                              | -                            | O      | -    |
| Max_Pres_Value      | REAL                              | -                            | O      | -    |
| Resolution          | REAL                              | -                            | O      | -    |
| COV_Increment       | REAL                              | 0                            | O      | W    |
| Time_Delay          | Unsigned                          | -                            | O      | -    |
| Notification_Class  | Unsigned                          | -                            | O      | -    |
| High_Limit          | REAL                              | -                            | O      | -    |
| Low_Limit           | REAL                              | -                            | O      | -    |
| Deadband            | REAL                              | -                            | O      | -    |
| Limit_Enable        | BACnetLimitEnable                 | -                            | O      | -    |
| Event_Enable        | BACnetEventTransitionBits         | -                            | O      | -    |
| Acked_Transitions   | BACnetEventTransitionBits         | -                            | O      | -    |
| Notify_Type         | BACnetNotifyType                  | -                            | O      | -    |
| Event_Time_Stamps   | BACnetArray[N] of BACnetTimeStamp | -                            | O      | -    |
| Profile_Name        | CharacterString                   | -                            | O      | -    |

### 5.3.21 UnoccupiedCoolSetPoint (Analog Value Object Type)

It indicates the current Setpoint when Cool mode is selected, Occupancy is enabled, and the room is unoccupied.

| Property Identifier | Property Datatype                 | Value                        | ASHRAE | IBOX |
|---------------------|-----------------------------------|------------------------------|--------|------|
| Object_Identifier   | BACnetObjectIdentifier            | (Analog Value, 3)            | R      | R    |
| Object_Name         | CharacterString                   | "UnoccupiedCoolSetPoint"     | R      | R    |
| Object_Type         | BACnetObjectType                  | ANALOG_VALUE (2)             | R      | R    |
| Present_Value       | REAL                              | 0 .. 65535                   | R      | R    |
| Description         | CharacterString                   | -                            | O      | -    |
| Status_Flags        | BACnetStatusFlags                 | {FALSE, FALSE, FALSE, FALSE} | R      | R    |
| Event_State         | BACnetEventState                  | STATE_NORMAL (0)             | R      | R    |
| Reliability         | BACnetReliability                 | NO_FAULT_DETECTED (0)        | O      | R    |
| Out_Of_Service      | BOOLEAN                           | FALSE                        | R      | R    |
| Update_Interval     | Unsigned                          | -                            | O      | -    |
| Units               | BACnetEngineeringUnits            | Degrees Celsius (62)         | R      | R    |
| Min_Pres_Value      | REAL                              | -                            | O      | -    |
| Max_Pres_Value      | REAL                              | -                            | O      | -    |
| Resolution          | REAL                              | -                            | O      | -    |
| COV_Increment       | REAL                              | 0                            | O      | W    |
| Time_Delay          | Unsigned                          | -                            | O      | -    |
| Notification_Class  | Unsigned                          | -                            | O      | -    |
| High_Limit          | REAL                              | -                            | O      | -    |
| Low_Limit           | REAL                              | -                            | O      | -    |
| Deadband            | REAL                              | -                            | O      | -    |
| Limit_Enable        | BACnetLimitEnable                 | -                            | O      | -    |
| Event_Enable        | BACnetEventTransitionBits         | -                            | O      | -    |
| Acked_Transitions   | BACnetEventTransitionBits         | -                            | O      | -    |
| Notify_Type         | BACnetNotifyType                  | -                            | O      | -    |
| Event_Time_Stamps   | BACnetArray[N] of BACnetTimeStamp | -                            | O      | -    |
| Profile_Name        | CharacterString                   | -                            | O      | -    |

## 5.3.22 UnoccupiedHeatSetPoint (Analog Value Object Type)

It indicates the current Setpoint when Heat mode is selected, and Occupancy is enabled, and the room is unoccupied.

| Property Identifier | Property Datatype                 | Value                        | ASHRAE | IBOX |
|---------------------|-----------------------------------|------------------------------|--------|------|
| Object_Identifier   | BACnetObjectIdentifier            | (Analog Value, 4)            | R      | R    |
| Object_Name         | CharacterString                   | "UnoccupiedHeatSetPoint"     | R      | R    |
| Object_Type         | BACnetObjectType                  | ANALOG_VALUE (2)             | R      | R    |
| Present_Value       | REAL                              | 0 .. 65535                   | R      | R    |
| Description         | CharacterString                   | -                            | O      | -    |
| Status_Flags        | BACnetStatusFlags                 | {FALSE, FALSE, FALSE, FALSE} | R      | R    |
| Event_State         | BACnetEventState                  | STATE_NORMAL (0)             | R      | R    |
| Reliability         | BACnetReliability                 | NO_FAULT_DETECTED (0)        | O      | R    |
| Out_Of_Service      | BOOLEAN                           | FALSE                        | R      | R    |
| Update_Interval     | Unsigned                          | -                            | O      | -    |
| Units               | BACnetEngineeringUnits            | Degrees Celsius (62)         | R      | R    |
| Min_Pres_Value      | REAL                              | -                            | O      | -    |
| Max_Pres_Value      | REAL                              | -                            | O      | -    |
| Resolution          | REAL                              | -                            | O      | -    |
| COV_Increment       | REAL                              | 0                            | O      | W    |
| Time_Delay          | Unsigned                          | -                            | O      | -    |
| Notification_Class  | Unsigned                          | -                            | O      | -    |
| High_Limit          | REAL                              | -                            | O      | -    |
| Low_Limit           | REAL                              | -                            | O      | -    |
| Deadband            | REAL                              | -                            | O      | -    |
| Limit_Enable        | BACnetLimitEnable                 | -                            | O      | -    |
| Event_Enable        | BACnetEventTransitionBits         | -                            | O      | -    |
| Acked_Transitions   | BACnetEventTransitionBits         | -                            | O      | -    |
| Notify_Type         | BACnetNotifyType                  | -                            | O      | -    |
| Event_Time_Stamps   | BACnetArray[N] of BACnetTimeStamp | -                            | O      | -    |
| Profile_Name        | CharacterString                   | -                            | O      | -    |

### 5.3.23 OccupancyContinuousCheck (Binary Value Object Type)

It indicates if the system is continuously checking the setpoint and occupancy conditions.

| Property Identifier       | Property Datatype                 | Value                        | ASHRAE | IBOX |
|---------------------------|-----------------------------------|------------------------------|--------|------|
| Object_Identifier         | BACnetObjectIdentifier            | (Binary Value, 0)            | R      | R    |
| Object_Name               | CharacterString                   | "OccupancyContinuousCheck"   | R      | R    |
| Object_Type               | BACnetObjectType                  | BINARY_VALUE (5)             | R      | R    |
| Present_Value             | BACnetBinaryPV                    | INACTIVE (0) / ACTIVE (1)    | W      | W    |
| Description               | CharacterString                   | -                            | O      | -    |
| Status_Flags              | BACnetStatusFlags                 | {FALSE, FALSE, FALSE, FALSE} | R      | R    |
| Event_State               | BACnetEventState                  | STATE_NORMAL (0)             | R      | R    |
| Reliability               | BACnetReliability                 | NO_FAULT_DETECTED (0)        | O      | R    |
| Out_Of_Service            | BOOLEAN                           | FALSE                        | R      | R    |
| Inactive_Text             | CharacterString                   | "Disabled"                   | O      | R    |
| Active_Text               | CharacterString                   | "Enabled"                    | O      | R    |
| Change_Of_State_Time      | BACnetDatetime                    | -                            | O      | -    |
| Change_Of_State_Count     | Unsigned                          | -                            | O      | -    |
| Time_Of_State_Count_Reset | BACnetDatetime                    | -                            | O      | -    |
| Elapsed_Active_Time       | Unsigned                          | -                            | O      | -    |
| Time_Of_Active_Time_Reset | BACnetDatetime                    | -                            | O      | -    |
| Minimum_Off_Time          | Unsigned32                        | -                            | O      | -    |
| Minimum_On_Time           | Unsigned32                        | -                            | O      | -    |
| Priority_Array            | BACnetPriorityArray               | BACnetPriorityArray          | R      | -    |
| Relinquish_Default        | BACnetBinaryPV                    | INACTIVE (0)                 | R      | -    |
| Time_Delay                | Unsigned                          | -                            | O      | -    |
| Notification_Class        | Unsigned                          | -                            | O      | -    |
| Alarm_Value               | BACnetBinaryPV                    | -                            | O      | -    |
| Event_Enable              | BACnetEventTransitionBits         | -                            | O      | -    |
| Acked_Transitions         | BACnetEventTransitionBits         | -                            | O      | -    |
| Notify_Type               | BACnetNotifyType                  | -                            | O      | -    |
| Event_Time_Stamps         | BACnetArray[N] of BACnetTimeStamp | -                            | O      | -    |
| Profile_Name              | CharacterString                   | -                            | O      | -    |

**5.3.24 UnoccupiedDeadbandAction (Binary Value Object Type)**

It indicates the action to be performed by the system when Unoccupancy is enabled and Room Temperature is within the deadband.

| Property Identifier       | Property Datatype                   | Value                        | ASHRAE | IBOX |
|---------------------------|-------------------------------------|------------------------------|--------|------|
| Object_Identifier         | BACnetObjectIdentifier              | (Binary Value, 1)            | R      | R    |
| Object_Name               | CharacterString                     | "UnoccupiedDeadbandAction"   | R      | R    |
| Object_Type               | BACnetObjectType                    | BINARY_VALUE (5)             | R      | R    |
| Present_Value             | BACnetBinaryPV                      | INACTIVE (0) / ACTIVE (1)    | W      | W    |
| Description               | CharacterString                     | -                            | O      | -    |
| Status_Flags              | BACnetStatusFlags                   | {FALSE, FALSE, FALSE, FALSE} | R      | R    |
| Event_State               | BACnetEventState                    | STATE_NORMAL (0)             | R      | R    |
| Reliability               | BACnetReliability                   | NO_FAULT_DETECTED (0)        | O      | R    |
| Out_Of_Service            | BOOLEAN                             | FALSE                        | R      | R    |
| Inactive_Text             | CharacterString                     | "Off"                        | O      | R    |
| Active_Text               | CharacterString                     | "CurrentMode"                | O      | R    |
| Change_Of_State_Time      | BACnetDatetime                      | -                            | O      | -    |
| Change_Of_State_Count     | Unsigned                            | -                            | O      | -    |
| Time_Of_State_Count_Reset | BACnetDatetime                      | -                            | O      | -    |
| Elapsed_Active_Time       | Unsigned                            | -                            | O      | -    |
| Time_Of_Active_Time_Reset | BACnetDatetime                      | -                            | O      | -    |
| Minimum_Off_Time          | Unsigned32                          | -                            | O      | -    |
| Minimum_On_Time           | Unsigned32                          | -                            | O      | -    |
| Priority_Array            | BACnetPriorityArray                 | BACnetPriorityArray          | R      | -    |
| Relinquish_Default        | BACnetBinaryPV                      | INACTIVE (0)                 | R      | -    |
| Time_Delay                | Unsigned                            | -                            | O      | -    |
| Notification_Class        | Unsigned                            | -                            | O      | -    |
| Alarm_Value               | BACnetBinaryPV                      | -                            | O      | -    |
| Event_Enable              | BACnetEventTransitionBits           | -                            | O      | -    |
| Acked_Transitions         | BACnetEventTransitionBits           | -                            | O      | -    |
| Notify_Type               | BACnetNotifyType                    | -                            | O      | -    |
| Event_Time_Stamps         | BACnetArray[N]<br>ofBACnetTimeStamp | -                            | O      | -    |
| Profile_Name              | CharacterString                     | -                            | O      | -    |

## 5.3.25 RemoteControllerProhibit\_status (Multistate Input Object Type)

It indicates the status prohibition of the remote controller.

| Property Identifier | Property Datatype                    | Value                                                           | ASHRAE | IBOX |
|---------------------|--------------------------------------|-----------------------------------------------------------------|--------|------|
| Object_Identifier   | BACnetObjectIdentifier               | (Multi-state Input, 6)                                          | R      | R    |
| Object_Name         | CharacterString                      | "RemoteControllerProhibit_status"                               | R      | R    |
| Object_Type         | BACnetObjectType                     | MULTISTATE_INPUT(13)                                            | R      | R    |
| Present_Value       | Unsigned                             | 1 ~ 2                                                           | R      | R    |
| Description         | CharacterString                      | -                                                               | O      | -    |
| Device_Type         | CharacterString                      | -                                                               | O      | -    |
| Status_Flags        | BACnetStatusFlags                    | {FALSE, FALSE/TRUE, FALSE, FALSE}                               | R      | R    |
| Event_State         | BACnetEventState                     | STATE_NORMAL (0)                                                | R      | R    |
| Reliability         | BACnetReliability                    | NO_FAULT_DETECTED (0),<br>UNRELIABLE_OTHER (7)                  | O      | R    |
| Out_Of_Service      | BOOLEAN                              | FALSE/TRUE                                                      | R      | R    |
| Number_Of_States    | Unsigned                             | 2                                                               | R      | R    |
| State_Text          | BACnetArray[N] of<br>CharacterString | <i>Check Remote Controller Prohibit Status<br/>table below.</i> | O      | R    |
| Time_Delay          | Unsigned                             | -                                                               | O      | -    |
| Notification_Class  | Unsigned                             | -                                                               | O      | -    |
| Alarm_Values        | List of Unsigned                     | -                                                               | O      | -    |
| Fault_Values        | List of Unsigned                     | -                                                               | O      | -    |
| Event_Enable        | BACnetEventTransitionBits            | -                                                               | O      | -    |
| Acked_Transitions   | BACnetEventTransitionBits            | -                                                               | O      | -    |
| Notify_Type         | BACnetNotifyType                     | -                                                               | O      | -    |
| Event_Time_Stamps   | BACnetArray[N] of<br>BACnetTimeStamp | -                                                               | O      | -    |
| Profile_Name        | CharacterString                      | -                                                               | O      | -    |

### Remote controller prohibit status table

Remote controller prohibit interpretation is possible using the value in the following correspondence table.

| Present_Value | Contents displayed in State_Text |
|---------------|----------------------------------|
| 1             | Unlocked                         |
| 2             | Locked                           |

## 5.3.26 RemoteControllerProhibit\_command (Multistate Output Object Type)

It allows control over the vertical air direction (Up/Down) for the indoor unit.

| Property Identifier | Property Datatype                 | Value                                                                | ASHRAE | IBOX |
|---------------------|-----------------------------------|----------------------------------------------------------------------|--------|------|
| Object_Identifier   | BACnetObjectIdentifier            | (Multi-state Output, 5)                                              | R      | R    |
| Object_Name         | CharacterString                   | "RemoteControllerProhibit_command"                                   | R      | R    |
| Object_Type         | BACnetObjectType                  | MULTISTATE_OUTPUT (14)                                               | R      | R    |
| Present_Value       | Unsigned                          | 1 ~ 2                                                                | W      | W    |
| Description         | CharacterString                   | -                                                                    | O      | -    |
| Device_Type         | CharacterString                   | -                                                                    | O      | -    |
| Status_Flags        | BACnetStatusFlags                 | {FALSE, FALSE, FALSE, FALSE}                                         | R      | R    |
| Event_State         | BACnetEventState                  | STATE_NORMAL (0)                                                     | R      | R    |
| Reliability         | BACnetReliability                 | NO_FAULT_DETECTED (0)                                                | O      | R    |
| Out_Of_Service      | BOOLEAN                           | FALSE                                                                | R      | R    |
| Number_Of_States    | Unsigned                          | 2                                                                    | R      | R    |
| State_Text          | BACnetArray[N] of CharacterString | <i>Check Remote Controller Prohibit Command setting table below.</i> | O      | R    |
| Priority_Array      | BACnetPriorityArray               | -                                                                    | R      | R    |
| Relinquish_Default  | Unsigned                          | -                                                                    | R      | R    |
| Time_Delay          | Unsigned                          | -                                                                    | O      | -    |
| Notification_Class  | Unsigned                          | -                                                                    | O      | -    |
| Feedback_Value      | Unsigned                          | -                                                                    | O      | -    |
| Event_Enable        | BACnetEventTransitionBits         | -                                                                    | O      | -    |
| Acked_Transitions   | BACnetEventTransitionBits         | -                                                                    | O      | -    |
| Notify_Type         | BACnetNotifyType                  | -                                                                    | O      | -    |
| Event_Time_Stamps   | BACnetArray[N] of BACnetTimeStamp | -                                                                    | O      | -    |
| Profile_Name        | CharacterString                   | -                                                                    | O      | -    |

### Remote controller prohibit command setting table

Remote controller prohibit interpretation is possible using the value in the following correspondence table.

| Present_Value | Contents displayed in State_Text |
|---------------|----------------------------------|
| 1             | Unlocked                         |
| 2             | Locked                           |

## 5.3.27 DIP\_SW\_S1\_status (Analog Input Object Type)

It indicates the status of the DIP switch 1 in decimal value. To get the micro-switch position, just translate the value into binary. It is only read after booting the device.

| Property Identifier       | Property Datatype                 | Value                        | ASHRAE | IBOX |
|---------------------------|-----------------------------------|------------------------------|--------|------|
| Object_Identifier         | BACnetObjectIdentifier            | (Analog Input, 9)            | R      | R    |
| Object_Name               | CharacterString                   | "DIP_SW_S1_status"           | R      | R    |
| Object_Type               | BACnetObjectType                  | ANALOG_INPUT (0)             | R      | R    |
| Present_Value             | BACnetBinaryPV                    | 0...255*                     | R      | R    |
| Description               | CharacterString                   | -                            | O      | -    |
| Device_Type               | CharacterString                   | -                            | O      | -    |
| Status_Flags              | BACnetStatusFlags                 | {FALSE, FALSE, FALSE, FALSE} | R      | R    |
| Event_State               | BACnetEventState                  | STATE_NORMAL (0)             | R      | R    |
| Reliability               | BACnetReliability                 | NO_FAULT_DETECTED (0)        | O      | R    |
| Out_Of_Service            | BOOLEAN                           | FALSE / TRUE                 | R      | R    |
| Polarity                  | BACnetPolarity                    | NORMAL (0)                   | R      | R    |
| Inactive_Text             | CharacterString                   |                              | O      | R    |
| Active_Text               | CharacterString                   |                              | O      | R    |
| Change_Of_State_Time      | BACnetDatetime                    | -                            | O      | -    |
| Change_Of_State_Count     | Unsigned                          | -                            | O      | -    |
| Time_Of_State_Count_Reset | BACnetDatetime                    | -                            | O      | -    |
| Elapsed_Active_Time       | Unsigned                          | -                            | O      | -    |
| Time_Of_Active_Time_Reset | BACnetDatetime                    | -                            | O      | -    |
| Time_Delay                | Unsigned                          | -                            | O      | -    |
| Notification_Class        | Unsigned                          | -                            | O      | -    |
| Alarm_Value               | BACnetBinaryPV                    | -                            | O      | -    |
| Event_Enable              | BACnetEventTransitionBits         | -                            | O      | -    |
| Acked_Transitions         | BACnetEventTransitionBits         | -                            | O      | -    |
| Notify_Type               | BACnetNotifyType                  | -                            | O      | -    |
| Event_Time_Stamps         | BACnetArray[N] of BACnetTimeStamp | -                            | O      | -    |
| Profile_Name              | CharacterString                   | -                            | O      | -    |
| Units                     | BACnetEngineeringUnits            | No units (95)                | R      | R    |
| COV_Increment             | REAL                              | 0                            | O      | W    |

## 5.3.28 DIP\_SW\_S2\_status (Analog Input Object Type)

It indicates the status of the DIP switch 2 in decimal value. To get the micro-switch position, just translate the value into binary. It is only read after booting the device.

| Property Identifier       | Property Datatype                 | Value                        | ASHRAE | IBOX |
|---------------------------|-----------------------------------|------------------------------|--------|------|
| Object_Identifier         | BACnetObjectIdentifier            | (Analog Input, 10)           | R      | R    |
| Object_Name               | CharacterString                   | DIP_SW_S2_status             | R      | R    |
| Object_Type               | BACnetObjectType                  | ANALOG_INPUT (0)             | R      | R    |
| Present_Value             | BACnetBinaryPV                    | 0...255*                     | R      | R    |
| Description               | CharacterString                   | -                            | O      | -    |
| Device_Type               | CharacterString                   | -                            | O      | -    |
| Status_Flags              | BACnetStatusFlags                 | {FALSE, FALSE, FALSE, FALSE} | R      | R    |
| Event_State               | BACnetEventState                  | STATE_NORMAL (0)             | R      | R    |
| Reliability               | BACnetReliability                 | NO_FAULT_DETECTED (0)        | O      | R    |
| Out_Of_Service            | BOOLEAN                           | FALSE                        | R      | R    |
| Polarity                  | BACnetPolarity                    | NORMAL (0)                   | R      | R    |
| Inactive_Text             | CharacterString                   |                              | O      | R    |
| Active_Text               | CharacterString                   |                              | O      | R    |
| Change_Of_State_Time      | BACnetDatetime                    | -                            | O      | -    |
| Change_Of_State_Count     | Unsigned                          | -                            | O      | -    |
| Time_Of_State_Count_Reset | BACnetDatetime                    | -                            | O      | -    |
| Elapsed_Active_Time       | Unsigned                          | -                            | O      | -    |
| Time_Of_Active_Time_Reset | BACnetDatetime                    | -                            | O      | -    |
| Time_Delay                | Unsigned                          | -                            | O      | -    |
| Notification_Class        | Unsigned                          | -                            | O      | -    |
| Alarm_Value               | BACnetBinaryPV                    | -                            | O      | -    |
| Event_Enable              | BACnetEventTransitionBits         | -                            | O      | -    |
| Acked_Transitions         | BACnetEventTransitionBits         | -                            | O      | -    |
| Notify_Type               | BACnetNotifyType                  | -                            | O      | -    |
| Event_Time_Stamps         | BACnetArray[N] of BACnetTimeStamp | -                            | O      | -    |
| Profile_Name              | CharacterString                   | -                            | O      | -    |
| Units                     | BACnetEngineeringUnits            | No units (95)                | R      | R    |
| COV_Increment             | REAL                              | 0                            | O      | W    |

## 5.3.29 SerialNumber (Analog Input Object Type)

It indicates the serial number of the device. Serial number follows the next rule **000KXXXXXX**, where:

- **000K** is constant and no included in Present Value property.
- **XXXXXX** is the unique serial number of the device. It is the information provided through the Present Value.

| Property Identifier       | Property Datatype                 | Value                        | ASHRAE | IBOX |
|---------------------------|-----------------------------------|------------------------------|--------|------|
| Object_Identifier         | BACnetObjectIdentifier            | (Analog Input, 11)           | R      | R    |
| Object_Name               | CharacterString                   | SerialNumber                 | R      | R    |
| Object_Type               | BACnetObjectType                  | ANALOG_INPUT (0)             | R      | R    |
| Present_Value             | BACnetBinaryPV                    | 00000...99999                | R      | R    |
| Description               | CharacterString                   | -                            | O      | -    |
| Device_Type               | CharacterString                   | -                            | O      | -    |
| Status_Flags              | BACnetStatusFlags                 | {FALSE, FALSE, FALSE, FALSE} | R      | R    |
| Event_State               | BACnetEventState                  | STATE_NORMAL (0)             | R      | R    |
| Reliability               | BACnetReliability                 | NO_FAULT_DETECTED (0)        | O      | R    |
| Out_Of_Service            | BOOLEAN                           | FALSE                        | R      | R    |
| Polarity                  | BACnetPolarity                    | NORMAL (0)                   | R      | R    |
| Inactive_Text             | CharacterString                   |                              | O      | R    |
| Active_Text               | CharacterString                   |                              | O      | R    |
| Change_Of_State_Time      | BACnetDatetime                    | -                            | O      | -    |
| Change_Of_State_Count     | Unsigned                          | -                            | O      | -    |
| Time_Of_State_Count_Reset | BACnetDatetime                    | -                            | O      | -    |
| Elapsed_Active_Time       | Unsigned                          | -                            | O      | -    |
| Time_Of_Active_Time_Reset | BACnetDatetime                    | -                            | O      | -    |
| Time_Delay                | Unsigned                          | -                            | O      | -    |
| Notification_Class        | Unsigned                          | -                            | O      | -    |
| Alarm_Value               | BACnetBinaryPV                    | -                            | O      | -    |
| Event_Enable              | BACnetEventTransitionBits         | -                            | O      | -    |
| Acked_Transitions         | BACnetEventTransitionBits         | -                            | O      | -    |
| Notify_Type               | BACnetNotifyType                  | -                            | O      | -    |
| Event_Time_Stamps         | BACnetArray[N] of BACnetTimeStamp | -                            | O      | -    |
| Profile_Name              | CharacterString                   | -                            | O      | -    |
| Units                     | BACnetEngineeringUnits            | No units (95)                | R      | R    |
| COV_Increment             | REAL                              | 0                            | O      | W    |

## 5.3.30 AC IU address (Multistate Value Object Type)

It indicates the address of the indoor unit in the Ductless system.

| Property Identifier | Property Datatype                 | Value                                          | ASHRAE | IBOX |
|---------------------|-----------------------------------|------------------------------------------------|--------|------|
| Object_Identifier   | BACnetObjectIdentifier            | (Multi-state Output, 1)                        | R      | R    |
| Object_Name         | CharacterString                   | "AC IU address"                                | R      | R    |
| Object_Type         | BACnetObjectType                  | MULTISTATE_VALUE (19)                          | R      | R    |
| Present_Value       | Unsigned                          | 1 ~ 64                                         | W      | W    |
| Description         | CharacterString                   | -                                              | O      | -    |
| Status_Flags        | BACnetStatusFlags                 | {FALSE, FALSE, FALSE, FALSE}                   | R      | R    |
| Event_State         | BACnetEventState                  | STATE_NORMAL (0)                               | R      | R    |
| Reliability         | BACnetReliability                 | NO_FAULT_DETECTED (0)                          | O      | R    |
| Out_Of_Service      | BOOLEAN                           | FALSE                                          | R      | R    |
| Number_Of_States    | Unsigned                          | 64                                             | R      | R    |
| State_Text          | BACnetArray[N] of CharacterString | <i>Check AC IU address setting table below</i> | O      | R    |
| Priority_Array      | BACnetPriorityArray               | -                                              | R      | -    |
| Relinquish_Default  | Unsigned                          | -                                              | R      | -    |
| Time_Delay          | Unsigned                          | -                                              | O      | -    |
| Notification_Class  | Unsigned                          | -                                              | O      | -    |
| Alarm_Value         | Unsigned                          | -                                              | O      | -    |
| Fault_Value         | Unsigned                          | -                                              | O      | -    |
| Event_Enable        | BACnetEventTransitionBits         | -                                              | O      | -    |
| Acked_Transitions   | BACnetEventTransitionBits         | -                                              | O      | -    |
| Notify_Type         | BACnetNotifyType                  | -                                              | O      | -    |
| Event_Time_Stamps   | BACnetArray[N] of BACnetTimeStamp | -                                              | O      | -    |
| Profile_Name        | CharacterString                   | -                                              | O      | -    |

### AC IU address values table

Check AC indoor unit address values in the following correspondence table.

| Present_Value | Contents displayed in State_Text | AC Indoor unit address |
|---------------|----------------------------------|------------------------|
| 1             | 0                                | 0                      |
| 2             | 1                                | 1                      |
| 3             | 2                                | 2                      |
| ...           | ...                              | ...                    |
| 62            | 61                               | 61                     |
| 63            | 62                               | 62                     |
| 64            | 63                               | 63                     |

## 5.3.31 Ductless\_DIP\_SW\_setting (Multistate Input Object Type)

It indicates the DIP-SW-setting for the Ductless system.

| Property Identifier | Property Datatype                    | Value                                                 | ASHRAE | IBOX |
|---------------------|--------------------------------------|-------------------------------------------------------|--------|------|
| Object_Identifier   | BACnetObjectIdentifier               | (Multi-state Input, 11)                               | R      | R    |
| Object_Name         | CharacterString                      | "Ductless_DIP_SW_setting"                             | R      | R    |
| Object_Type         | BACnetObjectType                     | MULTISTATE_INPUT(13)                                  | R      | R    |
| Present_Value       | Unsigned                             | 1 ~ 5                                                 | R      | R    |
| Description         | CharacterString                      | -                                                     | O      | -    |
| Device_Type         | CharacterString                      | -                                                     | O      | -    |
| Status_Flags        | BACnetStatusFlags                    | {FALSE, FALSE/TRUE, FALSE, FALSE}                     | R      | R    |
| Event_State         | BACnetEventState                     | STATE_NORMAL (0)                                      | R      | R    |
| Reliability         | BACnetReliability                    | NO_FAULT_DETECTED (0),<br>UNRELIABLE_OTHER (7)        | O      | R    |
| Out_Of_Service      | BOOLEAN                              | FALSE/TRUE                                            | R      | R    |
| Number_Of_States    | Unsigned                             | 5                                                     | R      | R    |
| State_Text          | BACnetArray[N] of<br>CharacterString | <i>Check Ductless DIP SW setting table<br/>below.</i> | O      | R    |
| Time_Delay          | Unsigned                             | -                                                     | O      | -    |
| Notification_Class  | Unsigned                             | -                                                     | O      | -    |
| Alarm_Values        | List of Unsigned                     | -                                                     | O      | -    |
| Fault_Values        | List of Unsigned                     | -                                                     | O      | -    |
| Event_Enable        | BACnetEventTransitionBits            | -                                                     | O      | -    |
| Acked_Transitions   | BACnetEventTransitionBits            | -                                                     | O      | -    |
| Notify_Type         | BACnetNotifyType                     | -                                                     | O      | -    |
| Event_Time_Stamps   | BACnetArray[N] of<br>BACnetTimeStamp | -                                                     | O      | -    |
| Profile_Name        | CharacterString                      | -                                                     | O      | -    |

### Ductless DIP SW setting table

Ductless DIP SW setting table interpretation is possible using the value in the following correspondence table.

| Present_Value | Contents displayed in State_Text |
|---------------|----------------------------------|
| 1             | Auto (detecting)                 |
| 2             | Auto V4                          |
| 3             | Auto V6                          |
| 4             | V4                               |
| 5             | V6                               |

## 5.4 Considerations on Temperature Objects

The behavior of the temperature objects is described in detail in this section.

- **Setpoint\_command (Analog Output Object Type)**  
This is the adjustable temperature setpoint value that must be required by the user.

**Present value** can be read or written.

- **RoomTemperature\_status (Analog Input Object Type)**  
This object reports the temperature that is currently used by the Ductless indoor unit as the reference of its own control loop. Depending on the configuration of the indoor unit, this value can be the temperature reported by the sensor on the return path of the Ductless indoor unit or the sensor of its remote controller.

**Present value** can be read only.

- **RoomTemperature\_command (Analog Output Object Type)**  
This object allows us to provide an external temperature's sensor from the BACnet side. Ductless indoor unit does not allow, on devices like INBACMID001I100 connected to XYE bus, to provide directly a temperature to be used as a reference of the control loop of the AC indoor unit. To overcome this limitation and enable the usage of an external temperature sensor, INBACMID001I100 applies the following mechanism called "Virtual Temperature":
  - After receiving **RoomTemperature\_command** and **Setpoint\_command**, INBACMID001I100 is going to estimate the appropriate temperature setpoint.

Example. If a **Setpoint\_command** = 22°C, and **RoomTemperature\_command** = 20°C are received, INBACMID001I100 will assume that the user is demanding a +2°C increase in temperature.

- By knowing at any time, the reference temperature currently used by the indoor unit (the return temperature), INBACMID001I100 can calculate the required temperature setpoint needed to apply the decrease/increase on the real temperature and reach the temperature chosen by the user.

Following the example, if INBACMID001I100 reads a **RoomTemperature\_command** = 24°C in the indoor unit, it will apply a final setpoint of 24°C + 2°C = 26°C.

- At this moment, every time that INBACMID001I100 detects a change on the ambient temperature reported by the indoor unit, it will also change the required setpoint to keep the temperature required by the user at any time.

If we follow the example, if INBACMID001I100 receives a new temperature value coming from the indoor unit of 25°C, INBACMID001I100 will automatically adjust the temperature setpoint required of the AC indoor unit to 25°C + 2°C = 27°C.

- In general, INBACMID001I100 is constantly applying the "Virtual Temperature" formula:  
$$S_{AC} = S_u - (T_u - T_{AC})$$

Where:

$S_{AC}$  - setpoint value currently applied to the indoor unit

$S_u$  - setpoint value

$T_u$  - external temperature reference written at BACnet side

$T_{AC}$  - ambient temperature that the indoor unit is using as the reference of its own control loop

When INBACMID001I100 detects a change in any of the values of  $\{S_u, T_u, T_{AC}\}$ , it will send the new setpoint ( $S_{AC}$ ) to the indoor unit.

- After a device booting, **Present value** for **RoomTemperature\_command** has a value 0 and the property "Realibility" is displayed as *Unreliable Other* (7). This "Realibility" status means that no external temperature reference has being provided to the object, so the system is not applying the Virtual

temperature function. However, after receiving the first value, "Reliability" will change into *NoFault Detected (0)*. After that, any value can be used in the temperature range, including 0.

- **Setpoint\_status (Analog Input Object Type)**
- This register will show the real temperature sent to the indoor unit. It is the temperature that the AC unit is applying as a setpoint. Its behavior depends on virtual temperature function:
  - If virtual temperature is not in use, its value will be the same that **Setpoint\_command** or the one sent by different means (IR remote, wall-mounted remote, etc.).
  - If virtual temperature is being used, the value will be the real setpoint modified by this function according to the formula explained above.

**Present value** can be read only.

Moreover, notice that temperature's values of all these four objects are expressed according to the temperature's format configured through its onboard DIP-Switches (See [6 CONNECTIONS AND SWITCHES](#)). The following formats are possible:

- **Celsius value:** Value in BACnet object is the temperature value in Celsius (i.e. a value "22" in the BACnet object must be interpreted as 22°C).
- **Fahrenheit value:** Value in BACnet object is the temperature value in Fahrenheit (i.e. a value "72" in the BACnet object must be interpreted as 72°F (~22°C)).


## 6 Connections and switches

### 6.1 Connect to the XYE terminals

Disconnect mains power from the AC unit.

Connect the interface to XYE terminals in the indoor unit. The XYE is a three-wires bus of the Ductless system. Respect the XYE polarity when connecting the interface.

**⚠ Important:** Remember that switch changes are only applied after an Intesis power cycle.



The power supply must comply with NEC Class 2 or Limited Power Source (LPS) and SELV rated power supply. Respect the polarity. Apply always a voltage within the range admitted and of enough power (12V DC/AC, min. 200 mA).

#### SW1 – Device and AC settings

| Binary value<br>b1...b5 | Switches<br>1 2 3 4 5 6 7 8 | Description                                                    |
|-------------------------|-----------------------------|----------------------------------------------------------------|
| 00xxxxxx                | ↓ ↓ x x x x x x             | Auto Midea V4/V6 detection (valor por defecto - default value) |
| 01xxxxxx                | ↓ ↑ x x x x x x             | Reserved                                                       |
| 10xxxxxx                | ↑ ↓ x x x x x x             | Force Midea V4                                                 |
| 11xxxxxx                | ↑ ↑ x x x x x x             | Force Midea V6                                                 |
| xx0xxxxx                | x x ↓ x x x x x             | Not used (valor por defecto - default value)                   |
| xx1xxxxx                | x x ↑ x x x x x             | Not used                                                       |
| xxx0xxxx                | x x x ↓ x x x x             | Not used (valor por defecto - default value)                   |
| xxx1xxxx                | x x x ↑ x x x x             | Not used                                                       |
| xxxx0xxx                | x x x x ↓ x x x             | Low Power Mode                                                 |
| xxxx1xxx                | x x x x ↑ x x x             | High Performance mode (valor por defecto - default value)      |

**⚠ Important:** This switch determines the performance and consumption of the device. Running in **High Performance Mode** means maximum consumption and maximum device performance. This should be the mode established. If it is necessary to decrease device consumption, change the mode to **Low Power Mode**.

#### SW2 – Temperature magnitude (°C/°F)

| Binary value<br>b0...b1 | Switches<br>1 2 3 4 5 6 7 8 | Description                                                                     |
|-------------------------|-----------------------------|---------------------------------------------------------------------------------|
| xxxxxxx0                | x x x x x x ↓               | Temperature values in Bacnet are represented in Celsius degrees (Default value) |
| xxxxxxx1                | x x x x x x ↑               | Temperature values in Bacnet are represented in Fahrenheit degrees              |

## 6.2 Connect to BACnet MS/TP

Connect the EIA485 bus wires to the plug-in terminal block (EIA485) of INBACMID001I100; respect the polarity on this connection (A+ and B-). Connect the ground signal to the plug-in terminal block (SG).

Respect the maximum distance of 1.200 meters for the bus, no loop or star topologies are allowed for EIA485 bus.

Remember that a terminator resistor of 120  $\Omega$  must be present at each end of the bus to avoid signal reflections and a polarization mechanism. Please, use switch **SW3** to configure these parameters.

| Binary value<br>$b_2...b_0$ | Switches<br>1 2 3 | Description                                                                                              |
|-----------------------------|-------------------|----------------------------------------------------------------------------------------------------------|
| 0xx                         | ↓ x x             | EIA485 bus without termination resistor. The gateway is not at one end of the EIA485 bus (default value) |
| 1xx                         | ↑ x x             | 120 $\Omega$ termination resistor active. The gateway is at one end of the EIA485 bus                    |
| x00                         | x ↓ ↓             | No bus polarization (Default value)                                                                      |
| x11                         | x ↑ ↑             | Bus polarization active                                                                                  |

Please, check configuration on **SW2** and **SW3** before connecting to BACnet MS/TP.

### 6.2.1 MS/TP MAC address switch configuration

MAC address can be configured using switch **SW2**

| Binary value<br>$b_0...b_7$ | Switches<br>1 2 3 4 5 6 7 8 | MAC address          |
|-----------------------------|-----------------------------|----------------------|
| 0000000x                    | ↓ ↓ ↓ ↓ ↓ ↓ ↓ x             | 0<br>(Default value) |
| 1000000x                    | ↑ ↓ ↓ ↓ ↓ ↓ ↓ x             | 1                    |
| 0100000x                    | ↓ ↑ ↓ ↓ ↓ ↓ ↓ x             | 2                    |
| 1100000x                    | ↑ ↑ ↓ ↓ ↓ ↓ ↓ x             | 3                    |
| ....                        | ....                        | ...                  |
| 1011111x                    | ↑ ↓ ↑ ↑ ↑ ↑ ↑ x             | 125                  |
| 0111111x                    | ↓ ↑ ↑ ↑ ↑ ↑ ↑ x             | 126                  |
| 1111111x                    | ↑ ↑ ↑ ↑ ↑ ↑ ↑ x             | 127                  |

The MAC address selected may affect on the Device Instance. If the "Auto Device Instance" is used, keep in mind that the Device Instance will be built using the "Device Instance Base" + the address selected in SWP2 P1-P7. Please, check section **5.3.1 DUCTLESS AC GATEWAY (DEVICE OBJECT TYPE)** for more information.

### 6.2.2 BACnet MS/TP baudrate

Select the right baudrate for BACnet MS/TP communication using switch **SW1**.

| Binary value<br>$b_5...b_4$ | Switches<br>1 2 3 4 5 6 7 8 | Description                    |
|-----------------------------|-----------------------------|--------------------------------|
| xxxxx000                    | x x x x x ↓ ↓ ↓             | Autobaudrate (default value) * |
| xxxxx100                    | x x x x x ↑ ↓ ↓             | 9600 bps                       |
| xxxxx010                    | x x x x x ↓ ↑ ↓             | 19200 bps                      |
| xxxxx110                    | x x x x x ↑ ↑ ↓             | 38400 bps                      |
| xxxxx001                    | x x x x x ↓ ↓ ↑             | 57600 bps                      |
| xxxxx101                    | x x x x x ↑ ↓ ↑             | 76800 bps                      |
| xxxxx011                    | x x x x x ↓ ↑ ↑             | 115200 bps                     |
| xxxxx111                    | x x x x x ↑ ↑ ↑             | Autobaudrate *                 |

\* Note: If Autobaudrate is selected, the INBACMID001I100 will look for another BACnet MS/TP device with a fixed baudrate to match this value. Once detected, the baudrate will not be modified until a device reset is produced.

## 6.3 Connect to an external power supply

It is necessary to use an external power supply connected to PWR terminals. Respect the polarity (- +). The power supply must comply with NEC Class 2 or Limited Power Source (LPS) and SELV rated power supply. Respect the polarity. Apply always a voltage within the range admitted and of enough power (12V DC/AC, min. 200 mA).

## 7 Set-up process and troubleshooting

### 7.1 Pre-requisites

For a BACnet MS/TP integration, it is necessary to have the BACnet MS/TP Master device operative and well connected to the BACnet MS/TP port of the INBACMID0011100.

Items supplied by HMS Networks for this integration are:

- Intesis INBACMID0011100 interface with Ductless AC external protocol firmware loaded.
- Product documentation.

### 7.2 Physical checking

First point to check are the gateway physical connections:


- 1.- Make sure that the gateway is correctly connected to the AC unit.
- 2.- Check that the AC unit is connected to mains.
- 3.- Check the EIA485 connection from the gateway to the BACnet MS/TP. Remember to verify polarity and terminal resistors configuration.
- 4.- Check that the interface is properly connected to an external power supply verifying the polarity.

### 7.3 LED status

There are three leds at the bottom of the device. On start up, all leds blink once and then turn off. After that booting, LED status will be updated.

Please, check the table below for more information:

| LED           | Status    | Description                      |
|---------------|-----------|----------------------------------|
| L1<br>(red)   | ON Steady | BACnet MS/TP link                |
|               | Blinking  | Activity on the BACnet MS/TP bus |
|               | Flashing  | BACnet MS/TP link not performed  |
| L2<br>(green) | ON Steady | Communication error              |
|               | Blinking  | AC Error                         |
|               | OFF       | Communication OK                 |



## 7.4 Occupancy

Each indoor unit has its own occupancy signal. Remember that this signal needs to be feed by an external sensor which indicates if there is presense or not (occupancy). This signal is processed directly in the INBACMID001I100.

When occupancy mode is active, according to current room temperature it will set the mode, setpoint and on/off, for example:

- Room Temperature > OCS: Setpoint = OCS, Mode = Cool, On/Off = On
- Room Temperature < OHS: Setpoint = OHS, Mode = Heat, On/Off = On
- OCS < Room Temperature > OHS: Setpoint = OCS/OHS depending on current mode (if Fan or Dry mode is active => no setpoint is sent), On/Off = On


When unoccupancy mode is active, according to current room temperature it will set the mode, setpoint and on/off, for example:

- Room Temperature > UCS: Setpoint = UCS, Mode = Cool, On/Off = On
- Room Temperature < UHS: Setpoint = UHS, Mode = Heat, On/Off = On
- UCS < Room Temperature > UHS: Setpoint = UCS/UHS depending on current mode (if Fan or Dry mode is active => no setpoint is sent), On/Off = On (if Unoccupancy Deadband Action is = 1)

These checks will be done each time the indoor unit occupancy status is changed, and if **check continuously** checkbox is checked, also each time the room temperature changes.

The configuration set on the occupany signals is applied from the very first moment the occupancy signal is enabled until the user changes the setpoint, mode or the On/Off signal, which disables occupancy functionality.

The minimum difference between Cool and Heat SetPoints must be 2°C/4°F.



## **8 Restore factory Settings**

### **8.1 Restore factory Settings**

To restore device factory settings, it is necessary to complete the following process:

1. Set **SW1** and **SW2** DIP switches to ON position.
2. Reset the device performing a POWER OFF and a POWER ON.
3. After booting, the leds (green+red+yellow) should be blinking in S.O.S morse sequence.
4. At this moment, a 30 seconds countdown will start to set all SW1 and SW2 switches to OFF position.
5. By completing these previous steps, the device will be restored to Factory Settings.

To continue working with the device, remember to proceed as usual:

1. Set again switches to reach user desired configuration
2. Reset the device (POWER OFF + POWER ON).

## 9 AC Unit Types compatibility

Please, check compatibility list to know which Ductless units are compatible with our gateway.

Compatibility:

Only specific Carrier DLS indoor product families are tested for compatibility with the Intesis BACnet MS/TP 1:1 gateway INBACMID0011100. Ductless indoor unit backward compatibility as well as future versions' compatibility is not guaranteed.

|                |
|----------------|
| Phased Out     |
| Not Compatible |
| Current Model  |



Net dimensions (DxWxH): (3 7 x 2.1 x 2.3 in) ( 93 x 53 x 58 mm)

Compatibility between the Intesis BACnet gateway and the factory wired wall controller.



| Carrier Model Number | Indoor Unit Type     | Size | Midea protocol | Compatible        | Phased Out   | KSACN0101AAA | KSACN0601AAA | KSACN0701AAA | KSACN0801AAA |
|----------------------|----------------------|------|----------------|-------------------|--------------|--------------|--------------|--------------|--------------|
| 40 MPHA              | HighWall             | All  | V4             | YES               |              | No           | No           | No           | No           |
| 40 MAQ               | HighWall             | All  | V4             | YES* See Note 1   | Yes Q1, 2021 | Yes          | No           | No           | No           |
| 40 MAHB              | HighWall             | All  | V4             | YES** See Note 2  |              | Yes          | No           | No           | No           |
| 40 MHQ               | HighWall             | All  | V4             | Yes               |              | Yes          | No           | No           | No           |
| 40 MHHC              | HighWall             | All  | Forced / V4    | YES*** See Note 3 |              | Yes          | No           | No           | No           |
| 40 MBCQ              | Cassette             | All  | V4             | Yes               |              | Yes          | No           | Yes          | No           |
| 40 MBAA              | Ducted               | N/A  | N/A            | Not Compatible    |              | N/A          | N/A          | N/A          | N/A          |
| 40 MBDQ              | Ducted               | All  | V4             | Yes               |              | Yes          | No           | Yes          | No           |
| 40 MBFQ              | Underceiling / Floor | N/A  | N/A            | Not Compatible    |              | N/A          | N/A          | N/A          | N/A          |

Notes:

\* 1: 40MAQ The mid-tier Ductless High Wall 40MAQB\*\*B---3 indoor unit type, will need to have the display and adaptor board replaced to function with the Intesis MS/TP BACnet gateway. The 40MAQ Adapter Board, P/N 17222000A50275, and Display Board Assembly, P/N 17222000A17852, can be ordered from RC.


\*\* 2: The 40MAHB Indoor unit requires that a multi function board and 7 pin wiring harness are added to the indoor unit at the time of installation. The multifunction board P/N 17122000A38610 and wiring harness P/N 17401204A02537 can be ordered as an accessory.

\*\*\* 3: The 40MHHC is a cooling only system. Please consider this when completing the integration. The only Modes that should be mapped to the BACnet controls system should be Cooling & Fan.

The wireless infrared controller that comes with the indoor unit can be used at the same time as the Intesis BACnet gateway or disabled by configuration.

## 10 Mechanical & electrical characteristics

|                                           |                                                                                                                                                                                                          |                       |                                                                                                                         |
|-------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-------------------------------------------------------------------------------------------------------------------------|
| Enclosure                                 | Plastic, type PC (UL 94 V-0)<br>Net dimensions (dxwxh):<br>93 x 53 x 58 mm / 3.7" x 2.1" x 2.3"<br>Color: Light Grey. RAL 7035                                                                           | Operation Temperature | 0°C to +60°C                                                                                                            |
| Weight                                    | 85 g.                                                                                                                                                                                                    | Stock Temperature     | -20°C to +85°C                                                                                                          |
| Mounting                                  | <ul style="list-style-type: none"> <li>Wall</li> <li>DIN rail EN60715 TH35.</li> </ul>                                                                                                                   | Operational Humidity  | 5% to 95% RH, with no condensation                                                                                      |
| Terminal Wiring (for low-voltage signals) | For terminal: solid wires or stranded wires (twisted or with ferrule)<br>1 core: 0.5mm <sup>2</sup> ... 2.5mm <sup>2</sup><br>2 cores: 0.5mm <sup>2</sup> ... 1.5mm <sup>2</sup><br>3 cores: not allowed | Stock Humidity        | <95% RH, with no condensation                                                                                           |
| BACnet MS/TP port                         | 1 x Serial EIA485 Plug-in screw terminal block (3 poles):<br>B, A, SG<br>SELV                                                                                                                            | Isolation voltage     | 1500 VDC. between RS485 and RC5 bus                                                                                     |
| AC unit port                              | 1 x RC5 or Serial EIA-485 Plug-in screw terminal block (3 poles):<br>SG, B, A<br>SELV                                                                                                                    | Isolation resistance  | 1000 MΩ                                                                                                                 |
| Switch 1 (SW1)                            | 1 x DIP-Switch for AC features and RC5 bus baud rate                                                                                                                                                     | Protection            | IP20 (IEC60529)                                                                                                         |
| Switch 2 (SW2)                            | 1 x DIP-Switch for bus device address and temperature information                                                                                                                                        | External power supply | 12VDC/AC 0.2A NEC Class 2 or Limited Power Source (PS2) and SELV rated PS. Max. 3 meters between device and external PS |
| Switch 3 (SW3)                            | 1 x DIP-Switch for primary EIA bus configuration                                                                                                                                                         | LED indicators        | 2 x Onboard LED - Operational status                                                                                    |



## 11 Error codes

Below you can find a list of error codes from Ductless air conditioning system.

| Error Code | Error in Remote Controller | Error description                                                                |
|------------|----------------------------|----------------------------------------------------------------------------------|
| 0          | N/A                        | No active error                                                                  |
| 1          | E0                         | Phase error or error in the phase sequence                                       |
| 2          | E1                         | Communication error                                                              |
| 3          | E2                         | T1 sensor error                                                                  |
| 4          | E3                         | T2A sensor error                                                                 |
| 5          | E4                         | T2B sensor error                                                                 |
| 6          | E5                         | T3 temperature and T4 temperature Compressor discharge temperature sensors error |
| 7          | E6                         | Zero cross error detection                                                       |
| 8          | E7                         | EEPROM memory error                                                              |
| 9          | E8                         | Indoor fan speeds out of control                                                 |
| 10         | E9                         | Communication error between the main panel and the visualization panel           |
| 11         | EA                         | Compressor's current overload error (4 times)                                    |
| 12         | EB                         | Inverter module protection                                                       |
| 13         | EC                         | Cooling error                                                                    |
| 14         | ED                         | Outdoor unit fault protection                                                    |
| 15         | EE                         | Water level fault detection                                                      |
| 16         | EF                         | Other errors                                                                     |
| 17         | P0                         | Vaporizer temperature protection                                                 |
| 18         | P1                         | Thawing or cold air protection                                                   |
| 19         | P2                         | Condenser high temperatures protection                                           |
| 20         | P3                         | Compressor temperature protection                                                |
| 21         | P4                         | Evacuation duct temperature protection                                           |
| 22         | P5                         | Discharge high pressure protection                                               |
| 23         | P6                         | Discharge low pressure protection                                                |
| 24         | P7                         | Current overload or under load protection                                        |
| 25         | P8                         | Compressor's current overload protection                                         |
| 26         | P9                         | Reserved                                                                         |
| 27         | PA                         | Reserved                                                                         |
| 28         | PB                         | Reserved                                                                         |
| 29         | PC                         | Reserved                                                                         |
| 30         | PD                         | Reserved                                                                         |
| 31         | PE                         | Reserved                                                                         |
| 32         | PF                         | Other protection measures                                                        |
| 65535 (-1) | N/A                        | Error in the communication of INMBSMID--I000 with the AC unit                    |

In case you detect an error code not listed, contact your nearest technical support service for more information on the error meaning.

53DS-900---117 (115 v)  
53DS-900---118 (230 v)

Accessory Condensate Pump  
for Ductless Split System  
Cooling Only and Heat Pump High Wall Units  
(Size 009-036)


## Installation Instructions

**NOTE:** Read and become familiar with these instructions before beginning installation.

### SAFETY CONSIDERATIONS

Improper installation, adjustment, alteration, service, maintenance, or use can cause explosion, fire, electrical shock, or other conditions which may cause death, personal injury, or property damage. Consult a qualified installer, service agency, or your distributor or branch for information or assistance. The qualified installer or agency must use factory-authorized kits or accessories when modifying this product. Refer to the individual instructions packaged with the kits or accessories when installing.

Follow all safety codes. Wear safety glasses, protective clothing, and work gloves. Use quenching cloth for brazing operations. Have fire extinguisher available. Read these instructions thoroughly and follow all warnings or cautions included in literature and attached to the unit. Consult local building codes and current editions of the National Electrical Code (NEC) NFPA 70. In Canada, refer to current editions of the Canadian electrical code CSA 22.1.

Recognize safety information. This is the safety-alert symbol . When you see this symbol on the unit and in instructions or manuals, be alert to the potential for personal injury. Understand these signal words; DANGER, WARNING, and CAUTION. These words are used with the safety-alert symbol. DANGER identifies the most serious hazards which **will** result in severe personal injury or death. WARNING signifies hazards which **could** result in personal injury or death. CAUTION is used to identify unsafe practices which **would** result in minor personal injury or product and property damage. NOTE is used to highlight suggestions which **will** result in enhanced installation, reliability, or operation.



### CAUTION

#### UNIT OPERATION HAZARD

Failure to follow this caution may result in unit failure and/or damage.  
Always follow instructions properly.




Fig. 1 – Accessory Condensate Pump Kit

A12227

Table 1—Accessory Condensate Pump Kit Contents

| ITEM                                       | QTY |
|--------------------------------------------|-----|
| 16-ft Transparent Suction/Discharge Tubing | 1   |
| Condensate Pump Assembly                   | 1   |
| Low-Voltage Power Cord                     | 1   |
| Transparent Detection Unit Vent Tubing     | 1   |
| Power Cable                                | 1   |
| Wire Ties                                  | 6   |
| Wall Mount Bracket                         | 1   |
| Adhesive                                   | 1   |
| Detection Unit Mounting Bracket            | 1   |
| Rubber Adapter                             | 1   |
| Detection Unit                             | 1   |



### WARNING

#### ELECTRICAL SHOCK HAZARD

Failure to follow this warning could result in personal injury or death.

Before beginning any modification or installation of this kit, be sure the main electrical disconnect is in the OFF position. Ensure power is disconnected to the fan coil unit. On some systems both the fan coil and the outdoor unit may be on the same disconnect. Tag the disconnect switch with a suitable warning label. There may be more than one disconnect.

Table 2—Accessory Package Usage

| BASE UNIT       | ACCESSORY MODEL NUMBER       |                                  |
|-----------------|------------------------------|----------------------------------|
|                 | 53DS-900---117<br>(115-1-60) | 53DS-900---118<br>(208/230-1-60) |
|                 | WIRING FIG. NO.              | WIRING FIG. NO.                  |
| 40GVC009---1    | 16                           |                                  |
| 40GVQ009---1    | 17                           |                                  |
| 40GVC012---1    | 16                           |                                  |
| 40GVQ012---1    | 17                           |                                  |
| 40GVC012---3    |                              | 18                               |
| 40GVQ012---3    |                              | 18                               |
| 40GVC018---3    |                              | 19                               |
| 40GVQ018---3    |                              | 19                               |
| 40GVC024---3    |                              | 19                               |
| 40GVQ024---3    |                              | 19                               |
| 40GVQ030---3    |                              | 19                               |
| 40GVC036---3    |                              | 19                               |
| 40GVQ036---3    |                              | 19                               |
| 40GVM009---3    |                              | 20                               |
| 40GVM012---3    |                              | 20                               |
| 40GVM018---3    |                              | 20                               |
| 40GXC(Q)009---1 | 11                           |                                  |
| 40GXC(Q)012---1 | 11                           |                                  |
| 40GXC(Q)018---3 | 14                           | 15                               |
| 40GXC(Q)024---3 | 14                           | 15                               |
| 40GXM009---3    | 14                           | 15                               |
| 40GXM012---3    | 14                           | 15                               |
| 40GXM018---3    | 14                           | 15                               |
| 40MVC(Q)009---1 | 8                            |                                  |
| 40MVC(Q)012---1 | 8                            |                                  |
| 40MVC(Q)012---3 | 9                            | 10                               |
| 40MVC(Q)018---3 | 14                           | 15                               |
| 40MVC(Q)024---3 | 14                           | 15                               |
| 40QNC(Q)030---3 |                              | 13                               |
| 40QNC(Q)036---3 |                              | 13                               |
| 40QNC018024---3 |                              | 12                               |
| 40QNC018---3    |                              | 12                               |
| 40QNC024---3    |                              | 12                               |
| PW3C(H)AM009    | 8                            |                                  |
| PW3C(H)AM012    | 8                            |                                  |
| PW3C(H)NM018    | 14                           | 15                               |
| PW3C(H)NM024    | 14                           | 15                               |
| RAS-09LKV-UL    | 14                           | 15                               |
| RAS-12LKV-UL    | 14                           | 15                               |
| RAS-15LKV-UL    | 14                           | 15                               |
| RAS-17LKV-UL    | 14                           | 15                               |
| RAS-22LKV-UL    | 14                           | 15                               |
| RAV-SP180KRT-UL | 14                           | 15                               |
| RAV-SP240KRT-UL | 14                           | 15                               |

## GENERAL

Use the two-part accessory kit (condensate pump and detection unit) with high wall fan coils. The pump operates whenever the condensate level in the detection unit is high enough to cause the magnetic float switch to send a signal to start the pump.

The float switch in the detection unit also prevents overflow and can act as a safety device by shutting down the system. The detection unit comes with normally closed (NC) alarm contacts (user optional, but recommended). The normally closed alarm contact is a dry contact rated for 8 amps at 250 volts. In the event of a problem such as a clogged drain or pump discharge line, the alarm contact can be wired to shut down the entire system. The condensate pump provides 10 ft (3.0 m) maximum suction lift (A)-Fig. 2.




Fig. 2 – Maximum Lengths

A12134

## INSTALLATION

Refer to Fig. 1 and Table 1 for kit content.

**NOTE:** To make the installation easier, install the detection unit assembly before installing the fan coil unit.

1. Unpack the contents of the condensate pump accessory package. Attach the rubber adapter and transparent vent tubing to the detection unit (see Fig. 6). Rubber adapter may be cut to size if 5/8" connection is required. If 7/8" connection to unit drain pipe is required, use rubber adapter as shipped. Do not use a vent tube longer than 2.95" (75 mm). Slide the mounting bracket onto the bottom of the detection unit. Uncoil the low voltage power cord.
2. Remove the fan coil mounting bracket from the back of the unit. Connect the detection unit with the rubber adapter, to the condensate drain line (see Fig. 6).
3. Peel the adhesive cover on the back of the detection unit mounting bracket and attach it to the inside of the unit adjacent to the fan coil drain as shown in Fig. 6. **Make sure the detection is installed horizontally for proper operation of the float switch.**
4. Attach one end of the transparent tubing to the detection unit. The tube can be connected to either the front or the rear as shown in Fig. 3. block the unused outlet with the plug supplied.





Fig. 3 – Detection Unit

A09398


5. Connect one end of the low voltage power cord to the telephone jack socket in the detection unit and route the cord and transparent drain tubing through the knockout on the side of the unit enclosure (see Fig. 6).
6. Determine the mounting location of the pump assembly. **The pump assembly must always be above the level of the detection unit.** For best operation, it is recommended that the pump assembly be mounted in a vertical position with the flow arrow on the pump pointing up (see Fig. 7). **Do not exceed 10 ft. (3.0 m) maximum suction lift.**

**NOTE:** in most applications, the pump will need to be mounted outside of the high wall unit for proper orientation (i.e. above drop ceiling).

7. Screw the bracket to the wall and attach the pump to the bracket as shown in Fig. 4 and Fig. 5.



**Fig. 4 – Pump Assembly Vertical**



**Fig. 5 – Pump Assembly Horizontal**

A12228

If the pump is not mounted in the vertical position, make sure that plug on the pump is above the refrigerant tubing. This is required to avoid water leaking onto the pump causing a short circuit. **The pump cannot be splashed nor located in a damp environment.**

8. Connect the other end of the low voltage power cord from the detection unit to the telephone jack socket in the pump assembly.
9. Cut the suction, transparent drain tubing after determining where it will connect to the inlet side of the pump mounted on the wall. Remove the cap on the pump inlet and connect draining tubing.

10. Attach the remaining transparent tubing to the discharge side of the pump. Keep the pipe vertical for at least 4 or 5 inches and do not exceed the 33 ft (10 m) limit or the value shown in (B) of Table 3 and Table 4. **In order to avoid siphoning action and running the pump dry, always connect the discharge tube to the drain at a higher level than the pump itself (pump should be higher than detection unit).** Be sure the condensate is discharged to a safe location where the presence of water does not pose any safety or health hazards.
11. Install the transparent vent tube (provided) on top of the detection unit. Route tube so it will stay vertical (see Fig. 6).
12. Wire the pump and the alarm circuit using the appropriate wiring diagram listed in Table 2.
13. Prime the pump at start-up and after each maintenance operation. To ensure proper operation, the suction pipe and part of the discharge pipe must be slowly filled with water using a squeeze bottle.
14. Test the unit. When the unit is mounted in place, the condensate pump system must be tested.
  - a. Be sure the Hi-Wall unit is installed on a level plane. Remove the front cover of the unit.
  - b. Slowly fill the condensate drain pan with water. Observe the pump discharge tubing to be sure that the pump is operating. If condensate is not being discharged through the discharge tubing, check to be sure that the lines are not kinked or obstructed, and installation parameters have been followed. If the optional alarm contact is wired, continue to pour water until the alarm circuit triggers.


**Table 3—True Flow Rates (Gallons / Hr)**

| 53DS-900 --- 117, 118 Condensate Pump Flow Rates |                          |                                                 |     |     |     |
|--------------------------------------------------|--------------------------|-------------------------------------------------|-----|-----|-----|
| Refer to Fig. 2 for (A), (B), (C)                |                          | Total tube length, 1/4" flexible hose (C)<br>ft |     |     |     |
| Suction Head (A)<br>ft                           | Discharge Head (B)<br>ft | 15                                              | 30  | 60  | 100 |
| 0                                                | 0                        | 5.0                                             | 4.7 | 4.5 | 4.2 |
|                                                  | 6                        | 4.2                                             | 3.9 | 3.7 | 3.5 |
|                                                  | 13                       | 3.0                                             | 2.9 | 2.8 | 2.6 |
|                                                  | 20                       |                                                 | 2.5 | 2.0 | 1.7 |
|                                                  | 26                       |                                                 | 1.6 | 1.3 | 1.1 |
|                                                  | 33                       |                                                 | 1.1 | 0.9 | 0.7 |
| 3.3                                              | 0                        | 3.7                                             | 3.4 | 3.2 | 2.9 |
|                                                  | 6                        | 2.9                                             | 2.6 | 2.4 | 2.1 |
|                                                  | 13                       | 0.5                                             | 1.8 | 1.6 | 1.3 |
|                                                  | 20                       |                                                 | 1.2 | 1.1 |     |
| 6.6                                              | 0                        | 2.9                                             | 2.6 | 2.4 | 2.1 |
|                                                  | 6                        | 2.4                                             | 2.1 | 1.8 | 1.6 |
|                                                  | 13                       |                                                 | 1.5 | 1.3 | 1.2 |
| 10                                               | 0                        | 2.6                                             | 2.4 | 2.1 | 1.8 |
|                                                  | 6                        | 2.1                                             | 1.8 | 1.6 | 1.3 |
|                                                  | 13                       |                                                 | 1.3 | 1.1 |     |

**Table 4—True Flow Rates (Liters / Hr)**


| 53DS-900 --- 117, 118 Condensate Pump Flow Rates |                          |                                                 |      |      |      |
|--------------------------------------------------|--------------------------|-------------------------------------------------|------|------|------|
| Refer to Fig. 2 for (A), (B), (C)                |                          | Total tube length, 1/4" flexible hose (C)<br>ft |      |      |      |
| Suction Head (A)<br>ft                           | Discharge Head (B)<br>ft | 15                                              | 30   | 60   | 100  |
| 0                                                | 0                        | 18.9                                            | 17.8 | 17.0 | 15.9 |
|                                                  | 6                        | 15.9                                            | 14.8 | 14.0 | 13.2 |
|                                                  | 13                       | 11.4                                            | 11.0 | 10.6 | 9.8  |
|                                                  | 20                       |                                                 | 9.5  | 7.6  | 6.4  |
|                                                  | 26                       |                                                 | 6.1  | 4.9  | 4.2  |
|                                                  | 33                       |                                                 | 4.2  | 3.4  | 2.6  |
| 3.3                                              | 0                        | 14.0                                            | 12.9 | 12.1 | 11.0 |
|                                                  | 6                        | 11.0                                            | 9.8  | 9.1  | 7.9  |
|                                                  | 13                       | 1.9                                             | 6.8  | 6.1  | 4.9  |
|                                                  | 20                       |                                                 | 4.5  | 4.2  |      |
| 6.6                                              | 0                        | 11.0                                            | 9.8  | 9.1  | 7.9  |
|                                                  | 6                        | 9.1                                             | 7.9  | 6.8  | 6.1  |
|                                                  | 13                       | 0.0                                             | 5.7  | 4.9  | 4.5  |
| 10                                               | 0                        | 9.8                                             | 9.1  | 7.9  | 6.8  |
|                                                  | 6                        | 7.9                                             | 6.8  | 6.1  | 4.9  |
|                                                  | 13                       |                                                 | 4.9  | 4.2  |      |

**NOTE:** Maximum suction plus discharge head is 33 ft (10 m). Longer lengths indicate horizontal condition.




A12229

**Fig. 6 – Rear of High Wall Unit with Mounted Condensate Pump**




A12230

**Fig. 7 – Accessory Condensate Pump Connections**




**Fig. 8 – 009, 012 (115-1-60) WIRING SCHEMATIC**

A12393




**Fig. 9 – (208/230-1-60) WIRING SCHEMATIC**

A12136




**Fig. 10 – (208/230-1-60) WIRING SCHEMATIC**

A13106




**Fig. 11 – (115-1-60) WIRING SCHEMATIC**

A12395




**Fig. 12 - (208/230-1-60) WIRING SCHEMATIC**

A12396




**Fig. 13 - (208/230-1-60) WIRING SCHEMATIC**

A12430




**Fig. 14 – (115-1-60) WIRING SCHEMATIC**

A13107




**Fig. 15 – (208/230-1-60) WIRING SCHEMATIC**

A13108




**Fig. 16 – 40GVC 9k, 12k (115-1-60) WIRING SCHEMATIC**

A13098




**Fig. 17 – 40GVQ 9k, 12k (115-1-60) WIRING SCHEMATIC**

A13099




**Fig. 18 – 40GVC/Q 12k (208/230-1-60) WIRING SCHEMATIC**

A13100



**Fig. 19 – 40GVC/Q 18k, 24k, 30k, 36k (208/230-1-60) WIRING SCHEMATIC**

A13101



**Fig. 20 – 40GVM 9k, 12k, 18k (208/230-1-60) WIRING SCHEMATIC**

A13102

## CLEANING AND MAINTENANCE



### WARNING

#### ELECTRICAL SHOCK HAZARD


Failure to follow this warning could result in personal injury or death.

Disconnect all power to unit to avoid possible electrical shock during cleaning or maintenance. Set unit power switch to OFF position.


At the beginning of each season clean the detection unit.

1. Disconnect tubing and low voltage power cord from the detection unit and slide unit out of mounting bracket
2. Remove the top of the detection unit and take out the float.
3. Clean the detection unit and the float using a solution of water containing 5% bleach.
4. Replace the float in its original position with the magnet side facing up.
5. Snap cover back into place.
6. Perform an operational test (see item 13 under installation section).


N730-03-Edition 13/11




**SIDE VIEW RETRACTED**



**SIDE VIEW EXPANDED**



**END VIEW RETRACTED**



**END VIEW EXPANDED**


(\*) - WIDTH IS ADJUSTABLE IN 1" INCREMENTS

**IMPORTANT NOTE: THE INSTALLER IS RESPONSIBLE FOR THETHERING AND BOLTING UNITS TO WITHSTAND WIND AND/OR SEISMIC LOADS.**

UNLESS OTHERWISE SPECIFIED:  
DIMENSIONS ARE IN INCHES (MILLIMETERS)  
TOLERANCES ARE: ANGLES ±1.0°  
FRACTIONAL SIZES X/16  
INCHES (MILLIMETERS)  
X = ±0.1 [X = ±2.5]  
XX = ±0.01 [X = ±1.3]  
XXX = ±0.005 [X = ±0.125]



|                                                                                                                                                                                                                                                                   |                                                                         |                            |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|----------------------------|
| CONFIDENTIAL - PROPRIETARY - DO NOT COPY<br>THIS INFORMATION IS FOR THE EXCLUSIVE USE OF THE<br>INSTALLER AND IS NOT TO BE COPIED OR<br>REPRODUCED OR DISTRIBUTED IN ANY FORM WITHOUT<br>WRITTEN PERMISSION FROM DIVERSITECH CORPORATION.<br>DO NOT SCALE DRAWING | MATERIAL:<br><br>DWG. NO. MINI SPLIT STAND - 1801<br>MODEL NO. QSMS1801 | WEIGHT<br>GMS.<br><br>REV. |
|                                                                                                                                                                                                                                                                   |                                                                         |                            |
|                                                                                                                                                                                                                                                                   | DESCRIPTION                                                             |                            |



| ITEM NO. | PART NUMBER | DESCRIPTION                     | Default/<br>QTY. |
|----------|-------------|---------------------------------|------------------|
| 1        | MS110       | Mini Split 18in J-Bar           | 4                |
| 2        | MS106       | Mini Split Extension Bar        | 2                |
| 3        | MS119       | Mini Split Long Saddle Arm      | 2                |
| 4        | MS114       | Mini Split Wide Stability Arm   | 2                |
| 5        | MS105       | Mini Split 6x6 Feet             | 4                |
| 6        | QSR042      | Mini Split Rubber Foot          | 8                |
| 7        | QSR008      | 1/4-20x1/2in Zinc Hex Bolt      | 8                |
| 8        | QSR015      | 1/4in Bonded Washers            | 8                |
| 9        | HDKMS05     | Hardware kit for QSMS1802, 2402 | 1                |

NOTE - ALL ASSEMBLY HARDWARE IS INCLUDED

UNLESS OTHERWISE SPECIFIED:  
 DIMENSIONS ARE IN INCHES (MILLIMETERS)  
 TOLERANCES ARE: ANGLES ±1.0°  
 FRACTIONAL SIZES XX/164

| INCHES        | MILLIMETERS   |
|---------------|---------------|
| .X = ±0.1     | [.X = ±2.5]   |
| .XX = ±0.01   | [.X = ±1.3]   |
| .XXX = ±0.005 | [.XX = ±0.13] |

THIRD ANGLE  
PROJECTION



|                                                                                                                                                                                                                                                                                                                                        |                                                                        |                |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------|----------------|
| CONFIDENTIAL - PROPRIETARY - DO NOT COPY<br>INFORMATION SET FORTH IN THIS DOCUMENT AND RELATED<br>INFORMATION IS THE CONFIDENTIAL PROPERTY OF DIVERSITECH<br>CORPORATION AND IS NOT TO BE COPIED OR<br>REPRODUCED OR DISTRIBUTED IN ANY FORM WITHOUT PRIOR<br>WRITTEN PERMISSION FROM DIVERSITECH CORPORATION.<br>DO NOT SCALE DRAWING | MATERIAL:<br>DWG. NO.<br>MINI SPLIT STAND - 1801<br>MODEL NO. QSMS1801 | WEIGHT<br>GMS. |
|                                                                                                                                                                                                                                                                                                                                        |                                                                        | REV.<br>2 of 2 |



426 INDUSTRIAL AVENUE, SUITE 146  
WILLISTON, VT 05495  
P: (802)862-9381  
WWW.MJINC.COM



81 Maple Street • Burlington VT 054  
802-864-6844 • [www.hfrinc.com](http://www.hfrinc.com)  
Architecture • Planning • Interiors

## PROJECT MILESTONE

### CONSTRUCTION PLANS

[illegible]

BURLINGTON SCHOOL DISTRICT

BURLINGTON, VERMONT


BURLINGTON AVIATION TECHNICAL CENTER

200 DAVINCI DRIVE, SOUTH BURLINGTON, VT 05403

**CLIENT:**

**PROJECT:**

|                 |            |
|-----------------|------------|
| <b>DRAWN</b>    | WH         |
| <b>DESIGNED</b> | MM         |
| <b>CHECKED</b>  | PP         |
| <b>SCALE</b>    |            |
| <b>DATE</b>     | 11/04/24   |
| <b>PROJECT</b>  | T-18715.02 |



**DRAWING TITLE**

## MECHANICAL SCHEDULES

DRAWING NUMBER

M002

## VRF SYSTEM INDOOR UNIT SCHEDULE

| UNIT NO. | AREA SERVED | MAX<br>SUPPLY<br>C.F.M | ELECTRICAL |     |             |     |              | HEATING<br>MBH | COOLING<br>MBH | PHYSICAL PROPERTIES |        |         |             | DESIGN BASIS            | NOTES |
|----------|-------------|------------------------|------------|-----|-------------|-----|--------------|----------------|----------------|---------------------|--------|---------|-------------|-------------------------|-------|
|          |             |                        | MCA        | MOP | VOLTS/PHASE | KW  | CONN. POINTS |                |                | LENGTH'             | DEPTH" | HEIGHT" | WEIGHT LBS. |                         |       |
| AC-130   | RM. 130     | 755                    | N/A        | N/A | 208/1       | N/A | 1            | N/A            | 24             | 46-1/16             | 11-5/8 | 14-3/8  | 46          | TRANE - TPKA0A0241KA70A | 1     |

NOTES:  
1. UNIT POWERED BY OUTDOOR UNIT.

## VRF SYSTEM OUTDOOR UNIT SCHEDULE

| UNIT NO. | LOCATION | SYSTEM SERVED | EER/SEER | COP | NOMINAL CAPACITY |          | ELECTRICAL  |          |          |             | PHYSICAL PROPERTIES |         |         |             | DESIGN BASIS             | NOTES |
|----------|----------|---------------|----------|-----|------------------|----------|-------------|----------|----------|-------------|---------------------|---------|---------|-------------|--------------------------|-------|
|          |          |               |          |     | MBH HEAT         | MBH COOL | VOLTS/PHASE | UNIT MCA | UNIT MOP | CONN. POINT | WIDTH"              | DEPTH"  | HEIGHT" | WEIGHT LBS. |                          |       |
| OSHP-1   | SITE     | AC-130        | 0/21.4   | 3.7 | N/A              | 24       | 208/1       | 19       | 26       | 1           | 37-13/32            | 14-3/16 | 37-1/8  | 151         | TRANE - TRU/YA0241HA70NA | -     |

**FINANCIAL ASSISTANCE AWARD****FEDERAL AWARD ID NUMBER**

60NANB23D159

**RECIPIENT NAME**

Burlington School District

**PERIOD OF PERFORMANCE**

09/01/2023 - 08/31/2026

**STREET ADDRESS**

150 Colchester Ave

**FEDERAL SHARE OF COST**

\$9,900,000.00

**CITY, STATE ZIP**

Burlington, VT 05401-1422

**RECIPIENT SHARE-OF COST**

\$0.00

**AUTHORITY**

Consolidated Appropriations Act, 2022

**TOTAL ESTIMATED COST**

\$9,900,000.00

**CFDA NO. AND NAME**

11.617 Congressionally-Identified Projects

**PROJECT TITLE:**

Burlington Aviation Technology Center Facility

This Award Document (Form CD-450) signed by the Grants Officer constitutes an obligation of Federal funding. By signing this Form CD-450, the Recipient agrees to comply with the Award provisions checked below and attached. Upon acceptance by the Recipient, the Form CD-450 must be signed by an authorized representative of the Recipient and returned to the Grants Officer. If not signed and returned without modifications by the Recipient within 30 days of receipt, the Grants Officer may unilaterally withdraw this Award offer and de-obligate the funds.

☒ DEPARTMENT OF COMMERCE FINANCIAL ASSISTANCE STANDARD TERMS AND CONDITIONS

R &amp; D AWARD

FEDERAL-WIDE RESEARCH TERMS AND CONDITIONS, AS ADOPTED BY THE DEPT. OF COMMERCE

☒ SPECIFIC AWARD CONDITIONS

☒ LINE ITEM BUDGET

☒ 2 CFR PART 200, UNIFORM ADMINISTRATIVE REQUIREMENTS, COST PRINCIPLES, AND AUDIT REQUIREMENTS, AS ADOPTED PURSUANT TO 2 CFR § 1327.101

48 CFR PART 31, CONTRACT COST PRINCIPLES AND PROCEDURES

MULTI-YEAR AWARD. PLEASE SEE THE MULTI-YEAR SPECIFIC AWARD CONDITION.

☒ OTHER(S): U.S. DEPARTMENT OF COMMERCE, NATIONAL INSTITUTE OF STANDARDS AND TECHNOLOGY  
STANDARD TERMS AND CONDITIONS FOR EXTRAMURAL CONSTRUCTION PROJECTS, MAY 11,  
2023

SIGNATURE OF DEPARTMENT OF COMMERCE GRANTS OFFICER

SHIOU YUN LIU

Digitally signed by SHIOU YUN

LIU

Date: 2023.09.15 08:23:32 -04'00'

Shiou Liu

DATE

PRINTED NAME, PRINTED TITLE, AND SIGNATURE OF AUTHORIZED RECIPIENT OFFICIAL

Tom Flanagan, Superintendent



DATE

9/18/23

Award Number: 60NANB23D159, Amendment Number 0

Federal Program Officer: Robert Slocum

Requisition Number: 195161

Employer Identification Number: 471351664

UEI Number: VCCSKXGSMEJ5

Recipient ID: 1155128

Requestor ID: 1155128

**Award ACCS Information**

| Bureau | FCFY | Project-Task | Organization           | Object Class | Obligation Amount |
|--------|------|--------------|------------------------|--------------|-------------------|
| 57     | 2023 | 1959000-000  | 10-19-0195-00-00-00-00 | 41-98-00-00  | \$9,900,000.00    |

**Award Contact Information**

| Contact Type   | Contact Name        | Email              | Phone      |
|----------------|---------------------|--------------------|------------|
| Administrative | Mr. Barry Gruessner | bgruessn@bsdvt.org | 8028648462 |

**NIST Grants Officer:**

Shiou Liu  
100 Bureau Drive, MS 1650  
Gaithersburg, MD 20899-1650  
(301) 975-8245

**NIST Grants Specialist:**

LaShae Green  
100 Bureau Drive, MS 1650  
Gaithersburg, MD 20899-1650  
(301) 975-3070

**NATIONAL INSTITUTE OF STANDARDS AND TECHNOLOGY  
2022 CONGRESSIONALLY IDENTIFIED CONSTRUCTION GRANT PROGRAM  
FINANCIAL ASSISTANCE  
SPECIFIC AWARD CONDITIONS**

---

**1. Description of Work:**

The National Institute of Standards and Technology (NIST) hereby enters into this grant number 60NANB23D159 with Burlington School District to support the work described in the proposal entitled “Burlington Aviation Technology Center Facility” dated November 17, 2022, and any revisions received during the application review, which are hereby incorporated into this award by reference.

The scope of work for this project is anticipated to provide a total building space in the range of 30,000 to 45,000 gross SF to include classrooms, offices, shops/tech areas, storage, hangar space and general building facilities with the intent to educate up to 150 high school students and adults each year with the technical center housing aviation for 11<sup>th</sup> and 12<sup>th</sup> graders as well as adult programs that finishes the airframe and powerplant training.

Work will be completed in accordance with the schedule submitted by Burlington School District in the Project Management and Schedule dated November 17, 2022.

The Burlington School District shall diligently pursue the development of the project to ensure completion within this time schedule and shall promptly notify NIST in writing of any event that could substantially delay meeting any of the prescribed time limits for the project as set forth above. The Burlington School District further acknowledges that failure to meet the development time schedule may result in NIST taking action to suspend or terminate the Award in accordance with the regulations set forth at 2 CFR § 200.339.

Where the terms of this award and the proposal differ, the terms of this award shall prevail.

**2. Recipient Contact Information:**

**Administrative:**

Barry Gruessner  
Grants Director  
Burlington School District  
150 Colchester Avenue  
Burlington, VT 05401-1422  
Telephone: 802-864-8462  
Email: [bgruessn@bsdvt.org](mailto:bgruessn@bsdvt.org)

NIST Financial Assistance Award Number: 60NANB23D159

Amendment: NEW

Recipient: Burlington School District

**Authorized Representative:**

Tom Flanagan  
Superintendent  
Burlington School District  
150 Colchester Avenue  
Burlington, VT 05401-1422  
Telephone: 802-865-5332  
Email: [tflanagan@bsdvt.org](mailto:tflanagan@bsdvt.org)

**3. NIST Award Contact Information:**

**Grants Officer:**

Michelle Shiouyun Liu  
National Institute of Standards and Technology  
100 Bureau Drive, Mail Stop 1650  
Gaithersburg, MD 20899-1650  
Telephone: 301-975-8245  
Email: [shiouyun.liu@nist.gov](mailto:shiouyun.liu@nist.gov)

**Grants Specialist:**

LaShae Green  
National Institute of Standards and Technology  
100 Bureau Drive, Mail Stop 1650  
Gaithersburg, MD 20899-1650  
Telephone: 301-975-3070  
Email: [lashae.green@nist.gov](mailto:lashae.green@nist.gov)

**Federal Program Officer:**

Robert Slocum  
National Institute of Standards and Technology  
100 Bureau Drive  
Gaithersburg, MD 20899  
Email: [robert.slocum@nist.gov](mailto:robert.slocum@nist.gov)

**4. Award Payments:**

This award is hereby funded through advanced payments using the Department of Treasury's Automated Standard Application for Payments (ASAP) system. Payments will be issued in accordance with 2 CFR § 200.305 and the Department of Commerce Financial Assistance Standard Terms and Conditions, B.02, dated November 12, 2020.

Payments for allowable costs may be drawn down as needed by the Recipient enrolled in ASAP. Funds may be requested through ASAP by the authorized *Payment Requestor* who is the individual designated by the Recipient to access Federal funds.

NIST Financial Assistance Award Number: 60NANB23D159

Amendment: NEW

Recipient: Burlington School District

This award has the following control or withdrawal limits set in ASAP:

- ☐ None
- ☐ Agency Review required for all withdrawals (see explanation below)
- ☐ Agency Review required for all withdrawal requests over  
\$ \_\_\_\_\_ (see explanation below)
- ☒ Maximum Draw Amount controls (see explanation below)
  - \$ \_\_\_\_\_ each month
  - \$ \_\_\_\_\_ each quarter
  - \$0.00 \_\_\_\_\_ Max drawdown amount

**Explanation:**

**Environmental & Historic Compliance Requirements**

A total of \$9,900,000.00 in Federal funding is hereby withheld until the requirements identified in Specific Award Condition (SAC) #17 Environmental and Historic Review is satisfied. A Six-Month Expenditure Plan may be submitted to request funding for expenditures limited to Environmental and Historic Requirement compliance as identified in SAC #17.

In addition, the final site selection for the Burlington Aviation Technology Center Facility must be provided to NIST and approved by NIST prior to advertisement of construction. All federal funding is hereby withheld until this requirement is satisfied, as identified in SAC #19 Final Site Selection, below.

**5. Return Payments for Funds Withdrawn through ASAP:**

Funds that have been withdrawn through ASAP may be returned to ASAP via the Automated Clearing House (ACH) or via FEDWIRE. The ACH or FEDWIRE transaction may only be completed by the Recipient's financial institution. Full or partial amounts of payments received by a Payment Requestor/Recipient Organization may be returned to ASAP. All funds returned to the ASAP system will be credited to the ASAP Suspense Account. The Suspense Account allows the Regional Financial Center to monitor returned items and ensure that funds are properly credited to the correct ASAP account. Returned funds that cannot be identified and classified to an ASAP account will be dishonored and returned to the originating depository financial institution (ODFI). The Payment Requestor/Recipient Organization should notify the NIST Grants Office and provide a reason whenever return payments are made.

It is essential that the Payment Requestor/Recipient Organization provide its financial institution with ASAP account information (ALC, Recipient ID and Account ID) to which the return is to be credited. Additional detailed information is accessible at:  
<https://www.fiscal.treasury.gov/asap/>.

**6. Period of Performance and Funding Limitations:**

NIST Financial Assistance Award Number: 60NANB23D159  
Amendment: NEW  
Recipient: Burlington School District

The period of performance and budget incorporated into this award cover a 3-year period of performance and provide for a maximum total amount of \$9,900,000.00 in Federal funding. This award is being fully funded via this award action.

The maximum amount of NIST funding in support of this award will not exceed the amount specified in the award documents, unless otherwise amended in writing by the NIST Grants Officer. The Department of Commerce is not liable for any obligations, expenditures, or commitments which involve any amount in excess of the Federal funds being made available pursuant to this award.

**7. Request for Application - 2022 Congressionally Identified Construction Grant Program:**

The Department of Commerce, National Institute of Standards and Technology Request for Application (RFA) No. 2022-NIST-RFA-CICGP-01, dated October 18, 2022, is incorporated by reference into this award. It is accessible at:  
<https://www.grants.gov/web/grants/view-opportunity.html?oppId=344108>

**8. Department of Commerce Pre-Award Notification Requirements for Grants and Cooperative Agreements:**

The Department of Commerce Pre-Award Notification Requirements for Grants and Cooperative Agreements as published in the *Federal Register* on December 30, 2014 (79 FR 78390) is incorporated by reference into this award. It is accessible at:  
<http://www.gpo.gov/fdsys/pkg/FR-2014-12-30/pdf/2014-30297.pdf>.

**9. Uniform Administrative Requirements, Cost Principles and Audit Requirements**

Through 2 C.F.R. § 1327.101, the Department of Commerce adopted Uniform Administrative Requirements, Cost Principles, and Audit Requirements for Federal Awards at 2 C.F.R. Part 200, which apply to awards in this program. Refer to <http://go.usa.gov/SBYh> and <http://go.usa.gov/SBg4>. Awards issued pursuant to this program may be subject to specific award conditions as authorized by 2 C.F.R. § 200.208.

**10. Deviation to the Department of Commerce Financial Assistance Standard Terms and Conditions, Section A.01 "Reporting Requirements":**

The Recipient must submit a Federal Financial Report (SF-425) and Performance Progress Report on a quarterly basis for the periods ending March 31, June 30, September 30, and December 31, or any portion thereof.

Reports are due no later than 30 calendar days following the end of each reporting period. A final SF-425 and Performance Progress Report must be submitted within 120 days after the expiration of the period of performance.

All SF-425 and Performance Progress Reports must be submitted to: [GReports@nist.gov](mailto:GReports@nist.gov), within the prescribed timeframes identified in the terms and conditions of the award.

The Recipient organization name, NIST award number, and reporting period must be included in the email subject line. The Recipient contact information should be included in the body of the message. To the greatest extent possible, SF-425 and Performance Progress Reports should be submitted together in the same email.

SF-425 and Performance Progress Reports must not be sent directly to NIST personnel (e.g. Grants Specialist, Grants Officer, Administrative Assistant, GMD Division Chief, Federal Program Officer, etc.).

Any SF-425 or Performance Progress Reports sent directly to NIST personnel will be returned to the sender with instructions on how to submit through the [GReports@nist.gov](mailto:GReports@nist.gov) mailbox.

No other correspondence may be sent through this mailbox; timely responses to any other inquiries received in this mailbox are not guaranteed. The mailbox will not be used for any other purpose except for purposes identified above.

**11. Department of Commerce Financial Assistance Standard Terms and Conditions:**

As indicated on the Form CD-450 for this award, the Department of Commerce Financial Assistance Standard Terms and Conditions (ST&C) issued November 12, 2020, are incorporated by reference into this award. The Department's ST&C, as well as a link to 2 CFR Part 200, are accessible at: <https://www.commerce.gov/oam/policy/financial-assistance-policy>.

**12. NIST Standard Terms and Conditions for Extramural Construction Projects:**

As indicated on the Form CD-450 for this award, the National Institute of Standards and Technology Standard Terms and Conditions for Extramural Construction Projects (Construction ST&Cs) dated May 11, 2023 are incorporated by reference into this award. The Construction ST&Cs are accessible at [NIST Standard Terms and Conditions for Extramural Construction Projects | NIST](#).

**13. Unfunded Grant Actions Mailbox (UGAM):**

Requests for unfunded award actions, which include, but are not limited to, requests for no-cost extension, change in key personnel, change in scope of work, and budget revisions must be submitted to: [UGAM@nist.gov](mailto:UGAM@nist.gov), within the prescribed timeframes identified in the terms and conditions of the award.

NIST Financial Assistance Award Number: 60NANB23D159

Amendment: NEW

Recipient: Burlington School District

Unfunded award action requests and related correspondence, including justification to support the request, sent to the mailbox must contain the following information in the email subject line: (1) Recipient name; (2) NIST award number; (3) Principal Investigator/Project Director; and (4) Action being requested (e.g. no cost extension, change in key personnel, etc.).

Unfunded award action requests must not be sent directly to NIST personnel (e.g. Grants Specialist, Grants Officer, Administrative Assistant, GMD Director, Federal Program Officer, etc.).

Any requests sent directly to NIST personnel will be returned to the sender with instructions on how to submit through the UGAM@nist.gov mailbox.

No other correspondence may be sent through this mailbox; timely responses to any other inquiries received in this mailbox are not guaranteed. The mailbox will not be used for any other purpose except for purposes identified above.

Requests that are processed will be authorized via a Form CD-451 Amendment to the Financial Assistance Award or a Non-Funded Administrative Change Letter.

**14. Supervision of the Recipient's Staff and Associates and Compliance with NIST Policies on Use of Federal Facilities and Equipment:**

Consistent with Department of Commerce Financial Assistance Standard Terms and Conditions, Section A.05, nothing in this award will be construed as authorizing the Recipient or its employees, agents, or assigns to act as an agent or assign of NIST, and the Recipient must exercise all diligence to ensure that no third party construes the Recipient as an actual, ostensible, or apparent agent of NIST. For purposes of this award, the use of the term "personnel" herein includes all third parties, such as contractors, subrecipients, students, fellows, or others participating under the direction of the Recipient's programs. The Recipient acknowledges that it is independent of NIST in the performance of the approved projects, and that the Recipient assumes full and sole responsibility for all benefits and protections of the Recipient's personnel and agents whose services are utilized by the Recipient in the execution of this award.

Accordingly, the Recipient must control the means and manner of its personnel's activities on the project, including those conducted on a NIST campus, on Recipient property, and at other locations for the project. The Recipient must directly provide a salary, stipend, or other funding to the personnel, and must establish the work schedule and tenure for the personnel. The Recipient is the supervisor of record for the personnel and will coordinate with NIST as needed to ensure that the research remains consistent with NIST program objectives.

**15. Estimated Useful Life:**

The estimated useful life of the building renovation portion of this project is 15 years from when the date on which the Certificate of Occupancy for the renovations is issued.

**16. Property Trust Relationship and Public Notice Filings for Grant-Acquired Property:**

In accordance with 2 CFR § 200.316 (Property trust relationship), real property, equipment, and intangible property, that are acquired or improved with a Federal award must be held in trust by the non-Federal entity (*i.e.*, Recipient or Subrecipient) as trustee for the beneficiaries of the project or program under which the property was acquired or improved. This trust relationship exists throughout the duration of the property's estimated useful life, as determined by the Grants Officer in consultation with the Program Office, during which time the Federal Government retains an undivided, equitable reversionary interest in the property (Federal Interest). The non-Federal entity must comply with all use and disposition requirements and restrictions as set forth in 2 C.F.R. §§ 200.310 (Insurance coverage) through 200.316 (Property trust relationship), as applicable, and in the terms and conditions of the Federal award.

The Grants Officer may require a non-Federal entity (*i.e.*, a Recipient or Subrecipient) to execute and to record (as applicable) a statement of interest, financing statement (Form UCC-1), lien, mortgage or other public notice of record to indicate that real or personal property acquired or improved in whole or in part pursuant to this award is subject to the Federal Interest, and that certain use and disposition requirements apply to the property. The statement of interest, financing statement (Form UCC-1), lien, mortgage or other public notice must be acceptable in form and substance to the NIST Grants Officer and must be placed on record in accordance with applicable State and local law, with continuances re-filed as appropriate. In such cases, the NIST Grants Officer may further require the non-Federal entity to provide a written statement from a licensed attorney in the jurisdiction where the property is located, certifying that the Federal Interest has been protected, as required under the award and in accordance with applicable State and local law. The attorney's statement, along with a copy of the instrument reflecting the recordation of the Federal Interest, must be promptly returned to the Grants Officer.

Without releasing or excusing the non-Federal entity from these obligations, the non-Federal entity, by execution of the financial assistance award or by expending Federal financial assistance funds (in the case of a subrecipient), authorizes the NIST Grants Officer to file such notices and continuations as it determines to be necessary or convenient to disclose and protect the Federal Interest in the property. The NIST Grants Officer may elect not to release any or a portion of the Federal award funds until the non-Federal entity has complied with this provision and any other applicable award terms or conditions, unless other arrangements satisfactory to the NIST Grants Officer are made.

**17. Environmental and Historic Review:**

NIST Financial Assistance Award Number: 60NANB23D159

Amendment: NEW

Recipient: Burlington School District

The Recipient must comply with all applicable requirements, environmental and historic preservation laws, Executive Orders, regulations, standards, and guidance, and identify to NIST any impact a project may have on the environment or historic resources.

**Project implementation may not begin prior to the completion of a review of potential environmental impacts, per the National Environmental Policy Act of 1969 (42 U.S.C. 4321, et. seq.) (NEPA) and Section 106 of the National Historic Preservation Act of 1966 (16 U.S.C. § 470, et. seq.).**

The completion of NEPA compliance activities will result in one of the following: a Categorical Exclusion, an Environmental Assessment/Finding of No Significant Impact (EA/FONSI), or an Environmental Impact Statement. A decision document will not be issued until all required consultations, including, Section 7 of the Endangered Species Act (16 U.S.C. §1531, et. seq.), and any other required consultations are complete. The Recipient must also address compliance with all other applicable federal, state, and local environmental laws and regulations.

Under Section 106 of the NHPA, federal agencies, and by extension recipients of federal grant funds, must evaluate the potential effects of any proposed projects ("undertakings") on properties listed on, or eligible for listing on, the National Register of Historic Places. Grant recipients are encouraged to initiate Section 106 consultation with relevant State Historic Preservation Offices (SHPOs) or, in the case of institutions located on tribal lands, the proper Tribal Historic Preservation Office (THPO) as directed by NIST. NIST will remain involved in resolution in the event of an adverse effect determination.

**A Environmental and Historic Review, to include any required consultations under NEPA and Section 106 of the NHPA, must be completed no later than six months after the award start date; unless a formal request for extension is submitted and approved by the Grants Officer. The Recipient must comply with all conditions placed on the project as the result of the consultation processes. The Recipient may not expend any federal grant funds, except as authorized by the Grants Officer pursuant to approval of the 6-month expenditure plan (discussed below).**

The Recipient is required to provide the following information that will enable NIST to make a preliminary determination regarding the potential impact of the proposed project on environmental and historic resources:

**1. A thorough description of all proposed project activities, particularly buildings and other capital improvement activities that will be conducted. Include: (i) the area and extent of earthwork (drilling, excavation, fill, blasting, dredging, etc.), (ii) environmental communication, documentation, or permitting (planned, pending, or in place), (iii) any determination upon the project by any department of environment or other agency or office, (iv) floodplain mapping on the site itself or any adjacent or contiguous property, (v) any special interest in the project or the site, (vi) any public meetings planned or held regarding the on the site itself or adjacent or contiguous property, (vii) any threatened or**

endangered species or any migratory birds or bald or golden eagles on the site itself or adjacent or contiguous property, or (viii) any essential fish habitat or any portion of the National Wild and Scenic River System or Coastal Barrier System or navigable waters on the site itself or adjacent or contiguous property, (ix) any waters of any stream or other body of water “proposed or authorized, permitted or licensed to be impounded, diverted, or otherwise controlled or modified”, (x) any identified or potential wetland on the site itself or any adjacent or contiguous property, (xi) any hazardous or regulated substances or Superfund activity on the site itself or adjacent or contiguous property, and/or (xii) any invasive species on the site itself or adjacent or contiguous property.

2. Maps of the project area and ground-level and aerial photographs with installation/renovation locations clearly marked on the buildings impacted. Free online resources, such as Google maps or similar images, are acceptable.

3. For the list of buildings, referenced in Item #1, state the year those buildings were first constructed as well as the dates of any subsequent major renovations. For buildings that are 45 years old or older, provide photos of installation sites, as well as exterior and interior photos of the building. Provide any property relevant to this application which is (i) within the viewshed of a registered historic property or (ii) within a historic district or (iii) registered as historic itself or (iv) noted to be historically or architecturally significant in any study or article of public interest. Provide any communication, documentation, or permitting under the project, e.g., determination upon the project by a SHPO and/or THPO.

**NOTE: The Recipient must submit a draft Environmental and Historic Review with all initial required project information listed above in Items #1 – #3 to NIST via UGAM@nist.gov no later than 60 calendar days after award start date, unless an extension has been requested in writing by the Recipient and approved by the Grants Officer.**

Follow-on information may be required for NIST to determine the level of impacts of the project on environmental and historic resources. If consultation is required, grantees are encouraged to initiate consultation as referenced above and must provide NIST with relevant documentation of the consultation process. Once appropriate and applicable consultations have been completed, and environmental review documentation has been completed, NIST will review all documentation and determine whether the review sufficiently addresses all resource areas and whether the project may qualify for an approval decision.

Once the above information is provided, NIST will review and provide guidance on the next steps that the recipient should take regarding required consultations and/or environmental and historic preservation documentation required to make environmental determinations. Next steps may include, but are not limited to, the submittal and completion of the following:

1. The completion of any required consultations as described above where applicable and directed by NIST, to include consultations with the SHPO and/or THPO and the appropriate federally-recognized Native American tribes (if applicable), under Section 106 of the NHPA, and/or consultations with the USFWS under Section 7 of the ESA;
2. The completion of environmental review and issuance by NIST of a decision document, as described above, that meets the requirements of NEPA; and
3. Compliance with all other applicable federal, state, and local environmental laws and regulations.

The Recipient is required to provide any information requested by NIST in a timely and effective manner to ensure both initial and ongoing compliance with environmental and historic preservation laws, regulations, and best practices. All such information must be sent to the FPO.

The Recipient shall notify NIST within 24 hours upon receipt of any notices of foreclosure; notices for continuing consultation received from the SHPO, THPO or other consulting party; or notices of noncompliance received from consulting authorities or regulatory agencies. These notices shall be sent to the FPO. Projects which, after consultation with appropriate agencies, are determined to be ineligible for a CE will require the development of an EA/FONSI. The Recipient may wish to coordinate with NIST to rescope or descope the proposed project to avoid or minimize impacts to environmental and historic resources.

Any change to the approved project scope, resulting from consultations or for other reasons, that have the potential for altering the nature or extent of environmental or cultural resources impacts must immediately be brought to the attention of NIST and will be re-evaluated for compliance with applicable regulatory requirements.

For all ground disturbing activities in the vicinity of known archaeological sites or suspected or known burials, the Recipient must ensure that an archaeologist who meets the Secretary of the Interior's Professional Qualification Standards monitors ground disturbance, and if any potential archeological resources or buried human remains are discovered, then the Recipient must immediately cease construction in that area and notify NIST and the interested SHPO, THPO, and tribes. Such construction activities may then only continue with the written approval of NIST.

#### **6-Month Expenditure Plan**

While this SAC is in effect, the Recipient shall submit, in advance of any program fund drawdowns from ASAP.gov, a 6-month expenditure plan that presents the proposed expenditure of award funds prior to the completion of the environmental review process, including any preliminary procurement activities. The NEPA Coordinator and the Federal

Preservation Officer will review the plan and provide recommendations to the Federal Program Officer and the Grants Officer for final approval to ensure that the proposed activities and expenditures are reasonable and necessary in the context of environmental and historical compliance. Approval of the Grants Officer is required prior to fund drawdowns of the 6-Month Expenditure Plan through ASAP.gov.

The allowable use of funds for preliminary expenditures prior to beginning project implementation includes, but is not limited to, the initiation of activities necessary to meet the project completion requirements as specified in the award including environmental and historic preservation requirements:

1. Required environmental and historic preservation consultation activities;
2. Purchase or lease of equipment, or entering into binding contracts to do so; and
3. Purchase of applicable or conditional insurance.

The allowable use of preliminary expenditure funds is limited; must not result in an irrevocable commitment of resources; and is only allowed after inclusion in and approval of a 6-month expenditure plan.

#### **18. Signage and Public Acknowledgement Requirements:**

a. Signs - The Recipient is encouraged to include project signage, satisfactory in form and content to NIST, that identifies the nature of the project and indicates that “the project is funded by the Consolidated Appropriations Act, 2022.” In addition, guidelines for project signage, including an emblem and corresponding logomark, is available in the Official Investing in America Emblem Style Guide: <https://www.whitehouse.gov/wp-content/uploads/2023/02/Investing-in-America-Brand-Guide.pdf>. Costs associated with signage must be reasonable and limited. The Recipient is encouraged to use recycled or recovered materials when procuring signs. Signs should not be produced or displayed if doing so results in unreasonable cost, expense, or recipient burden. Any construction site sign should be displayed throughout the construction phase of the project in an easily visible location directly linked to the work taking place. The Recipient is responsible to maintain the sign in good condition throughout the construction period.

b. Plaque - Any plaque installed at the discretion of the Recipient, citing the origins or history of the project, should identify the project as a “project funded by Consolidated Appropriations Act, 2022.”

c. Communications - Any banner or other message intended for public display on the project site should remain within the spirit of transparency and public information provided herein.

#### **19. Final Site Selection:**

NIST Financial Assistance Award Number: 60NANB23D159

Amendment: NEW

Recipient: Burlington School District

Within 60 calendar days of the award start date, the Recipient must provide to the Federal Program Officer and Grants Specialist identified in this award, a final site selection for the Burlington Aviation Technology Center Facility. The site selection must be approved by NIST prior to advertisement of construction. All grant funding will be withheld until this Specific Award Condition is deemed satisfied in writing by the NIST Grants Officer.

---

**End of Specific Award Conditions**

### BUDGET INFORMATION - Construction Programs

**NOTE:** Certain Federal assistance programs require additional computations to arrive at the Federal share of project costs eligible for participation. If such is the case, you will be notified.

| COST CLASSIFICATION                                                                                                                                  | a. Total Cost                                 | b. Costs Not Allowable for Participation   | c. Total Allowable Costs (Columns a-b)                                                                                           |
|------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|--------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| 1. Administrative and legal expenses                                                                                                                 | \$ <input type="text"/>                       | \$ <input type="text"/>                    | \$ <input type="text"/>                                                                                                          |
| 2. Land, structures, rights-of-way, appraisals, etc.                                                                                                 | \$ <input type="text"/>                       | \$ <input type="text"/>                    | \$ <input type="text"/>                                                                                                          |
| 3. Relocation expenses and payments                                                                                                                  | \$ <input type="text"/>                       | \$ <input type="text"/>                    | \$ <input type="text"/>                                                                                                          |
| 4. Architectural and engineering fees                                                                                                                | \$ <input type="text" value="947,427.00"/>    | \$ <input type="text" value="547,427.00"/> | \$ <input type="text" value="400,000.00"/>                                                                                       |
| 5. Other architectural and engineering fees                                                                                                          | \$ <input type="text" value="50,000.00"/>     | \$ <input type="text"/>                    | \$ <input type="text" value="50,000.00"/>                                                                                        |
| 6. Project inspection fees                                                                                                                           | \$ <input type="text" value="600,000.00"/>    | \$ <input type="text"/>                    | \$ <input type="text" value="600,000.00"/>                                                                                       |
| 7. Site work                                                                                                                                         | \$ <input type="text" value="7,050,000.00"/>  | \$ <input type="text"/>                    | \$ <input type="text" value="7,050,000.00"/>                                                                                     |
| 8. Demolition and removal                                                                                                                            | \$ <input type="text"/>                       | \$ <input type="text"/>                    | \$ <input type="text"/>                                                                                                          |
| 9. Construction                                                                                                                                      | \$ <input type="text"/>                       | \$ <input type="text"/>                    | \$ <input type="text"/>                                                                                                          |
| 10. Equipment                                                                                                                                        | \$ <input type="text"/>                       | \$ <input type="text"/>                    | \$ <input type="text"/>                                                                                                          |
| 11. Miscellaneous                                                                                                                                    | \$ <input type="text"/>                       | \$ <input type="text"/>                    | \$ <input type="text"/>                                                                                                          |
| 12. SUBTOTAL (sum of lines 1-11)                                                                                                                     | \$ <input type="text" value="8,647,427.00"/>  | \$ <input type="text" value="547,427.00"/> | \$ <input type="text" value="8,100,000.00"/>                                                                                     |
| 13. Contingencies                                                                                                                                    | \$ <input type="text" value="1,800,000.00"/>  | \$ <input type="text"/>                    | \$ <input type="text" value="1,800,000.00"/>                                                                                     |
| 14. SUBTOTAL                                                                                                                                         | \$ <input type="text" value="10,447,427.00"/> | \$ <input type="text" value="547,427.00"/> | \$ <input type="text" value="9,900,000.00"/>                                                                                     |
| 15. Project (program) income                                                                                                                         | \$ <input type="text"/>                       | \$ <input type="text"/>                    | \$ <input type="text"/>                                                                                                          |
| 16. TOTAL PROJECT COSTS (subtract #15 from #14)                                                                                                      | \$ <input type="text" value="10,447,427.00"/> | \$ <input type="text" value="547,427.00"/> | \$ <input type="text" value="9,900,000.00"/>                                                                                     |
| <b>FEDERAL FUNDING</b>                                                                                                                               |                                               |                                            |                                                                                                                                  |
| 17. Federal assistance requested, calculate as follows:<br>(Consult Federal agency for Federal percentage share.) Enter the resulting Federal share. |                                               |                                            | Enter eligible costs from line 16c Multiply X <input type="text" value="100"/> %<br>\$ <input type="text" value="9,900,000.00"/> |

