

MEPNN Supplier Scouting Opportunity Synopsis

Section 1: General Information

Scouting Number	2025-310
Item to be Scouted	BABA Reinforcing steel
Days to be scouted	26
Response Due By	09/29/2025
Description	BABA Compliant: Reinforcing Steel: ASTM A615/A615M, Grade 60 (60,000 psi). 1. Type: Deformed billet steel bars

Section 2: Technical Information

Type of supplier being sought	Colorado Other
Details	BABAA-compliant self-certified manufacturers
Reason	BABA
Describe the manufacturing processes (elaborate to provide as much detail as possible)	Domestic components in each of the BABAA compliant manufactured products must exceed 55% of the total component cost and be assembled in the United States.
Provide dimensions / size / tolerances / performance specifications for the item	See attached specs and mechanical schedule for more information.
List required materials needed to make the product, including materials of product components	See attached specs and mechanical schedule for more information.
Are there applicable certification requirements?	Yes
Details	Build America, Buy America Act (BABAA) compliant
Are there applicable regulations?	Yes
Details	Must be able to submit BABAA manufactured product self-certification manufactured product letter that details a compliant product.
Are there any other standards, requirements, etc.?	No
Additional Technical Comments	See attached specs and mechanical schedule for more information.

Section 4: Business Information

Estimated potential business volume	TBD post selection. Cost should be the best available, and cannot increase the project cost by 25%.
Estimated target price / unit cost information (if unavailable explain)	TBD post selection. Cost should be the best available, and cannot increase the project cost by 25%.
When is it needed by?	Q1 2026
Describe packaging requirements	Must arrive undamaged
Where will this item be shipped?	Colorado

Additional Comments

Is there other information you would like to include?	<p>Nationwide Search</p> <p>Provide written documentation in response to the Supplier Scouting request of being a current Build America Buy America Act Reinforcing steel distributor with experience in manufacturing the system components, meeting the product performance requirements.</p> <p>Information on BABAA compliance requirements can be found at the Made in America Office link https://www.madeinamerica.gov/.</p>
---	--

1.05 QUALITY ASSURANCE

- A. Perform work of this Section in accordance with ACI 117, ACI 301, and ACI 318.
- B. Follow recommendations of ACI 301 when concreting during hot and cold weather.

PART 2 PRODUCTS

2.01 FORMWORK

- A. Formwork Design and Construction: Comply with guidelines of ACI 347R to provide formwork that will produce concrete complying with tolerances of ACI 117, unless otherwise specified.
- B. Forming Materials: Contractor's choice of standard products with sufficient strength to withstand hydrostatic head without distortion in excess of permitted tolerances.
 - 1. Limit concrete surface irregularities, designated as abrupt or gradual according to ACI 347R, as follows:
 - a. Class A: 1/8 inch for smooth formed finish surfaces exposed to view.
 - b. Class B: 1/4 inch for rough formed finished surfaces not exposed to view.
 - c. Permissible irregularity is a cumulative value due to all sources including layout, plumbness, member size, formwork offsets, joints, and member levelness. Permissible irregularity also applies between adjacent concrete surfaces on opposite sides of construction joints, expansion joints, or shrinkage pour strip if present.
 - 2. Form Facing for Exposed Finish Concrete: Contractor's choice of materials that will provide smooth, stain-free final appearance where specified for smooth formed finish.
 - 3. Form Coating: Release agent that will not adversely affect concrete or interfere with application of coatings.
 - 4. Form Ties: Cone snap type that will leave no metal within 1-1/2 inches of concrete surface.

2.02 REINFORCEMENT MATERIALS

- A. Reinforcing Steel: ASTM A615/A615M, Grade 60 (60,000 psi).
 - 1. Type: Deformed billet-steel bars.
 - 2. Finish: Unfinished, unless otherwise indicated.
- B. Steel Welded Wire Reinforcement (WWR): Plain type, ASTM A1064/A1064M.
 - 1. Form: Flat sheets.
 - 2. Mesh Size and Wire Gage: As indicated on Drawings.
- C. Reinforcement Accessories:
 - 1. Tie Wire: Annealed, minimum 16 gauge, 0.0508 inch.
 - 2. Chairs, Bolsters, Bar Supports, Spacers: Sized and shaped for adequate support of reinforcement during concrete placement.
 - 3. Provide stainless steel, galvanized, plastic, or plastic coated steel components for placement within 1-1/2 inches of weathering surfaces.

2.03 CONCRETE MATERIALS

- A. Cement: ASTM C150/C150M, Type as specified on structural Drawings; Portland type.
 - 1. Acquire cement for entire project from same source.